

FUJITSU Software

Symfoware Server V12.1.0

A decorative horizontal band with a red-to-dark-red gradient. It features abstract, glowing white and red lines that swirl and intersect, creating a sense of motion and energy.

Messages

Windows/Linux

J2UL-1742-08ENZ0(00)
December 2014

Preface

Purpose of this document

This document explains the messages output by Symfoware Server.

Intended readers

This document is intended for the following readers:

- Persons using Symfoware Server

Prerequisites

Knowledge of the following topics is required to read this document:

- A general understanding of computers
- Jobs
- PostgreSQL
- Linux
- Windows

L

W

Structure of this document

This document is structured as follows:

[Chapter 1 Overview of Messages](#)

This chapter explains the format in which messages are output.

[Chapter 2 Symfoware Server Messages](#)

This chapter explains the messages that are output and the actions to take based on the message information.

[Chapter 3 Mirroring Controller Messages](#)

This chapter explains messages output by the Mirroring Controller.

[Appendix A Messages Output by PL/extJava](#)

This appendix describes messages output by PL/extJava.

Export Restrictions

Exportation/release of this document may require necessary procedures in accordance with the regulations of your resident country and/or US export control laws.

Issue Date and Version

4th edition: December, 2014
Third edition: November, 2014
Second edition: January, 2014
First edition: November, 2013

Copyright

Copyright 2013-2014 FUJITSU LIMITED

Chapter 1 Overview of Messages

This chapter explains the format of messages.

1.1 Message Format

This section explains the format of messages.

- Output format
- Components

1.1.1 Output Format

The message output format is as follows:

Format of messages returned to an application

```
msgType: msgText (msgNumber)
```

Format of messages output to the server message log

```
SQLSTATE: date [processID]: [internalCode-1] user = userName, db = dbName, remote =  
clientIpAddress(portNumber) app = appName msgType: msgText (msgNumber)
```



See

Refer to "PostgreSQL Error Codes" under "Appendixes" in the PostgreSQL Documentation for information on SQLSTATE.



Note

- Notes on monitoring messages output to the server message log

Use SQLSTATE to monitor server messages, noting the following:

- Configuration method
 - Refer to "Error Log Settings" under "Setup" in the Installation and Setup Guide for Server for details.
- Notes
 - The user name, client IP address (port number), and application name may sometimes be blank.
 - Multiple message numbers may be output.

- Notes on monitoring messages returned to an application

You can output SQLSTATE to a message to be returned to an application. The following explains how to configure the settings for outputting SQLSTATE and gives cautions to be observed when doing so.

- How to configure the settings:
 - In the SET statement, set the log_error_verbosity parameter to VERBOSE.
 - For an application that uses the C language library, use the PQsetErrorVerbosity function to set message redundancy to PQERRORS_VERBOSE.
- Cautions
 - SQLSTATE is output only to messages to be returned to applications that use the C language library.

- In some cases, *userName*, *clientIpAddress(portNumber)*, and *applicationName* may be blank.
- Multiple message numbers may be output.
- If the email address "pgsql-bugs@postgresql.org" is output to the message and the cause of the error cannot be identified, contact Fujitsu technical support.



Example

Message output to the server message log

```
3D000: 2013-07-10 19:41:05 JST [13899]: [1-1] user = symfo,db = symfo,remote =  
127.0.0.1(51902) app = [unknown] FATAL: database "symfo" does not exist (10571)
```

1.1.2 Components

This section explains the components of a message.

Message type

The message type indicates the type of error denoted in the message.

The message type will be one of the following:

- Information (INFO, NOTICE, LOG, DEBUG)

This message type denotes a notification from the system, not an error. There is no need to take action.

- Warning (WARNING)

This message type denotes that no error occurred but confirmation or action is required by the user. Take the actions described in the "Action" section of the message.

- Error (ERROR, FATAL, PANIC)

This message type denotes that an error has occurred. Take the actions described in the "Action" section of the message.

- Supplementary information (DETAIL, HINT, QUERY, CONTEXT, LOCATION, STATEMENT)

This message type denotes supplementary information relating to the previous message. If the message was output in English, the message type will also be in English. (Detail, hint, query, context, location, statement)

Message text

The text of the message reports the status of the system or an error in the system.

The notation "@numeric character@" that appears in "[Chapter 2 Symfoware Server Messages](#)" indicates an embedded character string. A character string is output to a message that is actually output.

If a message locale other than 'ja' is specified, messages added by Symfoware Server will be output in English.

For other message locales, the messages are output in English.

However, messages output by the `pgx_jadmin` command will always be displayed in English regardless of the message locale.

Message number

The message number uniquely identifies each message. It is output as a string of five single-byte numeric characters. Use the message number that is output to find the explanation of the corresponding message in this document. The message numbers may change, so do not use them as keywords for monitoring.

No message number is assigned to messages output by a PL/pgSQL RAISE statement.

The message number is only output if the message locale is 'ja' or 'en'. For other message locales, the message number is not output.

1.2 Mirroring Controller Message Format

This section explains the format of messages output by the Mirroring Controller.

Mirroring Controller messages are output to the following locations:

L

- System log

W

- Event log

Output format

```
programName[processId]: msgType: msgText (msgNumber)
```

For *programName*, use the value of the `syslog_ident` parameter or `event_source` parameter defined in the `serverIdentifier.conf` file.

L

The message types output by Mirroring Controller, their severity, and their corresponding value in the system log are shown in the table below.

L

Table 1.1 Message type, severity, and corresponding value in the system log

Message type	Severity	Meaning	System log
INFO	Information	Provides information not categorized as LOG or NOTICE.	INFO
LOG		Provides information recognized as a particularly important event in tracing the operation history. (Example: Automatic switch is complete)	
NOTICE	Notice	Outputs information that takes into account the user instructions within the program in response to an executed or automatically executed process.	NOTICE
WARNING	Warning	Provides a warning, for example it will soon be impossible to maintain multiplexing capabilities.	WARNING
ERROR	Error	Reports that an error other than FATAL or PANIC has occurred.	ERROR
FATAL		Reports that an error has been detected requiring system recovery in one of the multiplexed database systems. It also reports the content and cause of the error.	CRIT
PANIC		Reports that an error has been detected requiring immediate system recovery in all multiplexed database systems. It also reports the content and cause of the error.	ALERT

W

The message types output by Mirroring Controller, their severity, and their corresponding value in the event log are shown in the table below.

Table 1.2 Message type, severity, and corresponding value in the event log

Message type	Severity	Meaning	Event log
INFO	Information	Provides information not categorized as LOG or NOTICE.	INFORMATION
LOG		Provides information recognized as a particularly important event in tracing the operation history. (Example: Automatic switch is complete)	
NOTICE	Notice	Outputs information that takes into account the user instructions within the program in response to an executed or automatically executed process.	
WARNING	Warning	Provides a warning, for example it will soon be impossible to maintain multiplexing capabilities.	WARNING
ERROR	Error	Reports that an error other than FATAL or PANIC has occurred.	ERROR
FATAL		Reports that an error has been detected requiring system recovery in one of the multiplexed database systems. It also reports the content and cause of the error.	
PANIC		Reports that an error has been detected requiring immediate system recovery in all multiplexed database systems. It also reports the content and cause of the error.	

The message severity has the following meanings:

- Information

Informational status. A message that was reported by the system is displayed. No action is required.

- Notice

Informational status, but a message that should be noted is displayed. If necessary, take the actions described in the "Action" section of the message.

- Warning

No error has occurred, but the user is requested to check, and take action. Take the actions described in the "Action" section of the message.

- Error

An error has occurred. Take the actions described in the "Action" section of the message.

1.3 Using this Document with FUJITSU Integrated System HA Database Ready

This section explains points to note when using the *Messages* manual with FUJITSU Integrated System HA Database Ready (hereafter abbreviated as "HA Database Ready").

- Check the content of the message, together with the database server status in "Appliance Manager".

- If the message indicates an "I/O processing error on the database server", read the "Action" section as follows:

The process was canceled due to a disk error in the database server. However, you can restart the application, because the database server is mirrored and will be automatically switched.

If the same error occurs when you restart the application, check if an error has occurred on the database server.

- The server message log can be referenced using the `pgx_log` of the system view.

Chapter 2 Symfoware Server Messages

This chapter explains messages output by the Symfoware Server.

2.1 Message Numbers Beginning with 10000

2.1.1 10001

no Snowball stemmer available for language "@1@" and encoding "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.1.2 10002

multiple StopWords parameters

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.1.3 10003

multiple Language parameters

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.1.4 10004

unrecognized Snowball parameter: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.1.5 10005

missing Language parameter

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.1.6 10006

could not determine which collation to use for index expression

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.1.7 10007

old GIN indexes do not support whole-index scans nor searches for nulls

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.1.8 10008

index row size @1@ exceeds maximum @2@ for index "@3@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.1.9 10009

"@1@" is an index

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.1.10 10010

could not create archive status file "@1@": @2@

[Description]

There was insufficient free space in the disk of the database server during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Delete user data stored in the database server to free up space on the disk.

2.1.11 10011

could not write archive status file "@1@": @2@

[Description]

There was insufficient free space in the disk of the database server during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Delete user data stored in the database server to free up space on the disk.

2.1.12 10012

could not seek in log file @1@, segment @2@ to offset @3@: @4@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.13 10013

could not write to log file @1@, segment @2@ at offset @3@, length @4@: @5@

[Description]

There are the following cases:

- failed to write transaction log file
- failed to write transaction log file on backup data storage destination

[System Processing]

Processing will be aborted.

[Action]

Lack of storage space or malfunction of storage allocating the file shown in this message is considered.

If it's true, recover the database system according to "Actions when an Error Occurs" of "Operation Guide" or "Cluster Operation Guide".

If it's not true, identify the cause according to the informations in this message such as errno, and work around.

The following major causes are considered.

- the file has no permission or the permission has been changed
- power of the storage allocating the file has been turned off
- unmounted the storage allocating the file
- another process or human operated the file
- the storage allocating the file has crashed

2.1.14 10014

updated min recovery point to @1@/@2@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.1.15 10015

could not open file "@1@" (log file @2@, segment @3@): @4@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.16 10016

could not create file "@1@": @2@

[Description]

There was insufficient free space in the disk of the database server during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Delete user data stored in the database server to free up space on the disk.

2.1.17 10017

could not write to file "@1@": @2@

[Description]

There was insufficient free space in the disk of the database server during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Delete user data stored in the database server to free up space on the disk.

2.1.18 10018

could not fsync file "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.19 10019

could not close file "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.20 10020

could not open file "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.21 10021

could not open file "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.22 10022

not enough data in file "@1@"

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.23 10023

could not link file "@1@" to "@2@" (initialization of log file @3@, segment @4@): @5@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.24 10024

could not rename file "@1@" to "@2@" (initialization of log file @3@, segment @4@): @5@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.25 10025

could not close log file @1@, segment @2@: @3@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.26 10026

could not read file "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.27 10027

could not remove file "@1@": @2@

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.1.28 10028

archive file "@1@" has wrong size: @2@ instead of @3@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.29 10029

restored log file "@1@" from archive

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.1.30 10030

could not restore file "@1@" from archive: return code @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.31 10031

@1@ "@2@" : return code @3@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.32 10032

could not open transaction log directory "@1@" : @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.33 10033

recycled transaction log file "@1@"

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.1.34 10034

removing transaction log file "@1@"

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.1.35 10035

could not rename old transaction log file "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.36 10036

could not remove old transaction log file "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.37 10037

required WAL directory "@1@" does not exist

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.38 10038

creating missing WAL directory "@1@"

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.1.39 10039

could not create missing directory "@1@" : @2@

[Description]

There was insufficient free space in the disk of the database server during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Delete user data stored in the database server to free up space on the disk.

2.1.40 10040

removing transaction log backup history file "@1@"

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.1.41 10041

incorrect hole size in record at @1@/@2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.42 10042

incorrect total length in record at @1@/@2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.43 10043

incorrect resource manager data checksum in record at @1@/@2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.44 10044

invalid record offset at @1@/@2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.45 10045

contrecord is requested by @1 @/@2@**[Description]**

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.46 10046

invalid xlog switch record at @1 @/@2@**[Description]**

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.47 10047

record with zero length at @1 @/@2@**[Description]**

A zero-length incomplete data was found in transaction log or archive log.

[System Processing]

There are the following cases:

- when the error type is information(INFO, NOTICE, LOG, DEBUG)

Continues processing.

- when the error type is error(ERROR, FATAL, PANIC)

Processing will be aborted.

[Action]

When the error type is information(INFO, NOTICE, LOG, DEBUG), no action is required.

When the error type is error(ERROR, FATAL, PANIC), take either of the following actions.

- when this message is output during activating instance

Recover the database system according to "Actions when an Error Occurs" of "Operation Guide" or "Cluster Operation Guide".

- when this message is output during recovering

Cannot continue to recover from the current backup data because an archive log in the backup has an error.

Recover from the other backup data if you have it.

2.1.48 10048

invalid record length at @1@/@2@

[Description]

invalid record length was found on archive log or transaction log data.

[System Processing]

The following causes could be considered.

- if the log level is information(INFO, NOTICE, LOG, DEBUG)

Continue processing.

- if the log level is error(ERROR, FATAL, PANIC)

Processing will be aborted.

[Action]

If the log level is information(INFO, NOTICE, LOG, DEBUG), no action is required.

When the log level is error(ERROR, FATAL, PANIC), take either of the following actions.

- if this message is output during starting instance

Please restore according to "Deal at the time of abnormality" of "Operation Guide" or "Cluster Operation Guide".

- if this message is output during recovering

Cannot continue to recover with the current backup data because an archive log in the backup has an error.

Recover from the other backup data.

2.1.49 10049

invalid resource manager ID @1@ at @2@/@3@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.50 10050

record with incorrect prev-link @1@/@2@ at @3@/@4@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.51 10051

record length @1@ at @2@/@3@ too long**[Description]**

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.52 10052

there is no contrecord flag in log file @1@, segment @2@, offset @3@**[Description]**

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.53 10053

invalid contrecord length @1@ in log file @2@, segment @3@, offset @4@**[Description]**

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.54 10054

invalid magic number @1@ in log file @2@, segment @3@, offset @4@**[Description]**

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.55 10055

invalid info bits @1@ in log file @2@, segment @3@, offset @4@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.56 10056

WAL file is from different database system

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.57 10057

unexpected pageaddr @1 @/ @2@ in log file @3@, segment @4@, offset @5@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.58 10058

unexpected timeline ID @1 @ in log file @2@, segment @3@, offset @4@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.59 10059

out-of-sequence timeline ID @1 @ (after @2@) in log file @3@, segment @4@, offset @5@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.60 10060

syntax error in history file: @1@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.61 10061

invalid data in history file: @1@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.62 10062

invalid data in history file "@1@"

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.63 10063

new timeline @1@ is not a child of database system timeline @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.1.64 10064

new target timeline is @1@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.1.65 10065

could not rename file "@1@" to "@2@" : @3@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.66 10066

could not link file "@1@" to "@2@" : @3@

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.1.67 10067

could not create control file "@1@" : @2@

[Description]

There was insufficient free space in the disk of the database server during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Delete user data stored in the database server to free up space on the disk.

2.1.68 10068

could not write to control file: @1 @

[Description]

There was insufficient free space in the disk of the database server during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Delete user data stored in the database server to free up space on the disk.

2.1.69 10069

could not fsync control file: @1 @

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.70 10070

could not close control file: @1 @

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.71 10071

could not open control file "@1 @": @2 @

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.72 10072

could not read from control file: @1@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.73 10073

database files are incompatible with server

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.1.74 10074

incorrect checksum in control file

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.75 10075

could not write bootstrap transaction log file: @1@

[Description]

There was insufficient free space in the disk of the database server during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Delete user data stored in the database server to free up space on the disk.

2.1.76 10076

could not fsync bootstrap transaction log file: @1@**[Description]**

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.77 10077

could not close bootstrap transaction log file: @1@**[Description]**

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.78 10078

could not open recovery command file "@1@": @2@**[Description]**

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.79 10079

parameter "@1@" requires a Boolean value**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.1.80 10080

recovery_target_timeline is not a valid number: "@1@"

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.81 10081

recovery_target_xid is not a valid number: "@1@"

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.82 10082

recovery_target_name is too long (maximum @1@ characters)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.1.83 10083

unrecognized recovery parameter "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.1.84 10084

recovery command file "@1@" specified neither primary_conninfo nor restore_command

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.1.85 10085

recovery command file "@1@" must specify restore_command when standby mode is not enabled

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.1.86 10086

recovery target timeline @1@ does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.1.87 10087

archive recovery complete

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.1.88 10088

recovery stopping after commit of transaction @1@, time @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.89 10089

recovery stopping before commit of transaction @1@, time @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.90 10090

recovery stopping after abort of transaction @1@, time @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.91 10091

recovery stopping before abort of transaction @1@, time @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.92 10092

recovery stopping at restore point "@1@", time @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.1.93 10093

recovery has paused

[Description]

An error occurred because execution is temporarily impossible.

[System Processing]

Processing will be aborted.

[Action]

Restart the application. If the same error occurs when you restart the application, to check if there are any problems in the database server.

2.1.94 10094

must be superuser to control recovery

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.1.95 10095

recovery is in progress

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.1.96 10096

hot standby is not possible because @1@ = @2@ is a lower setting than on the master server (its value was @3@)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.1.97 10097

WAL was generated with wal_level=minimal, data may be missing

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.1.98 10098

hot standby is not possible because wal_level was not set to "hot_standby" on the master server

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.1.99 10099

control file contains invalid data

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.2 Message Numbers Beginning with 10100

2.2.1 10100

database system was shut down at @1@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.2.2 10101

database system was shut down in recovery at @1@

[Description]

Displaying the date and time that the standby server is shut down last time.

[System Processing]

Continues processing.

[Action]

No action is required.

2.2.3 10102

database system shutdown was interrupted; last known up at @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.2.4 10103

database system was interrupted while in recovery at @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.2.5 10104

database system was interrupted while in recovery at log time @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.2.6 10105

database system was interrupted; last known up at @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.2.7 10106

requested timeline @1@ is not a child of database system timeline @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.2.8 10107

entering standby mode

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.2.9 10108

starting point-in-time recovery to XID @1@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.2.10 10109

starting point-in-time recovery to @1@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.2.11 10110

starting point-in-time recovery to "@1@"

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.2.12 10111

starting archive recovery

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.2.13 10112

checkpoint record is at @1@/@2@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.2.14 10113

could not find redo location referenced by checkpoint record

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.2.15 10114

could not locate required checkpoint record

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.2.16 10115

could not locate a valid checkpoint record

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.2.17 10116

using previous checkpoint record at @1@/@2@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.2.18 10117

redo record is at @1@/@2@; shutdown @3@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.2.19 10118

next transaction ID: @1 @/@2@; next OID: @3@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.2.20 10119

next MultiXactId: @1 @; next MultiXactOffset: @2@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.2.21 10120

oldest unfrozen transaction ID: @1 @, in database @2@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.2.22 10121

invalid next transaction ID

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.2.23 10122

invalid redo in checkpoint record

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.2.24 10123

invalid redo record in shutdown checkpoint

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.2.25 10124

database system was not properly shut down; automatic recovery in progress

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.2.26 10125

initializing for hot standby

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.2.27 10126

redo starts at @1 @/@2@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.2.28 10127

redo done at @1 @/@2@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.2.29 10128

last completed transaction was at log time @1 @

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.2.30 10129

redo is not required

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.2.31 10130

requested recovery stop point is before consistent recovery point

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.2.32 10131

WAL ends before end of online backup

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.2.33 10132

WAL ends before consistent recovery point

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.2.34 10133

selected new timeline ID: @1@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.2.35 10134

consistent recovery state reached at @1 @/@2@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.2.36 10135

invalid primary checkpoint link in control file

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.2.37 10136

invalid secondary checkpoint link in control file

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.2.38 10137

invalid checkpoint link in backup_label file

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.2.39 10138

invalid primary checkpoint record

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.2.40 10139

invalid secondary checkpoint record

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.2.41 10140

invalid checkpoint record

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.2.42 10141

invalid resource manager ID in primary checkpoint record

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.2.43 10142

invalid resource manager ID in secondary checkpoint record

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.2.44 10143

invalid resource manager ID in checkpoint record

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.2.45 10144

invalid xl_info in primary checkpoint record

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.2.46 10145

invalid xl_info in secondary checkpoint record

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.2.47 10146

invalid xl_info in checkpoint record

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.2.48 10147

invalid length of primary checkpoint record

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.2.49 10148

invalid length of secondary checkpoint record

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.2.50 10149

invalid length of checkpoint record

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.2.51 10150

shutting down

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.2.52 10151

database system is shut down

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.2.53 10152

concurrent transaction log activity while database system is shutting down

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.2.54 10153

skipping restartpoint, recovery has already ended

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.2.55 10154

skipping restartpoint, already performed at @1@/@2@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.2.56 10155

recovery restart point at @1@/@2@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.2.57 10156

restore point "@1@" created at @2@/@3@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.2.58 10157

unexpected timeline ID @1@ (after @2@) in checkpoint record

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.2.59 10158

unexpected timeline ID @1@ (should be @2@) in checkpoint record

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.2.60 10159

could not fsync log file @1@, segment @2@: @3@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.2.61 10160

could not fsync write-through log file @1@, segment @2@: @3@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.2.62 10161

could not fdatsync log file @1@, segment @2@: @3@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.2.63 10162

must be superuser or replication role to run a backup

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.2.64 10163

recovery is not in progress

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.2.65 10164

WAL level not sufficient for making an online backup

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.2.66 10165

backup label too long (max @1 @ bytes)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.2.67 10166

a backup is already in progress

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.2.68 10167

could not stat file "@1@": @2@

[Description]

There was insufficient free space in the disk of the database server during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Delete user data stored in the database server to free up space on the disk.

2.2.69 10168

a backup is not in progress

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.2.70 10169

invalid data in file "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.2.71 10170

pg_stop_backup cleanup done, waiting for required WAL segments to be archived

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.2.72 10171

pg_stop_backup still waiting for all required WAL segments to be archived (@1@ seconds elapsed)

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.2.73 10172

pg_stop_backup complete, all required WAL segments have been archived

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.2.74 10173

WAL archiving is not enabled; you must ensure that all required WAL segments are copied through other means to complete the backup

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.2.75 10174

must be superuser to switch transaction log files

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.2.76 10175

must be superuser to create a restore point

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.2.77 10176

WAL level not sufficient for creating a restore point

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.2.78 10177

value too long for restore point (maximum @1@ characters)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.2.79 10178

could not parse transaction log location "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.2.80 10179

could not read from log file @1@, segment @2@, offset @3@: @4@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.2.81 10180

received promote request

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.2.82 10181

trigger file found: @1@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.2.83 10182

database is not accepting commands to avoid wraparound data loss in database "@1@"

[Description]

An error occurred because execution is temporarily impossible.

[System Processing]

Processing will be aborted.

[Action]

Restart the application. If the same error occurs when you restart the application, to check if there are any problems in the database server.

2.2.84 10183

database is not accepting commands to avoid wraparound data loss in database with OID @1@

[Description]

An error occurred because execution is temporarily impossible.

[System Processing]

Processing will be aborted.

[Action]

Restart the application. If the same error occurs when you restart the application, to check if there are any problems in the database server.

2.2.85 10184

database "@1@" must be vacuumed within @2@ transactions

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.2.86 10185

database with OID @1@ must be vacuumed within @2@ transactions

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.2.87 10186

transaction ID wrap limit is @1@, limited by database with OID @2@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.2.88 10187

transaction identifier "@1@" is too long

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.2.89 10188

prepared transactions are disabled

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.2.90 10189

transaction identifier "@1@" is already in use

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.2.91 10190

maximum number of prepared transactions reached

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.2.92 10191

prepared transaction with identifier "@1@" is busy

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.2.93 10192

permission denied to finish prepared transaction

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.2.94 10193

prepared transaction belongs to another database

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.2.95 10194

prepared transaction with identifier "@1@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.2.96 10195

two-phase state file maximum length exceeded

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.2.97 10196

could not create two-phase state file "@1@": @2@

[Description]

There was insufficient free space in the disk of the database server during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Delete user data stored in the database server to free up space on the disk.

2.2.98 10197

could not write two-phase state file: @1@

[Description]

There was insufficient free space in the disk of the database server during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Delete user data stored in the database server to free up space on the disk.

2.2.99 10198

could not seek in two-phase state file: @1@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.2.100 10199

could not close two-phase state file: @1@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.3 Message Numbers Beginning with 10200

2.3.1 10200

could not open two-phase state file "@1@": @2@

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.3.2 10201

could not stat two-phase state file "@1@": @2@

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.3.3 10202

could not read two-phase state file "@1@": @2@

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.3.4 10203

two-phase state file for transaction @1@ is corrupt

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.3.5 10204

could not remove two-phase state file "@1@": @2@

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.3.6 10205

could not recreate two-phase state file "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.3.7 10206

could not fsync two-phase state file: @1@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.3.8 10207

could not fsync two-phase state file "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.3.9 10208

could not close two-phase state file "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.3.10 10209

removing future two-phase state file "@1@"

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.3.11 10210

removing corrupt two-phase state file "@1@"

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.3.12 10211

removing stale two-phase state file "@1@"

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.3.13 10212

recovering prepared transaction @1@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.3.14 10213

file "@1@" doesn't exist, reading as zeroes

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.3.15 10214

could not access status of transaction @1@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.3.16 10215

could not truncate directory "@1@": apparent wraparound

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.3.17 10216

removing file "@1@"

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.3.18 10217

cannot have more than 2^32-1 commands in a transaction

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.19 10218

maximum number of committed subtransactions (@1@) exceeded

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.20 10219

cannot PREPARE a transaction that has operated on temporary tables

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.21 10220

@1@ cannot run inside a transaction block

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.22 10221

@1@ cannot run inside a subtransaction

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.23 10222

@1@ cannot be executed from a function or multi-command string

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.24 10223

@1@ can only be used in transaction blocks

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.25 10224

there is already a transaction in progress

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.3.26 10225

there is no transaction in progress

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.3.27 10226

no such savepoint

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.28 10227

cannot have more than $2^{32}-1$ subtransactions in a transaction

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.29 10228

index "@1@" is not a btree

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.3.30 10229

version mismatch in index "@1@": file version @2@, code version @3@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.3.31 10230

index "@1@" contains unexpected zero page at block @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.3.32 10231

index "@1@" contains corrupted page at block @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.3.33 10232

duplicate key value violates unique constraint "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.34 10233

failed to re-find tuple within index "@1@"

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.3.35 10234

row is too big: size @1@, maximum size @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.36 10235

"@1@" is not an index

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.37 10236

"@1@" is a composite type

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.38 10237

could not obtain lock on row in relation "@1@"

[Description]

An error occurred because execution is temporarily impossible.

[System Processing]

Processing will be aborted.

[Action]

Restart the application. If the same error occurs when you restart the application, to check if there are any problems in the database server.

2.3.39 10238

hash indexes do not support whole-index scans

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.40 10239

index "@1@" is not a hash index

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.3.41 10240

index "@1@" has wrong hash version

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.3.42 10241

out of overflow pages in hash index "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.43 10242

index row size @1@ exceeds hash maximum @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.44 10243

column "@1@" cannot be declared SETOF

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.45 10244

number of columns (@1@) exceeds limit (@2@)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.46 10245

user-defined relation parameter types limit exceeded

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.47 10246

RESET must not include values for parameters

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.48 10247

unrecognized parameter namespace "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.49 10248

unrecognized parameter "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.50 10249

parameter "@1@" specified more than once

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.51 10250

invalid value for boolean option "@1@": @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.52 10251

invalid value for integer option "@1@": @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.53 10252

value @1@ out of bounds for option "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.54 10253

invalid value for floating point option "@1@": @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.55 10254

unsupported format code: @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.56 10255

number of index columns (@1@) exceeds limit (@2@)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.57 10256

index row requires @1@ bytes, maximum size is @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.58 10257

picksplit method for column @1@ of index "@2@" failed

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.3.59 10258

unlogged GiST indexes are not supported

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.60 10259

index "@1@" contains an inner tuple marked as invalid

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.61 10260

aggregate @1@ needs to have compatible input type and transition type

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.62 10261

could not create exclusion constraint "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.63 10262

conflicting key value violates exclusion constraint "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.64 10263

RIGHT JOIN is only supported with merge-joinable join conditions

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.65 10264

FULL JOIN is only supported with merge-joinable join conditions

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.66 10265

could not determine actual type of argument declared @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.67 10266

@1@ is not allowed in a SQL function

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.68 10267

@1@ is not allowed in a non-volatile function

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.69 10268

could not determine actual result type for function declared to return type @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.70 10269

set-valued function called in context that cannot accept a set

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.71 10270

return type mismatch in function declared to return @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.72 10271

return type @1@ is not supported for SQL functions

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.73 10272

cannot change sequence "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.74 10273

cannot change TOAST relation "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.75 10274

cannot insert into view "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.76 10275

cannot update view "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.77 10276

cannot copy from view "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.78 10277

cannot change foreign table "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.79 10278

cannot change relation "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.80 10279

cannot lock rows in sequence "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.81 10280

cannot lock rows in TOAST relation "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.82 10281

cannot lock rows in view "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.83 10282

cannot lock rows in foreign table "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.84 10283

cannot lock rows in relation "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.85 10284

null value in column "@1@" violates not-null constraint

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.86 10285

new row for relation "@1@" violates check constraint "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.87 10286

could not serialize access due to concurrent update

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.88 10287

ON COMMIT can only be used on temporary tables

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.89 10288

cannot create temporary table within security-restricted operation

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.90 10289

could not rewind hash-join temporary file: @1@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.3.91 10290

could not write to hash-join temporary file: @1@

[Description]

There was insufficient free space in the disk of the database server during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Delete user data stored in the database server to free up space on the disk.

2.3.92 10291

could not read from hash-join temporary file: @1@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.3.93 10292

relation "@1@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.94 10293

cursor "@1@" is not a SELECT query

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.95 10294

cursor "@1@" is held from a previous transaction

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.96 10295

cursor "@1@" has multiple FOR UPDATE/SHARE references to table "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.97 10296

cursor "@1@" does not have a FOR UPDATE/SHARE reference to table "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.98 10297

cursor "@1@" is not positioned on a row

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.99 10298

cursor "@1@" is not a simply updatable scan of table "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.3.100 10299

type of parameter @1@ (@2@) does not match that when preparing the plan (@3@)**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4 Message Numbers Beginning with 10300

2.4.1 10300

no value found for parameter @1@**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.2 10301

more than one row returned by a subquery used as an expression**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.3 10302

frame starting offset must not be null**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.4 10303

frame starting offset must not be negative

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.5 10304

frame ending offset must not be null

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.6 10305

frame ending offset must not be negative

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.7 10306

transaction left non-empty SPI stack

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.4.8 10307

subtransaction left non-empty SPI stack

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.4.9 10308

cannot open multi-query plan as cursor

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.10 10309

cannot open @1@ query as cursor

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.11 10310

DECLARE SCROLL CURSOR ... FOR UPDATE/SHARE is not supported

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.12 10311

number of array dimensions (@1@) exceeds the maximum allowed (@2@)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.13 10312

array subscript in assignment must not be null

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.14 10313

attribute @1@ has wrong type

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.15 10314

table row type and query-specified row type do not match

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.16 10315

**cannot pass more than @1@ argument to a function
cannot pass more than @2@ arguments to a function**

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.17 10316

functions and operators can take at most one set argument

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.18 10317

function returning setof record called in context that cannot accept type record

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.19 10318

function return row and query-specified return row do not match

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.20 10319

table-function protocol for materialize mode was not followed

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.21 10320

unrecognized table-function returnMode: @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.22 10321

function returning set of rows cannot return null value

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.23 10322

rows returned by function are not all of the same row type

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.24 10323

IS DISTINCT FROM does not support set arguments

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.25 10324

op ANY/ALL (array) does not support set arguments

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.26 10325

cannot merge incompatible arrays

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.27 10326

multidimensional arrays must have array expressions with matching dimensions

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.28 10327

NULLIF does not support set arguments

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.29 10328

domain @1@ does not allow null values

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.30 10329

value for domain @1@ violates check constraint "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.31 10330

aggregate function calls cannot be nested

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.32 10331

window function calls cannot be nested

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.33 10332

target type is not an array

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.34 10333

ROW() column has type @1@ instead of type @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.35 10334

could not identify a comparison function for type @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.36 10335

OFFSET must not be negative

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.37 10336

LIMIT must not be negative

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.38 10337

@1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.39 10338

could not find array type for data type @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.40 10339

cannot assign to system column "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.41 10340

cannot set an array element to DEFAULT

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.42 10341

cannot set a subfield to DEFAULT

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.43 10342

column "@1@" is of type @2@ but default expression is of type @3@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.44 10343

row expansion via "*" is not supported here

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.45 10344

cannot assign to field "@1@" of column "@2@" because its type @3@ is not a composite type

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.46 10345

cannot assign to field "@1@" of column "@2@" because there is no such column in data type @3@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.47 10346

array assignment requires type @1@ but expression is of type @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.48 10347

column "@1@" is of type @2@ but expression is of type @3@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.49 10348

cannot cast type @1@ to @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.50 10349

column "@1@" of relation "@2@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.51 10350

column name "@1@" specified more than once

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.52 10351

column reference "@1@" is ambiguous

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.53 10352

cross-database references are not implemented: "@1@.@2@.@3@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.54 10353

improper qualified name (too many dotted names): @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.55 10354

SELECT * with no tables specified is not valid

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.56 10355

there is no parameter \$@1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.57 10356

inconsistent types deduced for parameter \$@1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.58 10357

could not determine data type of parameter \$@1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.59 10358

identifier "@1@" will be truncated to "@2@"

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.4.60 10359

JOIN/ON clause refers to "@1@", which is not part of JOIN

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.61 10361

subquery in FROM cannot refer to other relations of same query level

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.62 10362

function expression in FROM cannot refer to other relations of same query level

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.63 10363

cannot use aggregate function in default expression

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.64 10364

cannot use window function in default expression

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.65 10365

column name "@1@" appears more than once in USING clause

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.66 10366

common column name "@1@" appears more than once in left table**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.67 10367

column "@1@" specified in USING clause does not exist in left table**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.68 10368

common column name "@1@" appears more than once in right table**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.69 10369

column "@1@" specified in USING clause does not exist in right table**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.70 10370

column alias list for "@1@" has too many entries

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.71 10371

argument of @1@ must not contain variables

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.72 10372

argument of @1@ must not contain aggregate functions

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.73 10373

argument of @1@ must not contain window functions

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.74 10374

@1@ "@2@" is ambiguous

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.75 10375

non-integer constant in @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.76 10376

@1@ position @2@ is not in select list

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.77 10377

window "@1@" is already defined

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.78 10378

schema "@1@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.79 10379

cannot override PARTITION BY clause of window "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.80 10380

cannot override ORDER BY clause of window "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.81 10381

cannot override frame clause of window "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.82 10382

in an aggregate with DISTINCT, ORDER BY expressions must appear in argument list

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.83 10383

for SELECT DISTINCT, ORDER BY expressions must appear in select list

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.84 10384

SELECT DISTINCT ON expressions must match initial ORDER BY expressions

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.85 10385

"@1@" is not a valid operator name

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.86 10386

extension "@1@" already exists, skipping

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.4.87 10387

array of serial is not implemented

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.88 10388

@1@ will create implicit sequence "@2@" for serial column "@3@.@4@"

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.4.89 10389

conflicting NULL/NOT NULL declarations for column "@1@" of table "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.90 10390

multiple default values specified for column "@1@" of table "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.91 10391

referenced relation "@1@" is not a table

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.92 10392

multiple primary keys for table "@1@" are not allowed

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.93 10393

cannot use an existing index in CREATE TABLE

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.94 10394

conversion "@1@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.95 10395

index "@1@" is already associated with a constraint

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.96 10396

[index "@1@" does not belong to table "@2@"](#)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.97 10397

[index "@1@" is not valid](#)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.4.98 10399

["@1@" is not a unique index](#)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5 Message Numbers Beginning with 10400

2.5.1 10400

[index "@1@" contains expressions](#)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.2 10401

"@1@" is a partial index

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.3 10402

"@1@" is a deferrable index

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.4 10403

index "@1@" does not have default sorting behavior

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.5 10404

column "@1@" named in key does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.6 10405

column "@1@" appears twice in primary key constraint

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.7 10406

column "@1@" appears twice in unique constraint

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.8 10407

index expression cannot return a set

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.9 10408

index expressions and predicates can refer only to the table being indexed

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.10 10409

rule WHERE condition cannot contain references to other relations

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.11 10410

cannot use aggregate function in rule WHERE condition

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.12 10411

cannot use window function in rule WHERE condition

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.13 10412

rules with WHERE conditions can only have SELECT, INSERT, UPDATE, or DELETE actions

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.14 10413

conditional UNION/INTERSECT/EXCEPT statements are not implemented

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.15 10414

ON SELECT rule cannot use OLD

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.16 10415

ON SELECT rule cannot use NEW

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.17 10416

ON INSERT rule cannot use OLD

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.18 10417

ON DELETE rule cannot use NEW

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.19 10418

cannot refer to OLD within WITH query

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.20 10419

cannot refer to NEW within WITH query

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.21 10420

misplaced DEFERRABLE clause

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.22 10421

multiple DEFERRABLE/NOT DEFERRABLE clauses not allowed

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.23 10422

misplaced NOT DEFERRABLE clause

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.24 10423

constraint declared INITIALLY DEFERRED must be DEFERRABLE

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.25 10424

misplaced INITIALLY DEFERRED clause

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.26 10425

multiple INITIALLY IMMEDIATE/DEFERRED clauses not allowed

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.27 10426

misplaced INITIALLY IMMEDIATE clause

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.28 10427

collations are not supported by type @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.29 10428

CREATE specifies a schema (@1@) different from the one being created (@2@)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.30 10429

table reference "@1@" is ambiguous

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.31 10430

table reference @1@ is ambiguous

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.32 10431

table name "@1@" specified more than once

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.33 10432

WITH query "@1@" has @2@ columns available but @3@ columns specified

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.34 10433

too many column aliases specified for function @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.35 10434

relation "@1@.@2@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.36 10435

type "@1@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.37 10436

a column definition list is only allowed for functions returning "record"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.38 10437

a column definition list is required for functions returning "record"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.39 10438

function "@1@" in FROM has unsupported return type @2@**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.40 10439

VALUES lists "@1@" have @2@ columns available but @3@ columns specified**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.41 10440

tables can have at most @1@ columns**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.42 10441

WITH query "@1@" does not have a RETURNING clause**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.43 10442

column @1@ of relation "@2@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.44 10443

invalid reference to FROM-clause entry for table "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.45 10444

missing FROM-clause entry for table "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.46 10445

unrecognized role option "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.47 10446

current database cannot be renamed

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.48 10447

time zone interval must be HOUR or HOUR TO MINUTE

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.49 10448

interval precision specified twice

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.50 10449

MATCH PARTIAL not yet implemented

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.51 10451

CREATE ASSERTION is not yet implemented

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.52 10452

DROP ASSERTION is not yet implemented

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.53 10453

RECHECK is no longer required

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.54 10454

missing argument

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.55 10455

WITH CHECK OPTION is not implemented

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.56 10457

number of columns does not match number of values

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.57 10458

LIMIT #,# syntax is not supported

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.58 10459

VALUES in FROM must have an alias

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.59 10460

subquery in FROM must have an alias

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.5.60 10461

precision for type float must be at least 1 bit

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.61 10462

precision for type float must be less than 54 bits

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.62 10463

UNIQUE predicate is not yet implemented

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.63 10464

RANGE PRECEDING is only supported with UNBOUNDED

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.64 10465

RANGE FOLLOWING is only supported with UNBOUNDED

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.65 10466

frame start cannot be UNBOUNDED FOLLOWING

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.66 10467

frame starting from following row cannot end with current row

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.67 10468

frame end cannot be UNBOUNDED PRECEDING

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.68 10469

frame starting from current row cannot have preceding rows

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.69 10470

frame starting from following row cannot have preceding rows

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.70 10471

type modifier cannot have parameter name

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.71 10472

wrong number of parameters on left side of OVERLAPS expression

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.72 10473

wrong number of parameters on right side of OVERLAPS expression

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.73 10474

syntax error

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.74 10475

multiple ORDER BY clauses not allowed

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.75 10476

multiple OFFSET clauses not allowed

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.76 10477

multiple LIMIT clauses not allowed

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.77 10478

multiple WITH clauses not allowed

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.78 10479

OUT and INOUT arguments aren't allowed in TABLE functions

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.79 10480

multiple COLLATE clauses not allowed

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.80 10481

operator does not exist: @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.81 10482

could not identify an ordering operator for type @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.82 10483

could not identify an equality operator for type @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.83 10484

operator requires run-time type coercion: @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.84 10485

operator @1@ is not commutative

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.85 10486

operator is only a shell: @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.86 10487

op ANY/ALL (array) requires array on right side

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.87 10488

op ANY/ALL (array) requires operator to yield boolean

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.88 10489

op ANY/ALL (array) requires operator not to return a set

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.89 10490

column "@1@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.90 10491

column "@1@" not found in data type @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.91 10492

could not identify column "@1@" in record data type

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.92 10493

column notation .@1@ applied to type @2@, which is not a composite type

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.93 10494

function @1@ does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.94 10495

NULLIF requires = operator to yield boolean

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.95 10496

arguments of row IN must all be row expressions

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.96 10498

subquery must return a column

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.5.97 10499

subquery must return only one column

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6 Message Numbers Beginning with 10500

2.6.1 10500

subquery has too many columns

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.2 10501

subquery has too few columns

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.3 10502

cannot determine type of empty array

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.4 10503

could not find range type for data type @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.5 10504

unnamed XML attribute value must be a column reference

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.6 10505

unnamed XML element value must be a column reference

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.7 10506

XML attribute name "@1@" appears more than once

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.8 10507

cannot cast XMLSERIALIZE result to @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.9 10508

unequal number of entries in row expressions

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.10 10509

cannot compare rows of zero length

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.11 10510

row comparison operator must yield type boolean, not type @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.12 10511

row comparison operator must not return a set

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.13 10512

could not determine interpretation of row comparison operator @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.14 10513

IS DISTINCT FROM requires = operator to yield boolean

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.15 10515

VALUES lists must all be the same length

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.16 10516

VALUES must not contain table references

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.17 10517

VALUES must not contain OLD or NEW references

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.18 10518

cannot use aggregate function in VALUES

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.19 10519

cannot use window function in VALUES

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.20 10520

INSERT has more expressions than target columns

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.21 10521

INSERT has more target columns than expressions

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.22 10522

DEFAULT can only appear in a VALUES list within INSERT

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.23 10523

SELECT FOR UPDATE/SHARE cannot be applied to VALUES

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.24 10524

SELECT FOR UPDATE/SHARE is not allowed with UNION/INTERSECT/EXCEPT

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.25 10525

invalid UNION/INTERSECT/EXCEPT ORDER BY clause

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.26 10526

INTO is only allowed on first SELECT of UNION/INTERSECT/EXCEPT

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.27 10527

UNION/INTERSECT/EXCEPT member statement cannot refer to other relations of same query level

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.28 10528

each @1@ query must have the same number of columns

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.29 10529

CREATE TABLE AS specifies too many column names

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.30 10530

cannot use aggregate function in UPDATE

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.31 10531

cannot use window function in UPDATE

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.32 10532

cannot use aggregate function in RETURNING

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.33 10533

cannot use window function in RETURNING

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.34 10534

RETURNING cannot contain references to other relations

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.35 10535

cannot specify both SCROLL and NO SCROLL

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.36 10537

DECLARE CURSOR must not contain data-modifying statements in WITH

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.37 10538

DECLARE CURSOR WITH HOLD ... FOR UPDATE/SHARE is not supported

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.38 10539

DECLARE INSENSITIVE CURSOR ... FOR UPDATE/SHARE is not supported

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.39 10540

SELECT FOR UPDATE/SHARE is not allowed with DISTINCT clause

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.40 10541

SELECT FOR UPDATE/SHARE is not allowed with GROUP BY clause

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.41 10542

SELECT FOR UPDATE/SHARE is not allowed with HAVING clause

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.42 10543

SELECT FOR UPDATE/SHARE is not allowed with aggregate functions

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.43 10544

SELECT FOR UPDATE/SHARE is not allowed with window functions

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.44 10545

SELECT FOR UPDATE/SHARE is not allowed with set-returning functions in the target list

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.45 10546

SELECT FOR UPDATE/SHARE must specify unqualified relation names

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.46 10547

SELECT FOR UPDATE/SHARE cannot be used with foreign table "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.47 10548

SELECT FOR UPDATE/SHARE cannot be applied to a join

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.48 10549

SELECT FOR UPDATE/SHARE cannot be applied to a function

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.49 10550

SELECT FOR UPDATE/SHARE cannot be applied to a WITH query

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.50 10551

relation "@1@" in FOR UPDATE/SHARE clause not found in FROM clause

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.51 10552

aggregate function calls cannot contain window function calls

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.52 10553

aggregates not allowed in WHERE clause

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.53 10554

aggregates not allowed in JOIN conditions

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.54 10555

aggregates not allowed in GROUP BY clause

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.55 10556

aggregate functions not allowed in a recursive query's recursive term

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.56 10557

window functions not allowed in WHERE clause

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.57 10558

window functions not allowed in JOIN conditions

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.58 10559

window functions not allowed in HAVING clause

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.59 10560

window functions not allowed in GROUP BY clause

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.60 10561

window functions not allowed in window definition

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.61 10562

column "@1@.@2@" must appear in the GROUP BY clause or be used in an aggregate function

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.62 10563

subquery uses ungrouped column "@1@.@2@" from outer query

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.63 10564

parameter name "@1@" used more than once

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.64 10565

positional argument cannot follow named argument

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.65 10566

@1@(*) specified, but @2@ is not an aggregate function

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.66 10567

DISTINCT specified, but @1@ is not an aggregate function

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.67 10568

ORDER BY specified, but @1@ is not an aggregate function

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.68 10569

OVER specified, but @1@ is not a window function nor an aggregate function

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.69 10570

function @1@ is not unique

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.70 10571

database "@1@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.71 10572

@1@(*) must be used to call a parameterless aggregate function

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.72 10573

aggregates cannot return sets

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.73 10574

aggregates cannot use named arguments

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.74 10575

window function call requires an OVER clause

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.75 10576

DISTINCT is not implemented for window functions

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.76 10577

aggregate ORDER BY is not implemented for window functions

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.77 10578

window functions cannot return sets

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.78 10579

window functions cannot use named arguments

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.79 10580

extension "@1@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.80 10582

aggregate @1@(*) does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.81 10583

server "@1@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.82 10584

function "@1@" is an aggregate function

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.83 10585

argument of @1@ must be a type name

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.84 10586

argument of @1@ must not return a set

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.85 10587

argument of @1@ must be type boolean, not type @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.86 10588

@1@ types @2@ and @3@ cannot be matched

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.87 10589

@1@ could not convert type @2@ to @3@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.88 10590

arguments declared "anyelement" are not all alike

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.89 10591

arguments declared "anyarray" are not all alike

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.90 10592

argument declared "anyarray" is not an array but type @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.91 10593

argument declared "anyarray" is not consistent with argument declared "anyelement"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.92 10594

could not determine polymorphic type because input has type "unknown"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.93 10595

type matched to anyonarray is an array type: @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.94 10596

type matched to anyenum is not an enum type: @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.95 10597

recursive reference to query "@1@" must not appear within its non-recursive term

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.96 10598

recursive reference to query "@1@" must not appear within a subquery

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.6.97 10599

recursive reference to query "@1@" must not appear within an outer join

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7 Message Numbers Beginning with 10600

2.7.1 10600

recursive reference to query "@1@" must not appear within INTERSECT

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.2 10601

recursive reference to query "@1@" must not appear within EXCEPT

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.3 10602

WITH query name "@1@" specified more than once

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.4 10604

WITH clause containing a data-modifying statement must be at the top level

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.5 10605

recursive query "@1@" column @2@ has type @3@ in non-recursive term but type @4@ overall

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.6 10606

recursive query "@1@" column @2@ has collation "@3@" in non-recursive term but collation "@4@" overall

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.7 10607

table "@1@" has @2@ columns available but @3@ columns specified

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.8 10608

mutual recursion between WITH items is not implemented

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.9 10609

recursive query "@1@" must not contain data-modifying statements

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.10 10610

recursive query "@1@" does not have the form non-recursive-term UNION [ALL] recursive-term

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.11 10611

ORDER BY in a recursive query is not implemented

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.12 10612

OFFSET in a recursive query is not implemented

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.13 10613

LIMIT in a recursive query is not implemented

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.14 10614

FOR UPDATE/SHARE in a recursive query is not implemented

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.15 10615

recursive reference to query "@1@" must not appear more than once

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.16 10616

unsafe use of string constant with Unicode escapes

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.17 10617

invalid Unicode escape

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.18 10618

unsafe use of \\' in a string literal

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.19 10619

@1@ at end of input

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.20 10620

@1@ at or near "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.21 10621

nonstandard use of \ in a string literal

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.22 10622

nonstandard use of \\ in a string literal

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.23 10623

nonstandard use of escape in a string literal

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.7.24 10624

collation mismatch between implicit collations "@1@" and "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.25 10625

collation mismatch between explicit collations "@1@" and "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.26 10626

target lists can have at most @1@ entries

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.27 10627

cannot subscript type @1@ because it is not an array

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.28 10628

array subscript must have type integer

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.29 10629

array assignment to "@1@" requires type @2@ but expression is of type @3@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.30 10630

improper @1@TYPE reference (too few dotted names): @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.31 10631

improper @1@TYPE reference (too many dotted names): @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.32 10632

type reference @1@ converted to @2@

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.7.33 10633

return type @1@ is only a shell

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.34 10634

type modifier cannot be specified for shell type "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.35 10635

type modifier is not allowed for type "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.36 10636

type modifiers must be simple constants or identifiers

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.37 10637

invalid type name "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.38 10638

canceling the wait for synchronous replication and terminating connection due to administrator command

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.7.39 10639

canceling wait for synchronous replication due to user request

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.7.40 10640

standby "@1@" now has synchronous standby priority @2@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.7.41 10641

standby "@1@" is now the synchronous standby with priority @2@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.7.42 10642

could not connect to the primary server: @1@

[Description]

The database server was disconnected during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Communication may have been disconnected for the following reasons:

- An error occurred in the communication line (TCP/IP etc.)
- The database server terminated abnormally.

Take the following actions:

- Eliminate the cause of the communication disconnection.

Examine the application and check whether the transaction for implementing update is a long transaction. Judge whether it is a long transaction from the following viewpoints and modify the application.

- a) If the COMMIT process is not executed after update, add the COMMIT process.
 - b) If the total number of update records in a single transaction is high, split it into short transactions.
 - c) If search was conducted for a long period of time after update, execute COMMIT after update or review the search SQL statement.
- If none of the above situations applies, perform the following:
 - a) Confirm that the database server has not stopped.
 - b) If the database server is starting or stopping, re-execute the command after the database server starts.

2.7.43 10643

could not receive database system identifier and timeline ID from the primary server: @1@

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.7.44 10644

invalid response from primary server

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.7.45 10645

database system identifier differs between the primary and standby

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.46 10646

timeline @1@ of the primary does not match recovery target timeline @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.7.47 10647

could not start WAL streaming: @1@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.7.48 10648

streaming replication successfully connected to primary

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.7.49 10649

socket not open

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.7.50 10650

select() failed: @1@

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.7.51 10651

could not receive data from WAL stream: @1@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.7.52 10652

replication terminated by primary server

[Description]

Primary server has stopped.

[System Processing]

Processing will be aborted.

[Action]

No action is required.

2.7.53 10653

could not send data to WAL stream: @1@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.7.54 10654

syntax error: unexpected character "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.55 10655

base backup could not send data, aborting backup

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.7.56 10656

duplicate option "@1@"**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.57 10657

shutdown requested, aborting active base backup**[Description]**

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.7.58 10658

could not stat file or directory "@1@": @2@**[Description]**

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.7.59 10659

could not remove symbolic link "@1@": @2@**[Description]**

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.7.60 10660

skipping special file "@1@"

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.7.61 10661

archive member "@1@" too large for tar format

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.62 10663

unexpected EOF on standby connection

[Description]

An error occurred because execution is temporarily impossible.

[System Processing]

Processing will be aborted.

[Action]

Restart the application. If the same error occurs when you restart the application, to check if there are any problems in the database server.

2.7.63 10664

invalid standby handshake message type @1@

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.7.64 10666

invalid standby query string: @1@

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.7.65 10667

terminating walsender process due to replication timeout

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.7.66 10668

standby "@1@" has now caught up with primary

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.7.67 10669

number of requested standby connections exceeds max_wal_senders (currently @1@)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.68 10670

requested WAL segment @1@ has already been removed

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.7.69 10671

could not read from log file @1 @, segment @2 @, offset @3 @, length @4 @: @5 @

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.7.70 10672

materialize mode required, but it is not allowed in this context

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.71 10673

terminating walreceiver process due to administrator command

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.7.72 10674

cannot continue WAL streaming, recovery has already ended

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.7.73 10675

authentication failed for user "@1@": host rejected

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.74 10676

Kerberos 5 authentication failed for user "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.75 10677

"trust" authentication failed for user "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.76 10678

Ident authentication failed for user "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.77 10679

Peer authentication failed for user "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.78 10680

password authentication failed for user "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.79 10681

GSSAPI authentication failed for user "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.80 10682

SSPI authentication failed for user "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.81 10683

PAM authentication failed for user "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.82 10684

LDAP authentication failed for user "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.83 10685

certificate authentication failed for user "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.84 10686

RADIUS authentication failed for user "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.85 10687

authentication failed for user "@1@": invalid authentication method**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.86 10689

connection requires a valid client certificate**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.87 10690

pg_hba.conf rejects replication connection for host "@1@", user "@2@", @3@**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.88 10691

pg_hba.conf rejects replication connection for host "@1@", user "@2@"**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.89 10692

pg_hba.conf rejects connection for host "@1@", user "@2@", database "@3@", @4@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.90 10693

[pg_hba.conf rejects connection for host "@1@", user "@2@", database "@3@"](#)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.91 10694

[no pg_hba.conf entry for replication connection from host "@1@", user "@2@", @3@](#)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.92 10695

[no pg_hba.conf entry for replication connection from host "@1@", user "@2@"](#)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.93 10696

[no pg_hba.conf entry for host "@1@", user "@2@", database "@3@", @4@](#)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.94 10697

no pg_hba.conf entry for host "@1@", user "@2@", database "@3@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.95 10698

MD5 authentication is not supported when "db_user_namespace" is enabled

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.7.96 10699

expected password response, got message type @1@

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.8 Message Numbers Beginning with 10700

2.8.1 10700

invalid password packet size

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.8.2 10701

received password packet

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.8.3 10702

Kerberos initialization returned error @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.4 10703

Kerberos keytab resolving returned error @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.5 10704

Kerberos sname_to_principal("@1@", "@2@") returned error @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.6 10705

Kerberos rcvauth returned error @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.7 10706

Kerberos unparse_name returned error @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.8 10707

GSSAPI is not supported in protocol version 2

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.8.9 10708

out of memory

[Description]

There was insufficient free space in the server's memory during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Estimate memory usage and take the following action:

- If the number of simultaneous connections from client applications is high, reduce it.
- If the number of simultaneous SQL executions is high, reduce it.

2.8.10 10709

expected GSS response, got message type @1@

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.8.11 10710

SSPI is not supported in protocol version 2

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.8.12 10711

expected SSPI response, got message type @1@

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.8.13 10712

could not create socket for Ident connection: @1@

[Description]

The database server was disconnected during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Communication may have been disconnected for the following reasons:

- An error occurred in the communication line (TCP/IP etc.)
- The database server terminated abnormally.

Take the following actions:

- Eliminate the cause of the communication disconnection.

Examine the application and check whether the transaction for implementing update is a long transaction. Judge whether it is a long transaction from the following viewpoints and modify the application.

- a) If the COMMIT process is not executed after update, add the COMMIT process.
- b) If the total number of update records in a single transaction is high, split it into short transactions.
- c) If search was conducted for a long period of time after update, execute COMMIT after update or review the search SQL statement.

- If none of the above situations applies, perform the following:

- a) Confirm that the database server has not stopped.
- b) If the database server is starting or stopping, re-execute the command after the database server starts.

2.8.14 10713

could not bind to local address "@1@": @2@

[Description]

The database server was disconnected during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Communication may have been disconnected for the following reasons:

- An error occurred in the communication line (TCP/IP etc.)
- The database server terminated abnormally.

Take the following actions:

- Eliminate the cause of the communication disconnection.

Examine the application and check whether the transaction for implementing update is a long transaction. Judge whether it is a long transaction from the following viewpoints and modify the application.

- a) If the COMMIT process is not executed after update, add the COMMIT process.
- b) If the total number of update records in a single transaction is high, split it into short transactions.
- c) If search was conducted for a long period of time after update, execute COMMIT after update or review the search SQL statement.

- If none of the above situations applies, perform the following:

- a) Confirm that the database server has not stopped.
- b) If the database server is starting or stopping, re-execute the command after the database server starts.

2.8.15 10714

could not connect to Ident server at address "@1@", port @2@: @3@

[Description]

The database server was disconnected during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Communication may have been disconnected for the following reasons:

- An error occurred in the communication line (TCP/IP etc.)
- The database server terminated abnormally.

Take the following actions:

- Eliminate the cause of the communication disconnection.

Examine the application and check whether the transaction for implementing update is a long transaction. Judge whether it is a long transaction from the following viewpoints and modify the application.

- a) If the COMMIT process is not executed after update, add the COMMIT process.
 - b) If the total number of update records in a single transaction is high, split it into short transactions.
 - c) If search was conducted for a long period of time after update, execute COMMIT after update or review the search SQL statement.
- If none of the above situations applies, perform the following:
 - a) Confirm that the database server has not stopped.
 - b) If the database server is starting or stopping, re-execute the command after the database server starts.

2.8.16 10715

could not send query to Ident server at address "@1@", port @2@: @3@

[Description]

The database server was disconnected during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Communication may have been disconnected for the following reasons:

- An error occurred in the communication line (TCP/IP etc.)
- The database server terminated abnormally.

Take the following actions:

- Eliminate the cause of the communication disconnection.

Examine the application and check whether the transaction for implementing update is a long transaction. Judge whether it is a long transaction from the following viewpoints and modify the application.

- a) If the COMMIT process is not executed after update, add the COMMIT process.
 - b) If the total number of update records in a single transaction is high, split it into short transactions.
 - c) If search was conducted for a long period of time after update, execute COMMIT after update or review the search SQL statement.
- If none of the above situations applies, perform the following:
 - a) Confirm that the database server has not stopped.
 - b) If the database server is starting or stopping, re-execute the command after the database server starts.

2.8.17 10716

could not receive response from Ident server at address "@1@", port @2@: @3@

[Description]

The database server was disconnected during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Communication may have been disconnected for the following reasons:

- An error occurred in the communication line (TCP/IP etc.)
- The database server terminated abnormally.

Take the following actions:

- Eliminate the cause of the communication disconnection.

Examine the application and check whether the transaction for implementing update is a long transaction. Judge whether it is a long transaction from the following viewpoints and modify the application.

- a) If the COMMIT process is not executed after update, add the COMMIT process.
 - b) If the total number of update records in a single transaction is high, split it into short transactions.
 - c) If search was conducted for a long period of time after update, execute COMMIT after update or review the search SQL statement.
- If none of the above situations applies, perform the following:
 - a) Confirm that the database server has not stopped.
 - b) If the database server is starting or stopping, re-execute the command after the database server starts.

2.8.18 10717

invalidly formatted response from Ident server: "@1@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.19 10718

peer authentication is not supported on this platform

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.8.20 10719

could not get peer credentials: @1@

[Description]

The database server was disconnected during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Communication may have been disconnected for the following reasons:

- An error occurred in the communication line (TCP/IP etc.)
- The database server terminated abnormally.

Take the following actions:

- Eliminate the cause of the communication disconnection.

Examine the application and check whether the transaction for implementing update is a long transaction. Judge whether it is a long transaction from the following viewpoints and modify the application.

- a) If the COMMIT process is not executed after update, add the COMMIT process.
 - b) If the total number of update records in a single transaction is high, split it into short transactions.
 - c) If search was conducted for a long period of time after update, execute COMMIT after update or review the search SQL statement.
- If none of the above situations applies, perform the following:
 - a) Confirm that the database server has not stopped.
 - b) If the database server is starting or stopping, re-execute the command after the database server starts.

2.8.21 10720

local user with ID @1@ does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.8.22 10721

empty password returned by client

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.8.23 10722

error from underlying PAM layer: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.24 10723

could not create PAM authenticator: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.25 10724

pam_set_item(PAM_USER) failed: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.26 10725

pam_set_item(PAM_CONV) failed: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.27 10726

pam_authenticate failed: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.28 10727

pam_acct_mgmt failed: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.29 10728

could not release PAM authenticator: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.30 10729

could not initialize LDAP: error code @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.31 10730

could not set LDAP protocol version: error code @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.32 10731

could not load wldap32.dll

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.33 10732

could not load function _ldap_start_tls_sA in wldap32.dll

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.34 10733

could not start LDAP TLS session: error code @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.35 10734

LDAP server not specified

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.8.36 10735

invalid character in user name for LDAP authentication

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.8.37 10736

could not perform initial LDAP bind for ldapbinddn "@1@" on server "@2@" : error code @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.38 10737

could not search LDAP for filter "@1@" on server "@2@" : error code @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.39 10738

LDAP search failed for filter "@1@" on server "@2@" : no such user

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.8.40 10739

LDAP search failed for filter "@1@" on server "@2@" : user is not unique (@3@ matches)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.8.41 10740

could not get dn for the first entry matching "@1@" on server "@2@" : @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.42 10741

could not unbind after searching for user "@1@" on server "@2@" : @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.43 10742

LDAP login failed for user "@1@" on server "@2@" : error code @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.44 10743

certificate authentication failed for user "@1@": client certificate contains no user name

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.8.45 10744

RADIUS server not specified

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.8.46 10745

RADIUS secret not specified

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.8.47 10746

could not translate RADIUS server name "@1@" to address: @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.8.48 10747

RADIUS authentication does not support passwords longer than 16 characters

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.8.49 10748

could not generate random encryption vector

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.50 10749

could not perform MD5 encryption of password

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.51 10750

could not create RADIUS socket: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.52 10751

could not bind local RADIUS socket: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.53 10752

could not send RADIUS packet: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.54 10753

timeout waiting for RADIUS response

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.55 10754

could not check status on RADIUS socket: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.56 10755

could not read RADIUS response: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.57 10756

RADIUS response was sent from incorrect port: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.58 10757

RADIUS response too short: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.59 10759

RADIUS response is to a different request: @1@ (should be @2@)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.60 10760

could not perform MD5 encryption of received packet

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.61 10761

RADIUS response has incorrect MD5 signature

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.62 10762

RADIUS response has invalid code (@1@) for user "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.63 10763

SSL error: @1@

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.8.64 10764

unrecognized SSL error code: @1@

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.8.65 10765

SSL renegotiation failure

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.8.66 10766

SSL failed to send renegotiation request

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.8.67 10767

could not create SSL context: @1@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.68 10768

could not load server certificate file "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.69 10769

could not access private key file "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.70 10770

private key file "@1@" has group or world access

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.71 10771

could not load private key file "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.72 10772

check of private key failed: @1@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.73 10774

could not load root certificate file "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.74 10775

SSL certificate revocation list file "@1@" ignored

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.8.75 10776

could not load SSL certificate revocation list file "@1@": @2@

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.8.76 10777

could not initialize SSL connection: @1@

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.8.77 10778

could not set SSL socket: @1@

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.8.78 10779

could not accept SSL connection: @1@

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.8.79 10780

could not accept SSL connection: EOF detected

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.8.80 10781

could not accept SSL connection: @1@

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.8.81 10782

SSL certificate's common name contains embedded null

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.8.82 10783

SSL connection from "@1@"

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.8.83 10784

could not translate host name "@1@" to address: @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.8.84 10785

could not translate service "@1@" to address: @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.8.85 10786

could not bind to all requested addresses: MAXLISTEN (@1@) exceeded

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.8.86 10787

could not create @1@ socket: @2@

[Description]

The database server was disconnected during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Communication may have been disconnected for the following reasons:

- An error occurred in the communication line (TCP/IP etc.)
- The database server terminated abnormally.

Take the following actions:

- Eliminate the cause of the communication disconnection.

Examine the application and check whether the transaction for implementing update is a long transaction. Judge whether it is a long transaction from the following viewpoints and modify the application.

- a) If the COMMIT process is not executed after update, add the COMMIT process.
 - b) If the total number of update records in a single transaction is high, split it into short transactions.
 - c) If search was conducted for a long period of time after update, execute COMMIT after update or review the search SQL statement.
- If none of the above situations applies, perform the following:
 - a) Confirm that the database server has not stopped.
 - b) If the database server is starting or stopping, re-execute the command after the database server starts.

2.8.87 10788

setsockopt(SO_REUSEADDR) failed: @1@

[Description]

The database server was disconnected during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Communication may have been disconnected for the following reasons:

- An error occurred in the communication line (TCP/IP etc.)
- The database server terminated abnormally.

Take the following actions:

- Eliminate the cause of the communication disconnection.

Examine the application and check whether the transaction for implementing update is a long transaction. Judge whether it is a long transaction from the following viewpoints and modify the application.

a) If the COMMIT process is not executed after update, add the COMMIT process.

b) If the total number of update records in a single transaction is high, split it into short transactions.

c) If search was conducted for a long period of time after update, execute COMMIT after update or review the search SQL statement.

- If none of the above situations applies, perform the following:

a) Confirm that the database server has not stopped.

b) If the database server is starting or stopping, re-execute the command after the database server starts.

2.8.88 10789

setsockopt(IPV6_V6ONLY) failed: @1@

[Description]

The database server was disconnected during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Communication may have been disconnected for the following reasons:

- An error occurred in the communication line (TCP/IP etc.)

- The database server terminated abnormally.

Take the following actions:

- Eliminate the cause of the communication disconnection.

Examine the application and check whether the transaction for implementing update is a long transaction. Judge whether it is a long transaction from the following viewpoints and modify the application.

a) If the COMMIT process is not executed after update, add the COMMIT process.

b) If the total number of update records in a single transaction is high, split it into short transactions.

c) If search was conducted for a long period of time after update, execute COMMIT after update or review the search SQL statement.

- If none of the above situations applies, perform the following:

a) Confirm that the database server has not stopped.

b) If the database server is starting or stopping, re-execute the command after the database server starts.

2.8.89 10790

could not bind @1@ socket: @2@

[Description]

The database server was disconnected during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Communication may have been disconnected for the following reasons:

- An error occurred in the communication line (TCP/IP etc.)
- The database server terminated abnormally.

Take the following actions:

- Eliminate the cause of the communication disconnection.

Examine the application and check whether the transaction for implementing update is a long transaction. Judge whether it is a long transaction from the following viewpoints and modify the application.

- If the COMMIT process is not executed after update, add the COMMIT process.
 - If the total number of update records in a single transaction is high, split it into short transactions.
 - If search was conducted for a long period of time after update, execute COMMIT after update or review the search SQL statement.
- If none of the above situations applies, perform the following:
 - Confirm that the database server has not stopped.
 - If the database server is starting or stopping, re-execute the command after the database server starts.

2.8.90 10791

could not listen on @1@ socket: @2@

[Description]

The database server was disconnected during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Communication may have been disconnected for the following reasons:

- An error occurred in the communication line (TCP/IP etc.)
- The database server terminated abnormally.

Take the following actions:

- Eliminate the cause of the communication disconnection.

Examine the application and check whether the transaction for implementing update is a long transaction. Judge whether it is a long transaction from the following viewpoints and modify the application.

- If the COMMIT process is not executed after update, add the COMMIT process.
 - If the total number of update records in a single transaction is high, split it into short transactions.
 - If search was conducted for a long period of time after update, execute COMMIT after update or review the search SQL statement.
- If none of the above situations applies, perform the following:
 - Confirm that the database server has not stopped.
 - If the database server is starting or stopping, re-execute the command after the database server starts.

2.8.91 10792

type @1@ does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.8.92 10793

could not set group of file "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.93 10794

could not set permissions of file "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.8.94 10795

could not accept new connection: @1@

[Description]

The database server was disconnected during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Communication may have been disconnected for the following reasons:

- An error occurred in the communication line (TCP/IP etc.)
- The database server terminated abnormally.

Take the following actions:

- Eliminate the cause of the communication disconnection.

Examine the application and check whether the transaction for implementing update is a long transaction. Judge whether it is a long transaction from the following viewpoints and modify the application.

- a) If the COMMIT process is not executed after update, add the COMMIT process.
 - b) If the total number of update records in a single transaction is high, split it into short transactions.
 - c) If search was conducted for a long period of time after update, execute COMMIT after update or review the search SQL statement.
- If none of the above situations applies, perform the following:
- a) Confirm that the database server has not stopped.
 - b) If the database server is starting or stopping, re-execute the command after the database server starts.

2.8.95 10796

could not set socket to non-blocking mode: @1@

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.8.96 10797

could not set socket to blocking mode: @1@

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.8.97 10798

could not receive data from client: @1@

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.8.98 10799

unexpected EOF within message length word

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.9 Message Numbers Beginning with 10800

2.9.1 10800

invalid message length

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.9.2 10801

incomplete message from client

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.9.3 10802

could not send data to client: @1@

[Description]

[System Processing]

[Action]

10803

authentication file token too long, skipping: "@1@"

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.9.4 10804

could not open secondary authentication file "@@1@" as "@2@" : @3@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.9.5 10805

could not translate host name "@1@", service "@2@" to address: @3@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.6 10806

authentication option "@1@" is only valid for authentication methods @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.9.7 10807

authentication method "@1@" requires argument "@2@" to be set

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.9.8 10808

local connections are not supported by this build

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.9.9 10809

hostssl requires SSL to be turned on

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.10 10810

hostssl is not supported by this build

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.9.11 10811

invalid connection type "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.12 10812

end-of-line before database specification

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.13 10813

end-of-line before role specification

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.14 10814

end-of-line before IP address specification

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.15 10815

invalid IP address "@1@": @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.16 10816

specifying both host name and CIDR mask is invalid: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.17 10817

invalid CIDR mask in address "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.18 10818

end-of-line before netmask specification

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.19 10819

invalid IP mask "@1@": @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.20 10820

IP address and mask do not match

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.21 10821

end-of-line before authentication method

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.22 10822

invalid authentication method "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.23 10823

invalid authentication method "@1@": not supported by this build

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.9.24 10824

krb5 authentication is not supported on local sockets

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.25 10825

gssapi authentication is not supported on local sockets

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.26 10826

peer authentication is only supported on local sockets

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.27 10827

cert authentication is only supported on hostssl connections

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.28 10828

authentication option not in name=value format: @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.29 10829

clientcert can only be configured for "hostssl" rows

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.30 10830

client certificates can only be checked if a root certificate store is available

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.9.31 10831

clientcert can not be set to 0 when using "cert" authentication

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.32 10832

invalid LDAP port number: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.33 10833

invalid RADIUS port number: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.34 10834

unrecognized authentication option name: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.35 10835

cannot use ldapbasedn, ldapbinddn, ldapbindpasswd, or ldapsearchattribute together with ldapprefix

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.36 10836

authentication method "ldap" requires argument "ldapbasedn", "ldapprefix", or "ldapsuffix" to be set

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.37 10837

could not open configuration file "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.9.38 10838

invalid regular expression "@1@": @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.39 10839

regular expression match for "@1@" failed: @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.40 10840

regular expression "@1@" has no subexpressions as requested by backreference in "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.41 10841

missing entry in file "@1@" at end of line @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.42 10842

provided user name (@1@) and authenticated user name (@2@) do not match

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.43 10843

no match in usermap "@1@" for user "@2@" authenticated as "@3@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.44 10844

could not open server file "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.9.45 10845

invalid large-object descriptor: @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.46 10846

permission denied for large object @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.47 10847

large object descriptor @1@ was not opened for writing

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.48 10848

must be owner of large object @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.49 10849

must be superuser to use server-side lo_import()

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.50 10850

could not read server file "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.9.51 10851

could not create server file "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.9.52 10852

must be superuser to use server-side lo_export()

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.53 10853

could not write server file "@1@": @2@

[Description]

There was insufficient free space in the disk of the database server during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Delete user data stored in the database server to free up space on the disk.

2.9.54 10854

could not write file "@1@": @2@

[Description]

There was insufficient free space in the disk of the database server during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Delete user data stored in the database server to free up space on the disk.

2.9.55 10855

no data left in message

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.9.56 10856

insufficient data left in message

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.57 10857

invalid string in message

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.9.58 10858

invalid message format

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.9.59 10859

"@1@" is not a sequence

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.60 10860

shared tables cannot be toasted after initdb

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.61 10861

cannot drop @1@ because it is required by the database system

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.62 10862

role @1@ was concurrently dropped

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.63 10863

tablespace @1@ was concurrently dropped

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.64 10864

database @1@ was concurrently dropped

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.65 10865

cannot drop objects owned by @1@ because they are required by the database system

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.66 10866

permission denied to create "@1@.@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.67 10867

joins can have at most @1@ columns

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.68 10868

column name "@1@" conflicts with a system column name

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.69 10869

column "@1@" specified more than once

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.70 10870

column "@1@" has type "unknown"**[Description]**

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.9.71 10871

column "@1@" has pseudo-type @2@**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.72 10872

composite type @1@ cannot be made a member of itself**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.73 10873

no collation was derived for column "@1@" with collatable type @2@**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.74 10874

relation "@1@" already exists

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.75 10875

type "@1@" already exists

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.76 10876

check constraint "@1@" already exists

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.77 10877

constraint "@1@" for relation "@2@" already exists

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.78 10878

merging constraint "@1@" with inherited definition

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.9.79 10879

cannot use column references in default expression

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.80 10880

default expression must not return a set

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.81 10881

cannot use subquery in default expression

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.82 10882

cannot use aggregate function in index expression

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.83 10883

cannot use window function in transform expression

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.84 10884

subfield "@1@" is of type @2@ but expression is of type @3@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.85 10885

only table "@1@" can be referenced in check constraint

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.86 10886

cannot use subquery in check constraint

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.87 10887

cannot use aggregate function in check constraint

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.88 10888

cannot use window function in check constraint

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.89 10889

unsupported ON COMMIT and foreign key combination

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.90 10890

cannot truncate a table referenced in a foreign key constraint

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.91 10891

invalid type internal size @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.92 10892

alignment "@1@" is invalid for passed-by-value type of size @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.93 10893

internal size @1@ is invalid for passed-by-value type

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.94 10894

alignment "@1@" is invalid for variable-length type

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.95 10895

fixed-size types must have storage PLAIN

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.96 10896

could not form array type name for type "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.97 10897

cannot determine transition data type

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.98 10898

return type of transition function @1@ is not @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.9.99 10899

must not omit initial value when transition function is strict and transition type is not compatible with input type

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10 Message Numbers Beginning with 10900

2.10.1 10900

cannot determine result data type

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.2 10901

unsafe use of pseudo-type "internal"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.3 10902

sort operator can only be specified for single-argument aggregates

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.4 10903

function @1@ returns a set

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.5 10904

function @1 @ requires run-time type coercion

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.6 10905

large object @1 @ does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.7 10906

primary keys cannot be expressions

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.8 10907

user-defined indexes on system catalog tables are not supported

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.9 10908

concurrent index creation on system catalog tables is not supported

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.10 10909

shared indexes cannot be created after initdb

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.11 10910

building index "@1@" on table "@2@"

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.10.12 10911

cannot reindex temporary tables of other sessions

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.13 10912

invalid enum label "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.14 10913

"@1@" is not an existing enum label

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.15 10914

ALTER TYPE ADD BEFORE/AFTER is incompatible with binary upgrade

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.16 10915

"@1@" is already an attribute of type @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.17 10916

function "@1@" already exists with same argument types

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.18 10917

cannot change return type of existing function

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.19 10918

cannot change name of input parameter "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.20 10919

cannot remove parameter defaults from existing function

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.21 10920

cannot change data type of existing parameter default value

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.22 10921

function "@1@" is not an aggregate function

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.23 10922

"@1@" is an aggregate function

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.24 10923

function "@1@" is a window function

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.25 10924

function "@1@" is not a window function

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.26 10925

there is no built-in function named "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.27 10926

SQL functions cannot return type @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.28 10927

SQL functions cannot have arguments of type @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.29 10928

invalid fork name

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.30 10929

cannot drop @1@ because @2@ requires it

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.31 10930

drop auto-cascades to @1@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.10.32 10931

cannot drop @1@ because other objects depend on it

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.33 10932

cannot drop desired object(s) because other objects depend on them

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.34 10934

constraint "@1@" for domain @2@ already exists

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.35 10935

table "@1@" has multiple constraints named "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.36 10936

constraint "@1@" for table "@2@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.37 10937

grant options can only be granted to roles

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.38 10938

no privileges were granted for column "@1@" of relation "@2@"

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.10.39 10939

no privileges were granted for "@1@"

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.10.40 10940

not all privileges were granted for column "@1@" of relation "@2@"

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.10.41 10941

not all privileges were granted for "@1@"

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.10.42 10942

no privileges could be revoked for column "@1@" of relation "@2@"

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.10.43 10943

no privileges could be revoked for "@1@"

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.10.44 10944

not all privileges could be revoked for column "@1@" of relation "@2@"

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.10.45 10945

not all privileges could be revoked for "@1@"

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.10.46 10946

invalid privilege type @1 @ for relation

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.47 10947

invalid privilege type @1 @ for sequence

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.48 10948

invalid privilege type @1 @ for database

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.49 10949

invalid privilege type @1 @ for domain

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.50 10950

invalid privilege type @1 @ for function

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.51 10951

invalid privilege type @1 @ for large object

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.52 10952

invalid privilege type @1 @ for language

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.53 10953

invalid privilege type @1 @ for schema

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.54 10954

invalid privilege type @1 @ for foreign-data wrapper

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.55 10955

invalid privilege type @1 @ for foreign server

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.56 10956

column privileges are only valid for relations

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.57 10957

conflicting or redundant options

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.58 10958

default privileges cannot be set for columns

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.59 10959

"@1@" is not a domain

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.60 10960

sequence "@1@" only supports USAGE, SELECT, and UPDATE privileges

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.10.61 10961

invalid privilege type USAGE for table

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.62 10962

invalid privilege type @1 @ for tablespace

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.63 10963

sequence "@1@" only supports SELECT column privileges

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.10.64 10964

language "@1@" is not trusted

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.65 10965

unrecognized privilege type "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.66 10966

permission denied for column @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.67 10967

permission denied for relation @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.68 10968

permission denied for sequence @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.69 10969

permission denied for database @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.70 10970

permission denied for function @1 @**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.71 10971

permission denied for operator @1 @**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.72 10972

permission denied for type @1 @**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.73 10973

permission denied for language @1 @**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.74 10974

permission denied for large object @1 @

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.75 10975

[permission denied for schema @1@](#)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.76 10976

[permission denied for operator class @1@](#)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.77 10977

[permission denied for operator family @1@](#)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.78 10978

[permission denied for collation @1@](#)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.79 10979

permission denied for conversion @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.80 10980

permission denied for tablespace @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.81 10981

permission denied for text search dictionary @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.82 10982

permission denied for text search configuration @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.83 10983

[permission denied for foreign-data wrapper @1@](#)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.84 10984

[permission denied for foreign server @1@](#)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.85 10985

[permission denied for extension @1@](#)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.86 10986

[must be owner of relation @1@](#)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.87 10987

must be owner of sequence @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.88 10988

must be owner of database @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.89 10989

must be owner of function @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.90 10990

must be owner of operator @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.91 10991

must be owner of type @1@**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.92 10992

must be owner of language @1@**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.93 10993

must be owner of large object @1@**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.94 10994

must be owner of schema @1@**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.95 10995

must be owner of operator class @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.96 10996

must be owner of operator family @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.97 10997

must be owner of collation @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.98 10998

must be owner of conversion @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.10.99 10999

must be owner of tablespace @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11 Message Numbers Beginning with 11000

2.11.1 11000

must be owner of text search dictionary @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.2 11001

must be owner of text search configuration @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.3 11002

must be owner of foreign-data wrapper @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.4 11003

must be owner of foreign server @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.5 11004

must be owner of extension @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.6 11005

permission denied for column "@1@" of relation "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.7 11006

role with OID @1@ does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.8 11007

attribute @1@ of relation with OID @2@ does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.9 11008

relation with OID @1@ does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.10 11009

database with OID @1@ does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.11 11010

function with OID @1@ does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.12 11011

language with OID @1@ does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.13 11012

schema with OID @1@ does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.14 11013

tablespace with OID @1@ does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.15 11014

foreign-data wrapper with OID @1@ does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.16 11015

foreign server with OID @1@ does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.17 11016

type with OID @1@ does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.18 11017

operator with OID @1@ does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.19 11018

operator class with OID @1@ does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.20 11019

operator family with OID @1@ does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.21 11020

text search dictionary with OID @1@ does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.22 11021

text search configuration with OID @1@ does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.23 11022

collation with OID @1@ does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.24 11023

conversion with OID @1@ does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.25 11024

extension with OID @1@ does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.26 11025

conversion "@1@" already exists

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.27 11026

default conversion for @1@ to @2@ already exists

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.28 11027

cross-database references are not implemented: @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.29 11028

temporary tables cannot specify a schema name

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.30 11029

no schema has been selected to create in

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.31 11030

text search parser "@1@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.32 11031

text search dictionary "@1@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.33 11032

text search template "@1@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.34 11033

text search configuration "@1@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.35 11034

@1@ is already in schema "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.36 11035

cannot move objects into or out of temporary schemas

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.37 11036

cannot move objects into or out of TOAST schema

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.38 11037

language "@1@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.39 11038

improper relation name (too many dotted names): @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.40 11039

collation "@1@" for encoding "@2@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.41 11040

cursor "@1@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.42 11041

permission denied to create temporary tables in database "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.43 11042

cannot create temporary tables during recovery

[Description]

An error occurred because execution is temporarily impossible.

[System Processing]

Processing will be aborted.

[Action]

Restart the application. If the same error occurs when you restart the application, to check if there are any problems in the database server.

2.11.44 11043

database name cannot be qualified

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.45 11044

extension name cannot be qualified

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.46 11045

"@1@" is not a table

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.47 11046

"@1@" is not a foreign table

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.48 11047

must be owner of type @1@ or type @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.49 11048

must be superuser

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.50 11049

must have CREATEROLE privilege

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.51 11050

schema "@1@" already exists

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.52 11051

@1@ is not a valid encoding name

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.53 11052

only binary operators can have commutators

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.54 11053

only binary operators can have join selectivity

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.55 11054

only binary operators can merge join

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.56 11055

only binary operators can hash

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.57 11056

only boolean operators can have negators

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.58 11057

only boolean operators can have restriction selectivity

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.59 11058

only boolean operators can have join selectivity

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.60 11059

only boolean operators can merge join

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.61 11060

only boolean operators can hash

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.62 11061

operator @1 @ already exists

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.63 11062

operator cannot be its own negator or sort operator

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.64 11063

cannot remove dependency on @1@ because it is a system object

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.65 11064

collation "@1@" for encoding "@2@" already exists

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.66 11065

collation "@1@" already exists

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.67 11066

cannot access temporary or unlogged relations during recovery

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.68 11067

SELECT FOR UPDATE/SHARE cannot be applied to the nullable side of an outer join

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.69 11068

could not implement GROUP BY

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.70 11069

could not implement DISTINCT

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.71 11070

could not implement window PARTITION BY

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.72 11071

could not implement window ORDER BY

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.73 11072

could not implement recursive UNION

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.74 11073

could not implement @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.75 11074

FULL JOIN is only supported with merge-joinable or hash-joinable join conditions

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.76 11075

unexpected EOF on client connection

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.11.77 11076

invalid frontend message type @1@

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.11.78 11077

statement: @1@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.11.79 11078

current transaction is aborted, commands ignored until end of transaction block

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.80 11079

duration: @1@ ms

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.11.81 11080

duration: @1@ ms statement: @2@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.11.82 11081

parse @1@: @2@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.11.83 11082

cannot insert multiple commands into a prepared statement

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.84 11083

duration: @1@ ms parse @2@: @3@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.11.85 11084

bind @1@ to @2@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.11.86 11085

prepared statement "@1@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.87 11086

bind message has @1@ parameter formats but @2@ parameters

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.11.88 11087

bind message supplies @1@ parameters, but prepared statement "@2@" requires @3@

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.11.89 11088

incorrect binary data format in bind parameter @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.90 11089

duration: @1@ ms bind @2@@3@@4@: @5@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.11.91 11090

table "@1@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.92 11091

@1@ @2@@3@@4@: @5@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.11.93 11092

duration: @1@ ms @2@ @3@@4@@5@: @6@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.11.94 11093

terminating connection because of crash of another server process

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.11.95 11094

floating-point exception

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.11.96 11095

terminating autovacuum process due to administrator command

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.11.97 11096

terminating connection due to conflict with recovery

[Description]

An error occurred because execution is temporarily impossible.

[System Processing]

Processing will be aborted.

[Action]

Restart the application. If the same error occurs when you restart the application, to check if there are any problems in the database server.

2.11.98 11097

terminating connection due to administrator command

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.11.99 11098

canceling authentication due to timeout

[Description]

Timeout occurred during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Check the following:

- If executing SQL that outputs a large volume of search results, add a conditional expression to filter the results further.
- If numerous SQLs are being simultaneously executed, reduce the number of simultaneously executed SQLs.
- If a large volume of data is to be updated in a single transaction, modify the SQL to reduce the volume of data to be updated in a single transaction.
- If executing a complex SQL, modify it to a simple SQL.
- Check if there are any problems in the network.

- Before conducting maintenance that involves the processing of a large volume of data, use the SET statement to temporarily increase the value of maintenance_work_mem.

2.11.100 11099

canceling statement due to statement timeout

[Description]

Timeout occurred during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Check the following:

- If executing SQL that outputs a large volume of search results, add a conditional expression to filter the results further.
- If numerous SQLs are being simultaneously executed, reduce the number of simultaneously executed SQLs.
- If a large volume of data is to be updated in a single transaction, modify the SQL to reduce the volume of data to be updated in a single transaction.
- If executing a complex SQL, modify it to a simple SQL.
- Check if there are any problems in the network.
- Before conducting maintenance that involves the processing of a large volume of data, use the SET statement to temporarily increase the value of maintenance_work_mem.

2.12 Message Numbers Beginning with 11100

2.12.1 11100

canceling autovacuum task

[Description]

Processing was canceled.

[System Processing]

Processing will be aborted.

[Action]

Check the message text.

2.12.2 11101

canceling statement due to conflict with recovery

[Description]

An error occurred because execution is temporarily impossible.

[System Processing]

Processing will be aborted.

[Action]

Restart the application. If the same error occurs when you restart the application, to check if there are any problems in the database server.

2.12.3 11102

canceling statement due to user request

[Description]

Processing was canceled.

[System Processing]

Processing will be aborted.

[Action]

Check the message text.

2.12.4 11103

stack depth limit exceeded

[Description]

The depth of the execution stack exceeded the allowable value during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

If executing a complex SQL, modify it to a simple SQL.

2.12.5 11104

--@1@ requires a value

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.6 11105

-c @1@ requires a value

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.7 11107

@1@: invalid command-line arguments

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.8 11108

@1@: no database nor user name specified

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.9 11109

invalid CLOSE message subtype @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.10 11110

invalid DESCRIBE message subtype @1@

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.12.11 11111

disconnection: session time: @1@: @2@: @3@. @4@ user=@5@ database=@6@ host=@7@ @8@ @9@

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.12.12 11112

permission denied: "@1@" is a system catalog

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.12.13 11113

cannot execute @1@ in a read-only transaction

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.14 11114

cannot execute @1@ during recovery

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.15 11115

cannot execute @1 @ within security-restricted operation

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.16 11116

must be superuser to do CHECKPOINT

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.17 11117

invalid argument size @1 @ in function call message

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.12.18 11118

fastpath function call: "@1@" (OID @2@)

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.12.19 11119

duration: @1@ ms fastpath function call: "@2@" (OID @3@)

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.12.20 11120

function call message contains @1@ arguments but function requires @2@

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.12.21 11121

function call message contains @1@ argument formats but @2@ arguments

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.12.22 11122

incorrect binary data format in function argument @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.23 11123

bind message has @1@ result formats but query has @2@ columns

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.12.24 11124

portal "@1@" cannot be run

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.25 11125

cursor can only scan forward

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.26 11126

could not open usermap file "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.12.27 11127

unexpected delimiter

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.28 11128

unexpected end of line or lexeme

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.29 11129

unexpected end of line

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.30 11130

thesaurus sample word "@1@" isn't recognized by subdictionary (rule @2@)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.31 11131

thesaurus sample word "@1@" is a stop word (rule @2@)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.32 11132

thesaurus substitute word "@1@" is a stop word (rule @2@)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.33 11133

thesaurus substitute word "@1@" isn't recognized by subdictionary (rule @2@)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.34 11134

thesaurus substitute phrase is empty (rule @1@)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.35 11135

multiple DictFile parameters

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.36 11136

multiple Dictionary parameters

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.37 11137

unrecognized Thesaurus parameter: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.38 11138

missing DictFile parameter

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.39 11139

missing Dictionary parameter

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.40 11140

invalid text search configuration file name "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.41 11141

could not open statistics file "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.12.42 11142

unrecognized headline parameter: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.43 11143

MinWords should be less than MaxWords

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.44 11144

MinWords should be positive

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.45 11145

ShortWord should be >= 0

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.46 11146

MaxFragments should be >= 0

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.47 11147

string is too long for tsvector (@1@ bytes, max @2@ bytes)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.48 11148

multiple Accept parameters

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.49 11149

unrecognized simple dictionary parameter: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.50 11150

could not open log file "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.12.51 11151

invalid regular expression: @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.52 11152

multibyte flag character is not allowed

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.53 11153

could not open synonym file "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.12.54 11154

ispell dictionary supports only default flag value

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.55 11155

wrong affix file format for flag

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.56 11156

unrecognized synonym parameter: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.57 11157

missing Synonyms parameter

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.58 11158

could not open thesaurus file "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.12.59 11159

word is too long to be indexed

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.12.60 11160

conversion from wchar_t to server encoding failed: @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.61 11161

text search parser does not support headline creation

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.62 11162

multiple AffFile parameters

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.63 11163

unrecognized Ispell parameter: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.64 11164

missing AffFile parameter

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.65 11165

WAL archival (archive_mode=on) requires wal_level "archive" or "hot_standby"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.66 11166

WAL streaming (max_wal_senders > 0) requires wal_level "archive" or "hot_standby"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.67 11167

invalid list syntax for "listen_addresses"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.68 11168

could not create listen socket for "@1@"

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.12.69 11169

could not create any TCP/IP sockets

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.12.70 11170

could not create Unix-domain socket

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.12.71 11171

no socket created for listening

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.12.72 11172

could not create I/O completion port for child queue

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.12.73 11173

could not load pg_hba.conf

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.12.74 11174

@1@: could not locate matching postgres executable

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.12.75 11175

could not open directory "@1@": @2@

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.12.76 11176

directory "@1@" does not exist

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.12.77 11177

could not read permissions of directory "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.12.78 11178

specified data directory "@1@" is not a directory

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.79 11179

data directory "@1@" has wrong ownership

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.80 11180

data directory "@1@" has group or world access

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.81 11181

select() failed in postmaster: @1@

[Description]

The database server was disconnected during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Communication may have been disconnected for the following reasons:

- An error occurred in the communication line (TCP/IP etc.)
- The database server terminated abnormally.

Take the following actions:

- Eliminate the cause of the communication disconnection.

Examine the application and check whether the transaction for implementing update is a long transaction. Judge whether it is a long transaction from the following viewpoints and modify the application.

- a) If the COMMIT process is not executed after update, add the COMMIT process.
 - b) If the total number of update records in a single transaction is high, split it into short transactions.
 - c) If search was conducted for a long period of time after update, execute COMMIT after update or review the search SQL statement.
- If none of the above situations applies, perform the following:
- a) Confirm that the database server has not stopped.
 - b) If the database server is starting or stopping, re-execute the command after the database server starts.

2.12.82 11182

incomplete startup packet

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.12.83 11183

invalid length of startup packet

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.12.84 11184

failed to send SSL negotiation response: @1@

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.12.85 11185

unsupported frontend protocol @1@.@2@: server supports @3@.0 to @4@.@5@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.86 11186

invalid value for boolean option "replication"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.87 11187

invalid startup packet layout: expected terminator as last byte

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.12.88 11188

no PostgreSQL user name specified in startup packet

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.89 11189

the database system is starting up

[Description]

An error occurred because execution is temporarily impossible.

[System Processing]

Processing will be aborted.

[Action]

Restart the application. If the same error occurs when you restart the application, to check if there are any problems in the database server.

2.12.90 11190

the database system is shutting down

[Description]

The database system is shutting down.

[System Processing]

Processing will be aborted.

[Action]

Retry any necessary applications or commands after restarting the database system.

2.12.91 11191

the database system is in recovery mode

[Description]

An error occurred because execution is temporarily impossible.

[System Processing]

Processing will be aborted.

[Action]

Restart the application. If the same error occurs when you restart the application, to check if there are any problems in the database server.

2.12.92 11192

sorry, too many clients already

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.12.93 11193

wrong key in cancel request for process @1@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.12.94 11194

PID @1@ in cancel request did not match any process

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.12.95 11195

received SIGHUP, reloading configuration files

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.12.96 11196

pg_hba.conf not reloaded

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.12.97 11197

received smart shutdown request

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.12.98 11198

received fast shutdown request

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.12.99 11199

aborting any active transactions

[Description]

Rollback any active transactions because the database system is being requested to shut down.

[System Processing]

Continues processing.

[Action]

Retry any necessary applications or commands after restarting the database system.

2.13 Message Numbers Beginning with 11200

2.13.1 11200

received immediate shutdown request

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.13.2 11201

aborting startup due to startup process failure

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.13.3 11202

database system is ready to accept connections

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.13.4 11203

terminating any other active server processes

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.13.5 11204

@1@ (PID @2@) exited with exit code @3@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.13.6 11205

@1@ (PID @2@) was terminated by exception 0x@3@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.13.7 11206

@1@ (PID @2@) was terminated by signal @3@: @4@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.13.8 11207

@1@ (PID @2@) was terminated by signal @3@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.13.9 11208

@1@ (PID @2@) exited with unrecognized status @3@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.13.10 11209

abnormal database system shutdown

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.13.11 11210

all server processes terminated; reinitializing

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.13.12 11211

could not fork new process for connection: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.13.13 11212

connection received: host=@1@ port=@2@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.13.14 11213

connection received: host=@1@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.13.15 11214

could not execute server process "@1@": @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.13.16 11215

database system is ready to accept read only connections

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.13.17 11216

could not fork startup process: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.13.18 11217

could not fork background writer process: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.13.19 11218

could not fork WAL writer process: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.13.20 11219

could not fork WAL receiver process: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.13.21 11220

could not fork archiver: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.13.22 11221

could not duplicate socket @1@ for use in backend: error code @2@

[Description]

The database server was disconnected during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Communication may have been disconnected for the following reasons:

- An error occurred in the communication line (TCP/IP etc.)
- The database server terminated abnormally.

Take the following actions:

- Eliminate the cause of the communication disconnection.

Examine the application and check whether the transaction for implementing update is a long transaction. Judge whether it is a long transaction from the following viewpoints and modify the application.

- a) If the COMMIT process is not executed after update, add the COMMIT process.
 - b) If the total number of update records in a single transaction is high, split it into short transactions.
 - c) If search was conducted for a long period of time after update, execute COMMIT after update or review the search SQL statement.
- If none of the above situations applies, perform the following:
 - a) Confirm that the database server has not stopped.
 - b) If the database server is starting or stopping, re-execute the command after the database server starts.

2.13.23 11223

transaction log switch forced (archive_timeout=@1 @)

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.13.24 11224

checkpoint request failed

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.13.25 11225

compacted fsync request queue from @1 @ entries to @2 @ entries

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.13.26 11226

could not resolve "localhost": @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.13.27 11227

trying another address for the statistics collector

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.13.28 11228

could not create socket for statistics collector: @1@

[Description]

The database server was disconnected during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Communication may have been disconnected for the following reasons:

- An error occurred in the communication line (TCP/IP etc.)
- The database server terminated abnormally.

Take the following actions:

- Eliminate the cause of the communication disconnection.

Examine the application and check whether the transaction for implementing update is a long transaction. Judge whether it is a long transaction from the following viewpoints and modify the application.

- a) If the COMMIT process is not executed after update, add the COMMIT process.
 - b) If the total number of update records in a single transaction is high, split it into short transactions.
 - c) If search was conducted for a long period of time after update, execute COMMIT after update or review the search SQL statement.
- If none of the above situations applies, perform the following:
- a) Confirm that the database server has not stopped.
 - b) If the database server is starting or stopping, re-execute the command after the database server starts.

2.13.29 11229

could not bind socket for statistics collector: @1@

[Description]

The database server was disconnected during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Communication may have been disconnected for the following reasons:

- An error occurred in the communication line (TCP/IP etc.)
- The database server terminated abnormally.

Take the following actions:

- Eliminate the cause of the communication disconnection.

Examine the application and check whether the transaction for implementing update is a long transaction. Judge whether it is a long transaction from the following viewpoints and modify the application.

- a) If the COMMIT process is not executed after update, add the COMMIT process.
 - b) If the total number of update records in a single transaction is high, split it into short transactions.
 - c) If search was conducted for a long period of time after update, execute COMMIT after update or review the search SQL statement.
- If none of the above situations applies, perform the following:
- a) Confirm that the database server has not stopped.
 - b) If the database server is starting or stopping, re-execute the command after the database server starts.

2.13.30 11230

could not get address of socket for statistics collector: @1@

[Description]

The database server was disconnected during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Communication may have been disconnected for the following reasons:

- An error occurred in the communication line (TCP/IP etc.)
- The database server terminated abnormally.

Take the following actions:

- Eliminate the cause of the communication disconnection.

Examine the application and check whether the transaction for implementing update is a long transaction. Judge whether it is a long transaction from the following viewpoints and modify the application.

- a) If the COMMIT process is not executed after update, add the COMMIT process.
- b) If the total number of update records in a single transaction is high, split it into short transactions.
- c) If search was conducted for a long period of time after update, execute COMMIT after update or review the search SQL statement.

- If none of the above situations applies, perform the following:

- a) Confirm that the database server has not stopped.
- b) If the database server is starting or stopping, re-execute the command after the database server starts.

2.13.31 11231

could not connect socket for statistics collector: @1@

[Description]

The database server was disconnected during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Communication may have been disconnected for the following reasons:

- An error occurred in the communication line (TCP/IP etc.)
- The database server terminated abnormally.

Take the following actions:

- Eliminate the cause of the communication disconnection.

Examine the application and check whether the transaction for implementing update is a long transaction. Judge whether it is a long transaction from the following viewpoints and modify the application.

- a) If the COMMIT process is not executed after update, add the COMMIT process.
- b) If the total number of update records in a single transaction is high, split it into short transactions.
- c) If search was conducted for a long period of time after update, execute COMMIT after update or review the search SQL statement.

- If none of the above situations applies, perform the following:

- a) Confirm that the database server has not stopped.
- b) If the database server is starting or stopping, re-execute the command after the database server starts.

2.13.32 11232

could not send test message on socket for statistics collector: @1@

[Description]

The database server was disconnected during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Communication may have been disconnected for the following reasons:

- An error occurred in the communication line (TCP/IP etc.)
- The database server terminated abnormally.

Take the following actions:

- Eliminate the cause of the communication disconnection.

Examine the application and check whether the transaction for implementing update is a long transaction. Judge whether it is a long transaction from the following viewpoints and modify the application.

- a) If the COMMIT process is not executed after update, add the COMMIT process.
 - b) If the total number of update records in a single transaction is high, split it into short transactions.
 - c) If search was conducted for a long period of time after update, execute COMMIT after update or review the search SQL statement.
- If none of the above situations applies, perform the following:
 - a) Confirm that the database server has not stopped.
 - b) If the database server is starting or stopping, re-execute the command after the database server starts.

2.13.33 11233

select() failed in statistics collector: @1@

[Description]

The database server was disconnected during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Communication may have been disconnected for the following reasons:

- An error occurred in the communication line (TCP/IP etc.)
- The database server terminated abnormally.

Take the following actions:

- Eliminate the cause of the communication disconnection.

Examine the application and check whether the transaction for implementing update is a long transaction. Judge whether it is a long transaction from the following viewpoints and modify the application.

- a) If the COMMIT process is not executed after update, add the COMMIT process.
 - b) If the total number of update records in a single transaction is high, split it into short transactions.
 - c) If search was conducted for a long period of time after update, execute COMMIT after update or review the search SQL statement.
- If none of the above situations applies, perform the following:
 - a) Confirm that the database server has not stopped.
 - b) If the database server is starting or stopping, re-execute the command after the database server starts.

2.13.34 11234

test message did not get through on socket for statistics collector

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.13.35 11235

could not receive test message on socket for statistics collector: @1@

[Description]

The database server was disconnected during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Communication may have been disconnected for the following reasons:

- An error occurred in the communication line (TCP/IP etc.)
- The database server terminated abnormally.

Take the following actions:

- Eliminate the cause of the communication disconnection.

Examine the application and check whether the transaction for implementing update is a long transaction. Judge whether it is a long transaction from the following viewpoints and modify the application.

- a) If the COMMIT process is not executed after update, add the COMMIT process.
 - b) If the total number of update records in a single transaction is high, split it into short transactions.
 - c) If search was conducted for a long period of time after update, execute COMMIT after update or review the search SQL statement.
- If none of the above situations applies, perform the following:
 - a) Confirm that the database server has not stopped.
 - b) If the database server is starting or stopping, re-execute the command after the database server starts.

2.13.36 11236

incorrect test message transmission on socket for statistics collector

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.13.37 11237

could not set statistics collector socket to nonblocking mode: @1@

[Description]

The database server was disconnected during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Communication may have been disconnected for the following reasons:

- An error occurred in the communication line (TCP/IP etc.)
- The database server terminated abnormally.

Take the following actions:

- Eliminate the cause of the communication disconnection.

Examine the application and check whether the transaction for implementing update is a long transaction. Judge whether it is a long transaction from the following viewpoints and modify the application.

- a) If the COMMIT process is not executed after update, add the COMMIT process.
 - b) If the total number of update records in a single transaction is high, split it into short transactions.
 - c) If search was conducted for a long period of time after update, execute COMMIT after update or review the search SQL statement.
- If none of the above situations applies, perform the following:
 - a) Confirm that the database server has not stopped.
 - b) If the database server is starting or stopping, re-execute the command after the database server starts.

2.13.38 11238

disabling statistics collector for lack of working socket

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.13.39 11239

could not fork statistics collector: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.13.40 11240

must be superuser to reset statistics counters

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.13.41 11241

unrecognized reset target: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.13.42 11243

could not read statistics message: @1@

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.13.43 11244

could not open temporary statistics file "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.13.44 11245

could not write temporary statistics file "@1@": @2@

[Description]

There was insufficient free space in the disk of the database server during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Delete user data stored in the database server to free up space on the disk.

2.13.45 11246

could not close temporary statistics file "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.13.46 11247

could not rename temporary statistics file "@1@" to "@2@": @3@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.13.47 11248

could not open dictionary file "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.13.48 11249

corrupted statistics file "@1@"

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.13.49 11250

database hash table corrupted during cleanup --- abort

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.13.50 11252

could not read from logger pipe: @1@

[Description]

The database server was disconnected during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Communication may have been disconnected for the following reasons:

- An error occurred in the communication line (TCP/IP etc.)
- The database server terminated abnormally.

Take the following actions:

- Eliminate the cause of the communication disconnection.

Examine the application and check whether the transaction for implementing update is a long transaction. Judge whether it is a long transaction from the following viewpoints and modify the application.

- a) If the COMMIT process is not executed after update, add the COMMIT process.
- b) If the total number of update records in a single transaction is high, split it into short transactions.
- c) If search was conducted for a long period of time after update, execute COMMIT after update or review the search SQL statement.

- If none of the above situations applies, perform the following:

- a) Confirm that the database server has not stopped.

b) If the database server is starting or stopping, re-execute the command after the database server starts.

2.13.51 11253

logger shutting down

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.13.52 11254

could not create pipe for syslog: @1@

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.13.53 11255

could not fork system logger: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.13.54 11256

could not redirect stdout: @1@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.13.55 11257

could not redirect stderr: @1@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.13.56 11258

could not open affix file "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.13.57 11259

disabling automatic rotation (use SIGHUP to re-enable)

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.13.58 11260

could not fork process: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.13.59 11261

archive_mode enabled, yet archive_command is not set

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.13.60 11262

transaction log file "@1@" could not be archived: too many failures

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.13.61 11263

archive command failed with exit code @1@

[Description]

An error occurred during executing the command specified by archive_command parameter at postgresql.conf.

[System Processing]

Processing will be aborted.

[Action]

Identify the cause according to the messages shown before this message and the return code shown in this message. And then work around if necessary.

2.13.62 11264

archive command was terminated by exception 0x@1@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.13.63 11265

archive command was terminated by signal @1@: @2@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.13.64 11266

archive command was terminated by signal @1@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.13.65 11267

archive command exited with unrecognized status @1@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.13.66 11268

archived transaction log file "@1@"

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.13.67 11269

could not open archive status directory "@1@": @2@**[Description]**

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.13.68 11270

could not fork autovacuum launcher process: @1@**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.13.69 11271

autovacuum launcher started**[Description]**

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.13.70 11272

autovacuum launcher shutting down**[Description]**

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.13.71 11273

could not fork autovacuum worker process: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.13.72 11274

autovacuum: processing database "@1@"

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.13.73 11275

autovacuum: dropping orphan temp table "@1@"."@2@" in database "@3@"

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.13.74 11276

autovacuum: found orphan temp table "@1@"."@2@" in database "@3@"

[Description]

Uncollected garbage of the temporary table was found during automatic vacuuming

[System Processing]

Continues processing.

[Action]

No action required. The garbage of the temporary table will be collected automatically later.

If you want to collect it and obtain the storage space immediately,

drop the schema derived from @1 with the database user having superuser permission.

2.13.75 11277

autovacuum not started because of misconfiguration

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.13.76 11278

no empty local buffer available

[Description]

There was insufficient free space in the disk of the database server during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Delete user data stored in the database server to free up space on the disk.

2.13.77 11279

cannot cluster temporary tables of other sessions

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.13.78 11280

unexpected data beyond EOF in block @1@ of relation @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.13.79 11281

invalid page header in block @1@ of relation @2@; zeroing out page

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.13.80 11282

invalid page header in block @1@ of relation @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.13.81 11283

could not write block @1@ of @2@

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.13.82 11284

could not truncate file "@1@": @2@

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.13.83 11285

cannot extend file "@1@" beyond @2@ blocks

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.13.84 11286

could not seek to block @1@ in file "@2@": @3@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.13.85 11287

could not extend file "@1@": @2@

[Description]

There was insufficient free space in the disk of the database server during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Delete user data stored in the database server to free up space on the disk.

2.13.86 11288

could not extend file "@1@": wrote only @2@ of @3@ bytes at block @4@

[Description]

There was insufficient free space in the disk of the database server during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Delete user data stored in the database server to free up space on the disk.

2.13.87 11289

could not read block @1@ in file "@2@": @3@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.13.88 11290

could not read block @1@ in file "@2@": read only @3@ of @4@ bytes

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.13.89 11291

could not write block @1@ in file "@2@": @3@

[Description]

There was insufficient free space in the disk of the database server during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Delete user data stored in the database server to free up space on the disk.

2.13.90 11292

could not write block @1@ in file "@2@": wrote only @3@ of @4@ bytes

[Description]

There was insufficient free space in the disk of the database server during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Delete user data stored in the database server to free up space on the disk.

2.13.91 11293

could not truncate file "@1@" to @2@ blocks: it's only @3@ blocks now

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.13.92 11294

could not truncate file "@1@" to @2@ blocks: @3@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.13.93 11295

could not fsync file "@1@" but retrying: @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.13.94 11296

could not forward fsync request because request queue is full

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.13.95 11297

could not open file "@1@" (target block @2@): @3@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.13.96 11298

could not seek to end of file "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.13.97 11299

memory for serializable conflict tracking is nearly exhausted

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.14 Message Numbers Beginning with 11300

2.14.1 11300

not enough shared memory for data structure "@1@" (@2@ bytes requested)

[Description]

There was insufficient free space in the database server's shared memory during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Estimate memory usage and take the following action:

- If the number of simultaneous connections from client applications is high, reduce it.
- If the number of simultaneous SQL executions is high, reduce it.

2.14.2 11301

deferrable snapshot was unsafe; trying a new one

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.14.3 11302

out of shared memory

[Description]

There was insufficient free space in the database server's shared memory during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Estimate memory usage and take the following action:

- If the number of simultaneous connections from client applications is high, reduce it.
- If the number of simultaneous SQL executions is high, reduce it.

2.14.4 11303

could not serialize access due to read/write dependencies among transactions

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.5 11304

deadlock detected

[Description]

An error occurred because execution is temporarily impossible.

[System Processing]

Processing will be aborted.

[Action]

Restart the application. If the same error occurs when you restart the application, to check if there are any problems in the database server.

2.14.6 11305

cannot acquire lock mode @1@ on database objects while recovery is in progress

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.7 11306

could not send signal to process @1@: @2@

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.14.8 11307

process @1@ avoided deadlock for @2@ on @3@ by rearranging queue order after @4@.@5@ ms

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.14.9 11308

process @1@ detected deadlock while waiting for @2@ on @3@ after @4@.@5@ ms

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.14.10 11309

process @1@ still waiting for @2@ on @3@ after @4@.@5@ ms

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.14.11 11310

process @1@ acquired @2@ on @3@ after @4@.@5@ ms

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.14.12 11311

process @1@ failed to acquire @2@ on @3@ after @4@.@5@ ms

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.14.13 11312

large object @1@ was not opened for writing

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.14 11313

large object @1@ was already dropped

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.15 11314

getrlimit failed: @1@

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.14.16 11315

insufficient file descriptors available to start server process

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.14.17 11316

out of file descriptors: @1@; release and retry

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.14.18 11317

temporary file: path "@1@", size @2@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.14.19 11318

could not read directory "@1@": @2@

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.14.20 11320

could not create directory "@1@": @2@

[Description]

There was insufficient free space in the disk of the database server during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Delete user data stored in the database server to free up space on the disk.

2.14.21 11321

not enough shared memory for elements of data structure "@1@" (@2@ bytes requested)

[Description]

There was insufficient free space in the database server's shared memory during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Estimate memory usage and take the following action:

- If the number of simultaneous connections from client applications is high, reduce it.
- If the number of simultaneous SQL executions is high, reduce it.

2.14.22 11322

could not create ShmemIndex entry for data structure "@1@"

[Description]

There was insufficient free space in the database server's shared memory during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Estimate memory usage and take the following action:

- If the number of simultaneous connections from client applications is high, reduce it.
- If the number of simultaneous SQL executions is high, reduce it.

2.14.23 11323

ShmemIndex entry size is wrong for data structure "@1@": expected @2@, actual @3@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.14.24 11324

requested shared memory size overflows size_t

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.25 11325

corrupted page pointers: lower = @1@, upper = @2@, special = @3@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.14.26 11326

corrupted item pointer: @1@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.14.27 11327

corrupted item lengths: total @1@, available space @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.14.28 11328

corrupted item pointer: offset = @1@, size = @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.14.29 11329

could not write block @1@ of temporary file: @2@

[Description]

There was insufficient free space in the disk of the database server during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Delete user data stored in the database server to free up space on the disk.

2.14.30 11330

could not read block @1@ of temporary file: @2@**[Description]**

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.14.31 11331

could not create unique index "@1@"**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.32 11332

could not find function "@1@" in file "@2@"**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.33 11333

could not access file "@1@": @2@**[Description]**

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.14.34 11334

could not load library "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.14.35 11335

incompatible library "@1@": missing magic block

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.36 11336

incompatible library "@1@": version mismatch

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.37 11337

incompatible library "@1@": magic block mismatch

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.38 11338

access to library "@1@" is not allowed

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.39 11339

invalid macro name in dynamic library path: @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.40 11340

zero-length component in parameter "dynamic_library_path"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.41 11341

component in parameter "dynamic_library_path" is not an absolute path

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.42 11342

could not determine actual result type for function "@1@" declared to return type @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.43 11343

number of aliases does not match number of columns

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.44 11344

no column alias was provided

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.45 11345

could not determine row description for function returning record

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.46 11346

internal function "@1@" is not in internal lookup table

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.47 11347

unrecognized API version @1@ reported by info function "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.48 11348

function @1@ has too many arguments (@2@, maximum is @3@)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.49 11349

cached plan must not change result type

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.50 11350

"@1@" is not a type

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.51 11351

record type has not been registered

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.52 11352

@1@ is not an enum

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.53 11353

could not create relation-cache initialization file "@1@": @2@

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.14.54 11354

cannot PREPARE a transaction that modified relation mapping

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.55 11355

could not open relation mapping file "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.14.56 11356

could not read relation mapping file "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.14.57 11357

relation mapping file "@1@" contains invalid data

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.14.58 11358

relation mapping file "@1@" contains incorrect checksum

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.14.59 11359

could not write to relation mapping file "@1@": @2@

[Description]

There was insufficient free space in the disk of the database server during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Delete user data stored in the database server to free up space on the disk.

2.14.60 11360

could not fsync relation mapping file "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.14.61 11361

could not close relation mapping file "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.14.62 11362

argument type @1@ is only a shell

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.63 11363

no binary input function available for type @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.64 11364

no binary output function available for type @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.65 11365

no input function available for type @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.66 11366

no output function available for type @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.67 11367

could not reopen file "@1@" as stderr: @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.14.68 11368

could not reopen file "@1@" as stdout: @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.14.69 11369

cursor "@1@" already exists

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.70 11370

closing existing cursor "@1@"

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.14.71 11371

cannot drop active portal "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.72 11372

cannot PREPARE a transaction that has created a cursor WITH HOLD

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.73 11373

word is too long (@1@ bytes, max @2@ bytes)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.74 11374

string is too long for tsvector (@1@ bytes, max @2@ bytes)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.75 11375

argument of ntile must be greater than zero

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.76 11376

argument of nth_value must be greater than zero

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.77 11377

could not determine input data types

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.78 11378

neither input type is an array

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.79 11379

integer out of range

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.80 11380

argument must be empty or one-dimensional array

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.81 11381

cannot concatenate incompatible arrays

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.82 11382

invalid number of dimensions: @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.83 11383

could not determine input data type

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.84 11384

invalid input syntax for type boolean: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.85 11385

division by zero

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.86 11386

invalid time zone name: "@1@"

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.14.87 11387

timestamp out of range

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.88 11388

cannot convert abstime "invalid" to timestamp

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.89 11389

invalid status in external "tinterval" value

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.90 11390

cannot convert reltime "invalid" to interval

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.91 11391

invalid input syntax for type money: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.92 11393

PID @1@ is not a PostgreSQL server process

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.14.93 11394

must be superuser to signal the postmaster

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.94 11395

failed to send signal to postmaster: @1@

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.14.95 11396

must be superuser to rotate log files

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.14.96 11397

rotation not possible because log collection not active

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.14.97 11398

global tablespace never has databases

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.14.98 11399

@1@ is not a tablespace OID

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.15 Message Numbers Beginning with 11400

2.15.1 11400

invalid input syntax for integer: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.2 11401

syntax error in tsquery: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.3 11402

syntax error in tsvector: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.4 11403

there is no escaped character: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.5 11404

wrong position info in tsvector: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.6 11405

sequence "@1@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.7 11406

more than one function named "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.8 11407

more than one operator named @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.9 11408

too many arguments

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.10 11409

invalid name syntax

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.11 11410

expected a left parenthesis

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.12 11411

expected a right parenthesis

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.13 11412

expected a type name

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.14 11413

improper type name

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.15 11414

invalid type modifier

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.16 11415

TIME(@1@)@2@ precision must not be negative

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.17 11416

TIME(@1@)@2@ precision reduced to maximum allowed, @3@

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.15.18 11417

date out of range: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.19 11418

date/time value "current" is no longer supported

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.20 11419

timestamp cannot be NaN

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.21 11420

timestamp(@1@) precision must be between @2@ and @3@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.22 11421

interval out of range

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.23 11422

invalid INTERVAL type modifier

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.24 11423

TIMESTAMP(@1 @)@2@ precision must not be negative

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.25 11424

TIMESTAMP(@1 @)@2@ precision reduced to maximum allowed, @3@

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.15.26 11425

interval(@1 @) precision must be between @2@ and @3@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.27 11426

cannot subtract infinite timestamps

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.28 11427

timestamp units "@1@" not supported

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.29 11428

"time" units "@1@" not recognized

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.30 11429

timestamp with time zone units "@1@" not supported

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.31 11430

"time with time zone" units "@1@" not recognized

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.32 11431

interval units "@1@" not supported

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.33 11432

timestamp units "@1@" not recognized

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.34 11433

could not convert to time zone "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.35 11434

time zone "@1@" not recognized

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.36 11435

interval time zone "@1@" must not specify month

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.37 11436

step size cannot equal zero

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.38 11437

invalid input syntax for uuid: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.39 11438

value "@1@" is out of range for type bigint

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.40 11439

bigint out of range

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.41 11440

smallint out of range

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.42 11441

OID out of range

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.43 11442

input of anonymous composite types is not implemented

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.44 11443

malformed record literal: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.45 11444

wrong number of columns: @1 @, expected @2 @

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.46 11445

wrong data type: @1 @, expected @2 @

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.47 11446

improper binary format in record column @1 @

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.48 11447

cannot compare dissimilar column types @1 @ and @2 @ at record column @3 @

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.49 11448

cannot compare record types with different numbers of columns

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.50 11449

int2vector has too many elements

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.51 11450

invalid int2vector data

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.52 11451

oidvector has too many elements

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.53 11452

invalid input syntax for type @1@: "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.54 11453

invalid cidr value: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.55 11454

could not format inet value: @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.56 11455

invalid address family in external "@1@" value

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.57 11456

invalid bits in external "@1@" value

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.58 11457

invalid length in external "@1@" value

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.59 11458

invalid external "cidr" value

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.60 11459

invalid mask length: @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.61 11460

could not format cidr value: @1@**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.62 11461

cannot AND inet values of different sizes**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.63 11462

cannot OR inet values of different sizes**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.64 11463

input is out of range**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.65 11464

cannot subtract inet values of different sizes

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.66 11465

invalid Datum pointer

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.67 11466

missing dimension value

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.68 11467

missing "]" in array dimensions

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.69 11468

upper bound cannot be less than lower bound

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.70 11469

array value must start with "{" or dimension information

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.71 11470

missing assignment operator

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.72 11471

array dimensions incompatible with array literal

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.73 11472

malformed array literal: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.74 11473

array size exceeds the maximum allowed (@1@)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.75 11474

invalid array flags

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.76 11475

wrong element type

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.77 11476

improper binary format in array element @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.78 11477

slices of fixed-length arrays not implemented

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.79 11478

wrong number of array subscripts

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.80 11479

array subscript out of range

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.81 11480

cannot assign null value to an element of a fixed-length array

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.82 11481

updates on slices of fixed-length arrays not implemented

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.83 11482

source array too small

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.84 11483

null array element not allowed in this context

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.85 11484

cannot compare arrays of different element types

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.86 11485

could not identify a hash function for type @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.87 11486

dimension array or low bound array cannot be null

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.88 11487

wrong range of array subscripts

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.89 11488

dimension values cannot be null

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.90 11489

value out of range: overflow

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.91 11490

value out of range: underflow

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.92 11491

invalid input syntax for type real: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.93 11492

"@1@" is out of range for type real

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.94 11493

invalid input syntax for type double precision: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.95 11494

"@1@" is out of range for type double precision

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.96 11495

cannot take square root of a negative number

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.97 11496

zero raised to a negative power is undefined

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.98 11497

a negative number raised to a non-integer power yields a complex result

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.99 11498

cannot take logarithm of zero

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.15.100 11499

cannot take logarithm of a negative number

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16 Message Numbers Beginning with 11500

2.16.1 11500

result is out of range

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.2 11501

count must be greater than zero

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.3 11502

operand, lower bound, and upper bound cannot be NaN

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.4 11503

lower and upper bounds must be finite

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.5 11504

lower bound cannot equal upper bound

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.6 11505

requested length too large

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.7 11506

requested character too large

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.8 11507

requested character too large for encoding: @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.9 11508

null character not permitted

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.10 11509

typmod array must be typecstring[]

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.11 11510

typmod array must be one-dimensional

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.12 11511

typmod array must not contain nulls

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.13 11512

suppress_redundant_updates_trigger: must be called as trigger

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.14 11513

suppress_redundant_updates_trigger: must be called on update

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.15 11514

suppress_redundant_updates_trigger: must be called before update

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.16 11515

suppress_redundant_updates_trigger: must be called for each row

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.17 11516

invalid input syntax for type box: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.18 11517

value "@1@" is out of range for type integer

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.19 11518

invalid oidvector data

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.20 11519

invalid input syntax for type line: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.21 11520

date/time value "@1@" is no longer supported

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.22 11521

date/time field value out of range: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.23 11522

interval field value out of range: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.24 11523

time zone displacement out of range: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.25 11524

unrecognized encoding: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.26 11525

invalid hexadecimal digit: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.27 11526

invalid hexadecimal data: odd number of digits

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.28 11527

unexpected "="

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.29 11528

invalid symbol

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.30 11529

invalid end sequence

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.31 11530

invalid input syntax for type bytea

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.32 11531

ts_stat query must return one tsvector column

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.33 11532

tsvector column "@1@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.34 11533

column "@1@" is not of tsvector type

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.35 11534

configuration column "@1@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.36 11535

column "@1@" is not of regconfig type

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.37 11536

configuration column "@1@" must not be null

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.38 11537

text search configuration name "@1@" must be schema-qualified

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.39 11538

column "@1@" is not of a character type

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.40 11539

ts_rewrite query must return two tsquery columns

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.41 11540

encoding conversion from @1@ to ASCII not supported

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.42 11541

"@1@" is not a valid encoding name

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.43 11542

@1@ is not a valid encoding code

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.44 11543

insert or update on table "@1@" violates foreign key constraint "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.45 11544

function "@1@" was not called by trigger manager

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.46 11545

function "@1@" must be fired AFTER ROW

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.47 11546

function "@1@" must be fired for INSERT

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.48 11547

function "@1@" must be fired for UPDATE

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.49 11548

function "@1@" must be fired for INSERT or UPDATE

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.50 11549

function "@1@" must be fired for DELETE

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.51 11550

no pg_constraint entry for trigger "@1@" on table "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.52 11551

referential integrity query on "@1@" from constraint "@2@" on "@3@" gave unexpected result

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.16.53 11552

update or delete on table "@1@" violates foreign key constraint "@2@" on table "@3@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.54 11553

invalid input value for enum @1@: "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.55 11554

invalid internal value for enum: @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.56 11555

could not determine actual enum type

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.57 11556

enum @1@ contains no values

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.58 11557

invalid format specification for an interval value

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.59 11558

"EEEE" must be the last pattern used

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.60 11559

"9" must be ahead of "PR"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.61 11560

"0" must be ahead of "PR"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.62 11561

multiple decimal points

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.63 11562

cannot use "V" and decimal point together

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.64 11563

cannot use "S" twice

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.65 11564

cannot use "S" and "PL"/"MI"/"SG"/"PR" together

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.66 11565

cannot use "S" and "MI" together

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.67 11566

cannot use "S" and "PL" together

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.68 11567

cannot use "S" and "SG" together

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.69 11568

cannot use "PR" and "S"/"PL"/"MI"/"SG" together

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.70 11569

cannot use "EEEE" twice

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.71 11570

"EEEE" is incompatible with other formats

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.72 11571

"@1@" is not a view

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.73 11572

could not determine which collation to use for regular expression

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.74 11573

could not determine which collation to use for lower() function

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.75 11574

could not determine which collation to use for upper() function

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.76 11575

invalid combination of date conventions

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.77 11576

conflicting values for "@1@" field in formatting string

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.78 11577

source string too short for "@1@" formatting field

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.79 11578

invalid argument for @1@: "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.80 11579

value for "@1@" in source string is out of range

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.81 11580

"TZ"/"tz" format patterns are not supported in to_date

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.82 11581

invalid input string for "Y,YYY"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.83 11582

hour "@1@" is invalid for the 12-hour clock

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.84 11583

inconsistent use of year @1@ and "BC"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.85 11584

cannot calculate day of year without year information

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.86 11585

"EEEE" not supported for input

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.87 11586

"RN" not supported for input

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.88 11587

could not open directory "@1@": @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.89 11588

array of weight must be one-dimensional

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.90 11589

array of weight is too short

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.91 11590

array of weight must not contain nulls

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.92 11591

weight out of range

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.93 11592

regular expression failed: @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.94 11593

invalid regexp option: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.95 11594

invalid escape string

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.96 11595

regex_split does not support the global option

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.97 11596

unsupported XML feature

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.98 11597

invalid encoding name "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.99 11598

invalid XML comment

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.16.100 11599

not an XML document

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17 Message Numbers Beginning with 11600

2.17.1 11600

invalid XML processing instruction

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.2 11601

xmlvalidate is not implemented

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.3 11602

could not initialize XML library

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.17.4 11603

date out of range

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.5 11604

invalid query

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.6 11605

invalid array for XML namespace mapping

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.7 11606

empty XPath expression

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.8 11607

neither namespace name nor URI may be null

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.9 11608

could not register XML namespace with name "@1@" and URI "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.10 11609

value "@1@" is out of range for type smallint

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.11 11610

value "@1@" is out of range for type oid

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.12 11611

value "@1@" is out of range for 8-bit integer

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.13 11612

gtsvector_in not implemented

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.14 11613

identifier too long

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.15 11614

invalid input syntax for type path: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.16 11615

no operand in tsquery: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.17 11616

value is too big in tsquery: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.18 11617

operand is too long in tsquery: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.19 11618

word is too long in tsquery: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.20 11619

text-search query doesn't contain lexemes: "@1@"

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.17.21 11620

length for type @1@ must be at least 1

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.22 11621

length for type @1@ cannot exceed @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.23 11622

value too long for type character(@1@)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.24 11623

value too long for type character varying(@1@)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.25 11624

reference to parent directory ("..") not allowed

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.26 11625

absolute path not allowed

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.27 11626

path must be in or below the current directory

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.28 11627

could not open file "@1@" for writing: @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.17.29 11628

could not seek in file "@1@" : @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.17.30 11629

must be superuser to read files

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.31 11630

requested length cannot be negative

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.32 11631

must be superuser to get file information

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.33 11632

must be superuser to get directory listings

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.34 11633

too many points requested

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.35 11634

could not format "path" value

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.36 11635

invalid input syntax for type point: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.37 11636

invalid input syntax for type lseg: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.38 11637

type "line" not yet implemented

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.39 11638

invalid input syntax for type polygon: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.40 11639

invalid number of points in external "path" value

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.41 11640

invalid input syntax for type circle: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.42 11641

invalid input syntax for type macaddr: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.43 11642

function "dist_lb" not implemented

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.44 11643

function "close_lb" not implemented

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.45 11644

cannot create bounding box for empty polygon

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.46 11645

invalid input syntax for type tinterval: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.47 11646

invalid number of points in external "polygon" value

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.48 11647

function "poly_distance" not implemented

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.49 11648

function "path_center" not implemented

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.50 11649

open path cannot be converted to polygon

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.51 11650

invalid input syntax for type numeric: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.52 11651

could not format "circle" value

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.53 11652

invalid radius in external "circle" value

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.54 11653

cannot convert circle with radius zero to polygon

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.55 11654

must request at least 2 points

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.56 11655

cannot convert empty polygon to circle

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.57 11656

bit string length @1@ does not match type bit(@2@)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.58 11657

"@1@" is not a valid binary digit

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.59 11658

"@1@" is not a valid hexadecimal digit

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.60 11659

invalid length in external bit string

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.61 11660

bit string too long for type bit varying(@1@)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.62 11661

negative substring length not allowed

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.63 11662

cannot AND bit strings of different sizes

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.64 11663

cannot OR bit strings of different sizes

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.65 11664

cannot XOR bit strings of different sizes

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.66 11665

bit index @1@ out of valid range (0..@2@)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.67 11666

new bit must be 0 or 1

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.68 11667

unrecognized key word: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.69 11668

missing name

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.70 11669

missing "=" sign

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.71 11670

invalid mode character: must be one of "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.72 11671

a name must follow the "/" sign

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.73 11672

defaulting grantor to user ID @1@

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.17.74 11673

ACL array contains wrong data type

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.75 11674

ACL arrays must be one-dimensional

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.76 11675

ACL arrays must not contain null values

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.77 11676

extra garbage at the end of the ACL specification

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.78 11677

grant options cannot be granted back to your own grantor

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.79 11678

dependent privileges exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.80 11679

aclinsert is no longer supported

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.81 11680

aclremove is no longer supported

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.82 11681

unrecognized privilege type: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.83 11682

must be member of role "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.84 11683

view "@1@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.85 11684

INTERVAL(@1@) precision must not be negative

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.86 11685

INTERVAL(@1@) precision reduced to maximum allowed, @2@

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.17.87 11686

timestamp out of range: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.88 11687

cannot subtract infinite dates

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.89 11688

date out of range for timestamp

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.90 11689

cannot convert reserved abstime value to date

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.91 11690

time out of range

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.92 11691

interval units "@1@" not recognized

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.93 11692

time zone displacement out of range

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.94 11693

timestamp with time zone units "@1@" not recognized

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.95 11694

"interval" time zone "@1@" not valid

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.96 11695

"@1@" is not a composite type

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.97 11696

invalid input syntax for type oid: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.98 11697

invalid octet value in "macaddr" value: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.99 11698

could not determine which collation to use for initcap() function

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.17.100 11699

could not convert string to UTF-16: error code @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18 Message Numbers Beginning with 11700

2.18.1 11700

could not compare Unicode strings: @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.2 11701

index @1@ out of valid range, 0..@2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.3 11702

field position must be greater than zero

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.4 11703

unterminated conversion specifier

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.5 11704

argument number is out of range

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.6 11705

conversion specifies argument 0, but arguments are numbered from 1

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.7 11706

could not create locale "@1@": @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.8 11707

collations with different collate and ctype values are not supported on this platform

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.9 11708

nondefault collations are not supported on this platform

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.10 11709

invalid multibyte character for locale

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.11 11710

could not determine which collation to use for ILIKE

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.12 11711

text-search query contains only stop words or doesn't contain lexemes, ignored

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.18.13 11712

invalid input syntax for type tid: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.14 11713

invalid length in external "numeric" value

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.15 11714

invalid sign in external "numeric" value

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.16 11715

invalid digit in external "numeric" value

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.17 11716

NUMERIC precision @1@ must be between 1 and @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.18 11717

NUMERIC scale @1@ must be between 0 and precision @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.19 11718

invalid NUMERIC type modifier

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.20 11719

value overflows numeric format

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.21 11720

cannot convert NaN to integer

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.22 11721

cannot convert NaN to bigint

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.23 11722

cannot convert NaN to smallint

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.24 11723

numeric field overflow

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.25 11724

argument for function "exp" too big

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.26 11725

cannot accept a value of type any

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.27 11726

cannot display a value of type any

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.28 11727

cannot accept a value of type anyarray

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.29 11728

cannot accept a value of type anyenum

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.30 11729

cannot accept a value of type anyrange

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.31 11730

cannot accept a value of type trigger

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.32 11731

cannot accept a value of type language_handler

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.33 11732

cannot display a value of type trigger

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.34 11733

cannot accept a value of type fdw_handler

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.35 11734

cannot display a value of type language_handler

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.36 11735

cannot accept a value of type internal

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.37 11736

cannot display a value of type fdw_handler

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.38 11737

cannot accept a value of type opaque

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.39 11738

cannot display a value of type internal

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.40 11739

cannot accept a value of type anyelement

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.41 11740

cannot display a value of type opaque

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.42 11741

cannot accept a value of type anynonarray

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.43 11742

cannot display a value of type anyelement

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.44 11743

cannot accept a value of a shell type

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.45 11744

cannot display a value of type anynonarray

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.46 11745

cannot accept a value of type pg_node_tree

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.47 11746

"char" out of range

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.48 11747

LIKE pattern must not end with escape character

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.49 11748

case insensitive matching not supported on type bytea

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.50 11749

regular-expression matching not supported on type bytea

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.51 11750

function @1 @ is not an aggregate

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.52 11751

rule "@1@" has unsupported event type @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.53 11752

replication connection authorized: user=@1@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.18.54 11753

connection authorized: user=@1@ database=@2@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.18.55 11754

database "@1@" has disappeared from pg_database

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.56 11755

database "@1@" is not currently accepting connections

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.57 11756

permission denied for database "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.58 11757

too many connections for role "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.59 11758

database locale is incompatible with operating system

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.60 11759

no roles are defined in this database system

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.18.61 11760

new replication connections are not allowed during database shutdown

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.62 11761

must be superuser to connect during database shutdown

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.63 11762

must be superuser to connect in binary upgrade mode

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.64 11763

remaining connection slots are reserved for non-replication superuser connections

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.65 11765

template database "@1@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.66 11766

database @1@ does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.67 11767

could not stat directory "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.18.68 11768

could not change directory to "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.18.69 11769

cannot set parameter "@1@" within security-restricted operation

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.70 11770

role "@1@" is not permitted to log in

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.71 11771

too many connections for database "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.72 11772

permission denied to set session authorization

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.73 11773

invalid role OID: @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.74 11774

could not create lock file "@1@": @2@**[Description]**

There was insufficient free space in the disk of the database server during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Delete user data stored in the database server to free up space on the disk.

2.18.75 11775

could not open stop-word file "@1@": @2@**[Description]**

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.18.76 11776

could not open lock file "@1@": @2@**[Description]**

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.18.77 11777

lock file "@1@" already exists**[Description]**

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.18.78 11778

pre-existing shared memory block (key @1@, ID @2@) is still in use

[Description]

An error occurred because execution is temporarily impossible.

[System Processing]

Processing will be aborted.

[Action]

Restart the application. If the same error occurs when you restart the application, to check if there are any problems in the database server.

2.18.79 11779

could not remove old lock file "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.18.80 11780

could not read lock file "@1@": @2@

[Description]

There was insufficient free space in the disk of the database server during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Delete user data stored in the database server to free up space on the disk.

2.18.81 11781

could not read from file "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.18.82 11782

"@1@" is not a valid data directory

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.83 11783

invalid list syntax in parameter "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.84 11784

loaded library "@1@"

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.18.85 11785

unexpected encoding ID @1@ for WIN character sets

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.18.86 11786

unexpected encoding ID @1@ for ISO 8859 character sets

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.18.87 11787

conversion between @1@ and @2@ is not supported

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.88 11788

default conversion function for encoding "@1@" to "@2@" does not exist

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.18.89 11789

invalid source encoding name "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.90 11790

invalid destination encoding name "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.91 11791

invalid byte value for encoding "@1@": 0x@2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.92 11792

encoding name too long

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.93 11793

invalid byte sequence for encoding "@1@": @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.94 11795

invalid encoding number: @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.95 11796

unrecognized configuration parameter "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.96 11797

parameter "@1@" cannot be changed

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.97 11798

parameter "@1@" cannot be changed without restarting the server

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.18.98 11799

parameter "@1@" cannot be changed now

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19 Message Numbers Beginning with 11800

2.19.1 11800

parameter "@1@" cannot be set after connection start

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.2 11801

permission denied to set role "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.3 11802

cannot set parameter "@1@" within security-definer function

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.4 11803

invalid value for parameter "@1@" : "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.5 11804

@1@ is outside the valid range for parameter "@2@" (@3@ .. @4@)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.6 11805

@1@ requires a numeric value

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.7 11806

@1@ is outside the valid range for parameter "@2@" (@3@ .. @4@)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.8 11807

must be superuser to examine "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.9 11808

SET @1@ takes only one argument

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.10 11809

SET requires parameter name

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.11 11810

attempt to redefine parameter "@1@"

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.19.12 11811

could not parse setting for parameter "@1@"

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.19.13 11812

invalid value for parameter "@1@" : @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.14 11813

invalid value for parameter "@1@": @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.15 11814

parameter "@1@" removed from configuration file, reset to default

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.19.16 11815

parameter "@1@" changed to "@2@"

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.19.17 11816

could not open configuration file "@1@": maximum nesting depth exceeded

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.18 11817

syntax error in file "@1@" line @2@, near end of line

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.19 11818

syntax error in file "@1@" line @2@, near token "@3@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.20 11819

user mapping not found for "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.21 11820

foreign-data wrapper "@1@" has no handler

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.22 11821

invalid option "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.23 11822

foreign-data wrapper "@1@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.24 11823

index "@1@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.25 11824

could not create shared memory segment: @1@

[Description]

There was insufficient free space in the database server's shared memory during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Estimate memory usage and take the following action:

- If the number of simultaneous connections from client applications is high, reduce it.
- If the number of simultaneous SQL executions is high, reduce it.

2.19.26 11825

could not stat data directory "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.19.27 11826

could not create semaphore: error code @1@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.19.28 11827

could not lock semaphore: error code @1@

[Description]

An error occurred because execution is temporarily impossible.

[System Processing]

Processing will be aborted.

[Action]

Restart the application. If the same error occurs when you restart the application, to check if there are any problems in the database server.

2.19.29 11828

could not unlock semaphore: error code @1@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.19.30 11829

could not try-lock semaphore: error code @1@

[Description]

An error occurred because execution is temporarily impossible.

[System Processing]

Processing will be aborted.

[Action]

Restart the application. If the same error occurs when you restart the application, to check if there are any problems in the database server.

2.19.31 11830

could not create semaphores: @1@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.19.32 11832

pre-existing shared memory block is still in use

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.19.33 11833

oldest xmin is far in the past

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.19.34 11834

some databases have not been vacuumed in over 2 billion transactions

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.19.35 11835

skipping analyze of "@1@" --- lock not available

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.19.36 11836

skipping "@1@" --- only superuser can analyze it

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.19.37 11837

skipping "@1@" --- only superuser or database owner can analyze it

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.19.38 11838

skipping "@1@" --- only table or database owner can analyze it

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.19.39 11839

skipping "@1@" --- cannot analyze non-tables or special system tables

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.19.40 11840

operator class "@1@" does not exist for access method "@2@", skipping

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.41 11841

operator family "@1@" does not exist for access method "@2@", skipping

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.42 11842

operator family "@1@" for access method "@2@" already exists

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.43 11843

access method "@1@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.44 11844

must be superuser to create an operator class

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.45 11845

invalid operator number @1@, must be between 1 and @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.46 11846

invalid procedure number @1@, must be between 1 and @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.47 11847

storage type specified more than once

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.48 11848

storage type cannot be different from data type for access method "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.49 11849

operator class "@1@" for access method "@2@" already exists

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.50 11850

could not make operator class "@1@" be default for type @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.51 11851

must be superuser to create an operator family

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.52 11852

must be superuser to alter an operator family

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.53 11853

operator argument types must be specified in ALTER OPERATOR FAMILY

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.54 11854

STORAGE cannot be specified in ALTER OPERATOR FAMILY

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.55 11855

one or two argument types must be specified

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.56 11856

index operators must be binary

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.57 11857

access method "@1@" does not support ordering operators

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.58 11858

index search operators must return boolean

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.59 11859

btree comparison procedures must have two arguments

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.60 11860

btree comparison procedures must return integer

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.61 11861

hash procedures must have one argument

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.62 11862

hash procedures must return integer

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.63 11863

associated data types must be specified for index support procedure

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.64 11864

procedure number @1 @ for (@2@, @3@) appears more than once

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.65 11865

operator number @1 @ for (@2@, @3@) appears more than once

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.66 11866

operator @1 @(@2@, @3@) already exists in operator family "@4@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.67 11867

function @1 @(@2@, @3@) already exists in operator family "@4@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.68 11868

operator @1 @(@2@, @3@) does not exist in operator family "@4@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.69 11869

function @1 @(@2@, @3@) does not exist in operator family "@4@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.70 11870

operator class "@1@" for access method "@2@" already exists in schema "@3@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.71 11871

operator family "@1@" for access method "@2@" already exists in schema "@3@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.72 11872

no security label providers have been loaded

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.73 11873

must specify provider when multiple security label providers have been loaded

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.74 11874

security label provider "@1@" is not loaded

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.75 11875

"@1@" is not a table, view, composite type, or foreign table

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.76 11876

aggregate attribute "@1@" not recognized

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.77 11877

parameter "lc_collate" must be specified

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.78 11878

database "@1@" does not exist, skipping

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.19.79 11879

collation "@1@" for encoding "@2@" already exists in schema "@3@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.80 11880

function @1@ already exists in schema "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.81 11881

unrecognized value for EXPLAIN option "@1@": "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.82 11882

unrecognized EXPLAIN option "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.83 11883

EXPLAIN option BUFFERS requires ANALYZE

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.84 11884

@1@ already exists in schema "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.85 11885

collation attribute "@1@" not recognized

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.19.86 11886

aggregate stype must be specified

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.87 11887

aggregate sfunc must be specified

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.88 11888

aggregate input type must be specified

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.89 11889

basetype is redundant with aggregate input type specification

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.90 11890

aggregate transition data type cannot be @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.91 11891

function @1 @(@2@) does not exist, skipping

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.19.92 11892

collation "@1@" already exists in schema "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.19.93 11894

vacuuming "@1@.@2@"

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.19.94 11895

relation "@1@" page @2@ is uninitialized --- fixing

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.19.95 11896

"@1@" : removed @2@ row versions in @3@ pages

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.19.96 11897

"@1@": found @2@ removable, @3@ nonremovable row versions in @4@ pages

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.19.97 11898

"@1@": removed @2@ row versions in @3@ pages

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.19.98 11899

scanned index "@1@" to remove @2@ row versions

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.20 Message Numbers Beginning with 11900

2.20.1 11900

index "@1@" now contains @2@ row versions in @3@ pages

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.20.2 11901

"@1@": truncated @2@ to @3@ pages

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.20.3 11902

option "@1@" not found

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.4 11903

option "@1@" provided more than once

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.5 11904

permission denied to change owner of foreign-data wrapper "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.6 11905

function @1@ must return type "fdw_handler"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.7 11906

permission denied to create foreign-data wrapper "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.8 11907

foreign-data wrapper "@1@" already exists

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.9 11908

permission denied to alter foreign-data wrapper "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.10 11909

changing the foreign-data wrapper handler can change behavior of existing foreign tables

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.20.11 11910

changing the foreign-data wrapper validator can cause the options for dependent objects to become invalid

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.20.12 11912

foreign-data wrapper "@1@" does not exist, skipping

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.20.13 11913

server "@1@" already exists

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.14 11914

type "@1@" does not exist, skipping

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.20.15 11915

user mapping "@1@" already exists for server @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.16 11916

user mapping "@1@" does not exist for the server

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.17 11917

server "@1@" does not exist, skipping

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.20.18 11918

user mapping "@1@" does not exist for the server, skipping

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.20.19 11919

foreign table "@1@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.20 11920

collation "@1@" does not exist, skipping

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.20.21 11921

tablespace "@1@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.22 11922

conversion "@1@" does not exist, skipping

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.20.23 11923

constraint "@1@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.24 11924

schema "@1@" does not exist, skipping

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.20.25 11925

extension "@1@" does not exist, skipping

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.20.26 11926

operator @1@ does not exist, skipping

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.20.27 11927

@1@ is not a domain

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.28 11929

table "@1@" does not exist, skipping

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.20.29 11930

constraints on foreign tables are not supported

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.30 11931

only shared relations can be placed in pg_global tablespace

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.31 11932

default values on foreign tables are not supported

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.32 11933

truncate cascades to table "@1@"

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.20.33 11934

cannot vacuum temporary tables of other sessions

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.34 11935

cannot inherit from temporary relation "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.35 11936

relation "@1@" would be inherited from more than once

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.36 11937

merging multiple inherited definitions of column "@1@"

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.20.37 11938

inherited column "@1@" has a type conflict

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.38 11939

inherited column "@1@" has a collation conflict

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.39 11940

inherited column "@1@" has a storage parameter conflict

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.40 11941

merging column "@1@" with inherited definition

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.20.41 11942

column "@1@" has a type conflict

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.42 11943

column "@1@" has a collation conflict

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.43 11944

column "@1@" has a storage parameter conflict

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.44 11945

column "@1@" inherits conflicting default values

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.45 11946

check constraint name "@1@" appears multiple times but with different expressions

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.46 11947

cannot rename column of typed table

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.47 11948

"@1@" is not a table, view, composite type, index, or foreign table

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.48 11949

inherited column "@1@" must be renamed in child tables too

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.49 11950

cannot rename system column "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.50 11951

cannot rename inherited column "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.51 11952

column "@1@" of relation "@2@" already exists

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.52 11953

cannot @1@ "@2@" because it is being used by active queries in this session

[Description]

An error occurred because execution is temporarily impossible.

[System Processing]

Processing will be aborted.

[Action]

Restart the application. If the same error occurs when you restart the application, to check if there are any problems in the database server.

2.20.53 11954

cannot @1@ "@2@" because it has pending trigger events

[Description]

An error occurred because execution is temporarily impossible.

[System Processing]

Processing will be aborted.

[Action]

Restart the application. If the same error occurs when you restart the application, to check if there are any problems in the database server.

2.20.54 11955

type @1@ is not a composite type

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.55 11956

cannot rewrite system relation "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.56 11957

cannot truncate temporary tables of other sessions

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.57 11958

rewriting table "@1@"

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.20.58 11959

verifying table "@1@"

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.20.59 11960

column "@1@" contains null values

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.60 11961

check constraint "@1@" is violated by some row

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.61 11962

"@1@" is not a table or index

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.62 11963

"@1@" is not a table or view

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.63 11964

"@1@" is not a table or foreign table

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.64 11965

"@1@" is not a table, composite type, or foreign table

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.65 11966

"@1@" is of the wrong type

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.66 11967

cannot alter type "@1@" because it is the type of a typed table

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.67 11968

type @1@ is not a domain

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.68 11969

cannot add column to typed table

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.69 11970

child table "@1@" has different type for column "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.70 11971

child table "@1@" has different collation for column "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.71 11972

child table "@1@" has a conflicting "@2@" column

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.72 11973

merging definition of column "@1@" for child "@2@"

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.20.73 11974

column must be added to child tables too

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.74 11975

cannot alter system column "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.75 11976

column "@1@" is in a primary key

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.76 11977

statistics target @1@ is too low

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.77 11978

lowering statistics target to @1@

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.20.78 11979

invalid storage type "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.79 11980

column data type @1@ can only have storage PLAIN

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.80 11981

cannot drop column from typed table

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.81 11982

column "@1@" of relation "@2@" does not exist, skipping

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.20.82 11983

cannot drop system column "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.83 11984

cannot drop inherited column "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.84 11985

ALTER TABLE / ADD CONSTRAINT USING INDEX will rename index "@1@" to "@2@"

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.20.85 11986

constraint must be added to child tables too

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.86 11987

inherited relation "@1@" is not a table

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.87 11988

constraints on permanent tables may reference only permanent tables

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.88 11989

constraints on unlogged tables may reference only permanent or unlogged tables

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.89 11990

constraints on temporary tables may reference only temporary tables

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.90 11991

number of referencing and referenced columns for foreign key disagree

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.91 11992

foreign key constraint "@1@" cannot be implemented

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.92 11993

constraint "@1@" of relation "@2@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.93 11994

column "@1@" referenced in foreign key constraint does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.94 11995

cannot have more than @1@ keys in a foreign key

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.95 11996

cannot use a deferrable primary key for referenced table "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.96 11997

there is no primary key for referenced table "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.97 11998

cannot use a deferrable unique constraint for referenced table "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.20.98 11999

there is no unique constraint matching given keys for referenced table "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21 Message Numbers Beginning with 12000

2.21.1 12000

validating foreign key constraint "@1@"

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.21.2 12001

cannot drop inherited constraint "@1@" of relation "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.3 12002

constraint "@1@" of domain "@2@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.4 12003

constraint "@1@" of relation "@2@" does not exist, skipping

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.21.5 12004

cannot alter column type of typed table

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.6 12005

cannot alter inherited column "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.7 12006

transform expression must not return a set

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.8 12007

cannot use subquery in index expression

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.9 12008

cannot use aggregate function in transform expression

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.10 12010

column "@1@" cannot be cast automatically to type @2@**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.11 12011

type of inherited column "@1@" must be changed in child tables too**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.12 12012

cannot alter type of column "@1@" twice**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.13 12013

default for column "@1@" cannot be cast automatically to type @2@**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.14 12014

cannot alter type of a column used by a view or rule

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.15 12015

cannot alter type of a column used in a trigger definition

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.16 12016

cannot change owner of index "@1@"

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.21.17 12017

cannot change owner of sequence "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.18 12018

"@1@" is not a table, index, or foreign table

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.19 12019

index "@1@" for table "@2@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.20 12020

cannot have multiple SET TABLESPACE subcommands

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.21 12021

"@1@" is not a table, index, or TOAST table

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.22 12022

cannot move system relation "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.23 12023

cannot rewrite temporary tables of other sessions

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.24 12024

cannot change inheritance of typed table

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.25 12025

circular inheritance not allowed

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.26 12026

table "@1@" without OIDs cannot inherit from table "@2@" with OIDs

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.27 12027

column "@1@" in child table must be marked NOT NULL

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.28 12028

child table is missing column "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.29 12029

child table "@1@" has different definition for check constraint "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.30 12030

child table is missing constraint "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.31 12031

relation "@1@" is not a parent of relation "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.32 12032

typed tables cannot inherit

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.33 12033

table is missing column "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.34 12034

table has column "@1@" where type requires "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.35 12035

table "@1@" has different type for column "@2@"**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.36 12036

table has extra column "@1@"**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.37 12037

"@1@" is not a typed table**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.38 12038

cannot move an owned sequence into another schema**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.39 12039

conversion "@1@" already exists in schema "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.40 12040

unlogged sequences are not supported

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.41 12041

nextval: reached maximum value of sequence "@1@" (@2@)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.42 12042

nextval: reached minimum value of sequence "@1@" (@2@)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.43 12043

currval of sequence "@1@" is not yet defined in this session

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.44 12044

lastval is not yet defined in this session

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.45 12045

setval: value @1@ is out of bounds for sequence "@2@" (@3@..@4@)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.46 12046

INCREMENT must not be zero

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.47 12047

MINVALUE (@1@) must be less than MAXVALUE (@2@)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.48 12048

START value (@1@) cannot be less than MINVALUE (@2@)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.49 12049

START value (@1@) cannot be greater than MAXVALUE (@2@)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.50 12050

RESTART value (@1@) cannot be less than MINVALUE (@2@)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.51 12051

RESTART value (@1@) cannot be greater than MAXVALUE (@2@)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.52 12052

CACHE (@1@) must be greater than zero

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.53 12053

invalid OWNED BY option

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.54 12054

sequence must have same owner as table it is linked to

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.55 12055

sequence must be in same schema as table it is linked to

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.56 12056

invalid cursor name: must not be empty

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.57 12057

utility statements cannot be prepared

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.58 12058

prepared statement is not a SELECT

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.59 12059

wrong number of parameters for prepared statement "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.60 12060

cannot use subquery in EXECUTE parameter

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.61 12061

cannot use aggregate function in EXECUTE parameter

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.62 12062

cannot use window function in EXECUTE parameter

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.63 12063

parameter \$@1@ of type @2@ cannot be coerced to the expected type @3@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.64 12064

prepared statement "@1@" already exists

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.65 12065

unnamed prepared statement does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.66 12066

skipping vacuum of "@1@" --- lock not available

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.21.67 12067

skipping "@1@" --- only superuser can vacuum it

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.21.68 12068

skipping "@1@" --- only superuser or database owner can vacuum it

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.21.69 12069

skipping "@1@" --- only table or database owner can vacuum it

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.21.70 12070

skipping "@1@" --- cannot vacuum non-tables or special system tables

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.21.71 12071

analyzing "@1@.@2@" inheritance tree

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.21.72 12072

analyzing "@1@.@2@"

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.21.73 12073

automatic analyze of table "@1@.@2@.@3@" system usage: @4@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.21.74 12074

"@1@": scanned @2@ of @3@ pages, containing @4@ live rows and @5@ dead rows; @6@ rows in sample, @7@ estimated total rows

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.21.75 12075

cannot move temporary tables of other sessions

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.76 12076

there is no previously clustered index for table "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.77 12077

cannot cluster a shared catalog

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.78 12078

cannot access temporary tables of other sessions

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.79 12079

"@1@" is not an index for table "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.80 12080

cannot cluster on index "@1@" because access method does not support clustering

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.81 12081

cannot cluster on partial index "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.82 12082

cannot cluster on invalid index "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.83 12083

clustering "@1@.@2@" using index scan on "@3@"

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.21.84 12084

clustering "@1@.@2@" using sequential scan and sort

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.21.85 12086

invalid statement name: must not be empty

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.86 12087

could not reposition held cursor

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.87 12088

SQL function cannot return shell type @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.88 12089

type "@1@" is only a shell

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.21.89 12090

type "@1@" is not yet defined

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.90 12091

SQL function cannot accept shell type @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.91 12092

type @1@ is only a shell

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.21.92 12093

token type "@1@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.93 12094

functions cannot accept set arguments

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.94 12095

VARIADIC parameter must be the last input parameter

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.95 12096

VARIADIC parameter must be an array

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.96 12097

argument name "@1@" used more than once

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.97 12098

only input parameters can have default values

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.21.98 12099

cannot use table references in parameter default value

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22 Message Numbers Beginning with 12100

2.22.1 12100

cannot use subquery in parameter default value

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.2 12101

cannot use aggregate function in parameter default value

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.3 12102

cannot use window function in parameter default value

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.4 12103

input parameters after one with a default value must also have defaults

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.5 12104

no function body specified

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.6 12105

no language specified

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.7 12106

COST must be positive

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.8 12107

ROWS must be positive

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.9 12108

unrecognized function attribute "@1@" ignored

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.22.10 12109

only one AS item needed for language "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.11 12110

role "@1@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.12 12111

function result type must be @1@ because of OUT parameters

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.13 12112

function result type must be specified

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.14 12113

ROWS is not applicable when function does not return a set

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.15 12114

aggregate @1@(@2@) does not exist, skipping

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.22.16 12116

source data type @1@ is a pseudo-type

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.17 12117

target data type @1@ is a pseudo-type

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.18 12118

cast function must take one to three arguments

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.19 12119

argument of cast function must match or be binary-coercible from source data type

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.20 12120

second argument of cast function must be type integer

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.21 12121

third argument of cast function must be type boolean

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.22 12122

return data type of cast function must match or be binary-coercible to target data type

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.23 12123

cast function must not be volatile

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.24 12124

cast function must not be an aggregate function

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.25 12125

cast function must not be a window function

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.26 12126

cast function must not return a set

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.27 12127

must be superuser to create a cast WITHOUT FUNCTION

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.28 12128

source and target data types are not physically compatible

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.29 12129

composite data types are not binary-compatible

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.30 12130

enum data types are not binary-compatible

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.31 12131

array data types are not binary-compatible

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.32 12132

domain data types must not be marked binary-compatible

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.33 12133

source data type and target data type are the same

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.34 12134

cast from type @1@ to type @2@ already exists

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.35 12135

cast from type @1@ to type @2@ does not exist, skipping

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.22.36 12136

cast from type @1@ to type @2@ does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.37 12137

function "@1@" already exists in schema "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.38 12138

no inline code specified

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.39 12139

language "@1@" does not support inline code execution

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.40 12140

channel name cannot be empty

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.41 12141

channel name too long

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.42 12142

payload string too long

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.43 12143

cannot PREPARE a transaction that has executed LISTEN, UNLISTEN, or NOTIFY

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.44 12144

too many notifications in the NOTIFY queue

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.45 12145

NOTIFY queue is @1@@2@ full

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.22.46 12146

function @1@ must return type "language_handler"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.47 12147

must be superuser to create text search parsers

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.48 12148

text search parser parameter "@1@" not recognized

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.49 12149

text search parser start method is required

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.50 12150

text search parser gettoken method is required

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.51 12151

text search parser end method is required

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.52 12152

text search parser lextypes method is required

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.53 12153

must be superuser to rename text search parsers

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.54 12154

text search parser "@1@" does not exist, skipping

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.22.55 12155

must be superuser to rename text search templates

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.56 12156

text search parser "@1@" already exists

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.57 12157

text search template "@1@" does not accept options

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.58 12158

text search template is required

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.59 12159

text search dictionary "@1@" already exists

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.60 12160

text search dictionary "@1@" does not exist, skipping

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.22.61 12161

must be superuser to create text search templates

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.62 12162

text search template parameter "@1@" not recognized

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.63 12163

text search template lexize method is required

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.64 12165

text search template "@1@" already exists

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.65 12167

text search template "@1@" does not exist, skipping

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.22.66 12168

text search configuration parameter "@1@" not recognized

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.67 12169

cannot specify both PARSER and COPY options

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.68 12170

text search parser is required

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.69 12171

text search configuration "@1@" already exists

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.70 12172

text search configuration "@1@" does not exist, skipping

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.22.71 12174

mapping for token type "@1@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.72 12175

mapping for token type "@1@" does not exist, skipping

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.22.73 12176

invalid parameter list format: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.74 12177

group "@1@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.75 12178

invalid extension name: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.76 12179

invalid extension version name: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.77 12180

could not open extension control file "@1@" : @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.22.78 12181

parameter "@1@" cannot be set in a secondary extension control file

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.79 12183

parameter "@1@" must be a list of extension names

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.80 12184

unrecognized parameter "@1@" in file "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.81 12185

parameter "schema" cannot be specified when "relocatable" is true

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.82 12186

transaction control statements are not allowed within an extension script

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.83 12187

permission denied to create extension "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.84 12188

permission denied to update extension "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.85 12189

extension "@1@" has no update path from version "@2@" to version "@3@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.86 12190

relation "@1@" already exists, skipping

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.22.87 12191

extension "@1@" already exists

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.88 12192

nested CREATE EXTENSION is not supported

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.89 12193

version to install must be specified

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.90 12194

FROM version must be different from installation target version "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.91 12195

extension "@1@" must be installed in schema "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.92 12196

required extension "@1@" is not installed

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.93 12197

language "@1@" does not exist, skipping

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.22.94 12198

OID @1@ does not refer to a table

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.22.95 12199

table "@1@" is not a member of the extension being created

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23 Message Numbers Beginning with 12200

2.23.1 12200

extension "@1@" does not support SET SCHEMA

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.2 12201

nested ALTER EXTENSION is not supported

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.3 12202

version "@1@" of extension "@2@" is already installed

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.23.4 12203

@1@ is already a member of extension "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.5 12204

@1@ is not a member of extension "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.6 12205

using pg_pltemplate information instead of CREATE LANGUAGE parameters

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.23.7 12206

must be superuser to create procedural language "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.8 12207

function @1@ must return type "trigger"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.9 12208

unsupported language "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.10 12209

must be superuser to create custom procedural language

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.11 12210

changing return type of function @1@ from "opaque" to "language_handler"

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.23.12 12211

language "@1@" already exists

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.13 12212

relation "@1@" does not exist, skipping

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.23.14 12213

unacceptable schema name "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.15 12214

sequence "@1@" does not exist, skipping

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.23.16 12215

source encoding "@1@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.17 12216

destination encoding "@1@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.18 12217

encoding conversion function @1@ must return type "void"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.19 12218

view "@1@" does not exist, skipping

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.23.20 12219

relation "@1@" already exists in schema "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.21 12220

could not remove directory "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.23.22 12221

"@1@" exists but is not a directory

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.23 12222

permission denied to create tablespace "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.24 12223

tablespace location cannot contain single quotes

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.25 12224

tablespace location must be an absolute path

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.26 12225

tablespace location "@1@" is too long

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.27 12226

unacceptable tablespace name "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.28 12227

tablespace "@1@" already exists

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.29 12228

tablespaces are not supported on this platform

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.23.30 12229

window "@1@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.31 12230

index "@1@" does not exist, skipping

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.23.32 12231

tablespace "@1@" is not empty

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.33 12232

aggregate @1@ does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.34 12233

could not set permissions on directory "@1@" : @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.23.35 12234

some useless files may be left behind in old database directory "@1@"

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.23.36 12235

directory "@1@" already in use as a tablespace

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.37 12236

could not create symbolic link "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.23.38 12237

could not read symbolic link "@1@": @2@

[Description]

There was insufficient free space in the disk of the database server during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Delete user data stored in the database server to free up space on the disk.

2.23.39 12238

could not read directory "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.23.40 12239

"@1@" is a foreign table

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.41 12240

"@1@" is a view

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.42 12241

TRUNCATE FOR EACH ROW triggers are not supported

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.43 12242

INSTEAD OF triggers must be FOR EACH ROW

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.44 12243

INSTEAD OF triggers cannot have WHEN conditions

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.45 12244

INSTEAD OF triggers cannot have column lists

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.46 12245

cannot use subquery in trigger WHEN condition

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.47 12246

cannot use aggregate function in trigger WHEN condition

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.48 12247

cannot use window function in trigger WHEN condition

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.49 12248

statement trigger's WHEN condition cannot reference column values

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.50 12249

INSERT trigger's WHEN condition cannot reference OLD values

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.51 12250

DELETE trigger's WHEN condition cannot reference NEW values

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.52 12251

BEFORE trigger's WHEN condition cannot reference NEW system columns

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.53 12252

changing return type of function @1@ from "opaque" to "trigger"

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.23.54 12254

trigger "@1@" for relation "@2@" already exists

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.55 12255

ignoring incomplete trigger group for constraint "@1@" @2@

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.23.56 12256

converting trigger group into constraint "@1@" "@2@"

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.23.57 12257

trigger "@1@" for table "@2@" does not exist, skipping

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.23.58 12258

trigger "@1@" for table "@2@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.59 12259

permission denied: "@1@" is a system trigger

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.60 12260

trigger function @1@ returned null value

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.61 12261

BEFORE STATEMENT trigger cannot return a value

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.62 12262

constraint "@1@" is not deferrable

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.63 12263

rule "@1@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.64 12264

SYSID can no longer be specified

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.65 12265

invalid connection limit: @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.66 12266

must be superuser to create superusers

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.67 12267

must be superuser to create replication users

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.68 12268

permission denied to create database

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.69 12269

role name "@1@" is reserved

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.70 12270

role "@1@" already exists

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.71 12271

must be superuser to alter superusers

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.72 12272

must be superuser to alter replication users

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.73 12273

permission denied

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.74 12274

permission denied to create role

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.75 12275

tablespace "@1@" does not exist, skipping

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.23.76 12276

current user cannot be dropped

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.77 12277

session user cannot be dropped

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.78 12278

must be superuser to drop superusers

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.79 12279

role "@1@" cannot be dropped because some objects depend on it

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.80 12280

session user cannot be renamed

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.81 12281

current user cannot be renamed

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.82 12282

must be superuser to rename superusers

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.83 12283

permission denied to rename database

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.84 12284

MD5 password cleared because of role rename

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.23.85 12285

column names cannot be included in GRANT/REVOKE ROLE

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.86 12286

permission denied to drop role

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.87 12287

permission denied to drop objects

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.88 12288

must have admin option on role "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.89 12289

must be superuser to set grantor

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.90 12290

role "@1@" is a member of role "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.91 12291

role "@1@" is already a member of role "@2@"

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.23.92 12292

role "@1@" is not a member of role "@2@"

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.23.93 12293

COPY BINARY is not supported to stdout or from stdin

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.23.94 12294

could not write to COPY file: @1@

[Description]

There was insufficient free space in the disk of the database server during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Delete user data stored in the database server to free up space on the disk.

2.23.95 12295

connection lost during COPY to stdout

[Description]

The database server was disconnected during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Communication may have been disconnected for the following reasons:

- An error occurred in the communication line (TCP/IP etc.)
- The database server terminated abnormally.

Take the following actions:

- Eliminate the cause of the communication disconnection.

Examine the application and check whether the transaction for implementing update is a long transaction. Judge whether it is a long transaction from the following viewpoints and modify the application.

- a) If the COMMIT process is not executed after update, add the COMMIT process.
 - b) If the total number of update records in a single transaction is high, split it into short transactions.
 - c) If search was conducted for a long period of time after update, execute COMMIT after update or review the search SQL statement.
- If none of the above situations applies, perform the following:
 - a) Confirm that the database server has not stopped.
 - b) If the database server is starting or stopping, re-execute the command after the database server starts.

2.23.96 12296

could not read from COPY file: @1@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.23.97 12297

COPY from stdin failed: @1@

[Description]

Processing was canceled.

[System Processing]

Processing will be aborted.

[Action]

Check the message text.

2.23.98 12298

unexpected message type 0x@1@ during COPY from stdin

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.23.99 12299

must be superuser to COPY to or from a file

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24 Message Numbers Beginning with 12300

2.24.1 12300

COPY format "@1@" not recognized

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.2 12301

argument to option "@1@" must be a list of column names

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.3 12302

argument to option "@1@" must be a valid encoding name

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.4 12303

option "@1@" not recognized

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.24.5 12304

cannot specify DELIMITER in BINARY mode

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.6 12305

cannot specify NULL in BINARY mode

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.7 12306

COPY delimiter must be a single one-byte character

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.8 12307

COPY delimiter cannot be newline or carriage return

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.9 12308

COPY null representation cannot use newline or carriage return

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.10 12309

COPY delimiter cannot be "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.11 12310

COPY HEADER available only in CSV mode

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.12 12311

COPY quote available only in CSV mode

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.13 12312

COPY quote must be a single one-byte character

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.14 12313

COPY delimiter and quote must be different

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.15 12314

COPY escape available only in CSV mode

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.16 12315

COPY escape must be a single one-byte character

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.17 12316

COPY force quote available only in CSV mode

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.18 12317

COPY force quote only available using COPY TO**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.19 12318

COPY force not null available only in CSV mode**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.20 12319

COPY force not null only available using COPY FROM**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.21 12320

COPY delimiter must not appear in the NULL specification**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.22 12321

CSV quote character must not appear in the NULL specification

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.23 12322

table "@1@" does not have OIDs

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.24 12323

COPY (SELECT) WITH OIDS is not supported

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.25 12324

COPY (SELECT INTO) is not supported

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.26 12325

FORCE QUOTE column "@1@" not referenced by COPY

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.27 12326

FORCE NOT NULL column "@1@" not referenced by COPY

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.28 12327

cannot copy from sequence "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.29 12328

cannot copy from foreign table "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.30 12329

cannot copy to sequence "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.31 12330

cannot copy from non-table relation "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.32 12331

relative path not allowed for COPY to file

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.33 12332

could not open file "@1@" for reading: @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.24.34 12333

"@1@" is a directory

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.35 12334

cannot copy to view "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.36 12335

cannot copy to foreign table "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.37 12337

cannot copy to non-table relation "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.38 12338

COPY file signature not recognized

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.39 12339

invalid COPY file header (missing flags)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.40 12340

unrecognized critical flags in COPY file header

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.41 12341

invalid COPY file header (missing length)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.42 12342

invalid COPY file header (wrong length)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.43 12343

extra data after last expected column

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.44 12344

missing data for OID column

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.45 12345

null OID in COPY data

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.46 12346

invalid OID in COPY data

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.47 12347

missing data for column "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.48 12348

received copy data after EOF marker

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.49 12349

row field count is @1 @, expected @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.50 12350

literal carriage return found in data

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.51 12351

unquoted carriage return found in data

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.52 12352

literal newline found in data

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.53 12353

unquoted newline found in data

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.54 12354

end-of-copy marker does not match previous newline style

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.55 12355

end-of-copy marker corrupt

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.56 12356

unterminated CSV quoted field

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.57 12357

unexpected EOF in COPY data

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.58 12358

invalid field size

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.59 12359

incorrect binary data format

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.60 12360

must specify at least one column**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.61 12361

cannot use more than @1@ columns in an index**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.62 12362

cannot create index on foreign table "@1@"**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.63 12363

cannot create indexes on temporary tables of other sessions**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.64 12364

substituting access method "gist" for obsolete method "rtree"

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.24.65 12365

access method "@1@" does not support unique indexes

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.66 12366

access method "@1@" does not support multicolumn indexes

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.67 12367

access method "@1@" does not support exclusion constraints

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.68 12368

@1@ @2@ will create implicit index "@3@" for table "@4@"

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.24.69 12369

cannot use subquery in index predicate

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.70 12370

cannot use aggregate in index predicate

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.71 12371

functions in index predicate must be marked IMMUTABLE

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.72 12372

cannot use subquery in transform expression

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.73 12374

functions in index expression must be marked IMMUTABLE

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.74 12375

could not determine which collation to use for string comparison

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.75 12376

operator is not unique: @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.76 12377

operator @1@ is not a member of operator family "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.77 12378

access method "@1@" does not support ASC/DESC options

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.78 12379

access method "@1@" does not support NULLS FIRST/LAST options

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.79 12380

data type @1@ has no default operator class for access method "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.80 12381

operator class "@1@" does not accept data type @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.81 12382

there are multiple default operator classes for data type @1@**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.82 12383

table "@1@" has no indexes**[Description]**

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.24.83 12384

can only reindex the currently open database**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.84 12385

table "@1@.@2@" was reindexed**[Description]**

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.24.85 12386

@1@ requires a parameter

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.86 12387

@1@ requires a Boolean value

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.87 12389

argument of @1@ must be a name

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.88 12391

@1@ requires an integer value

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.89 12393

LOCATION is not supported anymore

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.24.90 12396

permission denied to copy database "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.91 12397

invalid server encoding @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.24.92 12399

new encoding (@1@) is incompatible with the encoding of the template database (@2@)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25 Message Numbers Beginning with 12400

2.25.1 12400

new collation (@1@) is incompatible with the collation of the template database (@2@)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.2 12401

new LC_CTYPE (@1@) is incompatible with the LC_CTYPE of the template database (@2@)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.3 12402

pg_global cannot be used as default tablespace

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.4 12403

cannot assign new default tablespace "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.5 12404

database "@1@" already exists

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.6 12405

source database "@1@" is being accessed by other users

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.7 12406

encoding "@1@" does not match locale "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.8 12407

role "@1@" does not exist, skipping

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.25.9 12408

cannot drop a template database

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.10 12409

cannot drop the currently open database

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.11 12410

database "@1@" is being accessed by other users

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.12 12411

permission denied to rename role

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.13 12412

current database cannot be changed

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.14 12413

cannot change the tablespace of the currently open database

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.15 12414

some relations of database "@1@" are already in tablespace "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.16 12415

permission denied to change owner of database

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.17 12416

=> is deprecated as an operator name

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.25.18 12417

SETOF type not allowed for operator argument

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.19 12418

operator attribute "@1@" not recognized

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.25.20 12419

operator procedure must be specified

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.21 12420

at least one of leftarg or rightarg must be specified

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.22 12421

restriction estimator function @1@ must return type "float8"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.23 12422

join estimator function @1@ must return type "float8"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.24 12424

must be superuser to create a base type

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.25 12425

type attribute "@1@" not recognized

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.25.26 12426

invalid type category "@1@": must be simple ASCII

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.27 12427

array element type cannot be @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.28 12428

alignment "@1@" not recognized

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.29 12429

storage "@1@" not recognized

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.30 12430

type input function must be specified

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.31 12431

type output function must be specified

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.32 12432

type modifier output function is useless without a type modifier input function

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.33 12433

changing return type of function @1@ from "opaque" to @2@

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.25.34 12434

type input function @1@ must return type @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.35 12435

changing return type of function @1@ from "opaque" to "cstring"

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.25.36 12436

type output function @1@ must return type "cstring"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.37 12437

type receive function @1@ must return type @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.38 12438

type send function @1@ must return type "bytea"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.39 12439

"@1@" is not a number

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.40 12440

"@1@" is not a valid base type for a domain

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.41 12441

multiple default expressions

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.42 12442

conflicting NULL/NOT NULL constraints

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.43 12443

unique constraints not possible for domains

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.44 12444

primary key constraints not possible for domains

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.45 12445

exclusion constraints not possible for domains

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.46 12446

foreign key constraints not possible for domains

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.47 12447

specifying constraint deferrability not supported for domains

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.48 12448

changing argument type of function @1@ from "opaque" to "cstring"

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.25.49 12449

changing argument type of function @1@ from "opaque" to @2@

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.25.50 12450

typmod_in function @1@ must return type "integer"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.51 12451

typmod_out function @1@ must return type "cstring"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.52 12452

type analyze function @1@ must return type "boolean"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.53 12453

column "@1@" of table "@2@" contains null values

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.54 12454

column "@1@" of table "@2@" contains values that violate the new constraint

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.55 12456

cannot use table references in domain check constraint

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.56 12457

@1@ is a table's row type

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.57 12458

cannot alter array type @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.58 12459

type "@1@" already exists in schema "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.59 12460

could not obtain lock on relation "@1@.@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.60 12462

could not determine which collation to use for view column "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.61 12463

view must have at least one column

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.62 12464

cannot drop columns from view

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.63 12465

cannot change name of view column "@1@" to "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.64 12466

cannot change data type of view column "@1@" from @2@ to @3@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.65 12467

views must not contain SELECT INTO

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.66 12468

views must not contain data-modifying statements in WITH

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.67 12469

CREATE VIEW specifies more column names than columns

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.68 12470

view "@1@" will be a temporary view

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.25.69 12471

views cannot be unlogged because they do not have storage

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.70 12472

rule "@1@" for relation "@2@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.71 12473

portal "@1@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.72 12474

there are multiple rules named "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.73 12475

rule "@1@" for relation "@2@" does not exist, skipping

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.25.74 12476

WITH query name "@1@" appears in both a rule action and the query being rewritten

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.75 12477

cannot have RETURNING lists in multiple rules

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.76 12478

multiple assignments to same column "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.77 12479

infinite recursion detected in rules for relation "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.78 12480

DO INSTEAD NOTHING rules are not supported for data-modifying statements in WITH

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.79 12481

conditional DO INSTEAD rules are not supported for data-modifying statements in WITH

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.80 12482

DO ALSO rules are not supported for data-modifying statements in WITH

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.81 12483

multi-statement DO INSTEAD rules are not supported for data-modifying statements in WITH

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.82 12484

cannot perform INSERT RETURNING on relation "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.83 12485

cannot perform UPDATE RETURNING on relation "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.84 12486

cannot perform DELETE RETURNING on relation "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.85 12487

WITH cannot be used in a query that is rewritten by rules into multiple queries

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.86 12488

conditional utility statements are not implemented

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.87 12489

WHERE CURRENT OF on a view is not implemented

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.88 12490

rule "@1@" for relation "@2@" already exists

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.89 12491

rule actions on OLD are not implemented

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.90 12492

rule actions on NEW are not implemented

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.91 12493

INSTEAD NOTHING rules on SELECT are not implemented

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.92 12494

multiple actions for rules on SELECT are not implemented

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.93 12495

rules on SELECT must have action INSTEAD SELECT

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.94 12496

rules on SELECT must not contain data-modifying statements in WITH

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.95 12497

event qualifications are not implemented for rules on SELECT

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.96 12498

"@1@" is already a view

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.25.97 12499

[view rule "@1@" must be named "@2@"](#)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26 Message Numbers Beginning with 12500

2.26.1 12500

[could not convert table "@1@" to a view because it is not empty](#)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.2 12501

[could not convert table "@1@" to a view because it has triggers](#)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.3 12502

[could not convert table "@1@" to a view because it has indexes](#)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.4 12503

could not convert table "@1@" to a view because it has child tables

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.5 12504

cannot have multiple RETURNING lists in a rule

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.6 12505

RETURNING lists are not supported in conditional rules

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.7 12506

RETURNING lists are not supported in non-INSTEAD rules

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.8 12507

SELECT rule's target list has too many entries

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.9 12508

RETURNING list has too many entries

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.10 12509

cannot convert relation containing dropped columns to view

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.11 12510

SELECT rule's target entry @1@ has different column name from "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.12 12511

SELECT rule's target entry @1@ has different type from column "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.13 12512

RETURNING list's entry @1@ has different type from column "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.14 12513

SELECT rule's target entry @1@ has different size from column "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.15 12514

RETURNING list's entry @1@ has different size from column "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.16 12515

SELECT rule's target list has too few entries

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.17 12516

RETURNING list has too few entries

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.18 12517

@1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.19 12518

Perl hash contains nonexistent column "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.20 12519

number of array dimensions (@1@) exceeds the maximum allowed (@2@)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.21 12520

multidimensional arrays must have array expressions with matching dimensions

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.22 12521

PL/Perl function must return reference to hash or array

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.23 12522

\$_TD->{new} does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.24 12523

\$_TD->{new} is not a hash reference

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.25 12524

PL/Perl functions cannot return type @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.26 12525

PL/Perl functions cannot accept type @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.27 12526

didn't get a CODE reference from compiling function "@1@"

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.26.28 12527

set-valued function called in context that cannot accept a set

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.29 12528

set-returning PL/Perl function must return reference to array or use return_next

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.30 12529

function returning record called in context that cannot accept type record

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.31 12530

ignoring modified row in DELETE trigger

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.26.32 12531

result of PL/Perl trigger function must be undef, "SKIP", or "MODIFY"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.33 12532

out of memory

[Description]

There was insufficient free space in the server's memory during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Estimate memory usage and take the following action:

- If the number of simultaneous connections from client applications is high, reduce it.
- If the number of simultaneous SQL executions is high, reduce it.

2.26.34 12533

trigger functions can only be called as triggers

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.35 12534

cannot use return_next in a non-SETOF function

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.36 12535

SETOF-composite-returning PL/Perl function must call return_next with reference to hash

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.37 12536

PL/pgSQL functions cannot accept type @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.38 12537

could not determine actual return type for polymorphic function "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.39 12538

trigger functions can only be called as triggers

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.40 12539

PL/pgSQL functions cannot return type @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.41 12540

trigger functions cannot have declared arguments

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.42 12541

parameter name "@1@" used more than once

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.43 12542

column reference "@1@" is ambiguous

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.44 12543

record "@1@" has no field "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.45 12544

variable "@1@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.46 12545

relation "@1@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.47 12546

variable "@1@" has pseudo-type @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.48 12547

relation "@1@" is not a table

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.49 12548

type "@1@" is only a shell

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.50 12549

unrecognized exception condition "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.51 12550

could not determine actual argument type for polymorphic function "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.52 12551

CONTINUE cannot be used outside a loop

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.53 12552

control reached end of function without RETURN

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.54 12553

set-valued function called in context that cannot accept a set

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.55 12554

control reached end of trigger procedure without RETURN

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.56 12555

trigger procedure cannot return a set

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.57 12556

variable "@1@" declared NOT NULL cannot default to NULL

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.58 12557

case not found

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.59 12558

lower bound of FOR loop cannot be null

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.60 12559

upper bound of FOR loop cannot be null

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.61 12560

BY value of FOR loop cannot be null

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.62 12561

BY value of FOR loop must be greater than zero

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.63 12562

cursor "@1@" already in use

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.64 12563

arguments given for cursor without arguments

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.65 12564

arguments required for cursor

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.66 12565

FOREACH expression must not be null

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.67 12566

FOREACH expression must yield an array, not type @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.68 12567

slice dimension (@1@) is out of the valid range 0..@2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.69 12568

FOREACH ... SLICE loop variable must be of an array type

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.70 12569

FOREACH loop variable must not be of an array type

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.71 12570

cannot use RETURN NEXT in a non-SETOF function

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.72 12571

wrong result type supplied in RETURN NEXT

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.73 12572

record "@1@" is not assigned yet

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.74 12573

wrong record type supplied in RETURN NEXT

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.75 12574

RETURN NEXT must have a parameter

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.76 12575

cannot use RETURN QUERY in a non-SETOF function

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.77 12576

RAISE without parameters cannot be used outside an exception handler

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.78 12577

too few parameters specified for RAISE

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.79 12578

too many parameters specified for RAISE

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.80 12579

RAISE statement option cannot be null

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.81 12580

RAISE option already specified: @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.82 12581

cannot COPY to/from client in PL/pgSQL

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.83 12582

cannot begin/end transactions in PL/pgSQL

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.84 12583

INTO used with a command that cannot return data

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.85 12584

query returned no rows

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.86 12585

query returned more than one row

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.87 12586

query has no destination for result data

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.88 12587

query string argument of EXECUTE is null

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.89 12588

EXECUTE of SELECT ... INTO is not implemented

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.90 12589

cursor variable "@1@" is null

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.91 12590

cursor "@1@" does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.92 12591

relative or absolute cursor position is null

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.93 12592

null value cannot be assigned to variable "@1@" declared NOT NULL

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.94 12593

cannot assign non-composite value to a row variable

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.95 12594

cannot assign non-composite value to a record variable

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.96 12595

number of array dimensions (@1@) exceeds the maximum allowed (@2@)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.97 12596

subscripted object is not an array

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.98 12597

array subscript in assignment must not be null

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.26.99 12598

query "@1@" did not return data

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27 Message Numbers Beginning with 12600

2.27.1 12600

row or record variable cannot be NOT NULL

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.2 12601

default value for row or record variable is not supported

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.3 12603

"@1@" is not a scalar variable

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.4 12604

loop variable of loop over rows must be a record or row variable or list of scalar variables

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.5 12605

cursor FOR loop must have only one target variable

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.6 12606

cursor FOR loop must use a bound cursor variable

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.7 12607

integer FOR loop must have only one target variable

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.8 12608

cannot specify REVERSE in query FOR loop

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.9 12609

loop variable of FOREACH must be a known variable or list of variables

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.10 12610

FETCH statement cannot return multiple rows

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.11 12611

cursor variable must be a simple variable

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.12 12612

variable "@1@" must be of type cursor or refcursor

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.13 12613

"@1@" is not a known variable

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.14 12614

missing "@1@" at end of SQL expression

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.15 12615

missing "@1@" at end of SQL statement

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.16 12616

RETURN cannot have a parameter in function returning set

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.17 12617

RETURN cannot have a parameter in function with OUT parameters

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.18 12618

RETURN cannot have a parameter in function returning void

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.19 12619

RETURN must specify a record or row variable in function returning row

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.20 12620

RETURN NEXT cannot have a parameter in function with OUT parameters

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.21 12621

RETURN NEXT must specify a record or row variable in function returning row

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.22 12622

"@1@" is declared CONSTANT

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.23 12623

record or row variable cannot be part of multiple-item INTO list

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.24 12624

too many INTO variables specified

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.25 12625

end label "@1@" specified for unlabelled block

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.26 12626

end label "@1@" differs from block's label "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.27 12627

cursor "@1@" has no arguments

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.28 12628

cursor "@1@" has arguments

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.29 12629

@1@ at end of input

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.30 12630

unexpected return value from trigger procedure

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.31 12631

PL/Python trigger function returned "MODIFY" in a DELETE trigger -- ignored

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.27.32 12632

TD["new"] deleted, cannot modify row

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.33 12633

TD["new"] is not a dictionary

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.34 12634

TD["new"] dictionary key at ordinal position @1@ is not a string

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.35 12635

key "@1@" found in TD["new"] does not exist as a column in the triggering row

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.36 12636

unsupported set function return mode

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.37 12637

returned object cannot be iterated

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.38 12638

PL/Python function with return type "void" did not return None

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.39 12639

forcibly aborting a subtransaction that has not been exited

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.27.40 12640

function returning record called in context that cannot accept type record

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.41 12641

trigger functions can only be called as triggers

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.42 12642

PL/Python functions cannot return type @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.43 12643

PL/Python functions cannot accept type @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.44 12644

cannot convert multidimensional array to Python list

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.45 12645

could not convert Python object into cstring: Python string representation appears to contain null bytes

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.46 12646

key "@1@" not found in mapping

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.47 12647

length of returned sequence did not match number of columns in row

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.48 12648

attribute "@1@" does not exist in Python object

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.49 12649

plpy.prepare: type name at ordinal position @1@ is not a string

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.50 12650

plpy.prepare does not support composite types

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.51 12651

Python major version mismatch in session

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.52 12652

@1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.53 12653

@1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.54 12654

out of memory

[Description]

There was insufficient free space in the server's memory during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Estimate memory usage and take the following action:

- If the number of simultaneous connections from client applications is high, reduce it.
- If the number of simultaneous SQL executions is high, reduce it.

2.27.55 12655

trigger functions can only be called as triggers

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.56 12656

PL/Tcl functions cannot return type @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.27.57 12657

PL/Tcl functions cannot return composite types

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.28 Message Numbers Beginning with 12700

2.28.1 12704

function "@1@" does not exist

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.28.2 12725

operator @1@ is not a valid ordering operator

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.29 Message Numbers Beginning with 12900

2.29.1 12908

could not remove cache file "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.29.2 12909

could not open tablespace directory "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.30 Message Numbers Beginning with 13000

2.30.1 13092

too few arguments for format

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.30.2 13093

unrecognized conversion specifier "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.30.3 13094

null values cannot be formatted as an SQL identifier

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.31 Message Numbers Beginning with 13300

2.31.1 13359

online backup was canceled, recovery cannot continue

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.31.2 13362

online backup mode canceled

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.31.3 13363

online backup mode was not canceled

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.32 Message Numbers Beginning with 13400

2.32.1 13449

cannot convert whole-row table reference

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.32.2 13452

cannot alter type "@1@" because column "@2@.@3@" uses it

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.32.3 13453

cannot alter foreign table "@1@" because column "@2@.@3@" uses its row type

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.32.4 13454

cannot alter table "@1@" because column "@2@.@3@" uses its row type

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.32.5 13478

parameter "lc_ctype" must be specified

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.32.6 13481

operator family "@1@" does not exist for access method "@2@"

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.32.7 13490

directories for tablespace @1@ could not be removed

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.32.8 13497

cannot drop extension "@1@" because it is being modified

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.32.9 13499

pg_extension_config_dump() can only be called from an SQL script executed by CREATE EXTENSION

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.33 Message Numbers Beginning with 13500

2.33.1 13508

must be superuser to set schema of @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.33.2 13580

cannot PREPARE while holding both session-level and transaction-level locks on the same object

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.33.3 13589

sending cancel to blocking autovacuum PID @1@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.33.4 13597

not enough elements in RWConflictPool to record a read/write conflict

[Description]

There was insufficient free space in the server's memory during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Estimate memory usage and take the following action:

- If the number of simultaneous connections from client applications is high, reduce it.
- If the number of simultaneous SQL executions is high, reduce it.

2.33.5 13598

not enough elements in RWConflictPool to record a potential read/write conflict

[Description]

There was insufficient free space in the server's memory during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Estimate memory usage and take the following action:

- If the number of simultaneous connections from client applications is high, reduce it.
- If the number of simultaneous SQL executions is high, reduce it.

2.34 Message Numbers Beginning with 13700

2.34.1 13761

cannot move extension "@1@" into schema "@2@" because the extension contains the schema

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.35 Message Numbers Beginning with 13800

2.35.1 13833

column @1@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.35.2 13860

symbolic link "@1@" target is too long

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.35.3 13863

invalid standby message type "@1@"

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.35.4 13864

unexpected message type "@1@"

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.35.5 13884

could not create signal listener pipe for PID @1@: error code @2@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.36 Message Numbers Beginning with 13900

2.36.1 13922

could not close handle to backend parameter variables: error code @1@

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.36.2 13941

conflicting constraint properties

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.36.3 13943

@1@ constraints cannot be marked DEFERRABLE

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.36.4 13944

@1@ constraints cannot be marked NOT VALID

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.37 Message Numbers Beginning with 14000

2.37.1 14024

column name must be qualified

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.37.2 14028

cannot create relations in temporary schemas of other sessions

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.37.3 14029

cannot create temporary relation in non-temporary schema

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.37.4 14030

only temporary relations may be created in temporary schemas

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.37.5 14042

cannot reassign ownership of objects owned by @1@ because they are required by the database system

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.38 Message Numbers Beginning with 14100

2.38.1 14104

cannot convert Perl array to non-array type @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.38.2 14105

cannot convert Perl hash to non-composite type @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.39 Message Numbers Beginning with 14200

2.39.1 14211

PL/Tcl functions cannot accept type @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.39.2 14218

"@1@" is a table

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.39.3 14282

cannot add schema "@1@" to extension "@2@" because the schema contains the extension

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.39.4 14284

could not identify current directory: @1@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.39.5 14285

invalid binary "@1@"

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.39.6 14286

could not read binary "@1@"

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.39.7 14287

could not find a "@1@" to execute

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.39.8 14288

could not change directory to "@1@"

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.39.9 14289

could not read symbolic link "@1@"

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.39.10 14290

child process exited with exit code @1@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.39.11 14291

child process was terminated by exception 0x@1@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.39.12 14292

child process was terminated by signal @1@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.39.13 14293

child process was terminated by signal @1@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.39.14 14294

child process exited with unrecognized status @1@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.39.15 14295

could not identify current directory: @1@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.39.16 14296

invalid binary "@1@"

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.39.17 14297

could not read binary "@1@"

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.39.18 14298

could not find a "@1@" to execute

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.39.19 14299

could not change directory to "@1@"

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40 Message Numbers Beginning with 14300

2.40.1 14300

could not read symbolic link "@1@"

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.2 14301

child process exited with exit code @1@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.3 14302

child process was terminated by exception 0x@1@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.4 14303

child process was terminated by signal @1@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.5 14304

child process was terminated by signal @1@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.6 14305

child process exited with unrecognized status @1@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.7 14306

could not identify current directory: @1@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.8 14307

invalid binary "@1@"

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.9 14308

could not read binary "@1@"

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.10 14309

could not find a "@1@" to execute

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.11 14310

could not change directory to "@1@"

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.12 14311

could not read symbolic link "@1@"

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.13 14312

child process exited with exit code @1@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.14 14313

child process was terminated by exception 0x@1@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.15 14314

child process was terminated by signal @1@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.16 14315

child process was terminated by signal @1@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.17 14316

child process exited with unrecognized status @1@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.18 14318

could not identify current directory: @1@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.19 14319

invalid binary "@1@"

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.20 14320

could not read binary "@1@"

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.21 14321

could not find a "@1@" to execute

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.22 14322

could not change directory to "@1@"

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.23 14323

could not read symbolic link "@1@"

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.24 14324

child process exited with exit code @1@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.25 14325

child process was terminated by exception 0x@1@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.26 14326

child process was terminated by signal @1@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.27 14327

child process was terminated by signal @1@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.28 14328

auto-open of the keystore has been enabled

[Description]

Enabled automatic opening of the keystore.

[System Processing]

Continues processing.

[Action]

No action required.

2.40.29 14329

could not identify current directory: @1@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.30 14330

invalid binary "@1@"

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.31 14331

could not read binary "@1@"

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.32 14332

could not find a "@1@" to execute

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.33 14333

could not change directory to "@1@"

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.34 14334

could not read symbolic link "@1@"

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.35 14335

child process exited with exit code @1@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.36 14336

child process was terminated by exception 0x@1@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.37 14337

child process was terminated by signal @1@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.38 14338

child process was terminated by signal @1@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.39 14339

@1@: no database directory specified and environment variable PGDATA unset

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.40 14340

could not identify current directory: @1@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.41 14341

invalid binary "@1@"

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.42 14342

could not read binary "@1@"

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.43 14343

could not find a "@1@" to execute

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.44 14344

could not change directory to "@1@"

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.45 14345

could not read symbolic link "@1@"

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.46 14346

child process exited with exit code @1 @

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.47 14347

child process was terminated by exception 0x@1 @

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.48 14348

child process was terminated by signal @1 @

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.49 14349

child process was terminated by signal @1 @

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.40.50 14351

could not access directory for core file "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.40.51 14352

path specified by configuration parameter "@1@" is invalid: "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.40.52 14353

WAL archiving is not active

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.40.53 14354

could not set permissions on path specified by configuration parameter "@1@": "@2@": @3@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.40.54 14359

could not extend file "@1@", but retrying: @2@

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.40.55 14360

could not read block @1@ in file "@2@", but retrying: @3@

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.40.56 14361

could not write block @1@ in file "@2@", but retrying: @3@

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.40.57 14362

invalid page header in block @1@ of relation @2@, but retrying

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.40.58 14363

Calculated checksum does not match value stored in block @1@ of relation @2@, but retrying

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.40.59 14364

Calculated checksum does not match value stored in block @1@ of relation @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.40.60 14366

a failure has occurred while multiplexing transaction log files

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.40.61 14367

multiplexing of transaction log files has been stopped

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.40.62 14368

must be superuser to control WAL multiplexing

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.40.63 14369

WAL multiplexing is not configured

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.40.64 14370

WAL multiplexing is already paused

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.40.65 14371

WAL multiplexing is not paused

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.40.66 14372

could not fork XLog multiplexer process: @1@**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.40.67 14373

could not set junction for "@1@": @2@**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.40.68 14374

could not set junction for "@1@": @2@**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.40.69 14375

could not remove file or directory "@1@": @2@**[Description]**

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.40.70 14376

could not remove file "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.40.71 14377

could not set junction for "@1@": @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.40.72 14378

could not get junction for "@1@": @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.40.73 14379

could not open directory "@1@": @2@

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.40.74 14380

could not read directory "@1@": @2@

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.40.75 14381

could not stat file or directory "@1@": @2@

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.40.76 14384

could not determine encoding for locale "@1@": codeset is "@2@"

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.40.77 14385

could not remove file or directory "@1@": @2@

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.40.78 14388

@1@ at or near "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.40.79 14390

query "@1@" returned more than one row

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.40.80 14391

query "@1@" is not a SELECT

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.40.81 14392

block label must be placed before DECLARE, not after

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.40.82 14393

collations are not supported by type @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.40.83 14394

row or record variable cannot be CONSTANT

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.40.84 14395

cannot use serializable mode in a hot standby

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.40.85 14399

KNN search is not supported for btree_gist type @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.41 Message Numbers Beginning with 14400

2.41.1 14400

<datatype>key_in() not implemented

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.41.2 14401

<datatype>key_out() not implemented

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.41.3 14402

money out of range

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.41.4 14403

Command error occurred during access to the view. view name: "@1@" command name: "@2@" detail: "@3@"

[Description]

An internal command process error occurred in the database server.

[System Processing]

Processing is aborted.

[Action]

This messages is output in the case of HA Database Ready.

The error occurred due to insufficient memory or a disk error. To check the cause and take the following action:

- Insufficient memory:

Estimate memory usage and take the following action:

a) If the number of simultaneous connections from client applications is high, reduce it.

b) If the number of simultaneous SQL executions is high, reduce it.

- Disk error:

You can restart the application, because the database server is mirrored and will be automatically switched.

If the same error occurs when you restart the application, to confirm that there is no other error in the database server.

2.41.5 14404

I/O error occurred during access to the view. view name: "@1@" file name: "@2@" function: "@3@" detail: "@4@"

[Description]

An error occurred during database server I/O processing.

[System Processing]

Processing is aborted.

[Action]

This messages is output in the case of HA Database Ready.

The process was canceled due to a disk error in the database server. However, you can restart the application, because the database server is mirrored and will be automatically switched.

If the same error occurs when you restart the application, to confirm that there is no error in the database server.

2.41.6 14405

File is inconsistent during access to the view. file name: "@1@" line number: @2@

[Description]

An internal inconsistency was detected in a file of the database server.

[System Processing]

Processing is aborted.

[Action]

This messages is output in the case of HA Database Ready.

The process was canceled due to a disk error in the database server. However, you can restart the application, because the database server is mirrored and will be automatically switched.

If the same error occurs when you restart the application, to confirm that there is no error in the database server.

2.41.7 14406

Data error occurred during access to the view. view name: "@1@" command name: "@2@" data: "@3@"

[Description]

An internal command process error occurred in the database server.

[System Processing]

Processing is aborted.

[Action]

This messages is output in the case of HA Database Ready.

Contact Fujitsu technical support.

2.41.8 14407

must be superuser to use pgstattuple functions

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.41.9 14408

"@1@" (@2@) is not supported

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.41.10 14409

page offset number out of range

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.41.11 14410

block number out of range

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.41.12 14411

relation "@1@" is not a btree index

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.41.13 14412

duration: %.3f ms plan:%s

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.41.14 14414

unrecognized strategy number: @1@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.41.15 14417

could not read pg_stat_statement file "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.41.16 14418

could not rename pg_stat_statement file "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.41.17 14419

could not write lock file "@1@": @2@

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.41.18 14420

pg_stat_statements must be loaded via shared_preload_libraries

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.41.19 14421

Expected 1 tuple with 3 fields, got @1@ tuples with @2@ fields.

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.41.20 14422

The primary's identifier is @1@, the standby's identifier is @2@.

[Description]

An error occurred during I/O processing in the database server.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.41.21 14423

The transaction has already committed locally, but might not have been replicated to the standby.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.22 14424

You can choose the collation by applying the COLLATE clause to one or both expressions.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.23 14425

Query has too few columns.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.24 14426

Cannot cast type @1@ to @2@ in column @3@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.25 14427

Query has too many columns.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.26 14428

@1@ versus @2@

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.27 14429

Could not choose a best candidate function. You might need to add explicit type casts.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.28 14430

No aggregate function matches the given name and argument types. Perhaps you misplaced ORDER BY; ORDER BY must appear after all regular arguments of the aggregate.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.29 14431

No function matches the given name and argument types. You might need to add explicit type casts.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.30 14432

There is a WITH item named "@1@", but it cannot be referenced from this part of the query.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.31 14433

Use WITH RECURSIVE, or re-order the WITH items to remove forward references.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.32 14434

Perhaps you meant to reference the table alias "@1@".

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.33 14435

There is an entry for table "@1@", but it cannot be referenced from this part of the query.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.34 14436

String constants with Unicode escapes cannot be used when standard_conforming_strings is off.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.35 14437

Unicode escapes must be \uXXXX or \UXXXXXXXX.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.36 14438

Use " to write quotes in strings. \' is insecure in client-only encodings.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.37 14439

Use " to write quotes in strings, or use the escape string syntax (E'...').

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.38 14440

Use the escape string syntax for backslashes, e.g., E'\\'.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.39 14441

Use the escape string syntax for escapes, e.g., E'\\r\\n'.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.40 14442

Cast the output of the non-recursive term to the correct type.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.41 14443

Use the COLLATE clause to set the collation of the non-recursive term.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.42 14444

Explicitly cast to the desired type, for example ARRAY[]::integer[].

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.43 14445

Row comparison operators must be associated with btree operator families.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.44 14446

There are multiple equally-plausible candidates.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.45 14447

You will need to rewrite or cast the expression.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.46 14448

Use an explicit ordering operator or modify the query.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.47 14449

Could not choose a best candidate operator. You might need to add explicit type casts.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.48 14450

No operator matches the given name and argument type(s). You might need to add explicit type casts.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.49 14451

Aggregates with DISTINCT must be able to sort their inputs.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.50 14452

Constraint "@1@" contains a whole-row reference to table "@2@".

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.51 14453

Index "@1@" contains a whole-row table reference.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.52 14454

Cannot create a primary key or unique constraint using such an index.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.53 14455

Cannot create a non-deferrable constraint using a deferrable index.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.54 14456

Ordering operators must be "<" or ">" members of btree operator families.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.55 14457

Update your data type.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.56 14458

Use NONE to denote the missing argument of a unary operator.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.57 14459

Use separate LIMIT and OFFSET clauses.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.58 14460

For example, FROM (VALUES ...) [AS] foo.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.59 14461

For example, FROM (SELECT ...) [AS] foo.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.60 14462

Use SELECT ... UNION ALL ... instead.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.61 14463

The insertion source is a row expression containing the same number of columns expected by the INSERT. Did you accidentally use extra parentheses?

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.62 14464

Only result column names can be used, not expressions or functions.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.63 14465

Add the expression/function to every SELECT, or move the UNION into a FROM clause.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.64 14466

Scrollable cursors must be READ ONLY.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.65 14467

Holdable cursors must be READ ONLY.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.66 14468

Insensitive cursors must be READ ONLY.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.67 14469

Valid options in this context are: @1@

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.68 14470

Specify OWNED BY table.column or OWNED BY NONE.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.69 14471

Extension names must not be empty.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.70 14472

Extension names must not contain "--".

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.71 14473

Extension names must not begin or end with "-".

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.72 14474

Extension names must not contain directory separator characters.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.73 14475

Version names must not be empty.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.74 14476

Version names must not contain "--".

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.75 14477

Version names must not begin or end with "-".

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.76 14478

Version names must not contain directory separator characters.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.77 14479

Must be superuser to create this extension.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.78 14480

Must be superuser to update this extension.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.79 14481

@1@ is not in the extension's schema "@2@"

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.80 14482

Consider using tablespaces instead.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.81 14483

Use the same encoding as in the template database, or use template0 as template.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.82 14484

Use the same collation as in the template database, or use template0 as template.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.83 14485

Use the same LC_CTYPE as in the template database, or use template0 as template.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.84 14486

There is a conflict because database "@1@" already has some tables in this tablespace.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.85 14487

The chosen LC_CTYPE setting requires encoding "@1@".

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.86 14488

The chosen LC_COLLATE setting requires encoding "@1@".

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.87 14489

You must move them back to the database's default tablespace before using this command.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.88 14490

There are @1@ other session(s) and @2@ prepared transaction(s) using the database.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.89 14493

@1@ dead row versions cannot be removed yet. @2@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.90 14494

The prefix "pg_" is reserved for system schemas.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.91 14495

This name may be disallowed altogether in future versions of PostgreSQL.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.92 14496

The server process with PID @1@ is among those with the oldest transactions.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.93 14497

The NOTIFY queue cannot be emptied until that process ends its current transaction.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.94 14498

Use the COLLATE clause to set the collation explicitly.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.41.95 14499

[The supported languages are listed in the pg_pltemplate system catalog.](#)

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42 Message Numbers Beginning with 14500

2.42.1 14500

[Anyone can COPY to stdout or from stdin. psql's \copy command also works for anyone.](#)

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.2 14501

[Try the COPY \(SELECT ...\) TO variant.](#)

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.3 14502

[COPY @1@, line @2@, column @3@](#)

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.4 14503

COPY @1@, line @2@

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.5 14504

COPY @1@, line @2@, column @3@: "@4@"

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.6 14505

COPY @1@, line @2@, column @3@: null input

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.7 14506

COPY @1@, line @2@: "@3@"

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.8 14507

Use "\\r" to represent carriage return.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.9 14508

Use quoted CSV field to represent carriage return.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.10 14509

Use "\\n" to represent newline.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.11 14510

Use quoted CSV field to represent newline.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.12 14511

@1@ dead row versions cannot be removed yet. There were @2@ unused item pointers. @3@ pages are entirely empty. @4@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.13 14512

[@1@](#).

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.14 14513

[@1@ index row versions were removed. @2@ index pages have been deleted, @3@ are currently reusable. @4@](#).

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.15 14514

[Operator class "@1@" already is the default.](#)

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.16 14515

[Must be superuser to change owner of a foreign-data wrapper.](#)

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.17 14516

The owner of a foreign-data wrapper must be a superuser.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.18 14517

Must be superuser to create a foreign-data wrapper.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.19 14518

Must be superuser to alter a foreign-data wrapper.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.20 14520

Expected @1@ parameters but got @2@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.21 14521

Close open transactions soon to avoid wraparound problems.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.22 14522

You might have already suffered transaction-wraparound data loss.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.23 14523

Must be superuser to create a tablespace.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.24 14524

The prefix "pg_" is reserved for system tablespaces.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.25 14525

Create this directory for the tablespace before restarting the server.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.26 14526

You can remove the directories manually if necessary.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.27 14527

Use ALTER FOREIGN TABLE instead.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.28 14528

You can alter type @1@, which will alter the array type as well.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.29 14529

Tables cannot have INSTEAD OF triggers.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.30 14530

Views cannot have row-level BEFORE or AFTER triggers.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.31 14531

Views cannot have TRUNCATE triggers.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.32 14532

"@1@" versus "@2@"

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.33 14533

To resolve the conflict, specify a default explicitly.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.34 14534

Use ALTER TYPE instead.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.35 14535

Use ALTER ... CASCADE to alter the typed tables too.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.36 14536

Key columns "@1@" and "@2@" are of incompatible types: @3@ and @4@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.37 14537

@1@ depends on @2@

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.38 14538

Change the ownership of the index's table, instead.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.39 14539

Sequence "@1@" is linked to table "@2@".

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.40 14540

"@1@" is already a child of "@2@".

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.41 14541

Only commutative operators can be used in exclusion constraints.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.42 14542

The exclusion operator must be related to the index operator class for the constraint.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.43 14543

You must specify an operator class for the index or define a default operator class for the data type.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.44 14544

Creating a shell type definition.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.45 14545

Use CREATE LANGUAGE to load the language into the database.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.46 14546

Use DROP AGGREGATE to drop aggregate functions.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.47 14547

Use ALTER AGGREGATE to rename aggregate functions.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.48 14548

Use ALTER AGGREGATE to change owner of aggregate functions.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.49 14549

Key @1@ is duplicated.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.50 14550

Perhaps out of disk space?

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.51 14551

Perhaps you need a different "datestyle" setting.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.52 14552

The operating system could not find any locale data for the locale name "@1@".

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.53 14553

The server's LC_CTYPE locale is probably incompatible with the database encoding.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.54 14554

Provide two argument types for operator.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.55 14555

Missing left parenthesis.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.56 14556

Too few columns.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.57 14557

Unexpected end of input.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.58 14558

Too many columns.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.59 14559

Junk after right parenthesis.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.60 14560

Intervals are not tied to specific calendar dates.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.61 14561

"EEEE" may only be used together with digit and decimal point patterns.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.62 14562

Do not mix Gregorian and ISO week date conventions in a formatting template.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.63 14563

This value contradicts a previous setting for the same field type.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.64 14564

Field requires @1@ characters, but only @2@ remain.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.65 14565

If your source string is not fixed-width, try using the "FM" modifier.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.66 14566

Field requires @1@ characters, but only @2@ could be parsed.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.67 14567

Value must be an integer.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.68 14568

Value must be in the range @1@ to @2@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.69 14569

The given value did not match any of the allowed values for this field.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.70 14570

Use the 24-hour clock, or give an hour between 1 and 12.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.71 14571

Escape string must be empty or one character.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.72 14572

Value has bits set to right of mask.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.73 14573

Target must be "bgwriter".

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.74 14574

Identifier must be less than @1@ characters.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.75 14575

This functionality requires the server to be built with libxml support.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.76 14576

You need to rebuild PostgreSQL using --with-libxml.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.77 14577

XML processing instruction target name cannot be "@1@".

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.78 14578

XML processing instruction cannot contain "?>".

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.79 14579

libxml2 has incompatible char type: sizeof(char)=@1@, sizeof(xmlChar)=@2@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.80 14580

XML does not support infinite date values.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.81 14581

XML does not support infinite timestamp values.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.82 14582

The array must be two-dimensional with length of the second axis equal to 2.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.83 14583

ACL key word must be "group" or "user".

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.84 14584

A name must follow the "group" or "user" key word.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.85 14585

Use CASCADE to revoke them too.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.86 14586

Dimension array must be one dimensional.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.87 14587

Lower bound of dimension array must be one.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.88 14588

Low bound array has different size than dimensions array.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.89 14589

MATCH FULL does not allow mixing of null and nonnull key values.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.90 14590

Remove this referential integrity trigger and its mates, then do ALTER TABLE ADD CONSTRAINT.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.91 14591

This is most likely due to a rule having rewritten the query.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.92 14592

No rows were found in "@1@".

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.93 14593

Key (@1@)=(@2@) is not present in table "@3@".

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.94 14594

Key (@1@)=(@2@) is still referenced from table "@3@".

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.95 14595

A field with precision @1@, scale @2@ must round to an absolute value less than @3@@4@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.96 14596

Arrays with element types @1@ and @2@ are not compatible for concatenation.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.97 14597

Arrays of @1@ and @2@ dimensions are not compatible for concatenation.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.98 14598

Arrays with differing element dimensions are not compatible for concatenation.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.42.99 14599

Arrays with differing dimensions are not compatible for concatenation.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43 Message Numbers Beginning with 14600

2.43.1 14600

Is another postgres (PID @1@) running in data directory "@2@"?

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.2 14601

Is another postmaster (PID @1@) running in data directory "@2@"?

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.3 14602

Is another postgres (PID @1@) using socket file "@2@"?

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.4 14603

Is another postmaster (PID @1@) using socket file "@2@"?

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.5 14604

If you're sure there are no old server processes still running, remove the shared memory block or just delete the file "@1@".

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.6 14605

The file seems accidentally left over, but it could not be removed. Please remove the file by hand and try again.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.7 14606

File "@1@" is missing.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.8 14607

File "@1@" does not contain valid data.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.9 14608

You might need to initdb.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.10 14609

The data directory was initialized by PostgreSQL version @1@.@2@, which is not compatible with this version @3@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.11 14610

Specify an absolute path.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.12 14611

Set up WAL archiving when you configure "@1@" parameter.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.13 14612

Database OID @1@ now seems to belong to "@2@".

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.14 14613

User does not have CONNECT privilege.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.15 14614

The database was initialized with LC_COLLATE "@1@", which is not recognized by setlocale().

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.16 14615

Recreate the database with another locale or install the missing locale.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.17 14616

The database was initialized with LC_CTYPE "@1@", which is not recognized by setlocale().

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.18 14617

You should immediately run CREATE USER "@1@" SUPERUSER;.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.19 14618

It seems to have just been dropped or renamed.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.20 14619

The database subdirectory "@1@" is missing.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.21 14620

String of @1@ bytes is too long for encoding conversion.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.22 14621

Continuing anyway, but there's something wrong.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.23 14622

Failed while creating memory context "@1@".

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.24 14623

Failed on request of size @1@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.25 14624

Extension libraries are required to use the PG_MODULE_MAGIC macro.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.26 14625

Server is version @1@.@2@, library is version @3@.@4@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.27 14626

Specify a relation name as well as a rule name.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.28 14627

You need an unconditional ON INSERT DO INSTEAD rule with a RETURNING clause.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.29 14628

You need an unconditional ON UPDATE DO INSTEAD rule with a RETURNING clause.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.30 14629

You need an unconditional ON DELETE DO INSTEAD rule with a RETURNING clause.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.31 14630

Use views or triggers instead.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.32 14631

Use triggers instead.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.33 14632

Use views instead.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.34 14633

In particular, the table cannot be involved in any foreign key relationships.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.35 14634

Failed system call was shmget(key=@1 @, size=@2 @, 0@3 @).

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.36 14635

This error usually means that PostgreSQL's request for a shared memory segment exceeded your kernel's SHMMAX parameter. You can either reduce the request size or reconfigure the kernel with larger SHMMAX. To reduce the request size (currently @1 @ bytes), reduce PostgreSQL's shared memory usage, perhaps by reducing shared_buffers or max_connections. If the request size is already small, it's possible that it is less than your kernel's SHMMIN parameter, in which case raising the request size or reconfiguring SHMMIN is called for. The PostgreSQL documentation contains more information about shared memory configuration.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.37 14636

This error usually means that PostgreSQL's request for a shared memory segment exceeded available memory or swap space, or exceeded your kernel's SHMALL parameter. You can either reduce the request size or reconfigure the kernel with larger SHMALL. To reduce the request size (currently @1 @ bytes), reduce PostgreSQL's shared memory usage, perhaps by reducing shared_buffers or max_connections. The PostgreSQL documentation contains more information about shared memory configuration.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.38 14637

This error does **not mean that you have run out of disk space. It occurs either if all available shared memory IDs have been taken, in which case you need to raise the SHMMNI parameter in your kernel, or because the system's overall limit for shared memory has been reached. If you cannot increase the shared memory limit, reduce PostgreSQL's shared memory request (currently @1@ bytes), perhaps by reducing shared_buffers or max_connections. The PostgreSQL documentation contains more information about shared memory configuration.**

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.39 14638

Failed system call was CreateFileMapping(size=@1@, name=@2@).

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.40 14639

Check if there are any old server processes still running, and terminate them.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.41 14640

Failed system call was DuplicateHandle.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.42 14641

Failed system call was MapViewOfFileEx.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.43 14642

Failed system call was semget(@1 @, @2@, 0@3@).

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.44 14643

This error does *not* mean that you have run out of disk space. It occurs when either the system limit for the maximum number of semaphore sets (SEMMNI), or the system wide maximum number of semaphores (SEMMNS), would be exceeded. You need to raise the respective kernel parameter. Alternatively, reduce PostgreSQL's consumption of semaphores by reducing its max_connections parameter. The PostgreSQL documentation contains more information about configuring your system for PostgreSQL.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.45 14644

You possibly need to raise your kernel's SEMVMX value to be at least @1@. Look into the PostgreSQL documentation for details.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.46 14645

Some of the datatypes only support hashing, while others only support sorting.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.47 14646

Window partitioning columns must be of sortable datatypes.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.48 14647

Window ordering columns must be of sortable datatypes.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.49 14648

SQL function "@1@" during startup

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.50 14649

All column datatypes must be hashable.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.51 14650

See server log for query details.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.52 14651

Client IP address resolved to "@1@", forward lookup matches.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.53 14652

Client IP address resolved to "@1@", forward lookup not checked.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.54 14653

Client IP address resolved to "@1@", forward lookup does not match.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.55 14654

LDAP over SSL is not supported on this platform.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.56 14655

Is another postmaster already running on port @1@? If not, remove socket file "@2@" and retry.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.57 14656

Is another postmaster already running on port @1@? If not, wait a few seconds and retry.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.58 14657

Anyone can use the client-side lo_import() provided by libpq.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.59 14658

Anyone can use the client-side lo_export() provided by libpq.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.60 14659

Permissions should be u=rw (0600) or less.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.61 14660

SSL library does not support certificate revocation lists.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.62 14662

line @1@ of configuration file "@2@"

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.63 14663

Set ssl = on in postgresql.conf.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.64 14664

Compile with --with-openssl to use SSL connections.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.65 14666

Cannot enlarge string buffer containing @1@ bytes by @2@ more bytes.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.66 14667

Please REINDEX it.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.67 14668

Values larger than 1/3 of a buffer page cannot be indexed. Consider a function index of an MD5 hash of the value, or use full text indexing.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.68 14669

Key @1@ already exists.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.69 14670

This may be because of a non-immutable index expression.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.70 14671

To fix this, do REINDEX INDEX "@1@".

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.71 14672

This is caused by an incomplete page split at crash recovery before upgrading to PostgreSQL 9.1.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.72 14673

The index is not optimal. To optimize it, contact a developer, or try to use the column as the second one in the CREATE INDEX command.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.73 14674

Could not open file "@1@": @2@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.74 14675

Could not seek in file "@1@" to offset @2@: @3@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.75 14676

Could not read from file "@1@" at offset @2@: @3@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.76 14677

Could not write to file "@1@" at offset @2@: @3@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.77 14678

Could not fsync file "@1@": @2@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.78 14679

Could not close file "@1@": @2@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.79 14680

Set max_prepared_transactions to a nonzero value.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.80 14681

Increase max_prepared_transactions (currently @1@).

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.81 14682

Must be superuser or the user that prepared the transaction.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.82 14683

Connect to the database where the transaction was prepared to finish it.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.83 14684

WAL file database system identifier is @1@, pg_control database system identifier is @2@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.84 14685

Incorrect XLOG_SEG_SIZE in page header.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.85 14686

Incorrect XLOG_BLCKSZ in page header.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.86 14687

Expected a numeric timeline ID.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.87 14688

Timeline IDs must be in increasing sequence.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.88 14689

Timeline IDs must be less than child timeline's ID.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.89 14690

The database cluster was initialized with PG_CONTROL_VERSION @1@ (0x@2@), but the server was compiled with PG_CONTROL_VERSION @3@ (0x@4@).

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.90 14691

This could be a problem of mismatched byte ordering. It looks like you need to initdb.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.91 14692

The database cluster was initialized with PG_CONTROL_VERSION @1@, but the server was compiled with PG_CONTROL_VERSION @2@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.92 14693

It looks like you need to initdb.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.93 14694

The database cluster was initialized with CATALOG_VERSION_NO @1@, but the server was compiled with CATALOG_VERSION_NO @2@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.94 14695

The database cluster was initialized with MAXALIGN @1 @, but the server was compiled with MAXALIGN @2@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.95 14696

The database cluster appears to use a different floating-point number format than the server executable.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.96 14697

The database cluster was initialized with BLCKSZ @1 @, but the server was compiled with BLCKSZ @2@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.97 14698

It looks like you need to recompile or initdb.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.43.98 14699

The database cluster was initialized with RELSEG_SIZE @1@, but the server was compiled with RELSEG_SIZE @2@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44 Message Numbers Beginning with 14700

2.44.1 14700

The database cluster was initialized with XLOG_BLCKSZ @1@, but the server was compiled with XLOG_BLCKSZ @2@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.2 14701

The database cluster was initialized with XLOG_SEG_SIZE @1@, but the server was compiled with XLOG_SEG_SIZE @2@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.3 14702

The database cluster was initialized with NAMEDATALEN @1@, but the server was compiled with NAMEDATALEN @2@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.4 14703

The database cluster was initialized with INDEX_MAX_KEYS @1@, but the server was compiled with INDEX_MAX_KEYS @2@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.5 14704

The database cluster was initialized with TOAST_MAX_CHUNK_SIZE @1@, but the server was compiled with TOAST_MAX_CHUNK_SIZE @2@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.6 14705

The database cluster was initialized without HAVE_INT64_TIMESTAMP but the server was compiled with HAVE_INT64_TIMESTAMP.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.7 14706

The database cluster was initialized with HAVE_INT64_TIMESTAMP but the server was compiled without HAVE_INT64_TIMESTAMP.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.8 14707

The database cluster was initialized without USE_FLOAT4_BYVAL but the server was compiled with USE_FLOAT4_BYVAL.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.9 14708

The database cluster was initialized with USE_FLOAT4_BYVAL but the server was compiled without USE_FLOAT4_BYVAL.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.10 14709

The database cluster was initialized without USE_FLOAT8_BYVAL but the server was compiled with USE_FLOAT8_BYVAL.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.11 14710

The database cluster was initialized with USE_FLOAT8_BYVAL but the server was compiled without USE_FLOAT8_BYVAL.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.12 14711

The database server will regularly poll the `pg_xlog` subdirectory to check for files placed there.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.13 14712

Execute `pg_xlog_replay_resume()` to continue.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.14 14713

Recovery control functions can only be executed during recovery.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.15 14714

This happens if you temporarily set `wal_level=minimal` without taking a new base backup.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.16 14715

Either set wal_level to "hot_standby" on the master, or turn off hot_standby here.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.17 14716

This probably means that some data is corrupted and you will have to use the last backup for recovery.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.18 14717

If this has occurred more than once some data might be corrupted and you might need to choose an earlier recovery target.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.19 14718

If you are not restoring from a backup, try removing the file "@1@/backup_label".

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.20 14719

Online backup started with `pg_start_backup()` must be ended with `pg_stop_backup()`, and all WAL up to that point must be available at recovery.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.21 14720

WAL control functions cannot be executed during recovery.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.22 14721

`wal_level` must be set to "archive" or "hot_standby" at server start.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.23 14722

Run `pg_stop_backup()` and try again.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.24 14723

If you're sure there is no backup in progress, remove file "@1@" and try again.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.25 14724

Check that your archive_command is executing properly. pg_stop_backup can be canceled safely, but the database backup will not be usable without all the WAL segments.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.26 14725

pg_xlogfile_name_offset() cannot be executed during recovery.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.27 14726

pg_xlogfile_name() cannot be executed during recovery.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.28 14727

xlog redo @1@

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.29 14728

"@1@" was renamed to "@2@".

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.30 14729

Could not rename "@1@" to "@2@": @3@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.31 14730

Stop the postmaster and use a standalone backend to vacuum that database. You might also need to commit or roll back old prepared transactions.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.32 14731

To avoid a database shutdown, execute a database-wide VACUUM in that database. You might also need to commit or roll back old prepared transactions.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.33 14732

Values larger than a buffer page cannot be indexed.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.34 14733

Valid values are between "@1@" and "@2@".

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.35 14734

Valid values are between "@1@" and "@2@".

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.36 14735

Returned type @1@ does not match expected type @2@ in column @3@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.37 14736

Number of returned columns (@1@) does not match expected column count (@2@).

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.38 14737

Attribute "@1@" of type @2@ does not match corresponding attribute of type @3@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.39 14738

Attribute "@1@" of type @2@ does not exist in type @3@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.40 14739

You need an unconditional ON INSERT DO INSTEAD rule or an INSTEAD OF INSERT trigger.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.41 14740

You need an unconditional ON UPDATE DO INSTEAD rule or an INSTEAD OF UPDATE trigger.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.42 14741

You need an unconditional ON DELETE DO INSTEAD rule or an INSTEAD OF DELETE trigger.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.43 14742

SQL function "@1@" statement @2@

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.44 14743

SQL function "@1@"

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.45 14744

SQL function "@1@" during inlining

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.46 14745

Function's final statement must be SELECT or INSERT/UPDATE/DELETE RETURNING.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.47 14746

Final statement must return exactly one column.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.48 14747

Actual return type is @1@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.49 14748

Final statement returns too many columns.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.50 14749

Final statement returns @1@ instead of @2@ at column @3@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.51 14750

Final statement returns too few columns.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.52 14751

Input has too many columns.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.53 14752

Table has type @1@ at ordinal position @2@, but query expects @3@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.54 14753

Query provides a value for a dropped column at ordinal position @1@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.55 14754

Input has too few columns.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.56 14755

Check for missing "SPI_finish" calls.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.57 14756

SQL statement "@1@"

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.58 14757

Table has type @1@, but query expects @2@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.59 14758

Table row contains @1@ attribute, but query expects @2@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.60 14759

Physical storage mismatch on dropped attribute at ordinal position @1@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.61 14760

Returned row contains @1@ attribute, but query expects @2@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.62 14761

Returned type @1@ at ordinal position @2@, but query expects @3@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.63 14762

Array with element type @1@ cannot be included in ARRAY construct with element type @2@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.64 14763

Key @1@ conflicts with key @2@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.65 14764

Key @1@ conflicts with existing key @2@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.66 14765

This has been seen to occur with buggy kernels; consider updating your system.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.67 14766

Multiple failures --- write error might be permanent.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.68 14767

writing block @1@ of relation @2@

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.69 14768

Only RowExclusiveLock or less can be acquired on database objects during recovery.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.70 14769

You might need to increase max_locks_per_transaction.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.71 14770

Not enough memory for reassigning the prepared transaction's locks.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.72 14771

You might need to run fewer transactions at a time or increase max_connections.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.73 14772

There might be an idle transaction or a forgotten prepared transaction causing this.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.74 14773

"default_transaction_isolation" is set to "serializable".

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.75 14774

You can use "SET default_transaction_isolation = 'repeatable read'" to change the default.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.76 14775

You might need to increase max_pred_locks_per_transaction.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.77 14776

The transaction might succeed if retried.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.78 14778

User transaction caused buffer deadlock with recovery.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.79 14779

System allows @1@, we need at least @2@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.80 14780

This indicates that the page was damaged while it was read, written, or stored on the disk due to a problem with the storage components.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.81 14781

Investigate the storage components such as disk device drivers, disk controllers, disk drives, BIOS, and volume management software to determine the root cause.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.82 14782

Check free disk space.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.83 14783

Consider increasing the configuration parameter "checkpoint_segments".

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.84 14784

Consult recent messages in the server log for details.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.85 14785

This may indicate an incomplete PostgreSQL installation, or that the file "@1@" has been moved away from its proper location.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.86 14786

The server must be started by the user that owns the data directory.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.87 14787

Permissions should be u=rwx (0700).

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.88 14788

See C include file "ntstatus.h" for a description of the hexadecimal value.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.89 14789

automatic vacuum of table "@1@.@2@.@3@"

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.90 14790

automatic analyze of table "@1@.@2@.@3@"

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.91 14791

Enable the "track_counts" option.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.92 14792

The failed archive command was: @1@

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.93 14793

Some of the transaction logs were lost that are necessary to recover the database completely.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.94 14794

Fix the problem by referring to the messages prior to this one. Then take a full backup of the database.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.95 14795

line @1@ of configuration file "@2@": "@3@"

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.96 14796

Words longer than @1@ characters are ignored.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.97 14797

Use "?" to represent a stop word within a sample phrase.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.98 14798

Declare it with SCROLL option to enable backward scan.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.44.99 14799

prepare: @1@

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45 Message Numbers Beginning with 14800

2.45.1 14800

parameters: @1@

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.2 14801

abort reason: recovery conflict

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.3 14802

User was holding shared buffer pin for too long.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.4 14803

User was holding a relation lock for too long.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.5 14804

User was or might have been using tablespace that must be dropped.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.6 14805

User query might have needed to see row versions that must be removed.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.7 14806

User was connected to a database that must be dropped.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.8 14807

The postmaster has commanded this server process to roll back the current transaction and exit, because another server process exited abnormally and possibly corrupted shared memory.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.9 14808

In a moment you should be able to reconnect to the database and repeat your command.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.10 14809

An invalid floating-point operation was signaled. This probably means an out-of-range result or an invalid operation, such as division by zero.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.11 14810

Increase the configuration parameter "max_stack_depth" (currently @1@kB), after ensuring the platform's stack depth limit is adequate.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.12 14811

Try "@1@ --help" for more information.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.13 14812

An aggregate returning a polymorphic type must have at least one polymorphic argument.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.14 14813

A function returning "internal" must have at least one "internal" argument.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.15 14814

Use DROP FUNCTION first.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.16 14815

Row type defined by OUT parameters is different.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.17 14816

System catalog modifications are currently disallowed.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.18 14817

Proceeding with relation creation anyway.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.19 14818

A relation has an associated type of the same name, so you must use a name that doesn't conflict with any existing type.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.20 14819

Table "@1@" references "@2@", but they do not have the same ON COMMIT setting.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.21 14820

Table "@1@" references "@2@".

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.22 14821

Truncate table "@1@" at the same time, or use TRUNCATE ... CASCADE.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.23 14822

Only superusers can use untrusted languages.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.24 14823

You can drop @1 @ instead.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.25 14824

Use DROP ... CASCADE to drop the dependent objects too.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.26 14825

An aggregate using a polymorphic transition type must have at least one polymorphic argument.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.27 14826

A function returning a polymorphic type must have at least one polymorphic argument.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.28 14827

Labels must be @1@ characters or less.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.29 14828

Valid fork names are "main", "fsm", and "vm".

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.30 14830

Continuing to retry for 30 seconds.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.31 14831

You might have antivirus, backup, or similar software interfering with the database system.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.32 14832

while executing PostgreSQL::InServer::SPI::bootstrap

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.33 14833

while parsing Perl initialization

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.34 14834

while running Perl initialization

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.35 14835

while executing PLC_TRUSTED

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.36 14836

while executing utf8fix

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.37 14837

while executing pperl.on_pperl_init

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.38 14838

while executing pperl.on_pperlu_init

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.39 14839

PL/Perl function "@1@"

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.40 14840

compilation of PL/Perl function "@1@"

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.41 14841

PL/Perl anonymous code block

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.42 14842

PL/Python function "@1@"

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.43 14843

PL/Python anonymous code block

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.44 14844

while modifying trigger row

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.45 14845

while creating return value

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.46 14846

Expected None or a string.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.47 14847

Expected None, "OK", "SKIP", or "MODIFY".

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.48 14848

PL/Python set-returning functions only support returning only value per call.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.49 14849

PL/Python set-returning functions must return an iterable object.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.50 14850

PL/Python does not support conversion to arrays of row types.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.51 14851

PL/Python only supports one-dimensional arrays.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.52 14852

To return null in a column, add the value None to the mapping with the key named after the column.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.53 14853

To return null in a column, let the returned object have an attribute named after column with value None.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.54 14854

This session has previously used Python major version @1@, and it is now attempting to use Python major version @2@.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.55 14855

Start a new session to use a different Python major version.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.56 14856

The arguments of the trigger can be accessed through TG_NARGS and TG_ARGV instead.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.57 14857

[compilation of PL/pgSQL function "@1@" near line @2@](#)

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.58 14858

[It could refer to either a PL/pgSQL variable or a table column.](#)

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.59 14859

[PL/pgSQL function @1@ line @2@ @3@](#)

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.60 14860

[PL/pgSQL function @1@ @2@](#)

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.61 14861

PL/pgSQL function @1@ line @2@ at @3@

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.62 14862

PL/pgSQL function @1@

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.63 14863

CASE statement is missing ELSE part.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.64 14864

The tuple structure of a not-yet-assigned record is indeterminate.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.65 14865

@1@

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.66 14866

Use a BEGIN block with an EXCEPTION clause instead.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.67 14867

If you want to discard the results of a SELECT, use PERFORM instead.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.68 14868

You might want to use EXECUTE ... INTO or EXECUTE CREATE TABLE ... AS instead.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.69 14869

Use RETURN NEXT or RETURN QUERY.

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.70 14870

@1@in PL/Tcl function "@2@"

[Description]

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.45.71 14871

could not translate host name "@1@" to address: @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.45.72 14872

Invalid definition statement format in connection configuration file. line number: @1@

[Description]

The format of a parameter definition statement in the connection configuration file is invalid.

[System Processing]

Processing is aborted.

[Action]

This messages is output in the case of HA Database Ready.

Correct the connection configuration file and restart the application.

2.45.73 14873

out of memory

[Description]

There was insufficient free space in the client's memory during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Estimate memory usage and take the following action:

- Modify the application to reduce memory usage.

2.45.74 14874

The same server name is specified by two or more SERVER parameters in the connection configuration file.

[Description]

The same server name is specified in multiple SERVER parameters in the connection configuration file.

[System Processing]

Processing is aborted.

[Action]

This messages is output in the case of HA Database Ready.

Correct the server name specified in the SERVER parameter of the connection configuration file, and restart the application.

2.45.75 14875

The connection configuration file cannot be opened. detail: "@1@"

[Description]

The process to open the connection configuration file failed.

[System Processing]

Processing is aborted.

[Action]

This messages is output in the case of HA Database Ready.

Check the state of the connection configuration file, remove the cause of the error, and restart the application.

2.45.76 14876

Line in connection configuration file is exceeding limit. line number: @1@

[Description]

The connection configuration file contains a line that exceeds the maximum length.

[System Processing]

Processing is aborted.

[Action]

This messages is output in the case of HA Database Ready.

Correct the connection configuration file and restart the application.

2.45.77 14877

host name must be specified

[Description]

The operating environment such as the status of the connection definition file and the connection method specification is abnormal.

[System Processing]

Processing will be aborted.

[Action]

Confirm that the operating environment such as the status of the connection definition file and the connection method specification is normal.

2.45.78 14878

could not set socket to blocking mode: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.45.79 14879

Kerberos 5 authentication rejected: @1@s

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.45.80 14880

could not restore non-blocking mode on socket: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.45.81 14881

GSSAPI continuation error

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.45.82 14882

duplicate GSS authentication request

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.45.83 14883

GSSAPI name import error

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.45.84 14884

SSPI continuation error

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.45.85 14885

could not acquire SSPI credentials

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.45.86 14886

SCM_CRED authentication method not supported

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.45.87 14887

Kerberos 4 authentication not supported

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.45.88 14888

Kerberos 5 authentication not supported

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.45.89 14889

GSSAPI authentication not supported

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.45.90 14890

SSPI authentication not supported

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.45.91 14891

Crypt authentication not supported

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.45.92 14892

authentication method @1@ not supported

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.45.93 14893

invalid sslmode value: "@1@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.45.94 14894

sslmode value "@1@" invalid when SSL support is not compiled in

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.45.95 14895

could not set socket to TCP no delay mode: @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.45.96 14896

could not connect to server: @1@ Is the server running locally and accepting connections on Unix domain socket "@2@"?

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.45.97 14897

could not connect to server: @1@ Is the server running on host "@2@" (@3@) and accepting TCP/IP connections on port @4@?

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.45.98 14898

could not connect to server: @1@ Is the server running on host "@2@" and accepting TCP/IP connections on port @3@?

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.45.99 14899

setsockopt(TCP_KEEPIDLE) failed: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.46 Message Numbers Beginning with 14900

2.46.1 14900

setsockopt(TCP_KEEPLIVE) failed: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.46.2 14901

setsockopt(TCP_KEEPIVTL) failed: @1@**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.46.3 14902

setsockopt(TCP_KEEPCNT) failed: @1@**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.46.4 14903

WSAIoctl(SIO_KEEPLIVE_VALS) failed: @1@i**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.46.5 14904

invalid port number: "@1@"**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.6 14905

could not find a suitable target server

[Description]

Could not find a suitable target server.

[System Processing]

Processing is aborted.

[Action]

Check following settings (host, IP address, port number, or targetServer):

- Connection string
- Connection service file
- Data source of JDBC or ODBC
- Environment variables for default connection parameter values(ex. PGHOST)
- Arguments of functions of libpq
- Options of command

2.46.7 14906

could not translate Unix-domain socket path "@1@" to address: @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.8 14907

invalid connection state, probably indicative of memory corruption

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.46.9 14908

could not create socket: @1@

[Description]

There was insufficient free space in the server's memory during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Estimate memory usage and take the following action:

- If the number of simultaneous connections from client applications is high, reduce it.
- If the number of simultaneous SQL executions is high, reduce it.

2.46.10 14909

could not set socket to non-blocking mode: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.46.11 14910

could not set socket to close-on-exec mode: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.46.12 14911

keepalives parameter must be an integer

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.13 14912

setsockopt(SO_KEEPALIVE) failed: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.46.14 14913

could not get socket error status: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.46.15 14914

could not get client address from socket: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.46.16 14915

requirepeer parameter is not supported on this platform

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.17 14916

could not get peer credentials: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.46.18 14917

local user with ID @1@ does not exist

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.19 14918

requirepeer specifies "@1@", but actual peer user name is "@2@"

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.20 14919

could not send startup packet: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.46.21 14920

server does not support auto connection switching

[Description]

The server does not support auto connection switching.

[System Processing]

Processing is aborted.

[Action]

Specify servers that support auto connection switching.

2.46.22 14921

unexpected message from server during startup

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.46.23 14922

could not send SSL negotiation packet: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.46.24 14923

server does not support SSL, but SSL was required

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.25 14924

received invalid response to SSL negotiation: @1@

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.46.26 14925

expected authentication request from server, but received @1@

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.46.27 14926

out of memory allocating GSSAPI buffer (@1@)

[Description]

There was insufficient free space in the client's memory during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Estimate memory usage and take the following action:

- Modify the application to reduce memory usage.

2.46.28 14927

invalid connection state @1@, probably indicative of memory corruption

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.46.29 14928

PGEventProc "@1@" failed during PGEVT_CONNRESET event

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.46.30 14929

invalid LDAP URL "@1@": scheme must be ldap://

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.31 14930

invalid LDAP URL "@1@": missing distinguished name

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.32 14931

invalid LDAP URL "@1@": must have exactly one attribute

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.33 14932

invalid LDAP URL "@1@": must have search scope (base/one/sub)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.34 14933

invalid LDAP URL "@1@": no filter

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.35 14934

invalid LDAP URL "@1@": invalid port number

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.36 14935

could not create LDAP structure

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.46.37 14936

lookup on LDAP server failed: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.46.38 14937

more than one entry found on LDAP lookup

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.39 14938

no entry found on LDAP lookup

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.40 14939

attribute has no values on LDAP lookup

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.41 14940

missing "=" after "@1@" in connection info string

[Description]

The operating environment such as the status of the connection definition file and the connection method specification is abnormal.

[System Processing]

Processing will be aborted.

[Action]

Confirm that the operating environment such as the status of the connection definition file and the connection method specification is normal.

2.46.42 14941

invalid connection option "@1@"

[Description]

The operating environment such as the status of the connection definition file and the connection method specification is abnormal.

[System Processing]

Processing will be aborted.

[Action]

Confirm that the operating environment such as the status of the connection definition file and the connection method specification is normal.

2.46.43 14942

unterminated quoted string in connection info string

[Description]

The operating environment such as the status of the connection definition file and the connection method specification is abnormal.

[System Processing]

Processing will be aborted.

[Action]

Confirm that the operating environment such as the status of the connection definition file and the connection method specification is normal.

2.46.44 14943

could not get home directory to locate service definition file

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.45 14944

definition of service "@1@" not found

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.46 14945

service file "@1@" not found

[Description]

The operating environment such as the status of the connection definition file and the connection method specification is abnormal.

[System Processing]

Processing will be aborted.

[Action]

Confirm that the operating environment such as the status of the connection definition file and the connection method specification is normal.

2.46.47 14946

line @1@ too long in service file "@2@"

[Description]

The operating environment such as the status of the connection definition file and the connection method specification is abnormal.

[System Processing]

Processing will be aborted.

[Action]

Confirm that the operating environment such as the status of the connection definition file and the connection method specification is normal.

2.46.48 14947

syntax error in service file "@1@", line @2@

[Description]

The operating environment such as the status of the connection definition file and the connection method specification is abnormal.

[System Processing]

Processing will be aborted.

[Action]

Confirm that the operating environment such as the status of the connection definition file and the connection method specification is normal.

2.46.49 14948

connection pointer is NULL

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.50 14951

password retrieved from file "@1@"

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.46.51 14952

command string is a null pointer

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.52 14953

statement name is a null pointer

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.53 14954

function requires at least protocol version 3.0

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.54 14955

no connection to the server

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.55 14956

another command is already in progress

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.56 14957

length must be given for binary parameter

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.57 14958

unexpected asyncStatus: @1@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.46.58 14959

PGEvtProc "@1@" failed during PGEVT_RESULTCREATE event

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.46.59 14960

COPY terminated by new PQexec

[Description]

Processing was canceled.

[System Processing]

Processing will be aborted.

[Action]

Check the message text.

2.46.60 14961

COPY IN state must be terminated first

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.61 14962

COPY OUT state must be terminated first

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.62 14963

PQexec not allowed during COPY BOTH

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.63 14964

no COPY in progress

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.64 14965

connection in wrong state

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.65 14966

invalid ExecStatusType code

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.66 14967

column number @1@ is out of range 0..@2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.67 14968

row number @1@ is out of range 0..@2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.68 14969

parameter number @1@ is out of range 0..@2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.69 14970

could not interpret result from server: @1@

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.46.70 14971

incomplete multibyte character

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.46.71 14972

cannot determine OID of function lo_truncate

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.72 14973

cannot determine OID of function lo_create

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.73 14974

could not open file "@1@": @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.74 14975

could not read from file "@1@": @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.75 14976

could not write to file "@1@": @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.76 14977

query to initialize large object functions did not return data

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.77 14978

cannot determine OID of function lo_open

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.78 14979

cannot determine OID of function lo_close

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.79 14980

cannot determine OID of function lo_creat

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.80 14981

cannot determine OID of function lo_unlink

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.81 14982

cannot determine OID of function lo_lseek

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.82 14983

cannot determine OID of function lo_tell

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.83 14984

cannot determine OID of function loread

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.84 14985

cannot determine OID of function lowrite

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.85 14986

integer of size @1@ not supported by pqGetInt

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.86 14987

integer of size @1@ not supported by pqPutInt

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.87 14988

connection not open

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.46.88 14989

server closed the connection unexpectedly This probably means the server terminated abnormally before or while processing the request.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.46.89 14990

timeout expired

[Description]

Timeout occurred during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Check the following:

- If executing SQL that outputs a large volume of search results, add a conditional expression to filter the results further.
- If numerous SQLs are being simultaneously executed, reduce the number of simultaneously executed SQLs.
- If a large volume of data is to be updated in a single transaction, modify the SQL to reduce the volume of data to be updated in a single transaction.
- If executing a complex SQL, modify it to a simple SQL.
- Check if there are any problems in the network.
- Before conducting maintenance that involves the processing of a large volume of data, use the SET statement to temporarily increase the value of maintenance_work_mem.

2.46.90 14991

socket not open

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.46.91 14992

select() failed: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.46.92 14993

[invalid setenv state @1@, probably indicative of memory corruption](#)

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.46.93 14994

[invalid state @1@, probably indicative of memory corruption](#)

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.46.94 14995

[message type 0x@1@ arrived from server while idle](#)

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.46.95 14996

[unexpected character @1@ following empty query response \("I" message\)](#)

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.46.96 14997

server sent data ("D" message) without prior row description ("T" message)

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.46.97 14998

server sent binary data ("B" message) without prior row description ("T" message)

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.46.98 14999

unexpected response from server; first received character was "@1@"

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.47 Message Numbers Beginning with 15000

2.47.1 15000

out of memory for query result

[Description]

There was insufficient free space in the client's memory during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Estimate memory usage and take the following action:

- Modify the application to reduce memory usage.

2.47.2 15001

lost synchronization with server, resetting connection

[Description]

The database server was disconnected during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Communication may have been disconnected for the following reasons:

- An error occurred in the communication line (TCP/IP etc.)
- The database server terminated abnormally.

Take the following actions:

- Eliminate the cause of the communication disconnection.

Examine the application and check whether the transaction for implementing update is a long transaction. Judge whether it is a long transaction from the following viewpoints and modify the application.

- If the COMMIT process is not executed after update, add the COMMIT process.
 - If the total number of update records in a single transaction is high, split it into short transactions.
 - If search was conducted for a long period of time after update, execute COMMIT after update or review the search SQL statement.
- If none of the above situations applies, perform the following:
 - Confirm that the database server has not stopped.
 - If the database server is starting or stopping, re-execute the command after the database server starts.

2.47.3 15002

protocol error: id=0x@1@

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.47.4 15003

server sent data ("D" message) without prior row description ("T" message)

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.47.5 15004

message contents do not agree with length in message type "@1@"

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.47.6 15005

lost synchronization with server: got message type "@1@", length @2@

[Description]

The database server was disconnected during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Communication may have been disconnected for the following reasons:

- An error occurred in the communication line (TCP/IP etc.)
- The database server terminated abnormally.

Take the following actions:

- Eliminate the cause of the communication disconnection.

Examine the application and check whether the transaction for implementing update is a long transaction. Judge whether it is a long transaction from the following viewpoints and modify the application.

- a) If the COMMIT process is not executed after update, add the COMMIT process.
- b) If the total number of update records in a single transaction is high, split it into short transactions.
- c) If search was conducted for a long period of time after update, execute COMMIT after update or review the search SQL statement.

- If none of the above situations applies, perform the following:

- a) Confirm that the database server has not stopped.

b) If the database server is starting or stopping, re-execute the command after the database server starts.

2.47.7 15006

unexpected field count in "D" message

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.47.8 15007

PQgetline: not doing text COPY OUT

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.47.9 15008

could not establish SSL connection: @1@

[Description]

The database server was disconnected during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Communication may have been disconnected for the following reasons:

- An error occurred in the communication line (TCP/IP etc.)
- The database server terminated abnormally.

Take the following actions:

- Eliminate the cause of the communication disconnection.

Examine the application and check whether the transaction for implementing update is a long transaction. Judge whether it is a long transaction from the following viewpoints and modify the application.

- a) If the COMMIT process is not executed after update, add the COMMIT process.
- b) If the total number of update records in a single transaction is high, split it into short transactions.
- c) If search was conducted for a long period of time after update, execute COMMIT after update or review the search SQL statement.

- If none of the above situations applies, perform the following:

- a) Confirm that the database server has not stopped.
- b) If the database server is starting or stopping, re-execute the command after the database server starts.

2.47.10 15009

SSL SYSCALL error: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.11 15010

SSL SYSCALL error: EOF detected

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.12 15011

SSL error: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.13 15012

SSL connection has been closed unexpectedly

[Description]

The database server was disconnected during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Communication may have been disconnected for the following reasons:

- An error occurred in the communication line (TCP/IP etc.)
- The database server terminated abnormally.

Take the following actions:

- Eliminate the cause of the communication disconnection.

Examine the application and check whether the transaction for implementing update is a long transaction. Judge whether it is a long transaction from the following viewpoints and modify the application.

- a) If the COMMIT process is not executed after update, add the COMMIT process.
 - b) If the total number of update records in a single transaction is high, split it into short transactions.
 - c) If search was conducted for a long period of time after update, execute COMMIT after update or review the search SQL statement.
- If none of the above situations applies, perform the following:
 - a) Confirm that the database server has not stopped.
 - b) If the database server is starting or stopping, re-execute the command after the database server starts.

2.47.14 15013

unrecognized SSL error code: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.15 15014

could not receive data from server: @1@

[Description]

The database server was disconnected during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Communication may have been disconnected for the following reasons:

- An error occurred in the communication line (TCP/IP etc.)
- The database server terminated abnormally.

Take the following actions:

- Eliminate the cause of the communication disconnection.

Examine the application and check whether the transaction for implementing update is a long transaction. Judge whether it is a long transaction from the following viewpoints and modify the application.

- a) If the COMMIT process is not executed after update, add the COMMIT process.

- b) If the total number of update records in a single transaction is high, split it into short transactions.
 - c) If search was conducted for a long period of time after update, execute COMMIT after update or review the search SQL statement.
- If none of the above situations applies, perform the following:
- a) Confirm that the database server has not stopped.
 - b) If the database server is starting or stopping, re-execute the command after the database server starts.

2.47.16 15015

could not send data to server: @1@

[Description]

The database server was disconnected during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Communication may have been disconnected for the following reasons:

- An error occurred in the communication line (TCP/IP etc.)
- The database server terminated abnormally.

Take the following actions:

- Eliminate the cause of the communication disconnection.

Examine the application and check whether the transaction for implementing update is a long transaction. Judge whether it is a long transaction from the following viewpoints and modify the application.

- a) If the COMMIT process is not executed after update, add the COMMIT process.
 - b) If the total number of update records in a single transaction is high, split it into short transactions.
 - c) If search was conducted for a long period of time after update, execute COMMIT after update or review the search SQL statement.
- If none of the above situations applies, perform the following:
- a) Confirm that the database server has not stopped.
 - b) If the database server is starting or stopping, re-execute the command after the database server starts.

2.47.17 15016

could not get server common name from server certificate

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.18 15017

SSL certificate's common name contains embedded null

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.19 15018

host name must be specified for a verified SSL connection

[Description]

The operating environment such as the status of the connection definition file and the connection method specification is abnormal.

[System Processing]

Processing will be aborted.

[Action]

Confirm that the operating environment such as the status of the connection definition file and the connection method specification is normal.

2.47.20 15019

server common name "@1@" does not match host name "@2@"

[Description]

The operating environment such as the status of the connection definition file and the connection method specification is abnormal.

[System Processing]

Processing will be aborted.

[Action]

Confirm that the operating environment such as the status of the connection definition file and the connection method specification is normal.

2.47.21 15020

could not create SSL context: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.22 15021

could not open certificate file "@1@": @2@

[Description]

The operating environment such as the status of the connection definition file and the connection method specification is abnormal.

[System Processing]

Processing will be aborted.

[Action]

Confirm that the operating environment such as the status of the connection definition file and the connection method specification is normal.

2.47.23 15022

could not read certificate file "@1@": @2@

[Description]

The operating environment such as the status of the connection definition file and the connection method specification is abnormal.

[System Processing]

Processing will be aborted.

[Action]

Confirm that the operating environment such as the status of the connection definition file and the connection method specification is normal.

2.47.24 15023

could not load SSL engine "@1@": @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.25 15024

could not initialize SSL engine "@1@": @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.26 15025

could not read private SSL key "@1@" from engine "@2@" : @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.27 15026

could not load private SSL key "@1@" from engine "@2@" : @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.28 15027

certificate present, but not private key file "@1@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.29 15028

private key file "@1@" has group or world access; permissions should be u=rw (0600) or less

[Description]

The operating environment such as the status of the connection definition file and the connection method specification is abnormal.

[System Processing]

Processing will be aborted.

[Action]

Confirm that the operating environment such as the status of the connection definition file and the connection method specification is normal.

2.47.30 15029

could not load private key file "@1@": @2@

[Description]

The operating environment such as the status of the connection definition file and the connection method specification is abnormal.

[System Processing]

Processing will be aborted.

[Action]

Confirm that the operating environment such as the status of the connection definition file and the connection method specification is normal.

2.47.31 15030

certificate does not match private key file "@1@": @2@

[Description]

The operating environment such as the status of the connection definition file and the connection method specification is abnormal.

[System Processing]

Processing will be aborted.

[Action]

Confirm that the operating environment such as the status of the connection definition file and the connection method specification is normal.

2.47.32 15031

could not read root certificate file "@1@": @2@

[Description]

The operating environment such as the status of the connection definition file and the connection method specification is abnormal.

[System Processing]

Processing will be aborted.

[Action]

Confirm that the operating environment such as the status of the connection definition file and the connection method specification is normal.

2.47.33 15032

SSL library does not support CRL certificates (file "@1@")

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.47.34 15033

could not get home directory to locate root certificate fileEither provide the file or change sslmode to disable server certificate verification.

[Description]

The operating environment such as the status of the connection definition file and the connection method specification is abnormal.

[System Processing]

Processing will be aborted.

[Action]

Confirm that the operating environment such as the status of the connection definition file and the connection method specification is normal.

2.47.35 15034

root certificate file "@1@" does not existEither provide the file or change sslmode to disable server certificate verification.

[Description]

The operating environment such as the status of the connection definition file and the connection method specification is abnormal.

[System Processing]

Processing will be aborted.

[Action]

Confirm that the operating environment such as the status of the connection definition file and the connection method specification is normal.

2.47.36 15035

certificate could not be obtained: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.37 15036

no SSL error reported

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.38 15037

SSL error code @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.39 15038

@1@: vacuuming database "@2@"

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.47.40 15040

only superuser can change options of a fdw foreign table

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.47.41 15041

period is required for fdw foreign tables

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.47.42 15042

skipped creating .ready file for multiplexed transaction log file "@1@"

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.47.43 15043

skipped recycling multiplexed transaction log file "@1@"

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.47.44 15044

skipped removing multiplexed transaction log file "@1@"

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.47.45 15045

no data found on line @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.46 15046

out of memory on line @1@

[Description]

There was insufficient free space in the server's memory during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Estimate memory usage and take the following action:

- If the number of simultaneous connections from client applications is high, reduce it.
- If the number of simultaneous SQL executions is high, reduce it.

2.47.47 15047

unsupported type "@1@" on line @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.48 15048

too many arguments on line @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.49 15049

too few arguments on line @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.50 15050

invalid input syntax for type int: "@1@", on line @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.51 15051

invalid input syntax for type unsigned int: "@1@", on line @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.52 15052

invalid input syntax for floating-point type: "@1@", on line @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.53 15053

invalid syntax for type boolean: "@1@", on line @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.54 15054

could not convert boolean value: size mismatch, on line @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.55 15055

empty query on line @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.56 15056

null value without indicator on line @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.57 15057

variable does not have an array type on line @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.58 15058

data read from server is not an array on line @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.59 15059

inserting an array of variables is not supported on line @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.60 15060

connection "@1@" does not exist on line @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.61 15061

not connected to connection "@1@" on line @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.62 15062

invalid statement name "@1@" on line @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.63 15063

descriptor "@1@" not found on line @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.64 15064

descriptor index out of range on line @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.65 15065

unrecognized descriptor item "@1@" on line @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.66 15066

variable does not have a numeric type on line @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.67 15067

variable does not have a character type on line @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.68 15068

error in transaction processing on line @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.69 15069

could not connect to database "@1@" on line @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.70 15070

SQL error @1@ on line @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.71 15071

the connection to the server was lost

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.72 15072

empty message text

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.73 15073

mapped win32 error code @1@ to @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.74 15074

SP-GiST inner tuple size @1@ exceeds maximum @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.75 15075

backup_label contains data inconsistent with control file

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.76 15076

WAL generated with full_page_writes=off was replayed since last restartpoint

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.77 15077

the standby was promoted during online backup

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.78 15078

WAL generated with full_page_writes=off was replayed during online backup

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.79 15079

xrecoff "@1@" is out of valid range, 0..@2@**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.80 15080

cannot set privileges of array types**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.81 15081

**drop cascades to @1@ other object
drop cascades to @2@ other objects****[Description]**

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.47.82 15082

constraint "@1@" conflicts with non-inherited constraint on relation "@2@"**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.83 15083

DROP INDEX CONCURRENTLY must be first action in transaction

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.84 15084

foreign-data wrapper name cannot be qualified

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.85 15085

domain "@1@" has multiple constraints named "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.86 15086

functions cannot have more than @1@ argument functions cannot have more than @2@ arguments

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.87 15087

skipping "@1@" --- cannot analyze this foreign table

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.47.88 15088

could not convert row type

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.47.89 15089

unexpected EOF on client connection with an open transaction

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.90 15090

EXPLAIN option TIMING requires ANALYZE

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.91 15091

only superuser can define a leakproof function

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.92 15092

cast will be ignored because the source data type is a domain

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.93 15093

cast will be ignored because the target data type is a domain

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.94 15094

btree sort support procedures must accept type "internal"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.95 15095

btree sort support procedures must return void

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.96 15096

Use DROP TABLE to remove a table.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.97 15097

Use DROP SEQUENCE to remove a sequence.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.98 15098

Use DROP VIEW to remove a view.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.47.99 15099

Use DROP INDEX to remove an index.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48 Message Numbers Beginning with 15100

2.48.1 15100

Use DROP TYPE to remove a type.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.2 15101

Use DROP FOREIGN TABLE to remove a foreign table.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.3 15102

DROP INDEX CONCURRENTLY does not support dropping multiple objects

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.4 15103

DROP INDEX CONCURRENTLY does not support CASCADE

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.5 15104

cannot inherit from temporary relation of another session

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.6 15105

constraints on temporary tables must involve temporary tables of this session

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.7 15106

constraint must be validated on child tables too

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.8 15107

cannot inherit to temporary relation of another session

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.9 15108

constraint "@1@" conflicts with non-inherited constraint on child table "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.10 15109

Found referenced table's UPDATE trigger.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.11 15110

Found referenced table's DELETE trigger.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.12 15111

Found referencing table's trigger.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.13 15112

CHECK constraints for domains cannot be marked NO INHERIT**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.14 15113

type attribute "subtype" is required**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.15 15114

range collation specified but subtype does not support collation**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.16 15115

range canonical function @1@ must be immutable**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.17 15116

range subtype diff function @1@ must return type double precision

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.18 15117

range subtype diff function @1@ must be immutable

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.19 15118

constraint "@1@" of domain "@2@" does not exist, skipping

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.20 15119

"@1@" : suspending truncate due to conflicting lock request

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.21 15120

cannot set transaction read-write mode inside a read-only transaction

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.22 15121

transaction read-write mode must be set before any query

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.23 15122

cannot set transaction read-write mode during recovery

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.24 15123

SET TRANSACTION ISOLATION LEVEL must be called before any query

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.25 15124

SET TRANSACTION ISOLATION LEVEL must not be called in a subtransaction

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.26 15125

SET TRANSACTION [NOT] DEFERRABLE cannot be called within a subtransaction

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.27 15126

SET TRANSACTION [NOT] DEFERRABLE must be called before any query

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.28 15127

cannot delete from view "@1@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.29 15128

GLOBAL is deprecated in temporary table creation

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.30 15129

duplicate trigger events specified

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.48.31 15130

unrecognized configuration parameter "@1@" in file "@2@" line @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.32 15131

configuration file "@1@" contains errors

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.33 15132

configuration file "@1@" contains errors; unaffected changes were applied

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.34 15133

configuration file "@1@" contains errors; no changes were applied

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.35 15134

too many syntax errors found, abandoning file "@1@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.36 15135

accepting GSS security context failed

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.37 15136

retrieving GSS user name failed

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.38 15137

could not acquire SSPI credentials

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.39 15138

could not accept SSPI security context

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.40 15139

could not get token from SSPI security context

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.41 15140

multiple values in ident field

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.48.42 15141

multiple values specified for connection type

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.48.43 15142

multiple values specified for host address

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.48.44 15143

multiple values specified for netmask

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.48.45 15144

multiple values specified for authentication type

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.48.46 15145

ident, peer, krb5, gssapi, sspi, and cert

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.48.47 15146

krb5, gssapi, and sspi

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.48.48 15147

configuration file "@1@" contains no entries

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.49 15148

Unix-domain socket path "@1@" is too long (maximum @2@ bytes)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.50 15149

@1@: WSASStartup failed: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.51 15150

@1 @: real and effective user IDs must match

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.52 15151

@1 @: invalid effective UID: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.53 15152

@1 @: could not determine user name (GetUserName failed)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.54 15153

too many range table entries

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.55 15154

SELECT ... INTO is not allowed here

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.56 15155

arguments declared "anyrange" are not all alike

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.57 15156

argument declared "anyrange" is not consistent with argument declared "anyelement"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.58 15157

could not load dbghelp.dll, cannot write crash dump

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.59 15158

could not load required functions in dbghelp.dll, cannot write crash dump

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.60 15159

could not open crash dump file "@1@" for writing: error code @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.61 15160

could not write crash dump to file "@1@": error code @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.62 15161

could not open process token: error code @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.63 15162

could not get SID for Administrators group: error code @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.64 15163

could not get SID for PowerUsers group: error code @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.65 15164

could not create signal listener pipe: error code @1@; retrying

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.66 15165

could not create signal dispatch thread: error code @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.67 15166

@1@: superuser_reserved_connections must be less than max_connections

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.68 15167

@1@: max_wal_senders must be less than max_connections

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.69 15168

@1@: invalid datetoken tables, please fix

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.70 15169

@1@: could not change permissions of external PID file "@2@": @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.71 15170

@1@: could not write external PID file "@2@": @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.72 15171

could not fork new process for connection:

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.73 15172

could not read exit code for process

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.74 15173

could not post child completion status

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.75 15174

could not write to log file: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.76 15175

invalid streaming start location

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.77 15176

unterminated quoted string

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.78 15177

unexpected WAL file size "@1@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.79 15178

unterminated bit string literal

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.80 15179

unterminated hexadecimal string literal

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.81 15180

invalid Unicode surrogate pair

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.82 15181

unterminated dollar-quoted string

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.83 15182

zero-length delimited identifier

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.84 15183

unterminated quoted identifier

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.85 15184

Unicode escape values cannot be used for code point values above 007F when the server encoding is not UTF8

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.86 15185

invalid Unicode escape value

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.87 15186

invalid Unicode escape character

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.88 15187

temporary file size exceeds temp_file_limit (@1@kB)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.89 15188

a snapshot-importing transaction must not be READ ONLY DEFERRABLE

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.90 15189

could not import the requested snapshot

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.91 15190

connection to client lost

[Description]

[System Processing]

[Action]

15191

invalid command-line argument for server process: @ 1 @

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.92 15192

must be superuser or have the same role to cancel queries running in other server processes

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.93 15193

must be superuser or have the same role to terminate other server processes

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.94 15194

range constructor flags argument must not be NULL

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.95 15195

result of range difference would not be contiguous

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.96 15196

result of range union would not be contiguous

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.97 15197

range lower bound must be less than or equal to range upper bound

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.98 15198

invalid range bound flags

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.48.99 15199

could not set up XML error handler

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.49 Message Numbers Beginning with 15200

2.49.1 15200

keystore_location is not supported by this build

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.49.2 15201

keystore location is not configured

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.49.3 15202

could not encrypt or decrypt data because the keystore is not open

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.49.4 15203

keystore is already open

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.49.5 15204

passphrase is too short or too long

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.49.6 15205

passphrase-based key derivation failed: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.49.7 15206

a new master encryption key has been set

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.8 15207

passphrase of the keystore has been changed

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.49.9 15208

encryption or decryption of data in tablespace @1@ failed: @2@**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.49.10 15209

encryption or decryption of data failed: @1@**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.49.11 15210

could not open keystore "@1@": necessary master encryption key does not exist in the keystore**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.49.12 15211

decryption of the auto-open keystore "@1@" failed: error code = @2@**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.49.13 15212

encryption of the auto-open keystore "@1@" failed: error code = @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.49.14 15213

keystore "@1@" is corrupted: size = @2@ bytes, expected size = @3@ bytes

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.49.15 15214

could not open keystore "@1@" : passphrase is wrong, or the auto-open keystore was created by another computer or user

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.49.16 15215

keystore "@1@" is corrupted: invalid CRC

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.49.17 15216

encryption or decryption of the keystore "@1@" failed: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.49.18 15217

character with byte sequence @1@ in encoding "@2@" has no equivalent in encoding "@3@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.49.19 15218

Enables the planner's use of sequential-scan plans.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.20 15219

Enables the planner's use of index-scan plans.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.21 15220

Enables the planner's use of index-only-scan plans.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.22 15221

Enables the planner's use of bitmap-scan plans.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.23 15222

Enables the planner's use of TID scan plans.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.24 15223

Enables the planner's use of explicit sort steps.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.25 15224

Enables the planner's use of hashed aggregation plans.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.26 15225

Enables the planner's use of materialization.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.27 15226

Enables the planner's use of nested-loop join plans.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.28 15227

Enables the planner's use of merge join plans.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.29 15228

Enables the planner's use of hash join plans.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.30 15229

Enables genetic query optimization.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.31 15230

Shows whether the current user is a superuser.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.49.32 15231

Enables advertising the server via Bonjour.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.33 15232

Enables SSL connections.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.34 15233

Forces synchronization of updates to disk.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.49.35 15234

Continues processing past damaged page headers.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.49.36 15235

Writes full pages to WAL when first modified after a checkpoint.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.49.37 15236

Logs each checkpoint.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.49.38 15237

Logs each successful connection.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.49.39 15238

Logs end of a session, including duration.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.49.40 15239

Turns on various assertion checks.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.49.41 15240

Terminate session on any error.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.49.42 15241

Restarts all server processes on WAL multiplexing errors.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.49.43 15242

Enables fast WAL multiplexing.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.44 15243

Enables encryption of temporary files used in large queries.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.45 15244

Reinitialize server after backend crash.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.49.46 15245

Logs the duration of each completed SQL statement.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.47 15246

Logs each query's parse tree.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.48 15247

Logs each query's rewritten parse tree.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.49 15248

Logs each query's execution plan.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.50 15249

Indents parse and plan tree displays.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.51 15250

Writes parser performance statistics to the server log.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.52 15251

Writes planner performance statistics to the server log.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.53 15252

Writes executor performance statistics to the server log.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.54 15253

Writes cumulative performance statistics to the server log.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.55 15254

No description available.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.56 15255

Collects information about executing commands.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.57 15256

Collects statistics on database activity.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.58 15257

Collects timing statistics for database I/O activity.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.59 15258

Updates the process title to show the active SQL command.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.60 15259

Starts the autovacuum subprocess.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.61 15260

Generates debugging output for LISTEN and NOTIFY.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.62 15261

Logs long lock waits.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.63 15262

Logs the host name in the connection logs.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.64 15263

Causes subtables to be included by default in various commands.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.49.65 15264

Encrypt passwords.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.66 15265

Treats "expr=NULL" as "expr IS NULL".

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.49.67 15266

Enables per-database user names.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.68 15267

This parameter doesn't do anything.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.49.69 15268

Sets the default read-only status of new transactions.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.70 15269

Sets the current transaction's read-only status.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.71 15270

Sets the default deferrable status of new transactions.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.72 15271

Whether to defer a read-only serializable transaction until it can be executed with no possible serialization failures.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.73 15272

Check function bodies during CREATE FUNCTION.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.74 15273

Enable input of NULL elements in arrays.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.75 15274

Create new tables with OIDs by default.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.76 15275

Start a subprocess to capture stderr output and/or csvlogs into log files.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.77 15276

Truncate existing log files of same name during log rotation.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.78 15277

Emit information about resource usage in sorting.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.79 15278

Generate debugging output for synchronized scanning.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.80 15279

Enable bounded sorting using heap sort.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.81 15280

Emit WAL-related debugging output.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.82 15281

Datetimes are integer based.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.83 15282

Sets whether Kerberos and GSSAPI user names should be treated as case-insensitive.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.84 15283

Warn about backslash escapes in ordinary string literals.

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.49.85 15284

Causes '...' strings to treat backslashes literally.

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.49.86 15285

Enable synchronized sequential scans.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.87 15286

Allows archiving of WAL files using archive_command.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.88 15287

Allows connections and queries during recovery.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.89 15288

Allows feedback from a hot standby to the primary that will avoid query conflicts.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.90 15289

Allows modifications of the structure of system tables.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.91 15290

Disables reading from system indexes.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.92 15291

Enables backward compatibility mode for privilege checks on large objects.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.93 15292

When generating SQL fragments, quote all identifiers.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.94 15293

Forces a switch to the next xlog file if a new file has not been started within N seconds.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.49.95 15294

Waits N seconds on connection startup after authentication.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.96 15295

Sets the default statistics target.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.97 15296

Sets the FROM-list size beyond which subqueries are not collapsed.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.98 15297

Sets the FROM-list size beyond which JOIN constructs are not flattened.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.99 15298

Sets the threshold of FROM items beyond which GEQO is used.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.49.100 15299

GEQO: effort is used to set the default for other GEQO parameters.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50 Message Numbers Beginning with 15300

2.50.1 15300

GEQO: number of individuals in the population.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.2 15301

GEQO: number of iterations of the algorithm.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.3 15302

Sets the time to wait on a lock before checking for deadlock.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.4 15303

Sets the maximum delay before canceling queries when a hot standby server is processing archived WAL data.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.5 15304

Sets the maximum delay before canceling queries when a hot standby server is processing streamed WAL data.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.6 15305

Sets the maximum interval between WAL receiver status reports to the primary.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.7 15306

Sets the maximum number of concurrent connections.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.8 15307

Sets the number of connection slots reserved for superusers.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.9 15308

Sets the number of shared memory buffers used by the server.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.10 15309

Sets the maximum number of temporary buffers used by each session.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.11 15310

Sets the TCP port the server listens on.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.12 15311

Sets the access permissions of the Unix-domain socket.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.13 15312

Sets the file permissions for log files.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.14 15313

Sets the maximum memory to be used for query workspaces.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.15 15314

Sets the maximum memory to be used for maintenance operations.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.16 15315

Sets the maximum stack depth, in kilobytes.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.17 15316

Limits the total size of all temporary files used by each session.

[Description]

There was insufficient free space in the disk of the database server during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Delete user data stored in the database server to free up space on the disk.

2.50.18 15317

Vacuum cost for a page found in the buffer cache.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.19 15318

Vacuum cost for a page not found in the buffer cache.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.20 15319

Vacuum cost for a page dirtied by vacuum.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.21 15320

Vacuum cost amount available before napping.**[Description]**

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.22 15321

Vacuum cost delay in milliseconds.**[Description]**

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.23 15322

Vacuum cost delay in milliseconds, for autovacuum.**[Description]**

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.24 15323

Vacuum cost amount available before napping, for autovacuum.**[Description]**

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.25 15324

Sets the maximum number of simultaneously open files for each server process.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.26 15325

Sets the maximum number of simultaneously prepared transactions.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.27 15326

Sets the maximum allowed duration of any statement.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.28 15327

Minimum age at which VACUUM should freeze a table row.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.29 15328

Age at which VACUUM should scan whole table to freeze tuples.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.30 15329

Number of transactions by which VACUUM and HOT cleanup should be deferred, if any.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.31 15330

Sets the maximum number of locks per transaction.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.32 15331

Sets the maximum number of predicate locks per transaction.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.33 15332

Sets the maximum allowed time to complete client authentication.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.34 15333

Waits N seconds on connection startup before authentication.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.35 15334

Sets the number of WAL files held for standby servers.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.36 15335

Sets the maximum distance in log segments between automatic WAL checkpoints.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.37 15336

Sets the maximum time between automatic WAL checkpoints.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.38 15337

Enables warnings if checkpoint segments are filled more frequently than this.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.39 15338

Sets the number of disk-page buffers in shared memory for WAL.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.40 15339

WAL writer sleep time between WAL flushes.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.41 15340

Sets the maximum number of simultaneously running WAL sender processes.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.42 15341

Sets the maximum time to wait for WAL replication.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.43 15342

Sets the delay in microseconds between transaction commit and flushing WAL to disk.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.44 15343

Sets the minimum concurrent open transactions before performing commit_delay.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.45 15344

Sets the number of digits displayed for floating-point values.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.46 15345

Sets the minimum execution time above which statements will be logged.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.47 15346

Sets the minimum execution time above which autovacuum actions will be logged.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.48 15347

Background writer sleep time between rounds.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.49 15348

Background writer maximum number of LRU pages to flush per round.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.50 15349

Number of simultaneous requests that can be handled efficiently by the disk subsystem.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.51 15350

Automatic log file rotation will occur after N minutes.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.52 15351

Automatic log file rotation will occur after N kilobytes.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.53 15352

Shows the maximum number of function arguments.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.54 15353

Shows the maximum number of index keys.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.55 15354

Shows the maximum identifier length.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.56 15355

Shows the size of a disk block.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.57 15356

Shows the number of pages per disk file.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.58 15357

Shows the block size in the write ahead log.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.59 15358

Shows the number of pages per write ahead log segment.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.60 15359

Time to sleep between autovacuum runs.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.61 15360

Minimum number of tuple updates or deletes prior to vacuum.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.62 15361

Minimum number of tuple inserts, updates, or deletes prior to analyze.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.63 15362

Age at which to autovacuum a table to prevent transaction ID wraparound.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.64 15363

Sets the maximum number of simultaneously running autovacuum worker processes.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.65 15364

Time between issuing TCP keepalives.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.66 15365

Time between TCP keepalive retransmits.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.67 15366

Set the amount of traffic to send and receive before renegotiating the encryption keys.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.68 15367

Maximum number of TCP keepalive retransmits.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.69 15368

Sets the maximum allowed result for exact search by GIN.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.70 15369

Sets the planner's assumption about the size of the disk cache.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.71 15370

Shows the server version as an integer.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.72 15371

Log the use of temporary files larger than this number of kilobytes.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.73 15372

Sets the size reserved for `pg_stat_activity.query`, in bytes.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.74 15373

Sets the planner's estimate of the cost of a sequentially fetched disk page.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.75 15374

Sets the planner's estimate of the cost of a nonsequentially fetched disk page.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.76 15375

Sets the planner's estimate of the cost of processing each tuple (row).

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.77 15376

Sets the planner's estimate of the cost of processing each index entry during an index scan.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.78 15377

Sets the planner's estimate of the cost of processing each operator or function call.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.79 15378

Sets the planner's estimate of the fraction of a cursor's rows that will be retrieved.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.80 15379

GEQO: selective pressure within the population.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.81 15380

GEQO: seed for random path selection.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.82 15381

Multiple of the average buffer usage to free per round.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.83 15382

Sets the seed for random-number generation.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.84 15383

Number of tuple updates or deletes prior to vacuum as a fraction of reltuples.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.85 15384

Number of tuple inserts, updates, or deletes prior to analyze as a fraction of reltuples.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.86 15385

Time spent flushing dirty buffers during checkpoint, as fraction of checkpoint interval.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.87 15386

Sets the shell command that will be called to archive a WAL file.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.88 15387

Sets the client's character set encoding.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.89 15388

Controls information prefixed to each log line.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.90 15389

Sets the time zone to use in log messages.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.91 15390

Sets the display format for date and time values.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.92 15391

Sets the default tablespace to create tables and indexes in.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.93 15392

Sets the tablespace(s) to use for temporary tables and sort files.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.94 15393

Sets the path for dynamically loadable modules.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.95 15394

Sets the location of the Kerberos server key file.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.96 15395

Sets the name of the Kerberos service.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.97 15396

Sets the Bonjour service name.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.98 15397

Shows the collation order locale.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.99 15398

Shows the character classification and case conversion locale.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.50.100 15399

Sets the language in which messages are displayed.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51 Message Numbers Beginning with 15400

2.51.1 15400

Sets the locale for formatting monetary amounts.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.2 15401

Sets the locale for formatting numbers.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.3 15402

Sets the locale for formatting date and time values.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.4 15403

Lists shared libraries to preload into server.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.5 15404

Lists shared libraries to preload into each backend.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.6 15405

Sets the schema search order for names that are not schema-qualified.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.7 15406

Sets the server (database) character set encoding.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.8 15407

Shows the server version.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.9 15408

Sets the current role.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.10 15409

Sets the session user name.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.11 15410

Sets the destination for server log output.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.12 15411

Sets the destination directory for log files.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.13 15412

Sets the file name pattern for log files.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.14 15413

Sets the program name used to identify PostgreSQL messages in syslog.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.15 15414

Sets the application name used to identify PostgreSQL messages in the event log.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.16 15415

Sets the time zone for displaying and interpreting time stamps.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.17 15416

Selects a file of time zone abbreviations.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.18 15417

Sets the current transaction's isolation level.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.19 15418

Sets the owning group of the Unix-domain socket.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.20 15419

Sets the directory where the Unix-domain socket will be created.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.21 15420

Sets the host name or IP address(es) to listen to.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.22 15421

Sets the server's data directory.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.23 15422

Sets the server's backup directory.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.24 15423

Sets the directory where multiplexed transaction log files are stored.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.25 15424

Sets the directory where server's core files are dumped.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.26 15425

Sets the location where the keystore is stored

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.27 15426

Sets the server's main configuration file.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.28 15427

Sets the server's "hba" configuration file.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.29 15428

Sets the server's "ident" configuration file.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.30 15429

Writes the postmaster PID to the specified file.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.31 15430

Location of the SSL server certificate file.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.32 15431

Location of the SSL server private key file.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.33 15432

Location of the SSL certificate authority file.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.34 15433

Location of the SSL certificate revocation list file.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.35 15434

Writes temporary statistics files to the specified directory.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.36 15435

List of names of potential synchronous standbys.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.37 15436

Sets default text search configuration.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.38 15437

Sets the list of allowed SSL ciphers.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.39 15438

Sets the application name to be reported in statistics and logs.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.40 15439

Sets whether "\" is allowed in string literals.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.41 15440

Sets the output format for bytea.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.42 15441

Sets the message levels that are sent to the client.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.43 15442

Enables the planner to use constraints to optimize queries.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.44 15443

Sets the transaction isolation level of each new transaction.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.45 15444

Sets the display format for interval values.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.46 15445

Sets the verbosity of logged messages.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.47 15446

Sets the message levels that are logged.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.48 15447

Causes all statements generating error at or above this level to be logged.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.49 15448

Sets the type of statements logged.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.50 15449

Sets the syslog "facility" to be used when syslog enabled.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.51 15450

Sets the session's behavior for triggers and rewrite rules.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.52 15451

Sets the current transaction's synchronization level.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.53 15452

Enables logging of recovery-related debugging information.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.54 15453

Collects function-level statistics on database activity.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.55 15454

Set the level of information written to the WAL.**[Description]**

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.56 15455

Selects the method used for forcing WAL updates to disk.**[Description]**

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.57 15456

Sets how binary values are to be encoded in XML.**[Description]**

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.58 15457

Sets whether XML data in implicit parsing and serialization operations is to be considered as documents or content fragments.**[Description]**

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.59 15458

Sets what to dump in core files.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.60 15459

Selects the algorithm for encrypting tablespaces.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.51.61 15460

@1@ cannot access the server configuration file "@2@": @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.51.62 15461

SET LOCAL TRANSACTION SNAPSHOT is not implemented

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.51.63 15462

SET AUTOCOMMIT TO OFF is no longer supported

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.51.64 15463

assertion checking is not supported by this build

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.51.65 15464

Bonjour is not supported by this build

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.51.66 15465

SSL is not supported by this build

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.51.67 15466

internal error: unrecognized run-time parameter type

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.51.68 15467

time zone abbreviation "@1@" is too long (maximum @2@ characters) in time zone file "@3@", line @4@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.51.69 15468

time zone offset @1@ is not a multiple of 900 sec (15 min) in time zone file "@2@", line @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.51.70 15469

time zone offset @1@ is out of range in time zone file "@2@", line @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.51.71 15470

missing time zone abbreviation in time zone file "@1@", line @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.51.72 15471

missing time zone offset in time zone file "@1@", line @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.51.73 15472

invalid number for time zone offset in time zone file "@1@", line @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.51.74 15473

invalid syntax in time zone file "@1@", line @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.51.75 15474

time zone abbreviation "@1@" is multiply defined

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.51.76 15475

invalid time zone file name "@1@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.51.77 15476

time zone file recursion limit exceeded in file "@1@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.51.78 15477

line is too long in time zone file "@1@", line @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.51.79 15478

@INCLUDE without file name in time zone file "@1@", line @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.51.80 15479

cannot export a snapshot from a subtransaction

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.51.81 15480

invalid snapshot data in file "@1@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.51.82 15481

SET TRANSACTION SNAPSHOT must be called before any query

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.51.83 15482

a snapshot-importing transaction must have isolation level **SERIALIZABLE** or **REPEATABLE READ**

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.51.84 15483

invalid snapshot identifier: "@1@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.51.85 15484

a serializable transaction cannot import a snapshot from a non-serializable transaction

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.51.86 15485

a non-read-only serializable transaction cannot import a snapshot from a read-only transaction

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.51.87 15486

cannot import a snapshot from a different database

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.51.88 15487

out of memory

[Description]

There was insufficient free space in the server's memory during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Estimate memory usage and take the following action:

- If the number of simultaneous connections from client applications is high, reduce it.
- If the number of simultaneous SQL executions is high, reduce it.

2.51.89 15488

@1@: could not open file "@2@" for reading: @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.51.90 15489

@1@: could not open file "@2@" for writing: @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.51.91 15490

@1@: could not write file "@2@" : @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.51.92 15491

@1@: could not execute command "@2@" : @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.51.93 15492

@1@: removing data directory "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.51.94 15493

@1@: failed to remove data directory

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.51.95 15494

@1@: removing contents of data directory "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.51.96 15495

@1@: failed to remove contents of data directory

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.51.97 15496

@1@: removing transaction log directory "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.51.98 15497

@1@: failed to remove transaction log directory

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.51.99 15498

@1@: removing contents of transaction log directory "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.51.100 15499

@1@: failed to remove contents of transaction log directory

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52 Message Numbers Beginning with 15500

2.52.1 15500

@1@: data directory "@2@" not removed at user's request

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.2 15501

@1@: transaction log directory "@2@" not removed at user's request

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.3 15502

@1@: could not obtain information about current user: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.4 15503

@1@: could not get current user name: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.5 15504

@1@: "@2@" is not a valid server encoding name

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.6 15505

@1@: could not create directory "@2@": @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.7 15506

@1@: file "@2@" does not exist

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.8 15507

@1@: could not access file "@2@": @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.9 15508

@1 @: file "@2@" is not a regular file

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.10 15509

Passwords didn't match.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.11 15510

@1 @: could not read password from file "@2@": @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.12 15511

@1 @: locale name too long, skipped: "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.13 15512

@1@: locale name has non-ASCII characters, skipped: "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.14 15513

No usable system locales were found.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.15 15514

not supported on this platform

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.16 15515

could not write to child process: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.17 15516

ok

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.52.18 15517

@1@: failed to restore old locale "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.19 15518

@1@: invalid locale name "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.20 15519

@1@: encoding mismatch

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.21 15521

@1@: could not open process token: error code @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.22 15522

@1@: could not to allocate SIDs: error code @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.23 15523

@1@: could not create restricted token: error code @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.24 15524

@1@: could not start process for command "@2@": error code @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.25 15525

@1@ initializes a PostgreSQL database cluster.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.26 15527

@1@: invalid authentication method "@2@" for "@3@" connections

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.27 15528

@1@: must specify a password for the superuser to enable @2@ authentication

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.28 15529

@1@: too many command-line arguments (first is "@2@")

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.29 15530

@1@: password prompt and password file cannot be specified together

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.30 15531

@1@: could not re-execute with restricted token: error code @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.31 15532

@1@: could not get exit code from subprocess: error code @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.32 15533

The program "postgres" is needed by @1@ but was not found in the same directory as "@2@". Check your installation.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.33 15534

The program "postgres" was found by "@1@" but was not the same version as @2@. Check your installation.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.34 15535

@1@: input file location must be an absolute path

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.35 15536

@1@: could not find suitable encoding for locale "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.36 15537

@1@: locale "@2@" requires unsupported encoding "@3@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.37 15538

@1@: could not find suitable text search configuration for locale "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.38 15539

@1@: warning: suitable text search configuration for locale "@2@" is unknown

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.52.39 15540

@1@: warning: specified text search configuration "@2@" might not match locale "@3@"

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.52.40 15541

The default text search configuration will be set to "@1@".

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.52.41 15542

@1@: directory "@2@" exists but is not empty

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.42 15543

@1@: could not access directory "@2@": @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.43 15544

@1@: transaction log directory location must be an absolute path

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.44 15545

@1@: could not create symbolic link "@2@": @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.45 15546

@1@: symlinks are not supported on this platform

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.46 15547

@1@: could not read from ready pipe: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.47 15548

@1@: could not parse transaction log location "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.48 15549

@1@: could not create pipe for background process: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.49 15550

@1@: could not create background process: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.50 15551

@1@: could not create background thread: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.51 15552

@1@: could not create directory "@2@": @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.52 15553

@1@: directory "@2@" exists but is not empty

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.53 15554

@1@: could not access directory "@2@": @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.54 15555

**@1@/@2@ kB (100@3@), @4@/@5@ tablespace @6@
@7@/@8@ kB (100@9@), @10@/@11@ tablespaces @12@**

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.52.55 15556

**@1@/@2@ kB (@3@@4@), @5@/@6@ tablespace (@7@)
@8@/@9@ kB (@10@@11@), @12@/@13@ tablespaces (@14@)**

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.52.56 15560

**@1@/@2@ kB (@3@@4@), @5@/@6@ tablespace
@7@/@8@ kB (@9@@10@), @11@/@12@ tablespaces**

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.52.57 15561

@1@: could not set compression level @2@: @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.58 15562

@1@: could not create compressed file "@2@": @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.59 15563

@1@: could not create file "@2@": @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.60 15564

@1@: could not get COPY data stream: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.61 15565

@1@: could not write to compressed file "@2@": @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.62 15566

@1@: could not write to file "@2@": @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.63 15567

@1@: could not close compressed file "@2@": @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.64 15568

@1@: could not close file "@2@": @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.65 15569

@1@: could not read COPY data: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.66 15570

@1@: invalid tar block header size: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.67 15571

@1 @: could not parse file size

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.68 15572

@1 @: could not parse file mode

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.69 15573

@1 @: could not set permissions on directory "@2@": @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.70 15574

@1 @: could not create symbolic link from "@2@" to "@3@": @4@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.71 15575

@1@: unrecognized link indicator "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.72 15576

@1@: could not set permissions on file "@2@": @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.73 15577

@1@: COPY stream ended before last file was finished

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.74 15578

@1@: could not send replication command "@2@": @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.75 15579

@1@: could not identify system: got @2@ rows and @3@ fields, expected @4@ rows and @5@ fields

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.76 15580

@1@: could not initiate base backup: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.77 15581

@1@: no start point returned from server

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.78 15582

@1@: could not get backup header: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.79 15583

@1@: no data returned from server

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.80 15584

@1@: can only write single tablespace to stdout, database has @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.81 15585

@1@: starting background WAL receiver

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.82 15586

@1@: could not get transaction log end position from server: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.83 15587

@1@: no transaction log end position returned from server

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.84 15588

@1@: final receive failed: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.85 15589

@1@: could not send command to background pipe: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.86 15590

@1@: could not wait for child process: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.87 15591

@1@: child @2@ died, expected @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.88 15592

@1@: child process did not exit normally

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.89 15593

@1@: child process exited with error @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.90 15594

@1@: could not wait for child thread: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.91 15595

@1@: could not get child thread exit status: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.92 15596

@1@: child thread exited with error @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.93 15597

@1@: invalid output format "@2@", must be "plain" or "tar"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.94 15598

@1@: cannot specify both --xlog and --xlog-method

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.52.95 15599

@1@: invalid compression level "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53 Message Numbers Beginning with 15600

2.53.1 15600

@1@: invalid checkpoint argument "@2@", must be "fast" or "spread"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.2 15601

@1@: invalid status interval "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.3 15602

@1@: too many command-line arguments (first is "@2@")

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.4 15603

@1@: no target directory specified

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.5 15604

@1@: only tar mode backups can be compressed

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.6 15605

@1@: wal streaming can only be used in plain mode

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.7 15606

@1@: this build does not support compression

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.8 15607

@1@: finished segment at @2@/@3@ (timeline @4@)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.9 15608

@1@: received interrupt signal, exiting.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.10 15609

@1@: could not open directory "@2@": @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.11 15610

@1@: could not parse transaction log file name "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.12 15611

@1@: could not stat file "@2@": @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.13 15612

@1@: segment file "@2@" has incorrect size @3@, skipping

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.14 15613

@1@: starting log streaming at @2@/@3@ (timeline @4@)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.15 15614

@1@: invalid port number "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.16 15615

@1@: disconnected.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.17 15616

@1@: disconnected. Waiting @2@ seconds to try again

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.18 15617

@1@: could not open transaction log file "@2@": @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.19 15618

@1@: could not stat transaction log file "@2@": @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.20 15619

@1@: transaction log file "@2@" has @3@ bytes, should be 0 or @4@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.21 15620

@1@: could not pad transaction log file "@2@": @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.22 15621

@1@: could not seek to beginning of transaction log file "@2@": @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.23 15622

@1@: could not determine seek position in file "@2@": @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.24 15623

@1@: could not fsync file "@2@": @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.25 15624

@1@: could not rename file "@2@": @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.26 15625

@1@: not renaming "@2@", segment is not complete.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.27 15626

@1@: system identifier does not match between base backup and streaming connection

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.28 15627

@1@: timeline does not match between base backup and streaming connection

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.29 15628

@1@: could not send feedback packet: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.30 15629

@1@: select() failed: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.31 15630

@1@: could not receive data from WAL stream: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.32 15631

@1@: keepalive message has incorrect size @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.33 15632

@1@: unrecognized streaming header: "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.34 15633

@1@: streaming header too small: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.35 15634

@1@: received transaction log record for offset @2@ with no file open

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.36 15635

@1@: got WAL data offset @2@, expected @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.37 15636

@1@: could not write @2@ bytes to WAL file "@3@": @4@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.38 15637

@1@: unexpected termination of replication stream: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.39 15638

@1@: replication stream was terminated before stop point

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.40 15639

@1@: could not close file @2@: @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.41 15640

@1@: could not connect to server

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.42 15641

@1@: could not connect to server: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.43 15642

@1@: could not determine server setting for integer_datetimes

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.44 15643

@1@: integer_datetimes compile flag does not match server

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.45 15644

not recorded

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.46 15645

@1@: could not find own program executable

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.47 15646

@1@: invalid argument: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.48 15647

@1@: no data directory specified

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.49 15648

@1@: could not open file "@2@" for reading: @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.50 15649

@1@: could not read file "@2@": @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.51 15652

child process exited with unrecognized status @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.52 15653

@1@: could not open PID file "@2@": @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.53 15654

@1@: invalid data in PID file "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.54 15655

@1@: -w option is not supported when starting a pre-9.1 server

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.55 15656

@1@: -w option cannot use a relative socket directory specification

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.56 15657

@1@: this data directory appears to be running a pre-existing postmaster

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.57 15658

@1@: cannot set core file size limit; disallowed by hard limit

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.58 15659

@1@: could not read file "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.59 15660

@1@: option file "@2@" must have exactly one line

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.60 15661

The program "@1@" is needed by @2@ but was not found in the same directory as "@3@". Check your installation.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.61 15662

The program "@1@" was found by "@2@" but was not the same version as @3@. Check your installation.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.62 15663

@1@: database system initialization failed

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.63 15664

@1@: another server might be running; trying to start server anyway

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.64 15665

@1 @: could not start server: exit code was @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.65 15666

@1 @: could not start serverExamine the log output.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.66 15667

@1 @: could not wait for server because of misconfiguration

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.67 15668

@1 @: PID file "@2@" does not exist

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.68 15669

Is server running?

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.69 15670

@1@: cannot stop server; single-user server is running (PID: @2@)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.70 15671

@1@: could not send stop signal (PID: @2@): @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.71 15673

@1@: server does not shut down

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.72 15674

@1@: cannot restart server; single-user server is running (PID: @2@)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.73 15675

@1@: old server process (PID: @2@) seems to be gone

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.74 15676

@1@: cannot reload server; single-user server is running (PID: @2@)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.75 15677

@1@: could not send reload signal (PID: @2@): @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.76 15678

@1 @: cannot promote server; single-user server is running (PID: @2@)**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.77 15679

@1 @: cannot promote server; server is not in standby mode**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.78 15680

@1 @: could not create promote signal file "@2@": @3@**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.79 15681

@1 @: could not write promote signal file "@2@": @3@**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.80 15682

@1 @: could not send promote signal (PID: @2@): @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.81 15683

@1@: could not send signal @2@ (PID: @3@): @4@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.82 15684

@1@: could not find own program executable

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.83 15685

@1@: could not find postgres program executable

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.84 15686

@1@: could not open service manager

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.85 15687

@1@: service "@2@" already registered

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.86 15688

@1@: could not register service "@2@": error code @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.87 15689

@1@: service "@2@" not registered

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.88 15690

@1@: could not open service "@2@": error code @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.89 15691

@1@: could not unregister service "@2@": error code @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.90 15692

Timed out waiting for server startup

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.91 15693

@1@: could not start service "@2@": error code @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.92 15695

@1@: could not open process token: error code @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.93 15696

@1@: could not allocate SIDs: error code @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.94 15697

@1@: could not create restricted token: error code @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.53.95 15699

@1@: unrecognized shutdown mode "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54 Message Numbers Beginning with 15700

2.54.1 15700

@1@: unrecognized signal name "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.2 15701

@1@: unrecognized start type "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.3 15702

@1@: could not determine the data directory using command "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.4 15703

@1@: -S option not supported on this platform

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.5 15704

@1@: too many command-line arguments (first is "@2@")

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.6 15705

@1@: missing arguments for kill mode

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.7 15706

@1@: unrecognized operation mode "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.8 15707

@1@: no operation specified

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.9 15708

child process exited with unrecognized status @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.10 15709

failed sanity check, parent OID @1@ of table "@2@" (OID @3@) not found

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.11 15710

could not parse numeric array "@1@": too many numbers

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.12 15711

could not parse numeric array "@1@": invalid character in number

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.13 15712

invalid compression code: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.14 15713

not built with zlib support

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.15 15714

could not initialize compression library: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.16 15715

could not close compression stream: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.17 15716

could not compress data: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.18 15717

could not write to output file: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.19 15718

could not uncompress data: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.20 15719

could not close compression library: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.21 15720

cannot duplicate null pointer

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.22 15721

@1@: unrecognized section name: "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.23 15722

out of on_exit_nicely slots

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.24 15723

could not close output file: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.25 15725

unexpected section code @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.26 15726

parallel restore is not supported with this archive file format

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.27 15727

parallel restore is not supported with archives made by pre-8.0 pg_dump

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.28 15728

cannot restore from compressed archive (compression not supported in this installation)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.29 15729

connecting to database for restore

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.54.30 15730

direct database connections are not supported in pre-1.3 archives

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.31 15731

warning from original dump file: @1@

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.54.32 15732

internal error -- WriteData cannot be called outside the context of a DataDumper routine

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.33 15733

large-object output not supported in chosen format

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.34 15734

restored @1 @ large object

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.35 15736

could not create large object @1 @: @2@

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.54.36 15737

could not open large object @1@: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.37 15738

could not open TOC file "@1@": @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.38 15740

could not find entry for ID @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.39 15741

could not close TOC file: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.40 15742

could not open output file "@1@": @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.41 15743

could not open output file: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.42 15744

wrote @1@ byte of large object data (result = @2@)

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.54.43 15746

could not write to large object (result: @1@, expected: @2@)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.44 15747

could not write to custom output routine

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.45 15748

Error while INITIALIZING:

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.46 15749

Error while PROCESSING TOC:

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.47 15750

Error while FINALIZING:

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.48 15751

Error from TOC entry @1@; @2@ @3@ @4@ @5@ @6@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.49 15752

bad dumpld

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.50 15753

bad table dumpld for TABLE DATA item

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.51 15754

unexpected data offset flag @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.52 15755

file offset in dump file is too large

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.53 15756

unexpected end of file

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.54 15757

directory name too long: "@1@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.55 15758

directory "@1@" does not appear to be a valid archive ("toc.dat" does not exist)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.56 15759

could not open input file "@1@": @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.57 15760

could not open input file: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.58 15761

could not read input file: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.59 15762

input file is too short (read @1@, expected 5)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.60 15763

input file appears to be a text format dump. Please use psql.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.61 15764

input file does not appear to be a valid archive (too short?)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.62 15765

input file does not appear to be a valid archive

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.63 15766

could not close input file: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.64 15767

unrecognized file format "@1@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.65 15768

entry ID @1@ out of range -- perhaps a corrupt TOC

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.66 15769

read TOC entry @1@ (ID @2@) for @3@ @4@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.67 15770

unrecognized encoding "@1@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.68 15771

invalid ENCODING item: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.69 15772

invalid STDSTRINGS item: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.70 15773

could not set session user to "@1@": @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.71 15774

could not set default_with_oids: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.72 15775

could not set search_path to "@1@": @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.73 15776

could not set default_tablespace to @1@: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.74 15779

did not find magic string in file header

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.75 15780

unsupported version (@1@.@2@) in file header

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.76 15781

sanity check on integer size (@1@) failed

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.77 15783

expected format (@1@) differs from format found in file (@2@)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.78 15786

worker process crashed: status @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.79 15787

processing missed item @1@ @2@ @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.80 15788

parallel_restore should not return

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.81 15789

could not create worker process: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.82 15790

could not create worker thread: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.83 15791

no item ready

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.84 15792

could not find slot of finished worker

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.85 15793

worker process failed: exit code @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.86 15794

transferring dependency @1@ -> @2@ to @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.87 15795

table "@1@" could not be created, will not restore its data

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.88 15796

invalid OID for large object

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.89 15797

unrecognized data block type (@1@) while searching archive

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.90 15798

error during file seek: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.54.91 15799

could not find block ID @1@ in archive -- possibly due to out-of-order restore request, which cannot be handled due to lack of data offsets in archive

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55 Message Numbers Beginning with 15800

2.55.1 15800

could not find block ID @1@ in archive -- possibly due to out-of-order restore request, which cannot be handled due to non-seekable input file

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.2 15801

could not find block ID @1@ in archive -- possibly corrupt archive

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.3 15802

found unexpected block ID (@1@) when reading data -- expected @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.4 15803

unrecognized data block type @1@ while restoring archive

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.5 15804

could not read from input file: end of file

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.6 15805

could not read from input file: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.7 15806

could not write byte: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.8 15807

could not close archive file: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.9 15808

can only reopen input archives

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.10 15809

parallel restore from standard input is not supported

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.11 15810

parallel restore from non-seekable file is not supported

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.12 15811

could not determine seek position in archive file: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.13 15812

could not set seek position in archive file: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.14 15814

could not parse version string "@1@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.15 15815

could not get server_version from libpq

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.16 15816

aborting because of server version mismatch

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.17 15817

failed to reconnect to database

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.18 15818

could not reconnect to database: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.19 15819

connection needs password

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.20 15820

already connected to a database

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.21 15821

failed to connect to database

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.22 15822

connection to database "@1@" failed: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.23 15823

query failed: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.24 15824

query was: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.25 15825

@1@: @2@ Command was: @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.26 15826

could not execute query

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.27 15827

error returned by PQputCopyData: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.28 15828

error returned by PQputCopyEnd: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.29 15829

COPY failed for table "@1@": @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.30 15830

could not start database transaction

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.31 15831

could not commit database transaction

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.32 15832

no output directory specified

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.33 15833

could not create directory "@1@": @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.34 15834

could not close data file: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.35 15835

could not open large object TOC file "@1@" for input: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.36 15836

invalid line in large object TOC file "@1@": "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.37 15837

error reading large object TOC file "@1@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.38 15838

could not close large object TOC file "@1@": @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.39 15839

could not write byte

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.40 15840

could not write to blobs TOC file

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.41 15841

file name too long: "@1@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.42 15842

this format cannot be read

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.43 15843

could not open TOC file "@1@" for output: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.44 15844

could not open TOC file for output: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.45 15845

compression is not supported by tar archive format

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.46 15846

could not open TOC file "@1@" for input: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.47 15847

could not open TOC file for input: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.48 15848

could not find file "@1@" in archive

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.49 15849

could not generate temporary file name: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.50 15850

could not open temporary file

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.51 15851

could not close tar member

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.52 15852

internal error -- neither th nor fh specified in tarReadRaw()

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.53 15853

invalid COPY statement -- could not find "copy" in string "@1@"**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.54 15854

invalid COPY statement -- could not find "from stdin" in string "@1@" starting at position @2@**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.55 15855

could not write null block at end of tar archive**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.56 15856

invalid OID for large object (@1@)**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.57 15857

archive member too large for tar format

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.58 15858

could not close temporary file: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.59 15859

actual file length (@1@) does not match expected (@2@)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.60 15860

could not output padding at end of tar member

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.61 15861

could not find header for file "@1@" in tar archive

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.62 15862

skipping tar member @1@

[Description]

Terminated normally but a warning was output.

[System Processing]

Continues processing.

[Action]

Check the message text and confirm that the event indicated in supplementary information reported by the system is a planned event.

2.55.63 15863

restoring data out of order is not supported in this archive format: "@1@" is required, but comes before "@2@" in the archive file.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.64 15864

incomplete tar header found (@1@ byte)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.65 15866

TOC Entry @1@ at @2@ (length @3@, checksum @4@)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.66 15867

corrupt tar header found in @1@ (expected @2@, computed @3@) file position @4@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.67 15868

@1@: too many command-line arguments (first is "@2@")

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.68 15869

could not open output file "@1@" for writing

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.69 15870

No matching schemas were found

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.70 15871

No matching tables were found

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.71 15872

invalid client encoding "@1@" specified

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.72 15873

invalid output format "@1@" specified

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.73 15874

server version must be at least 7.3 to use schema selection switches

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.74 15875

dumping contents of table @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.75 15876

Dumping the contents of table "@1@" failed: PQgetCopyData() failed.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.76 15877

Dumping the contents of table "@1@" failed: PQgetResult() failed.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.77 15878

error reading large object @1@: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.78 15879

could not find parent extension for @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.79 15881

schema with OID @1@ does not exist

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.80 15889

failed sanity check, parent table OID @1@ of pg_rewrite entry OID @2@ not found

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.81 15890

query produced null referenced table name for foreign key trigger "@1@" on table "@2@" (OID of table: @3@)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.82 15891

invalid column numbering in table "@1@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.83 15892

invalid adnum value @1@ for table "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.84 15893

expected @1@ check constraint on table "@2@" but found @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.55.85 15895

(The system catalogs might be corrupted.)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56 Message Numbers Beginning with 15900

2.56.1 15902

unrecognized provolatile value for function "@1@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.2 15907

could not parse default ACL list (@1@)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.3 15908

could not parse ACL list (@1@) for object "@2@" (@3@)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.4 15909

query to obtain definition of view "@1@" returned no data

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.5 15910

query to obtain definition of view "@1@" returned more than one definition

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.6 15911

definition of view "@1@" appears to be empty (length zero)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.7 15912

invalid column number @1@ for table "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.8 15913

missing index for constraint "@1@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.9 15914

unrecognized constraint type: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.10 15915

query to get data of sequence "@1@" returned @2@ row (expected 1)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.11 15917

query to get data of sequence "@1@" returned name "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.12 15918

unexpected tctype value: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.13 15919

invalid argument string (@1@) for trigger "@2@" on table "@3@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.14 15920

query to get rule "@1@" for table "@2@" failed: wrong number of rows returned

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.15 15921

query returned @1@ row instead of one: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.16 15923

invalid dumpId @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.17 15924

invalid dependency @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.18 15925

could not identify dependency loop

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.19 15927

The program "pg_dump" is needed by @1@ but was not found in the same directory as "@2@". Check your installation.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.20 15928

The program "pg_dump" was found by "@1@" but was not the same version as @2@. Check your installation.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.21 15929

@1@: could not connect to database "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.22 15930

@1@: could not connect to databases "postgres" or "template1"Please specify an alternative database.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.23 15931

@1@: could not open the output file "@2@": @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.24 15932

@1@: could not parse ACL list (@2@) for tablespace "@3@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.25 15933

@1@: could not parse ACL list (@2@) for database "@3@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.26 15934

@1@: pg_dump failed on database "@2@", exiting

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.27 15935

@1@: could not re-open the output file "@2@": @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.28 15936

@1@: running "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.29 15937

@1@: could not connect to database "@2@": @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.30 15938

@1@: could not get server version

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.31 15939

@1@: could not parse server version "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.32 15940

@1@: could not parse version "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.33 15941

@1@: executing @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.34 15942

@1@: query failed: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.35 15943

@1 @: query was: @2 @

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.36 15944

unrecognized archive format "@1 @"; please specify "c", "d", or "t"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.37 15946

@1 @: invalid argument for option -e

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.38 15947

@1 @: transaction ID epoch (-e) must not be -1

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.39 15948

@1@: invalid argument for option -x

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.40 15949

@1@: transaction ID (-x) must not be 0

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.41 15950

@1@: invalid argument for option -o

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.42 15951

@1@: OID (-o) must not be 0

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.43 15952

@1 @: invalid argument for option -m**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.44 15953

@1 @: multitransaction ID (-m) must not be 0**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.45 15954

@1 @: invalid argument for option -O**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.46 15955

@1 @: multitransaction offset (-O) must not be -1**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.47 15956

@1 @: invalid argument for option -l

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.48 15957

@1@: no data directory specified

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.49 15958

@1@: cannot be executed by "root"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.50 15959

@1@: could not change directory to "@2@": @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.51 15960

@1@: could not open file "@2@" for reading: @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.52 15961

If these values seem acceptable, use -f to force reset.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.53 15962

Transaction log reset

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.54 15963

@1@: could not read file "@2@": @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.55 15964

@1@: pg_control exists but has invalid CRC; proceed with caution

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.56 15965

@1@: pg_control exists but is broken or unknown version; ignoring it

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.57 15966

@1@: internal error -- sizeof(ControlFileData) is too large ... fix PG_CONTROL_SIZE

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.58 15967

@1@: could not create pg_control file: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.59 15968

@1@: could not write pg_control file: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.60 15969

@1@: fsync error: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.61 15970

@1@: could not open directory "@2@": @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.62 15971

@1@: could not read from directory "@2@": @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.63 15972

@1@: could not delete file "@2@": @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.64 15973

@1@: could not open file "@2@": @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.65 15974

@1@: could not write file "@2@": @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.66 15975

could not create directory "@1@": @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.67 15976

could not open directory "@1@": @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.68 15977

could not stat file "@1@": @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.69 15978

could not read symbolic link "@1@": @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.70 15979

could not create symbolic link "@1@": @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.71 15980

out of memory

[Description]

There was insufficient free space in the server's memory during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Estimate memory usage and take the following action:

- If the number of simultaneous connections from client applications is high, reduce it.
- If the number of simultaneous SQL executions is high, reduce it.

2.56.72 15981

could not open file "@1@": @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.73 15982

could not create file "@1@": @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.74 15983

could not read file "@1@": @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.75 15984

could not write to file "@1@": @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.76 15985

could not fsync file "@1@": @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.77 15986

could not close file "@1@": @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.78 15987

@1@: could not find own program executable

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.79 15988

@1@: invalid checkpoint argument "@2@", must be "fast" or "spread"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.80 15989

@1@: invalid argument @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.81 15990

@1@: option @2@ conflicts with option @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.82 15991

@1@: the configured database storage directory differs from the data_directory parameter

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.83 15992

@1@: an invalid value was specified for the option -@2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.84 15993

@1@: backup data "@2@" is lost

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.85 15994

@1@: cannot be run as root

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.86 15995

@1@: invalid option --@2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.87 15996

@1@: invalid option -@2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.88 15997

@1@: backup of the database has not yet been performed, or an incorrect backup storage directory was specified

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.89 15998

@1@: the database storage directory and the \$PGDATA environment variable have not been specified

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.56.90 15999

@1@: option @2@ is necessary for option @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57 Message Numbers Beginning with 16000

2.57.1 16000

@1@: the requested recovery point is earlier than the date and time that the backup finished

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.2 16001

@1@: the specified backup does not exist

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.3 16002

@1@: the directory "@2@" for the tablespace with OID "@3@" does not exist

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.4 16003

@1@: the specified backup storage directory "@2@" is not correct

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.5 16004

@1@: the specified database storage directory is not correct

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.6 16005

@1@: the token in the file "pg_hba.conf" is too long and will be skipped: "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.7 16006

the directory "@1@" for storing WAL does not exist

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.8 16007

@1@: "@2@" is being executed by another user

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.9 16008

@1@: the "@2@" parameter was not found

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.10 16009

@1@: could not find the configuration file "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.11 16010

@1@: could not open the configuration file "@2@": maximum nesting depth exceeded**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.12 16011

@1@: the PID file "@2@" does not exist**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.13 16012

@1@: the server is running**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.14 16013

@1@: the server is not running**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.15 16014

@1@: caught signal @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.16 16015

@1@: failed to build the absolute path "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.17 16016

@1@: failed to check the completion of archiving WAL files

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.18 16017

@1@: failed to connect to the database

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.19 16018

@1@: failed to get the database OID : @2@ (@3@)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.20 16019

@1@: failed to remove old backup data

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.21 16020

@1@: failed to restore the database storage directory "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.22 16021

@1@: failed to restore the tablespace directory "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.23 16022

@1@: retried backup @2@ times, but failed

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.24 16023

@1@: SQL command failed (@2@)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.25 16024

@1@: the database with OID @2@ was created during backup

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.26 16025

@1@: backup control function "@2@" failed

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.27 16026

@1@: command failed: "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.28 16027

@1@: could not close the file "@2@": @3@ (errno=@4@)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.29 16028

@1@: could not close the PID file "@2@": @3@ (errno=@4@)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.30 16029

@1@: could not create the directory "@2@": @3@ (errno=@4@)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.31 16030

@1@: could not create the file "@2@": @3@ (errno=@4@)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.32 16031

@1@: could not create the PID file "@2@": @3@ (errno=@4@)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.33 16032

@1@: could not create the symbolic link "@2@": @3@ (errno=@4@)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.34 16033

@1@: could not identify the current directory: @2@ (errno=@3@)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.35 16034

@1@: could not open the directory "@2@": @3@ (errno=@4@)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.36 16035

@1@: could not open the file "@2@": @3@ (errno=@4@)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.37 16036

@1@: could not open the PID file "@2@": @3@ (errno=@4@)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.38 16037

@1@: could not read the file "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.39 16038

@1@: could not read the PID file "@2@": @3@ (errno=@4@)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.40 16039

@1@: could not read the symbolic link "@2@": @3@ (errno=@4@)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.41 16040

@1@: could not remove the file "@2@": @3@ (errno=@4@)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.42 16041

@1@: could not remove the PID file "@2@": @3@ (errno=@4@)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.43 16042

@1@: could not rename the directory "@2@" to "@3@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.44 16043

@1@: could not rename the file "@2@" to "@3@": @4@ (errno=@5@)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.45 16044

@1@: could not write the file "@2@": @3@ (errno=@4@)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.46 16045

@1@: could not write the PID file "@2@": @3@ (errno=@4@)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.47 16046

@1@: failed to find the internal file "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.48 16047

@1@: failed to parse the internal file "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.49 16048

@1@: failed to parse the internal file: "@2@" (@3@)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.50 16049

@1@: failed to parse the configuration file "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.51 16050

@1@: failed to remove archived transaction log files

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.52 16051

@1@: failed to replace the contents of the pg_xlog directory

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.53 16052

@1@: failed to restore the configuration files**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.54 16053

@1@: invalid data in the PID file "@2@"**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.55 16054

@1@: out of memory**[Description]**

There was insufficient free space in the server's memory during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Estimate memory usage and take the following action:

- If the number of simultaneous connections from client applications is high, reduce it.
- If the number of simultaneous SQL executions is high, reduce it.

2.57.56 16055

@1@: cannot find the server process (PID: @2@)**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.57 16056

@1@: an error occurred during recovery

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.58 16057

@1@: could not remove the directory "@2@": @3@ (errno=@4@)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.59 16058

@1@: target "@2@" mismatch (internal error)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.60 16059

the program "@1@" is needed by @2@ but was not found in the same directory as "@3@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.61 16060

the program "@1@" was found in "@2@" but was not the same version as @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.62 16061

@1@: failed to get port number (internal error)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.63 16062

backup of configuration files completed successfully

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.57.64 16063

backup of database and configuration files completed successfully

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.57.65 16064

Confirm that the specified directory is correct. If it is correct, the backup data may be corrupted. Copy the backup data to the backup storage directory from backup media.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.66 16065

Check the installation.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.67 16066

Continue the backup.

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.57.68 16067

Create an empty directory "@1@" on which the database administrator has full permissions, and retry.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.69 16068

Create an empty directory "@1@" on which the database administrator has full permissions.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.70 16069

Recover the corrupt resource.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.71 16070

Is the server running?

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.72 16071

Please check whether the backup data exists or is not in the backup storage directory.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.73 16072

Please decrease the length of the path and retry.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.74 16073

Please decrease the number of digits and retry.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.75 16074

Please log in as the user that owns the server process.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.76 16075

Please remove the cause of the error, and retry.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.77 16076

Please set the database storage directory "@1@" to -D option, and retry.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.78 16077

Please set the recovery point to be after the date and time that the backup finished, and retry.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.79 16078

Please set the backup storage directory to the 'backup_destination' parameter and restart the server.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.80 16079

Please specify the database storage directory as "@1@" and retry.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.81 16080

Please specify the database storage directory correctly and retry.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.82 16081

Please specify the port number correctly and retry.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.83 16082

Please specify an integer greater than 0, and try again.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.84 16083

Please specify an integer greater than 0, or the 'all' keyword, and retry.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.85 16084

Please specify an integer greater than or equal to 0, and retry.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.86 16085

Please specify the backup storage directory correctly and retry.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.87 16086

Please specify the time stamp using the correct length and retry.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.88 16087

Please start the server and retry.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.89 16088

Please stop the server and retry.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.90 16089

Please wait for a short period and retry.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.91 16090

Recovery of database completed successfully.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.92 16091

Retrying backup. (@1@ times).

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.93 16092

Specify the backup storage directory with the -B option, and retry.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.94 16093

Refer to "@1@ --help" for more information.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.95 16094

Retry after the other process terminates.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.96 16095

Failed to identify backup data.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.97 16096

restore point name is too long (maximum @1@ bytes)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.98 16097

Try "@1@ --help" for more information.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.99 16098

@1@: keystore location is not specified

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.57.100 16099

@1@: too many command-line arguments (first is "@2@")

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58 Message Numbers Beginning with 16100

2.58.1 16100

@1@: no operation is specified

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.2 16101

@1@: could not open file "@2@": @3@ (errno=@4@)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.3 16102

@1@: could not read file "@2@": @3@ (errno=@4@)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.4 16103

@1@: keystore "@2@" is corrupted: size = @3@ bytes, expected size = @4@ bytes

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.5 16104

@1@: file "@2@" is not a keystore

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.6 16105

@1@: key is too long

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.7 16106

@1@: key is wrong

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.8 16107

@1@: passphrase-based key derivation failed: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.9 16108

@1@: decryption of the keystore failed: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.10 16109

@1@: decryption of the keystore failed: passphrase is wrong

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.11 16110

@1@: keystore "@2@" is corrupted: invalid CRC

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.12 16111

@1@: encryption of the keystore failed: error code = @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.13 16112

@1@: encryption of the keystore failed: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.14 16113

@1@: could not create file "@2@" : @3@ (errno=@4@)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.15 16114

@1@: could not write file "@2@": @3@ (errno=@4@)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.16 16115

child process exited with unrecognized status @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.17 16116

Invalid command \@1@. Try \? for help.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.18 16117

invalid command \@1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.19 16118

\\@1@: extra argument "@2@" ignored

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.20 16119

could not get home directory: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.21 16120

\\@1@: could not change directory to "@2@" : @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.22 16121

You are currently not connected to a database.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.23 16122

no query buffer

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.24 16123

@1@: invalid encoding name or conversion procedure not found

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.25 16124

\\@1@: missing required argument

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.26 16125

Passwords didn't match.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.27 16126

Password encryption failed.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.28 16127

\\@1@: error while setting variable

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.29 16128

out of memory

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.30 16129

\\@1@: environment variable name must not contain "="

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.31 16130

The server (version @1 @.@2@) does not support showing function source.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.32 16131

function name is required

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.33 16132

@1@: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.34 16133

@1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.35 16134

\connect: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.36 16137

environment variable PSQL_EDITOR_LINENUMBER_ARG must be set to specify a line number

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.37 16138

could not start editor "@1@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.38 16139

could not start /bin/sh

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.39 16140

could not locate temporary directory: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.40 16141

could not open temporary file "@1@": @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.41 16142

\pset: allowed formats are unaligned, aligned, wrapped, html, latex, troff-ms

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.42 16143

\pset: allowed line styles are ascii, old-ascii, unicode

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.43 16144

\pset: unknown option: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.44 16145

\\!: failed**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.45 16146

@1@: pg_strdup: cannot duplicate null pointer (internal error)**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.46 16147

connection to server was lost**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.47 16148

Failed.**[Description]**

Supplementary information was output.

[System Processing]

None.

[Action]

Refer to this message together with the message that was output immediately beforehand.

2.58.48 16149

unexpected PQresultStatus: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.49 16150

The server (version @1@.@2@) does not support savepoints for ON_ERROR_ROLLBACK.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.50 16151

unexpected transaction status (@1@)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.51 16152

\\copy: arguments required

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.52 16153

\\copy: parse error at "@1@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.53 16154

\\copy: parse error at end of line

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.54 16155

@1@: cannot copy from/to a directory

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.55 16156

could not write COPY data: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.56 16157

COPY data transfer failed: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.57 16158

Enter data to be copied followed by a newline.End with a backslash and a period on a line by itself.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.58 16159

aborted because of read failure

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.59 16160

The server (version @1@.@2@) does not support tablespaces.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.60 16161

\df only takes [antwS+] as options

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.61 16162

\\df does not take a "w" option with server version @1@.@2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.62 16163

The server (version @1@.@2@) does not support altering default privileges.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.63 16164

Did not find any relation named "@1@".

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.64 16165

Did not find any relation with OID @1@.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.65 16166

No per-database role settings support in this server version.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.66 16167

No matching settings found.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.67 16168

No settings found.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.68 16169

No matching relations found.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.69 16170

No relations found.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.70 16171

The server (version @1@.@2@) does not support collations.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.71 16172

The server (version @1@.@2@) does not support full text search.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.72 16173

Did not find any text search configuration named "@1@".

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.73 16174

The server (version @1@.@2@) does not support foreign-data wrappers.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.74 16175

The server (version @1@.@2@) does not support foreign servers.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.75 16176

The server (version @1@.@2@) does not support user mappings.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.76 16177

The server (version @1@.@2@) does not support foreign tables.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.77 16178

The server (version @1@.@2@) does not support extensions.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.78 16179

Did not find any extension named "@1@".

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.79 16180

Did not find any extensions.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.80 16181

could not get current user name: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.81 16182

could not read from input file: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.82 16183

could not save history to file "@1@": @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.83 16184

history is not supported by this installation

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.84 16185

@1@: not connected to a database

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.85 16186

@1@: current transaction is aborted

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.86 16187

@1@: unknown transaction status

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.87 16188

Cannot add header to table content: column count of @1@ exceeded.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.88 16189

Cannot add cell to table content: total cell count of @1@ exceeded.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.89 16190

invalid output format (internal error): @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.90 16191

skipping recursive expansion of variable "@1@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.91 16192

unterminated quoted string

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.92 16193

@1@: out of memory

[Description]

There was insufficient free space in the server's memory during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Estimate memory usage and take the following action:

- If the number of simultaneous connections from client applications is high, reduce it.
- If the number of simultaneous SQL executions is high, reduce it.

2.58.93 16194

can't escape without active connection

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.94 16195

@1@: could not open log file "@2@": @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.95 16196

@1@: could not set printing parameter "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.96 16197

@1@: could not delete variable "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.97 16198

@1@: could not set variable "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.58.98 16199

@1@: warning: extra command-line argument "@2@" ignored

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59 Message Numbers Beginning with 16200

2.59.1 16200

tab completion query failed: @1@Query was: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.2 16201

unrecognized Boolean value; assuming "on"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.3 16202

Try "@1@ --help" for more information.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.4 16203

@1@: too many command-line arguments (first is "@2@")

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.5 16204

@1@: cannot cluster all databases and a specific one at the same time

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.6 16205

@1@: cannot cluster a specific table in all databases

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.7 16206

@1@: clustering of table "@2@" in database "@3@" failed: @4@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.8 16207

@1@: clustering of database "@2@" failed: @3@**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.9 16208

@1@: clustering database "@2@"**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.10 16209

@1@: could not obtain information about current user: @2@**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.11 16210

@1@: could not get current user name: @2@**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.12 16211

@1@: out of memory

[Description]

There was insufficient free space in the server's memory during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Estimate memory usage and take the following action:

- If the number of simultaneous connections from client applications is high, reduce it.
- If the number of simultaneous SQL executions is high, reduce it.

2.59.13 16212

@1@: could not connect to database @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.14 16213

@1@: could not connect to database @2@: @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.15 16214

@1@: query failed: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.16 16215

pg_strdup: cannot duplicate null pointer (internal error)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.17 16216

out of memory

[Description]

There was insufficient free space in the server's memory during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Estimate memory usage and take the following action:

- If the number of simultaneous connections from client applications is high, reduce it.
- If the number of simultaneous SQL executions is high, reduce it.

2.59.18 16217

Cancel request sent

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.19 16218

Could not send cancel request: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.20 16219

@1@: only one of --locale and --lc-ctype can be specified**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.21 16220

@1@: only one of --locale and --lc-collate can be specified**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.22 16221

@1@: "@2@" is not a valid encoding name**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.23 16222

@1@: database creation failed: @2@**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.24 16223

@1@: comment creation failed (database was created): @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.25 16224

Procedural Languages

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.26 16225

@1@: missing required argument language name

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.27 16226

@1@: language "@2@" is already installed in database "@3@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.28 16227

@1@: language installation failed: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.29 16228

Passwords didn't match.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.30 16229

Password encryption failed.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.31 16230

@1@: creation of new role failed: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.32 16231

@1@: missing required argument database name

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.33 16232

Database "@1@" will be permanently removed.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.34 16233

@1@: database removal failed: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.35 16234

@1@: language "@2@" is not installed in database "@3@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.36 16235

@1@: language removal failed: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.37 16236

@1@: missing required argument role name

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.38 16237

Role "@1@" will be permanently removed.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.39 16238

@1@: removal of role "@2@" failed: @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.40 16239

@1@: cannot reindex all databases and a specific one at the same time

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.41 16240

@1@: cannot reindex all databases and system catalogs at the same time**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.42 16241

@1@: cannot reindex a specific table in all databases**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.43 16242

@1@: cannot reindex a specific index in all databases**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.44 16243

@1@: cannot reindex a specific table and system catalogs at the same time**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.45 16244

@1@: cannot reindex a specific index and system catalogs at the same time

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.46 16245

@1@: reindexing of table "@2@" in database "@3@" failed: @4@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.47 16246

@1@: reindexing of index "@2@" in database "@3@" failed: @4@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.48 16247

@1@: reindexing of database "@2@" failed: @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.49 16248

@1@: reindexing database "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.50 16249

@1@: reindexing of system catalogs failed: @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.51 16250

@1@: cannot use the "full" option when performing only analyze

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.52 16251

@1@: cannot use the "freeze" option when performing only analyze

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.53 16252

@1@: cannot vacuum all databases and a specific one at the same time

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.54 16253

@1@: cannot vacuum a specific table in all databases

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.55 16254

@1@: vacuuming of table "@2@" in database "@3@" failed: @4@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.56 16255

@1@: vacuuming of database "@2@" failed: @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.57 16256

SQL error: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.58 16257

variable "@1@" must have a numeric type

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.59 16258

descriptor "@1@" does not exist

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.60 16259

descriptor header item "@1@" does not exist

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.61 16260

nullable is always 1

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.62 16261

key_member is always 0

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.63 16262

descriptor item "@1@" is not implemented

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.64 16263

descriptor item "@1@" cannot be set

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.65 16264

@1@: could not open file "@2@": @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.66 16265

Try "@1@ --help" for more information.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.67 16266

@1@: parser debug support (-d) not available

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.68 16268

@1@: no input files specified

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.69 16269

cursor "@1@" has been declared but not opened

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.70 16270

could not remove output file "@1@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.71 16272

invalid bit string literal

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.72 16273

unterminated bit string literal

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.73 16274

unterminated hexadecimal string literal

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.74 16275

unterminated quoted string

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.75 16276

zero-length delimited identifier

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.76 16277

unterminated quoted identifier

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.77 16278

missing identifier in EXEC SQL UNDEF command

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.78 16279

missing matching "EXEC SQL IFDEF" / "EXEC SQL IFNDEF"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.79 16280

missing "EXEC SQL ENDIF;"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.80 16281

more than one EXEC SQL ELSE

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.81 16282

unmatched EXEC SQL ENDIF

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.82 16283

too many nested EXEC SQL IFDEF conditions

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.83 16284

missing identifier in EXEC SQL IFDEF command

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.84 16285

missing identifier in EXEC SQL DEFINE command

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.85 16286

syntax error in EXEC SQL INCLUDE command

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.86 16287

internal error: unreachable state; If the cause of errors cannot be found, contact the Fujitsu Systems Engineer (SE).

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause. If the cause of errors cannot be found, contact the Fujitsu Systems Engineer (SE).

2.59.87 16288

Error: include path "@1@/@2@" is too long on line @3@, skipping

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.88 16289

could not open include file "@1@" on line @2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.89 16290

cursor "@1@" does not exist

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.90 16291

initializer not allowed in type definition

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.91 16292

type name "string" is reserved in Informix mode

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.92 16293

type "@1@" is already defined

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.93 16294

multidimensional arrays for simple data types are not supported

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.94 16295

AT option not allowed in CLOSE DATABASE statement

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.95 16296

AT option not allowed in CONNECT statement

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.96 16297

AT option not allowed in DISCONNECT statement

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.97 16298

AT option not allowed in SET CONNECTION statement

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.59.98 16299

AT option not allowed in TYPE statement

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60 Message Numbers Beginning with 16300

2.60.1 16300

AT option not allowed in VAR statement

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.2 16301

AT option not allowed in WHENEVER statement

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.3 16302

unsupported feature will be passed to server

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.4 16303

SHOW ALL is not implemented

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.5 16304

COPY TO STDIN is not possible

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.6 16305

COPY FROM STDOUT is not possible

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.7 16306

COPY FROM STDIN is not implemented

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.8 16307

constraint declared INITIALLY DEFERRED must be DEFERRABLE

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.9 16308

using variable "@1@" in different declare statements is not supported

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.10 16309

cursor "@1@" is already defined

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.11 16310

no longer supported LIMIT #,# syntax passed to server

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.12 16311

subquery in FROM must have an alias

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.13 16312

CREATE TABLE AS cannot specify INTO

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.14 16313

expected "@", found "@1@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.15 16314

only protocols "tcp" and "unix" and database type "postgresql" are supported

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.16 16315

expected "://", found "@1@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.17 16316

Unix-domain sockets only work on "localhost" but not on "@1@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.18 16317

expected "postgresql", found "@1@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.19 16318

invalid connection type: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.20 16319

expected "@" or "://", found "@1@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.21 16320

invalid data type

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.22 16321

incomplete statement

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.23 16322

unrecognized token "@1@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.24 16323

only data types numeric and decimal have precision/scale argument

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.25 16324

interval specification not allowed here

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.26 16325

too many levels in nested structure/union definition

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.27 16326

pointers to varchar are not implemented

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.28 16327

using unsupported DESCRIBE statement

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.29 16328

initializer not allowed in EXEC SQL VAR command

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.30 16329

arrays of indicators are not allowed on input

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.31 16330

@1@ at or near "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.32 16331

out of memory

[Description]

There was insufficient free space in the server's memory during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Estimate memory usage and take the following action:

- If the number of simultaneous connections from client applications is high, reduce it.
- If the number of simultaneous SQL executions is high, reduce it.

2.60.33 16332

unrecognized variable type code @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.34 16333

variable "@1@" is hidden by a local variable of a different type

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.35 16334

variable "@1@" is hidden by a local variable

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.36 16335

indicator variable "@1@" is hidden by a local variable of a different type

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.37 16336

indicator variable "@1@" is hidden by a local variable

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.38 16337

indicator for array/pointer has to be array/pointer

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.39 16338

nested arrays are not supported (except strings)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.40 16339

indicator for struct has to be a struct

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.41 16340

indicator for simple data type has to be simple

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.42 16341

unrecognized descriptor item code @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.43 16342

incorrectly formed variable "@1@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.44 16343

variable "@1@" is not a pointer

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.45 16344

variable "@1@" is not a pointer to a structure or a union

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.46 16345

variable "@1@" is neither a structure nor a union

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.47 16346

variable "@1@" is not an array

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.48 16347

variable "@1@" is not declared

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.49 16348

indicator variable must have an integer type

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.50 16349

unrecognized data type name "@1@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.51 16350

multidimensional arrays are not supported

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.52 16351

multilevel pointers (more than 2 levels) are not supported; found @1@ level

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.53 16353

pointer to pointer is not supported for this data type

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.54 16354

multidimensional arrays for structures are not supported

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.55 16355

invalid URI propagated to internal parser routine: "@1@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.56 16356

end of string reached when looking for matching "]" in IPv6 host address in URI: "@1@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.57 16357

IPv6 host address may not be empty in URI: "@1@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.58 16358

unexpected character "@1@" at position @2@ in URI (expected ":" or "/"): "@3@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.59 16359

extra key/value separator "=" in URI query parameter: "@1@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.60 16360

missing key/value separator "=" in URI query parameter: "@1@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.61 16361

invalid URI query parameter: "@1@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.62 16362

invalid percent-encoded token: "@1@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.63 16363

forbidden value @1@00 in percent-encoded value: "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.64 16364

insufficient data in "T" message

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.65 16365

extraneous data in "T" message

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.66 16366

insufficient data in "D" message

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.67 16367

extraneous data in "D" message

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.68 16368

at character @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.69 16369

unrecognized socket error: 0x@1 @/@2@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.70 16370

If true, trusted and untrusted Perl code will be compiled in strict mode.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.71 16371

Perl initialization code to execute when a Perl interpreter is initialized.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.72 16372

Perl initialization code to execute once when plperl is first used.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.73 16373

Perl initialization code to execute once when pperl is first used.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.74 16374

duplicate declaration

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.75 16375

diagnostics item @1@ is not allowed in GET STACKED DIAGNOSTICS

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.76 16376

diagnostics item @1@ is not allowed in GET CURRENT DIAGNOSTICS

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.77 16377

unrecognized GET DIAGNOSTICS item

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.78 16378

unexpected end of function definition

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.79 16379

syntax error

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.80 16380

invalid SQLSTATE code

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.81 16381

syntax error, expected "FOR "

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.82 16382

mismatched parentheses

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.83 16383

missing expression

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.84 16384

missing SQL statement

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.85 16385

incomplete data type declaration

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.86 16386

missing data type declaration

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.87 16387

INTO specified more than once

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.88 16388

expected FROM or IN

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.89 16389

cursor "@1@" has no argument named "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.90 16390

value for parameter "@1@" of cursor "@2@" specified more than once

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.91 16391

unrecognized RAISE statement option

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.92 16392

syntax error, expected "="

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.93 16393

during initialization of execution state

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.94 16394

while storing call arguments into local variables

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.95 16395

during function entry

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.96 16396

while casting return value to function's return type

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.97 16397

returned record type does not match expected record type

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.98 16398

during function exit

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.60.99 16399

returned row structure does not match the structure of the triggering table

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61 Message Numbers Beginning with 16400

2.61.1 16400

during statement block local variable initialization

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.2 16401

during statement block entry

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.3 16402

during statement block exit

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.4 16403

during exception cleanup

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.5 16404

structure of query does not match function result type

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.6 16405

query "@1@" returned @2@ column query "@3@" returned @4@ columns

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.7 16406

Sets handling of conflicts between PL/pgSQL variable names and table column names.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.8 16407

plpy.cursor expected a query or a plan

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.9 16408

plpy.cursor takes a sequence as its second argument

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.10 16409

could not execute plan

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.11 16410

Expected sequence of @1@ argument, got @2@: @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.12 16412

iterating a closed cursor

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.13 16413

iterating a cursor in an aborted subtransaction

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.14 16414

fetch from a closed cursor

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.15 16415

closing a cursor in an aborted subtransaction

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.16 16416

error fetching next item from iterator

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.17 16417

PyList_SetItem() failed, while setting up arguments

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.18 16418

PyDict_SetItemString() failed, while setting up arguments

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.19 16419

could not create new dictionary while building trigger arguments

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.20 16420

untrapped error in initialization

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.21 16421

could not import "__main__" module

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.22 16422

could not create globals

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.23 16423

plan.status takes no arguments

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.24 16424

could not import "plpy" module

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.25 16425

could not add the spiexceptions module

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.26 16426

could not create the base SPI exceptions

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.27 16427

could not generate SPI exceptions

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.28 16428

could not unpack arguments in plpy.elog

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.29 16429

could not parse error message in plpy.elog

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.30 16430

could not compile PL/Python function "@1@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.31 16431

could not compile anonymous PL/Python code block

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.32 16432

command did not produce a result set

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.33 16433

second argument of plpy.prepare must be a sequence

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.34 16434

plpy.execute expected a query or a plan

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.35 16435

plpy.execute takes a sequence as its second argument

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.36 16436

unrecognized error in PLy_spi_execute_fetch_result

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.37 16437

this subtransaction has already been entered

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.38 16438

this subtransaction has already been exited

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.39 16439

this subtransaction has not been entered

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.40 16440

there is no subtransaction to exit from

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.41 16441

could not create new dictionary

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.42 16442

could not create new Python list

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.43 16443

could not create bytes representation of Python object

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.44 16444

could not create string representation of Python object

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.45 16445

return value of function with array return type is not a Python sequence

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.46 16446

could not extract bytes from encoded string

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.47 16447

The name: @1@ is invalid.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.48 16448

";" is not permitted in COBOL

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.49 16449

"END-EXEC" is not permitted in C

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.50 16450

missing "EXEC SQL ENDIF END-EXEC."

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.51 16451

debug line with EXEC SQL is not permitted

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.52 16452

SQL string literal cannot continue multiline by COBOL syntax

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.53 16453

COBOL string literal cannot continue multiline by SQL syntax

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.54 16454

syntax error at or near "END-EXEC" in declare section

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.55 16455

syntax error in include file

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.56 16456

internal error: unreachable state;

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.57 16457

could not open temporary file "@1@" for continue line

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.58 16458

FILLER or implicit FILLER is not available in EXEC SQL TYPE statement

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.59 16459

VALUE clause is not available in EXEC SQL TYPE statement

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.60 16460

REDEFINES clause is not available in EXEC SQL TYPE statement

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.61 16461

FILLER or implicit FILLER is not available in EXEC SQL VAR statement

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.62 16462

VALUE clause is not available in EXEC SQL VAR statement

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.63 16463

syntax error in WHENEVER statement

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.64 16464

FILLER or implicit FILLER is not available in TYPEDEF statement

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.65 16465

VALUE clause is not available in TYPEDEF statement

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.66 16466

REDEFINES clause is not available in TYPEDEF statement

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.67 16467

FILLER or implicit FILLER can use only for elementary item in group item

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.68 16468

USAGE clause is not available for group item name

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.69 16469

SIGN clause is not available for group item name

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.70 16470

VALUE clause is not available for group item name

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.71 16471

more than one USAGE clause

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.72 16472

more than one OCCURS clause

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.73 16473

more than one VALUE clause

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.74 16474

more than one SIGN clause

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.75 16475

more than one REDEFINES clause

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.76 16476

syntax error at or near "@1@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.77 16477

length of varchar type is not assigned

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.78 16478

invalid NULL is set

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.61.79 16479

you can not be set to more than 1024 bytes of the string

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.61.80 16480

group item is too deep

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.81 16481

multidimensional array is not supported

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.82 16482

syntax is not available

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.83 16483

there is a character code that can not be determined

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.84 16484

the number of variables reached the max number 1000000

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.85 16485

host array variable is needed when using FOR ARRAY_SIZE

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.86 16486

unsupported datatype found at FOR statement

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.87 16487

FOR value should be positive integer

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.88 16488

SELECT..INTO returns too many rows on line @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.89 16489

not prepared for charset_conv_convert

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

This messages is output in the case of HA Database Ready.

Contact Fujitsu technical support.

2.61.90 16490

iconv failed (@1@)

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

This messages is output in the case of HA Database Ready.

Contact Fujitsu technical support.

2.61.91 16491

@1@ failed

[Description]

Aborted the processing of this operation because an error occurred.

[System Processing]

Processing will be aborted.

[Action]

Identify the cause according to the messages shown before this message, and then work around if necessary.

2.61.92 16492

CREATE TRIGGER will create implicit function "@1@"."@2@"() for TRIGGER "@3@" on TABLE "@4@"

[Description]

Terminated normally.

[System Processing]

Continues processing.

[Action]

No action required.

2.61.93 16493

The cursor is invalid on line @1@

[Description]

An error occurred during execution of the command.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.61.94 16494

Constraint trigger "@1@" for relation "@2@" cannot be replaced with non-constraint trigger

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.61.95 16495

Trigger "@1@" for relation "@2@" cannot be replaced with constraint trigger

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.61.96 16496

invalid value for targetserver: "@1@"

[Description]

value of targetserver is invalid.

[System Processing]

Processing is aborted.

[Action]

Set one of the following:

- primary
- standby
- prefer_standby
- any(can be specified only JDBC)

2.61.97 16497

unterminated /*+ comment for hint of pg_hint_plan

[Description]

An unterminated /*+ comment for hint of pg_hint_plan is detected.

[System Processing]

Processing will be aborted.

[Action]

Terminate /*+ comment for hint of pg_hint_plan.

2.61.98 16498

trigger created with EXECUTE PROCEDURE cannot be replaced by DO block

[Description]

Trigger created with EXECUTE PROCEDURE cannot be replaced by DO block.

[System Processing]

Processing is aborted.

[Action]

Please redefine it after deleting the trigger.

2.61.99 16499

trigger created with DO block cannot be replaced by EXECUTE PROCEDURE

[Description]

Trigger created with DO block cannot be replaced by EXECUTE PROCEDURE.

[System Processing]

Processing is aborted.

[Action]

Please redefine it after deleting the trigger.

2.62 Message Numbers Beginning with 16500

2.62.1 16500

the connection is not the same as the connection in DECLARE STATEMENT, on line @1@

[Description]

The connection is not the same as the connection in DECLARE STATEMENT, on line @1@

[System Processing]

Processing is aborted.

[Action]

Please do not specify the connection when you use SQL statement identifier declared with DECLARE STATEMENT.

2.62.2 16501

cannot copy window "@1@" because it has a frame clause

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.62.3 16502

could not find any WAL files

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.62.4 16503

exceeded maxAllocatedDescs (@1@) while trying to open file "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.62.5 16504

exceeded maxAllocatedDescs (@1@) while trying to open directory "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.62.6 16505

tsquery is too large

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.62.7 16506

bit string length exceeds the maximum allowed (@1@)

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.62.8 16507

error occurred at @1 @: @2@ before error message processing is available

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.62.9 16508

language validation function @1 @ called for language @2@ instead of @3@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.62.10 16509

could not acquire mutex: @1 @

[Description]

The database server was disconnected during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Communication may have been disconnected for the following reasons:

- An error occurred in the communication line (TCP/IP etc.)
- The database server terminated abnormally.

Take the following actions:

- Eliminate the cause of the communication disconnection.

Examine the application and check whether the transaction for implementing update is a long transaction. Judge whether it is a long transaction from the following viewpoints and modify the application.

- a) If the COMMIT process is not executed after update, add the COMMIT process.
- b) If the total number of update records in a single transaction is high, split it into short transactions.
- c) If search was conducted for a long period of time after update, execute COMMIT after update or review the search

SQL statement.

- If none of the above situations applies, perform the following:

- a) Confirm that the database server has not stopped.
- b) If the database server is starting or stopping, re-execute the command after the database server starts.

2.62.11 16510

The sslservercertcn "@1@" could not be verified

[Description]

value of sslservercertcn is different from common name in the server certificate.

[System Processing]

Processing is aborted.

[Action]

Set SSL certificate's common name to sslservercertcn.

2.62.12 16511

@1@: must be superuser to run this command

[Description]

Must be superuser to run this command.

[System Processing]

Processing will be aborted.

[Action]

Re-execute the command by the superuser.

2.62.13 16512

@1@: must be database super user to run this command

[Description]

Must be database super user to run this command.

[System Processing]

Processing will be aborted.

[Action]

Re-execute the command by the database super user.

2.62.14 16513

@1@: no subcommand specified

[Description]

No subcommand specified.

[System Processing]

Processing will be aborted.

[Action]

Check the command-line, and re-execute the command with correct options or operands.

2.62.15 16514

@1 @: unrecognized subcommand "@2@"

[Description]

Unknown subcommand is specified.

[System Processing]

Processing will be aborted.

[Action]

Check the command-line, and re-execute the command with correct subcommand.

2.62.16 16515

@1 @: too many command-line arguments (first is "@2@")

[Description]

Too many command-line arguments.

[System Processing]

Processing will be aborted.

[Action]

Check the command-line, and re-execute the command with correct options or operands.

2.62.17 16516

@1 @: argument to an option "@2@" must be a list of port numbers

[Description]

Argument to the option must be a list of port numbers.

[System Processing]

Processing will be aborted.

[Action]

Specify multiple port number, separated by commas argument to an option, and re-execute the command. Specify a number from 1024 to 32767 for the port number.

2.62.18 16517

@1 @: invalid argument for an option "@2@"

[Description]

Invalid argument for an option.

[System Processing]

Processing will be aborted.

[Action]

Check the options specified in command-line, and re-execute the command with correct operands.

2.62.19 16518

@1 @: option "@2@" is required

[Description]

The indispensable option is not specified.

[System Processing]

Processing will be aborted.

[Action]

Check the command-line, and re-execute the command with correct options or confirm the indispensable option is being used correctly.

2.62.20 16519

@1 @: requires an option "@2@" or setting the "@3@" environment variable

[Description]

Requires an option or setting the environment variable.

[System Processing]

Processing will be aborted.

[Action]

Check the command-line, and re-execute the command with correct options. Or, set a correct value to the environment variable, and re-execute the command.

2.62.21 16520

@1 @: successfully completed

[Description]

Command successfully completed.

[System Processing]

Continues processing.

[Action]

No action required.

2.62.22 16521

@1 @: user "@2@" does not exist

[Description]

The user is not registered into OS.

[System Processing]

Processing will be aborted.

[Action]

Register the user into OS, and re-execute the command. Or, re-execute the command which specified the registered user.

2.62.23 16522

@1@: data directory "@2@" does not exist

[Description]

The data directory does not exist.

[System Processing]

Processing will be aborted.

[Action]

Confirm that an option "--cluster-standbynode" is being used correctly. Or, check the command-line, and re-execute the command with existing data directory.

2.62.24 16523

@1@: "@2@" is not a valid data directory

[Description]

The data directory is not valid.

[System Processing]

Processing will be aborted.

[Action]

Check the command-line, and re-execute the command with valid data directory.

2.62.25 16524

@1@: database cluster is not stopped

[Description]

Database cluster is not stopped.

[System Processing]

Processing will be aborted.

[Action]

Stop the database cluster, and re-execute the command.

2.62.26 16525

@1@: domain root "@2@" already exists

[Description]

The domain root already exists.

[System Processing]

Processing will be aborted.

[Action]

Check the command-line, and re-execute the command with correct domain root.

2.62.27 16526

@1@: could not create directory "@2@"

[Description]

Could not create the directory.

[System Processing]

Processing will be aborted.

[Action]

Check the following and eliminate the cause of errors, and re-execute the command.

- the state of a disk and file system to creating the directory
- permission of the upper directory of specified directory

2.62.28 16527

@1@: start of PL/extJava has timed out : @2@

[Description]

Timed out waiting for start of PL/extJava.

[System Processing]

Processing will be aborted.

[Action]

Re-execute the command after the load on the system has decreased.

2.62.29 16528

@1@: stop of PL/extJava has timed out : @2@

[Description]

Timed out waiting for stop of PL/extJava.

[System Processing]

Processing will be aborted.

[Action]

Re-execute the command after the load on the system has decreased.

2.62.30 16529

@1@: port number "@2@" is already in use

[Description]

The port number is already in use.

[System Processing]

Processing will be aborted.

[Action]

Re-execute the command with a port number which is not used in other processes.

2.62.31 16530

@1 @: domain name can only be specified "domain1"

[Description]

Domain name can only be specified "domain1".

[System Processing]

Processing will be aborted.

[Action]

Check the command-line, and re-execute the command with correct domain name.

2.62.32 16531

@1 @: domain "@2@" has already been created

[Description]

The domain has already been created.

[System Processing]

Processing will be aborted.

[Action]

Check the command-line, and re-execute the command with correct domain name.

2.62.33 16532

@1 @: domain "@2@" has not been created

[Description]

The domain has not been created.

[System Processing]

Processing will be aborted.

[Action]

Check the command-line, and re-execute the command with correct domain name.

2.62.34 16533

@1 @: permission denied to update file "@2@"

[Description]

Permission denied to update the file.

[System Processing]

Processing will be aborted.

[Action]

Permit writing to the file by execution user, and re-execute the command.

2.62.35 16534

@1@: container for database "@2@" does not exist

[Description]

Container for database does not exist.

[System Processing]

Processing will be aborted.

[Action]

Check the command-line, and re-execute the command with correct database name.

2.62.36 16535

@1@: container for database "@2@" already exists

[Description]

Container for database already exists.

[System Processing]

Processing will be aborted.

[Action]

Check the command-line, and re-execute the command with correct database name.

2.62.37 16536

@1@: command error occurred

[Description]

Internal command error occurred.

[System Processing]

Processing will be aborted.

[Action]

Fix the problem by referring to the messages prior to this one.

2.62.38 16537

@1@: the domain was not able to be deleted because there was a container

[Description]

The domain was not able to be deleted because the domain have a container.

[System Processing]

Processing will be aborted.

[Action]

Delete all containers on the domain, and re-execute the command. Or, re-execute the command with "--force" option.

2.62.39 16538

@1@: could not access the data directory

[Description]

Could not access the data directory.

[System Processing]

Processing will be aborted.

[Action]

Confirm that an option "--cluster-standbynode" is being used correctly. Or, specify database super user in "--dbadminuser" option and re-execute the command.

2.62.40 16539

@1@: server instance "@2@" does not exist

[Description]

Server instance does not exist.

[System Processing]

Processing will be aborted.

[Action]

Check the command-line, and re-execute the command with correct server instance.

2.62.41 16540

@1@: specified database name "@2@" does not follow the naming rules

[Description]

Specified database name does not follow the naming rules.

[System Processing]

Processing will be aborted.

[Action]

Check the command-line, and re-execute the command with correct database name.

2.62.42 16541

@1@: all the server instances of the container cannot be deleted

[Description]

All the server instances of the container cannot be deleted.

[System Processing]

Processing will be aborted.

[Action]

Check the command-line, and re-execute the command with correct database name.

2.62.43 16542

@1@: the mount does the shared-file system of the domain root or the data directory

[Description]

A command executing node is not a standby node.

[System Processing]

Processing will be aborted.

[Action]

Execute the command on standby node.

2.62.44 16543

@1@: cannot execute this subcommand on standby node

[Description]

Cannot execute this subcommand on standby node.

[System Processing]

Processing will be aborted.

[Action]

Execute the command on primary node.

2.62.45 16544

@1@: cannot execute this command concurrently

[Description]

Cannot execute this command concurrently.

[System Processing]

Processing will be aborted.

[Action]

Re-execute the command after a command executing was finished.

2.62.46 16545

@1@: domain root "@2@" does not exist

[Description]

Domain root does not exist.

[System Processing]

Processing will be aborted.

[Action]

Confirm that the shared-file system of the domain root is mounted. Or, restore domain root from backup and re-execute the command.

2.62.47 16546

parameter "@1@" necessary for the PL/extJava environment was not set

[Description]

PL/extJava environment was not set.

[System Processing]

Processing will be aborted.

[Action]

Set the PL/extJava environment.

2.62.48 16547

[mismatched parentheses](#)

[Description]

Missing parenthesis '(' or ')' in Java function definition.

[System Processing]

Processing will be aborted.

[Action]

Check the definition of Java function.

2.62.49 16548

[invalid format specification for Java function](#)

[Description]

Invalid format specification for Java function.

[System Processing]

Processing will be aborted.

[Action]

Check the definition of Java function.

Java function definition format is [package].[class].[method].

2.62.50 16549

[Java function cannot return type @1@](#)

[Description]

The specified data type is not supported as Java function.

[System Processing]

Processing will be aborted.

[Action]

Check the data type of return value.

2.62.51 16550

[Java function cannot accept type @1@](#)

[Description]

The specified data type is not supported as Java function arguments.

[System Processing]

Processing will be aborted.

[Action]

Check the data type of arguments value.

2.62.52 16551

could not execute the Java function at the application server: HTTP status code @1 @ details: "@2@"

[Description]

The application server could not execute the Java function.

[System Processing]

Processing will be aborted.

[Action]

Check the Java function of registered in application server.

Check the details.

- The classpath is not found. (plextjava_lib_dir=%s2)

%s2: directory

The directory that stores the Java function is not in the application server. Check the directory and register the Java function.

- The return type is different. (%s3)

%s3: data type

The return value of the Java function is not corresponding to the CREATE FUNCTION definition. Check the data type of Java function.

- The method is not found. (%s4)

%s4: data type

The Java function to which the data type is corresponding is not found. Check the data type of Java function.

- The class is not found. (%s5)

%s5: class name

The Java function to which the class name is corresponding is not found. Check the class name of Java function.

- The method is not static modifier. (%s6)

%s6: Java function name

The Java function is not defined by "Static". Check the Java function definition.

here is no executed authority. (%s7)

%s7: Java function name

The Java function is not defined by "Public". Check the Java function definition.

- Java application throws exception(%s8).

%s8: exception

The exception was generated by the Java function. Check the Java function definition.

- no message

The following causes are thought.

-There is a possibility that the container is not made. Make the container in application server.

a) There is a possibility where the number of server instances is insufficient. Add server instance (JavaVM) to the application server.

b) There is a possibility that memory shortage occurs. Check the Java application.

c) There is a possibility that the time-out is generated. Check the Java application.

d) There is a possibility that abnormality occurs by the application server. Check the following logs.

- Event log (For Windows(R))/system log (For Linux).

- Server log of container

- JavaVM log of container

- Trace log of Web server

- Internal log of Web server

2.62.53 16552

could not connect to application server: @1@

[Description]

Could not connect to application server.

[System Processing]

Processing will be aborted.

[Action]

Check the plexjava.http_port parameter in postgresql.conf.

2.62.54 16553

could not create socket for application server connection: @1@

[Description]

Could not create socket.

[System Processing]

Processing will be aborted.

[Action]

There is possible where an open number of files that can be used with the system is insufficient. Please confirm the total of the file that can be used with the system.

2.62.55 16554

could not send data to application server: @1@

[Description]

The application server was disconnected during execution of the Java function.

[System Processing]

Processing will be aborted.

[Action]

Check the message of application server.

2.62.56 16555

could not receive data from application server

[Description]

The application server was disconnected during execution of the Java function.

[System Processing]

Processing will be aborted.

[Action]

Check the message of application server.

2.62.57 16556

could not receive data from application server: @1@

[Description]

The application server was disconnected during execution of the Java function.

[System Processing]

Processing will be aborted.

[Action]

Check the message of application server.

2.62.58 16557

could not execute PL/extJava start command

[Description]

An error occurred during executing the command specified by plextjava.start_command parameter in postgresql.conf.

[System Processing]

Processing will be aborted.

[Action]

Check the plextjava.start_command parameter in postgresql.conf.

2.62.59 16558

PL/extJava start command failed with exit code @1@

[Description]

An error occurred during executing the command specified by plextjava.start_command parameter in postgresql.conf.

[System Processing]

Processing will be aborted.

[Action]

Check the exit code and the messages that was output before this.

2.62.60 16559

could not execute PL/extJava stop command

[Description]

An error occurred during executing the command specified by plextjava.stop_command parameter in postgresql.conf.

[System Processing]

Processing will be aborted.

[Action]

Check the plextjava.stop_command parameter in postgresql.conf.

2.62.61 16560

PL/extJava stop command failed with exit code @1@

[Description]

An error occurred during executing the command specified by plextjava.stop_command parameter in postgresql.conf.

[System Processing]

Processing will be aborted.

[Action]

Check the exit code and the messages that was output before this.

2.62.62 16561

could not execute PL/extJava forcible stop command

[Description]

An error occurred during executing the command specified by plextjava.forcible_stop_command parameter in postgresql.conf.

[System Processing]

Processing will be aborted.

[Action]

Check the plextjava.forcible_stop_command parameter in postgresql.conf.

2.62.63 16562

PL/extJava forcible stop command failed with exit code @1@

[Description]

An error occurred during executing the command specified by plextjava.forcible_stop_command parameter in postgresql.conf.

[System Processing]

Processing will be aborted.

[Action]

Check the exit code and the messages that was output before this.

2.62.64 16563

@1@: at least one option of "@2@" must be specified

[Description]

Must specify at least one option.

[System Processing]

Processing will be aborted.

[Action]

Check the command-line, and re-execute the command with correct options.

2.62.65 16574

@1@: could not write directory "@2@"

[Description]

Could not write the directory.

[System Processing]

Processing will be aborted.

[Action]

Check that the disk of the directory has free space, and check that the abnormalities of the disk have not occurred.

2.62.66 16575

@1@: cannot execute with "@2@" option in primary server

[Description]

Do not specify the option to execute the command in primary server.

[System Processing]

Processing will be aborted.

[Action]

Check the command-line, and re-execute the command with correct options.

Restore it because PL/extJava environment may be corrupted when the server is member nodes of the cluster.

2.62.67 16576

@1@: specify "@2@" option in standby server

[Description]

Specify the option to execute the command in standby server.

[System Processing]

Processing will be aborted.

[Action]

Check the command-line, and re-execute the command with correct options.

Restore it because PL/extJava environment may be corrupted when the server is member nodes of the cluster.

2.63 Message Numbers Beginning with 20000

2.63.1 20000

[listagg_transfn called in non-aggregate context](#)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.2 20001

[feature not supported](#)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.3 20002

[median4_transfn called in non-aggregate context](#)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.4 20003

[lock request error](#)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.5 20004

event registration error

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.6 20005

event name is NULL

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.7 20006

feature not supported

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.8 20007

not called by trigger manager

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.9 20008

not called on valid event**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.10 20009

SPI_connect failed**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.11 20010

not called with valid relation**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.12 20011

attribute event not found**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.13 20012

attribute message not found

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.14 20013

SPI_prepare failed

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.15 20014

can't execute sql

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.16 20015

SPI execute error

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.17 20016

invalid value for @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.18 20017

date out of range

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.19 20018

timestamp out of range

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.20 20019

invalid cursor number

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.21 20020

failed to execute SQL statement

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.22 20021

SQL is empty string

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.23 20022

host variable name "@1@" is too long

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.24 20023

host variable name is NULL

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.25 20024

no statement parsed

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.26 20025

host variable does not exist

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.27 20026

invalid length for host variable name

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.28 20027

invalid length for variable character string

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.29 20028

not all variables bound

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.30 20029

no statement execute**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.31 20030

not supported data type**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.32 20031

mismatch column_value data type and define_column data type**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.33 20032

mismatch select data type and define_column data type**[Description]**

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.34 20033

@1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.35 20034

invalid parameter

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.36 20035

null value not allowed

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.37 20036

invalid encoding name "@1@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.38 20037

program limit exceeded

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.39 20038

no data found

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.40 20039

SPI_prepare_failed

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.41 20040

start_line must be positive (@1@ passed)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.42 20041

end_line must be positive (@1@ passed)

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.43 20042

return type must be a row type

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.44 20043

failed to retrieve the default LC_COLLATE value

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.45 20044

failed to set the requested LC_COLLATE value [@1 @]

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.46 20045

failed to set back the default LC_COLLATE value [@1 @]

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.47 20046

unknown format

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.48 20047

function is called from invalid context

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.49 20048

argument is NULL

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.50 20049

out of memory

[Description]

There was insufficient free space in the server's memory during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Estimate memory usage and take the following action:

- If the number of simultaneous connections from client applications is high, reduce it.
- If the number of simultaneous SQL executions is high, reduce it.

2.63.51 20050

insufficient privilege

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.52 20051

datatype mismatch

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.53 20052

unexpected type: @1@

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.54 20053

pipe name is NULL

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.55 20054

pipe creation error

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.56 20055

message is NULL

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.57 20056

could not determine data type of input

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.58 20057

unknown equal operand for datatype

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.59 20058

cannot set range to negative number

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.60 20059

date is out of range

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.61 20060

nonbizday registration error

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.62 20061

nonbizday unregistration error

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.63 20062

plvlex.tokens is not available in the built

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.64 20063

too few parameters specified for template string

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.65 20064

substitution is NULL

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.66 20065

buffer overflow

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.67 20066

internal error

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.68 20067

Limit decreased to @1@ bytes.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.69 20068

Limit increased to @1@ bytes.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.70 20069

unknown option '@1@'

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.71 20070

too much large memory block request

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.72 20071

corrupted pointer

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.73 20072

unsafe use of string constant with Unicode escapes

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.74 20073

invalid Unicode escape

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.75 20074

unsafe use of \\' in a string literal

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.76 20075

@1@ at end of input

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.77 20076

@1@ at or near "@2@"

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.78 20077

dbms_yylex_init() failed: @1@.

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.79 20078

invalid hexadecimal digit

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.80 20079

nonstandard use of \\' in a string literal

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.81 20080

nonstandard use of \\ in a string literal

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.63.82 20081

nonstandard use of escape in a string literal

[Description]

An error occurred.

[System Processing]

Processing will be aborted.

[Action]

To investigate the cause of the occurrence from the message, and remove cause.

2.64 Message Numbers Beginning with 70000

2.64.1 70001

Error loading default settings from driverconfig.properties

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.64.2 70002

Your security policy has prevented the connection from being attempted. You probably need to grant the connect java.net.SocketPermission to the database server host and port that you wish to connect to.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.3 70003

Something unusual has occurred to cause the driver to fail. Please report this exception.

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.64.4 70004

Connection attempt timed out.

[Description]

Timeout occurred during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Check the following:

- If executing SQL that outputs a large volume of search results, add a conditional expression to filter the results further.
- If numerous SQLs are being simultaneously executed, reduce the number of simultaneously executed SQLs.
- If a large volume of data is to be updated in a single transaction, modify the SQL to reduce the volume of data to be updated in a single transaction.
- If executing a complex SQL, modify it to a simple SQL.
- Check if there are any problems in the network.
- Before conducting maintenance that involves the processing of a large volume of data, use the SET statement to temporarily increase the value of maintenance_work_mem.

2.64.5 70005

Interrupted while attempting to connect.

[Description]

The database server was disconnected during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Communication may have been disconnected for the following reasons:

- An error occurred in the communication line (TCP/IP etc.)
- The database server terminated abnormally.

Take the following actions:

- Eliminate the cause of the communication disconnection.

Examine the application and check whether the transaction for implementing update is a long transaction. Judge whether it is a long transaction from the following viewpoints and modify the application.

- a) If the COMMIT process is not executed after update, add the COMMIT process.
 - b) If the total number of update records in a single transaction is high, split it into short transactions.
 - c) If search was conducted for a long period of time after update, execute COMMIT after update or review the search SQL statement.
- If none of the above situations applies, perform the following:
- a) Confirm that the database server has not stopped.
 - b) If the database server is starting or stopping, re-execute the command after the database server starts.

2.64.6 70006

Method @1@ is not yet implemented.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.7 70007

Requested CopyIn but got @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.8 70008

Requested CopyOut but got @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.9 70009

Copying from database failed: @1@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.64.10 70010

This copy stream is closed.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.11 70011

Read from copy failed.

[Description]

The database server was disconnected during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Communication may have been disconnected for the following reasons:

- An error occurred in the communication line (TCP/IP etc.)
- The database server terminated abnormally.

Take the following actions:

- Eliminate the cause of the communication disconnection.

Examine the application and check whether the transaction for implementing update is a long transaction. Judge whether it is a long transaction from the following viewpoints and modify the application.

- a) If the COMMIT process is not executed after update, add the COMMIT process.
 - b) If the total number of update records in a single transaction is high, split it into short transactions.
 - c) If search was conducted for a long period of time after update, execute COMMIT after update or review the search SQL statement.
- If none of the above situations applies, perform the following:
- a) Confirm that the database server has not stopped.
 - b) If the database server is starting or stopping, re-execute the command after the database server starts.

2.64.12 70012

Cannot write to copy a byte of value @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.13 70013

A connection could not be made using the requested protocol @1@.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.14 70014

Premature end of input stream, expected @1@ bytes, but only read @2@.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.15 70015

Expected an EOF from server, got: @1@

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.64.16 70016

An unexpected result was returned by a query.

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.64.17 70017

Illegal UTF-8 sequence: byte @1@ of @2@ byte sequence is not 10xxxxxx: @3@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.18 70018

Illegal UTF-8 sequence: @1@ bytes used to encode a @2@ byte value: @3@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.19 70019

Illegal UTF-8 sequence: initial byte is @1@: @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.20 70020

Illegal UTF-8 sequence: final value is out of range: @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.21 70021

Illegal UTF-8 sequence: final value is a surrogate value: @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.22 70022

Zero bytes may not occur in string parameters.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.23 70023

Zero bytes may not occur in identifiers.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.24 70024

Cannot convert an instance of @1@ to type @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.25 70025

Connection refused. Check that the hostname and port are correct and that the postmaster is accepting TCP/IP connections.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.26 70026

The connection attempt failed.

[Description]

The database server was disconnected during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Communication may have been disconnected for the following reasons:

- An error occurred in the communication line (TCP/IP etc.)
- The database server terminated abnormally.

Take the following actions:

- Eliminate the cause of the communication disconnection.

Examine the application and check whether the transaction for implementing update is a long transaction. Judge whether it is a long transaction from the following viewpoints and modify the application.

- a) If the COMMIT process is not executed after update, add the COMMIT process.
- b) If the total number of update records in a single transaction is high, split it into short transactions.

c) If search was conducted for a long period of time after update, execute COMMIT after update or review the search SQL statement.

- If none of the above situations applies, perform the following:

a) Confirm that the database server has not stopped.

b) If the database server is starting or stopping, re-execute the command after the database server starts.

2.64.27 70027

The server does not support SSL.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.28 70028

An error occurred while setting up the SSL connection.

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.64.29 70029

Connection rejected: @1@.

[Description]

The database server was disconnected during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Communication may have been disconnected for the following reasons:

- An error occurred in the communication line (TCP/IP etc.)
- The database server terminated abnormally.

Take the following actions:

- Eliminate the cause of the communication disconnection.

Examine the application and check whether the transaction for implementing update is a long transaction. Judge whether it is a long transaction from the following viewpoints and modify the application.

- a) If the COMMIT process is not executed after update, add the COMMIT process.

- b) If the total number of update records in a single transaction is high, split it into short transactions.
 - c) If search was conducted for a long period of time after update, execute COMMIT after update or review the search SQL statement.
- If none of the above situations applies, perform the following:
- a) Confirm that the database server has not stopped.
 - b) If the database server is starting or stopping, re-execute the command after the database server starts.

2.64.30 70030

The server requested password-based authentication, but no password was provided.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.31 70031

The authentication type @1@ is not supported. Check that you have configured the pg_hba.conf file to include the client's IP address or subnet, and that it is using an authentication scheme supported by the driver.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.32 70032

Protocol error. Session setup failed.

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.64.33 70033

Backend start-up failed: @1@.

[Description]

The database server was disconnected during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Communication may have been disconnected for the following reasons:

- An error occurred in the communication line (TCP/IP etc.)
- The database server terminated abnormally.

Take the following actions:

- Eliminate the cause of the communication disconnection.

Examine the application and check whether the transaction for implementing update is a long transaction. Judge whether it is a long transaction from the following viewpoints and modify the application.

- a) If the COMMIT process is not executed after update, add the COMMIT process.
 - b) If the total number of update records in a single transaction is high, split it into short transactions.
 - c) If search was conducted for a long period of time after update, execute COMMIT after update or review the search SQL statement.
- If none of the above situations applies, perform the following:
 - a) Confirm that the database server has not stopped.
 - b) If the database server is starting or stopping, re-execute the command after the database server starts.

2.64.34 70034

The column index is out of range: @1 @, number of columns: @2 @.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.35 70035

No value specified for parameter @1 @.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.36 70036

Expected command status BEGIN, got @1@.

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.64.37 70037

Unexpected command status: @1@.

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.64.38 70038

An I/O error occurred while sending to the backend.

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.64.39 70039

Unknown Response Type @1@.

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.64.40 70040

Ran out of memory retrieving query results.

[Description]

There was insufficient free space in the server's memory during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Estimate memory usage and take the following action:

- If the number of simultaneous connections from client applications is high, reduce it.
- If the number of simultaneous SQL executions is high, reduce it.

2.64.41 70041

Unable to interpret the update count in command completion tag: @1@.

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.64.42 70042

Copy not implemented for protocol version 2

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.43 70043

SSPI authentication is not supported because it is not portable. Try configuring the server to use GSSAPI instead.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.44 70044

CommandComplete expected COPY but got:

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.64.45 70045

Tried to obtain lock while already holding it

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.46 70046

Tried to break lock on database connection

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.47 70047

Interrupted while waiting to obtain lock on database connection

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.48 70048

Unable to bind parameter values for statement.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.49 70049

Database connection failed when starting copy

[Description]

The database server was disconnected during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Communication may have been disconnected for the following reasons:

- An error occurred in the communication line (TCP/IP etc.)
- The database server terminated abnormally.

Take the following actions:

- Eliminate the cause of the communication disconnection.

Examine the application and check whether the transaction for implementing update is a long transaction. Judge whether it is a long transaction from the following viewpoints and modify the application.

- a) If the COMMIT process is not executed after update, add the COMMIT process.
 - b) If the total number of update records in a single transaction is high, split it into short transactions.
 - c) If search was conducted for a long period of time after update, execute COMMIT after update or review the search SQL statement.
- If none of the above situations applies, perform the following:
- a) Confirm that the database server has not stopped.
 - b) If the database server is starting or stopping, re-execute the command after the database server starts.

2.64.50 70050

Tried to cancel an inactive copy operation

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.51 70051

Database connection failed when canceling copy operation

[Description]

The database server was disconnected during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Communication may have been disconnected for the following reasons:

- An error occurred in the communication line (TCP/IP etc.)
- The database server terminated abnormally.

Take the following actions:

- Eliminate the cause of the communication disconnection.

Examine the application and check whether the transaction for implementing update is a long transaction. Judge whether it is a long transaction from the following viewpoints and modify the application.

- a) If the COMMIT process is not executed after update, add the COMMIT process.
 - b) If the total number of update records in a single transaction is high, split it into short transactions.
 - c) If search was conducted for a long period of time after update, execute COMMIT after update or review the search SQL statement.
- If none of the above situations applies, perform the following:
 - a) Confirm that the database server has not stopped.
 - b) If the database server is starting or stopping, re-execute the command after the database server starts.

2.64.52 70052

Missing expected error response to copy cancel request

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.64.53 70053

Got @!@ error responses to single copy cancel request

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.64.54 70054

Tried to end inactive copy

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.55 70055

Database connection failed when ending copy

[Description]

The database server was disconnected during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Communication may have been disconnected for the following reasons:

- An error occurred in the communication line (TCP/IP etc.)
- The database server terminated abnormally.

Take the following actions:

- Eliminate the cause of the communication disconnection.

Examine the application and check whether the transaction for implementing update is a long transaction. Judge whether it is a long transaction from the following viewpoints and modify the application.

- a) If the COMMIT process is not executed after update, add the COMMIT process.
 - b) If the total number of update records in a single transaction is high, split it into short transactions.
 - c) If search was conducted for a long period of time after update, execute COMMIT after update or review the search SQL statement.
- If none of the above situations applies, perform the following:
 - a) Confirm that the database server has not stopped.
 - b) If the database server is starting or stopping, re-execute the command after the database server starts.

2.64.56 70056

Tried to write to an inactive copy operation

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.57 70057

Database connection failed when writing to copy

[Description]

The database server was disconnected during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Communication may have been disconnected for the following reasons:

- An error occurred in the communication line (TCP/IP etc.)
- The database server terminated abnormally.

Take the following actions:

- Eliminate the cause of the communication disconnection.

Examine the application and check whether the transaction for implementing update is a long transaction. Judge whether it is a long transaction from the following viewpoints and modify the application.

- a) If the COMMIT process is not executed after update, add the COMMIT process.
 - b) If the total number of update records in a single transaction is high, split it into short transactions.
 - c) If search was conducted for a long period of time after update, execute COMMIT after update or review the search SQL statement.
- If none of the above situations applies, perform the following:
 - a) Confirm that the database server has not stopped.
 - b) If the database server is starting or stopping, re-execute the command after the database server starts.

2.64.58 70058

Tried to read from inactive copy

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.59 70059

Database connection failed when reading from copy

[Description]

The database server was disconnected during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Communication may have been disconnected for the following reasons:

- An error occurred in the communication line (TCP/IP etc.)
- The database server terminated abnormally.

Take the following actions:

- Eliminate the cause of the communication disconnection.

Examine the application and check whether the transaction for implementing update is a long transaction. Judge whether it is a long transaction from the following viewpoints and modify the application.

- a) If the COMMIT process is not executed after update, add the COMMIT process.
 - b) If the total number of update records in a single transaction is high, split it into short transactions.
 - c) If search was conducted for a long period of time after update, execute COMMIT after update or review the search SQL statement.
- If none of the above situations applies, perform the following:
 - a) Confirm that the database server has not stopped.
 - b) If the database server is starting or stopping, re-execute the command after the database server starts.

2.64.60 70060

Received CommandComplete "@1@" without an active copy operation

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.61 70061

Got CopyInResponse from server during an active @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.62 70062

Got CopyOutResponse from server during an active @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.63 70063

Got CopyData without an active copy operation

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.64 70064

Unexpected copydata from server for @1@

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.64.65 70065

Unexpected packet type during copy: @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.66 70066

Bind message length @1@ too long. This can be caused by very large or incorrect length specifications on InputStream parameters.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.67 70067

The server's client_encoding parameter was changed to @1@. The JDBC driver requires client_encoding to be UTF8 for correct operation.

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.64.68 70068

The server's DateStyle parameter was changed to @1@. The JDBC driver requires DateStyle to begin with ISO for correct operation.

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.64.69 70069

The server's standard_conforming_strings parameter was reported as @1@. The JDBC driver expected on or off.

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.64.70 70070

The driver currently does not support COPY operations.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.71 70071

This PooledConnection has already been closed.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.72 70072

Connection has been closed automatically because a new connection was opened for the same PooledConnection or the PooledConnection has been closed.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.73 70073

Connection has been closed.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.74 70074

Statement has been closed.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.75 70075

Failed to setup DataSource.

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.64.76 70076

DataSource has been closed.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.77 70077

Fastpath call @1@ - No result was returned and we expected an integer.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.78 70078

The fastpath function @1@ is unknown.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.79 70079

Conversion to type @1@ failed: @2@.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.80 70080

Cannot tell if path is open or closed: @1@.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.81 70081

GSS Authentication failed

[Description]

The database server was disconnected during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Communication may have been disconnected for the following reasons:

- An error occurred in the communication line (TCP/IP etc.)
- The database server terminated abnormally.

Take the following actions:

- Eliminate the cause of the communication disconnection.

Examine the application and check whether the transaction for implementing update is a long transaction. Judge whether it is a long transaction from the following viewpoints and modify the application.

- a) If the COMMIT process is not executed after update, add the COMMIT process.

- b) If the total number of update records in a single transaction is high, split it into short transactions.
 - c) If search was conducted for a long period of time after update, execute COMMIT after update or review the search SQL statement.
- If none of the above situations applies, perform the following:
- a) Confirm that the database server has not stopped.
 - b) If the database server is starting or stopping, re-execute the command after the database server starts.

2.64.82 70082

The array index is out of range: @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.83 70083

The array index is out of range: @1@, number of elements: @2@.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.84 70084

Truncation of large objects is only implemented in 8.3 and later servers.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.85 70085

Cannot truncate LOB to a negative length.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.86 70086

PostgreSQL LOBs can only index to: @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.87 70087

LOB positioning offsets start at 1.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.88 70088

free() was called on this LOB previously

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.89 70089

Unsupported value for stringtype parameter: @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.90 70090

unknownLength parameter value must be an integer

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.91 70091

No results were returned by the query.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.92 70092

A result was returned when none was expected.

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.64.93 70093

Custom type maps are not supported.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.94 70094

Failed to create object for: @1@.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.95 70095

Unable to load the class @1@ responsible for the datatype @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.96 70096

Cannot change transaction read-only property in the middle of a transaction.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.97 70097

Cannot commit when autoCommit is enabled.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.98 70098

This connection has been closed.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.64.99 70099

Cannot rollback when autoCommit is enabled.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65 Message Numbers Beginning with 70100

2.65.1 70100

Cannot change transaction isolation level in the middle of a transaction.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.2 70101

Transaction isolation level @1@ not supported.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.3 70102

Unable to translate data into the desired encoding.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.4 70103

Unable to determine a value for MaxIndexKeys due to missing system catalog data.

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.65.5 70104

Unable to find name datatype in the system catalogs.

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.65.6 70105

Operation requires a scrollable ResultSet, but this ResultSet is FORWARD_ONLY.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.7 70106

Unexpected error while decoding character data from a large object.

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.65.8 70107

Can't use relative move methods while on the insert row.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.9 70108

Invalid fetch direction constant: @1@.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.10 70109

Cannot call cancelRowUpdates() when on the insert row.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.11 70110

Cannot call deleteRow() when on the insert row.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.12 70111

Currently positioned before the start of the ResultSet. You cannot call deleteRow() here.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.13 70112

Currently positioned after the end of the ResultSet. You cannot call deleteRow() here.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.14 70113

There are no rows in this ResultSet.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.15 70114

Not on the insert row.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.16 70115

You must specify at least one column value to insert a row.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.17 70116

The JVM claims not to support the encoding: @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.18 70117

Provided InputStream failed.

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.65.19 70118

Provided Reader failed.

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.65.20 70119

Can't refresh the insert row.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.21 70120

Cannot call updateRow() when on the insert row.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.22 70121

Cannot update the ResultSet because it is either before the start or after the end of the results.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.23 70122

ResultSets with concurrency CONCUR_READ_ONLY cannot be updated.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.24 70123

No primary key found for table @1@.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.25 70124

Fetch size must be a value greater to or equal to 0.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.26 70125

Invalid character data was found. This is most likely caused by stored data containing characters that are invalid for the character set the database was created in. The most common example of this is storing 8bit data in a SQL_ASCII database.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.27 70126

Bad value for type @1@ : @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.28 70127

The column name @1@ was not found in this ResultSet.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.29 70128

ResultSet is not updateable. The query that generated this result set must select only one table, and must select all primary keys from that table. See the JDBC 2.1 API Specification, section 5.6 for more details.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.30 70129

This ResultSet is closed.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.31 70130

ResultSet not positioned properly, perhaps you need to call next.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.32 70131

Can't use query methods that take a query string on a PreparedStatement.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.33 70132

Multiple ResultSets were returned by the query.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.34 70133

A CallableStatement was executed with nothing returned.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.35 70134

A CallableStatement was executed with an invalid number of parameters

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.36 70135

A CallableStatement function was executed and the out parameter @1@ was of type @2@ however type @3@ was registered.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.37 70136

Maximum number of rows must be a value greater than or equal to 0.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.38 70137

Query timeout must be a value greater than or equals to 0.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.39 70138

The maximum field size must be a value greater than or equal to 0.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.40 70139

Unknown Types value.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.41 70140

Invalid stream length @1@.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.42 70141

The JVM claims not to support the @1@ encoding.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.43 70142

Unknown type @1@.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.44 70143

Cannot cast an instance of @1@ to type @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.45 70144

Unsupported Types value: @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.46 70145

Can't infer the SQL type to use for an instance of @1@. Use setObject() with an explicit Types value to specify the type to use.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.47 70146

This statement does not declare an OUT parameter. Use '{' ?= call ... '}' to declare one.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.48 70147

wasNull cannot be call before fetching a result.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.49 70148

Malformed function or procedure escape syntax at offset @1@.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.50 70149

Parameter of type @1@ was registered, but call to get@2@ (sqltype=@3@) was made.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.51 70150

A CallableStatement was declared, but no call to registerOutParameter(1, <some type>) was made.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.52 70151

No function outputs were registered.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.53 70152

Results cannot be retrieved from a CallableStatement before it is executed.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.54 70153

This statement has been closed.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.55 70154

Too many update results were returned.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.56 70155

Batch entry @1@ @2@ was aborted. Call getNextException to see the cause.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.57 70156

Unexpected error writing large object to database.

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.65.58 70157

@1 @ function takes one and only one argument.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.59 70158

@1 @ function takes two and only two arguments.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.60 70159

@1 @ function takes four and only four argument.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.61 70160

@1@ function takes two or three arguments.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.62 70161

@1@ function doesn't take any argument.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.63 70162

@1@ function takes three and only three arguments.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.64 70163

Interval @1@ not yet implemented

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.65 70164

Infinite value found for timestamp/date. This cannot be represented as time.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.66 70165

The class @1@ does not implement org.postgresql.util.PGobject.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.67 70166

Unknown ResultSet holdability setting: @1@.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.68 70167

Server versions prior to 8.0 do not support savepoints.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.69 70168

Cannot establish a savepoint in auto-commit mode.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.70 70169

Returning autogenerated keys is not supported.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.71 70170

The parameter index is out of range: @1@, number of parameters: @2@.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.72 70171

Returning autogenerated keys is only supported for 8.2 and later servers.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.73 70172

Returning autogenerated keys by column index is not supported.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.74 70173

Cannot reference a savepoint after it has been released.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.75 70174

Cannot retrieve the id of a named savepoint.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.76 70175

Cannot retrieve the name of an unnamed savepoint.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.77 70176

Invalid UUID data.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.78 70177

Unable to find server array type for provided name @1@.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.79 70178

Failed to set ClientInfo property: @1@

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.65.80 70179

ClientInfo property not supported.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.81 70180

Unable to decode xml data.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.82 70181

Unknown XML Source class: @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.83 70182

Unable to create SAXResult for SQLXML.

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.65.84 70183

Unable to create StAXResult for SQLXML

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.65.85 70184

Unknown XML Result class: @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.86 70185

This SQLXML object has already been freed.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.87 70186

This SQLXML object has not been initialized, so you cannot retrieve data from it.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.88 70187

Failed to convert binary xml data to encoding: @1@.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.89 70188

Unable to convert DOMResult SQLXML data to a string.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.90 70189

This SQLXML object has already been initialized, so you cannot manipulate it further.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.91 70190

Failed to initialize LargeObject API

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.65.92 70191

Large Objects may not be used in auto-commit mode.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.93 70192

The SSLSocketFactory class provided @1@ could not be instantiated.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.94 70193

Conversion of interval failed

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.95 70194

Conversion of money failed.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.96 70195

Transaction control methods setAutoCommit(true), commit, rollback and setSavePoint not allowed while an XA transaction is active.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.97 70196

Invalid flags

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.98 70197

xid must not be null

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.99 70198

Connection is busy with another transaction

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.65.100 70199

suspend/resume not implemented

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.66 Message Numbers Beginning with 70200

2.66.1 70200

Transaction interleaving not implemented

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.66.2 70201

Error disabling autocommit

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.66.3 70202

tried to call end without corresponding start call

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.66.4 70203

Not implemented: Prepare must be issued using the same connection that started the transaction

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.66.5 70204

Prepare called before end

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.66.6 70205

Server versions prior to 8.1 do not support two-phase commit.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.66.7 70206

Error preparing transaction

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.66.8 70207

Invalid flag

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.66.9 70208

Error during recover

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.66.10 70209

Error rolling back prepared transaction

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.66.11 70210

Not implemented: one-phase commit must be issued using the same connection that was used to start it

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.66.12 70211

commit called before end

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.66.13 70212

Error during one-phase commit

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.66.14 70213

Not implemented: 2nd phase commit must be issued using an idle connection

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.66.15 70214

Error committing prepared transaction

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.66.16 70215

Heuristic commit/rollback not supported

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.66.17 70216

Invalid definition statement format in connection configuration file. line number: @1@

[Description]

The format of a parameter definition statement in the connection configuration file is invalid.

[System Processing]

Processing is aborted.

[Action]

This messages is output in the case of HA Database Ready.

Correct the connection configuration file and restart the application.

2.66.18 70217

The same server name is specified by two or more SERVER parameters in the connection configuration file.

[Description]

The same server name is specified in multiple SERVER parameters in the connection configuration file.

[System Processing]

Processing is aborted.

[Action]

This messages is output in the case of HA Database Ready.

Correct the server name specified in the SERVER parameter of the connection configuration file, and restart the application.

2.66.19 70218

The connection configuration file cannot be opened. detail: "@1@"

[Description]

The process to open the connection configuration file failed.

[System Processing]

Processing is aborted.

[Action]

This messages is output in the case of HA Database Ready.

Check the state of the connection configuration file, remove the cause of the error, and restart the application.

2.66.20 70219

I/O error occurred during the reading of connection configuration file. file name: "@1@" detail: "@2@"

[Description]

An I/O error occurred during loading of the connection configuration file.

[System Processing]

Processing is aborted.

[Action]

This messages is output in the case of HA Database Ready.

Check the state of the connection configuration file, remove the cause of the error, and restart the application.

2.66.21 70220

server does not support auto connection switching

[Description]

The server does not support auto connection switching.

[System Processing]

Processing is aborted.

[Action]

Specify servers that support auto connection switching.

2.66.22 70221

could not find a suitable target server

[Description]

Could not find a suitable target server.

[System Processing]

Processing is aborted.

[Action]

Check following settings (host, IP address, port number, or targetServer):

- Connection string
- Connection service file
- Data source of JDBC or ODBC
- Environment variables for default connection parameter values(ex. PGHOST)
- Arguments of functions of libpq
- Options of command

2.66.23 70222

Invalid timeout (@1@<0).

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.66.24 70225

invalid value for targetserver: @1@

[Description]

value of targetserver is invalid.

[System Processing]

Processing is aborted.

[Action]

Set one of the following:

- primary
- standby
- prefer_standby
- any(can be specified only JDBC)

2.66.25 70226

The sslservercertcn @1@ could not be verified.

[Description]

value of sslservercertcn is different from common name in the server certificate.

[System Processing]

Processing is aborted.

[Action]

Set SSL certificate's common name to sslservercertcn.

2.66.26 70227

The sslservercertcn @1@ could not be verified by hostnameverifier @2@.

[Description]

value of sslservercertcn is different from common name in the server certificate.

[System Processing]

Processing is aborted.

[Action]

- Set SSL certificate's common name to sslservercertcn.
- Check the program of class specified by hostnameverifier.

2.67 Message Numbers Beginning with 80000

2.67.1 80001

The connection configuration file cannot be opened. detail: '@1@'

[Description]

The process to open the connection configuration file failed.

[System Processing]

Processing is aborted.

[Action]

This messages is output in the case of HA Database Ready.

Check the state of the connection configuration file, remove the cause of the error, and restart the application.

2.67.2 80002

Invalid definition statement format in connection configuration file. line number: @1@

[Description]

The format of a parameter definition statement in the connection configuration file is invalid.

[System Processing]

Processing is aborted.

[Action]

This messages is output in the case of HA Database Ready.

Correct the connection configuration file and restart the application.

2.67.3 80003

The same server name is specified by two or more SERVER parameters in the connection configuration file.

[Description]

The same server name is specified in multiple SERVER parameters in the connection configuration file.

[System Processing]

Processing is aborted.

[Action]

This messages is output in the case of HA Database Ready.

Correct the server name specified in the SERVER parameter of the connection configuration file, and restart the application.

2.67.4 80004

I/O error occurred during the reading of connection configuration file. file name: '@1@' detail: '@2@'

[Description]

An I/O error occurred during loading of the connection configuration file.

[System Processing]

Processing is aborted.

[Action]

This messages is output in the case of HA Database Ready.

Check the state of the connection configuration file, remove the cause of the error, and restart the application.

2.67.5 80005

CommandTimeout can't be less than zero.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.6 80006

The Connection is broken.

[Description]

The database server was disconnected during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Communication may have been disconnected for the following reasons:

- An error occurred in the communication line (TCP/IP etc.)
- The database server terminated abnormally.

Take the following actions:

- Eliminate the cause of the communication disconnection.

Examine the application and check whether the transaction for implementing update is a long transaction. Judge whether it is a long transaction from the following viewpoints and modify the application.

- a) If the COMMIT process is not executed after update, add the COMMIT process.
 - b) If the total number of update records in a single transaction is high, split it into short transactions.
 - c) If search was conducted for a long period of time after update, execute COMMIT after update or review the search SQL statement.
- If none of the above situations applies, perform the following:
 - a) Confirm that the database server has not stopped.
 - b) If the database server is starting or stopping, re-execute the command after the database server starts.

2.67.7 80007

The Connection is not open.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.8 80008

Parameter @1@ not found in query.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.9 80009

The Connection property can't be changed with an uncommitted transaction.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.10 80010

There is already an open DataReader associated with this Command which must be closed first.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.11 80011

@1@ does not exist in pg_proc

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.12 80012

Invalid parameter type: @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.13 80013

Connection is not open

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.14 80014

Connection already open

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.15 80015

Invalid database name: @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.16 80016

Connection string argument missing!

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.17 80017

Nested/Concurrent transactions aren't supported.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.18 80018

numeric value @1@ in SqlConnection exceeds maximum value @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.19 80019

numeric value @1@ in SqlConnection is below minimum value @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.20 80020

expecting @1@[True/False] value in SqlConnection

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.21 80021

expecting @1@[Numeric] value in SqlConnection

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.22 80022

expecting @1 @=[Protocol Version] value in ConnectionString

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.23 80023

key=value argument incorrect in ConnectionString

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.24 80024

Attempt to set compatibility with version @1@ when using version @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.25 80025

There is already an open DataReader associated with this Command which must be closed first.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.26 80026

ApplicationName not supported.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.27 80027

Timeout while getting a connection from pool.

[Description]

Timeout occurred during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Check the following:

- If executing SQL that outputs a large volume of search results, add a conditional expression to filter the results further.
- If numerous SQLs are being simultaneously executed, reduce the number of simultaneously executed SQLs.
- If a large volume of data is to be updated in a single transaction, modify the SQL to reduce the volume of data to be updated in a single transaction.
- If executing a complex SQL, modify it to a simple SQL.
- Check if there are any problems in the network.
- Before conducting maintenance that involves the processing of a large volume of data, use the SET statement to temporarily increase the value of maintenance_work_mem.

2.67.28 80028

Connection pool exceeds maximum size.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.29 80029

Not a COPY IN query: @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.30 80030

Copy can only start in Ready state, not in @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.31 80031

Tried to set Position of network stream @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.32 80032

Tried to read non-readable @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.33 80033

Tried to seek non-seekable @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.34 80034

Tried to set length of network stream @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.35 80035

Not a COPY OUT query, not in @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.36 80036

Copy can only start in Ready state, not in @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.37 80037

Tried to set Position of network stream @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.38 80038

Tried to write non-writable @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.39 80039

Tried to flush read-only @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.40 80040

Tried to seek non-seekable @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.41 80041

Tried to set length of network stream @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.42 80042

Do not change stream of an active @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.43 80043

Do not change delimiter of an active @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.44 80044

Do not change separator of an active @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.45 80045

Do not change escape symbol of an active @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.46 80046

Do not change null symbol of an active @1@**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.47 80047

Tried to add too many fields to a copy record with @1@ fields**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.48 80048

Invalid attempt to read when no data is present.**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.49 80049

Column index out of range**[Description]**

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.50 80050

could not find a suitable target server

[Description]

Could not find a suitable target server.

[System Processing]

Processing is aborted.

[Action]

Check following settings (host, IP address, port number, or targetServer):

- Connection string
- Connection service file
- Data source of JDBC or ODBC
- Environment variables for default connection parameter values(ex. PGHOST)
- Arguments of functions of libpq
- Options of command

2.67.51 80051

server does not support auto connection switching

[Description]

The server does not support auto connection switching.

[System Processing]

Processing is aborted.

[Action]

Specify servers that support auto connection switching.

2.67.52 80052

Only AuthenticationClearTextPassword and AuthenticationMD5Password supported for now. Received: @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.53 80053

A timeout has occurred. If you were establishing a connection, increase Timeout value in ConnectionString. If you were executing a command, increase the CommandTimeout value in ConnectionString or in your NpgsqlCommand object.

[Description]

Timeout occurred during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Check the following:

- If executing SQL that outputs a large volume of search results, add a conditional expression to filter the results further.
- If numerous SQLs are being simultaneously executed, reduce the number of simultaneously executed SQLs.
- If a large volume of data is to be updated in a single transaction, modify the SQL to reduce the volume of data to be updated in a single transaction.
- If executing a complex SQL, modify it to a simple SQL.
- Check if there are any problems in the network.
- Before conducting maintenance that involves the processing of a large volume of data, use the SET statement to temporarily increase the value of maintenance_work_mem.

2.67.54 80054

Connection establishment timeout. Increase Timeout value in ConnectionString.

[Description]

Timeout occurred during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Check the following:

- If executing SQL that outputs a large volume of search results, add a conditional expression to filter the results further.
- If numerous SQLs are being simultaneously executed, reduce the number of simultaneously executed SQLs.
- If a large volume of data is to be updated in a single transaction, modify the SQL to reduce the volume of data to be updated in a single transaction.
- If executing a complex SQL, modify it to a simple SQL.
- Check if there are any problems in the network.
- Before conducting maintenance that involves the processing of a large volume of data, use the SET statement to temporarily increase the value of maintenance_work_mem.

2.67.55 80055

Failed to establish a connection to '@1@'.

[Description]

The database server was disconnected during execution of the application.

[System Processing]

Processing will be aborted.

[Action]

Communication may have been disconnected for the following reasons:

- An error occurred in the communication line (TCP/IP etc.)
- The database server terminated abnormally.

Take the following actions:

- Eliminate the cause of the communication disconnection.

Examine the application and check whether the transaction for implementing update is a long transaction. Judge whether it is a long transaction from the following viewpoints and modify the application.

a) If the COMMIT process is not executed after update, add the COMMIT process.

b) If the total number of update records in a single transaction is high, split it into short transactions.

c) If search was conducted for a long period of time after update, execute COMMIT after update or review the search SQL statement.

- If none of the above situations applies, perform the following:

a) Confirm that the database server has not stopped.

b) If the database server is starting or stopping, re-execute the command after the database server starts.

2.67.56 80056

Ssl connection requested. No Ssl enabled connection from this host is configured.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.57 80057

Backend sent unrecognized response type: @1@

[Description]

An error occurred during communication between the application and the database server.

[System Processing]

Processing will be aborted.

[Action]

Check if there are any problems in the network, eliminate the cause of any error and re-execute the command.

2.67.58 80058

Store does not support specified edm type

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.59 80059

Can't cast @1@ into any valid DbType.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.60 80060

Cannot set NpgsqlDbType to just Array, Binary-Or with the element type (e.g. Array of Box is NpgsqlDbType.Array | NpgsqlDbType.Box).

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.61 80061

Can't cast @1@ into NpgsqlParameter

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.62 80062

Invalid attempt to read from column ordinal '@1@'. With CommandBehavior.SequentialAccess, you may only read from column ordinal '@2@' or greater.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.63 80063

this[] index value

[Description]

An unexpected error occurred.

[System Processing]

Processing will be aborted.

[Action]

Contact Fujitsu technical support.

2.67.64 80064

Field not found

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.65 80065

No transaction in progress.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.66 80066

Savepoint is not supported by backend.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.67 80067

Savepoint name cannot have semicolon.

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.68 80068

The collection is read-only

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.69 80069

NotSupported @1@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.70 80070

Require primitive EdmType

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.71 80071

NotSupported: @1@ @2@

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.72 80072

The authData parameter can only be null at the first call to continue!

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

2.67.73 80073

SSPI returned invalid number of output buffers

[Description]

An error occurred during execution of the application or command.

[System Processing]

Processing will be aborted.

[Action]

Check the message text and confirm that the application is written correctly and the command is being used correctly.

Chapter 3 Mirroring Controller Messages

This chapter explains messages output by the Mirroring Controller.

3.1 Message Numbers Beginning with MCA00000

3.1.1 MCA00001

"could not read file "{0}": exception={1}: {2}"

[Description]

Could not read the file.

[Parameters]

{0}: file name

{1}: exception type

{2}: exception detail

[System Processing]

Processing will be aborted.

[Action]

Identify the cause according to the message, and then remove it.

3.1.2 MCA00002

{0}: "wrong number of server ID in definition file "{1}""

[Description]

Invalid descriptions were found in definition file.

[Parameters]

{0}: command name

{1}: file name

[System Processing]

Processing will be aborted.

[Action]

Correct the definition file according to the message and parameter description of "Cluster Operation Guide".

3.1.3 MCA00003

{0}: "server ID not found in definition file "{1}" line {2}"

[Description]

Invalid descriptions were found in definition file.

[Parameters]

{0}: command name

{1}: file name

{2}: line number

[System Processing]

Processing will be aborted.

[Action]

Correct the definition file according to the message and parameter description of "Cluster Operation Guide".

3.1.4 MCA00004

{0}: "server ID specified in definition file "{1}" too long (max {2} bytes) line {3}"

[Description]

Invalid descriptions were found in definition file.

[Parameters]

{0}: command name

{1}: file name

{2}: max length of server ID

{3}: line number

[System Processing]

Processing will be aborted.

[Action]

Correct the definition file according to the message and parameter description of "Cluster Operation Guide".

3.1.5 MCA00005

"invalid host name or IP address "{1}" in definition file "{0}"

[Description]

Invalid descriptions were found in definition file.

[Parameters]

{0}: file name

{1}: host name or IP address

[System Processing]

Processing will be aborted.

[Action]

Correct the definition file according to the message and parameter description of "Cluster Operation Guide".

3.1.6 MCA00006

{0}: "invalid port number in definition file "{1}" line {2}"

[Description]

Invalid descriptions were found in definition file.

[Parameters]

{0}: command name

{1}: file name

{2}: line number

[System Processing]

Processing will be aborted.

[Action]

Correct the definition file according to the message and parameter description of "Cluster Operation Guide".

3.1.7 MCA00007

{0}: "invalid format specified in definition file "{1}" line {2}"

[Description]

Invalid descriptions were found in definition file.

[Parameters]

{0}: command name

{1}: file name

{2}: line number

[System Processing]

Processing will be aborted.

[Action]

Correct the definition file according to the message and parameter description of "Cluster Operation Guide".

3.1.8 MCA00008

{0}: "invalid value for parameter "{2}" in definition file "{1}"

[Description]

Invalid parameter was found in definition file.

[Parameters]

{0}: command name

{1}: file name

{2}: parameter name

[System Processing]

Processing will be aborted.

[Action]

Correct the definition file according to the message and parameter description of "Cluster Operation Guide".

3.1.9 MCA00009

{0}: "no value for parameter "{2}" specified in definition file "{1}"

[Description]

Invalid parameter was found in definition file.

[Parameters]

{0}: command name

{1}: file name

{2}: parameter name

[System Processing]

Processing will be aborted.

[Action]

Correct the definition file according to the message and parameter description of "Cluster Operation Guide".

3.1.10 MCA00010

{0}: "unrecognized parameter "{2}" in definition file "{1}"

[Description]

Unrecognized parameter was found in definition file.

[Parameters]

{0}: file name

{1}: command name

{2}: parameter name

[System Processing]

Processing will be aborted.

[Action]

Correct the definition file according to the message and parameter description of "Cluster Operation Guide".

3.1.11 MCA00011

%s: no operation mode specified

[Description]

No operation mode was specified.

[Parameters]

%s: command name

[System Processing]

Processing will be aborted.

[Action]

Re-execute after specifying operation modes.

3.1.12 MCA00012

%s: unrecognized operation mode "%s"

[Description]

Unrecognized operation mode was specified.

[Parameters]

%s: command name

%s: operation mode

[System Processing]

Processing will be aborted.

[Action]

Re-execute after specifying operation modes.

3.1.13 MCA00013

%s: option "%s" duplicated

[Description]

Certain option is duplicated.

[Parameters]

%s: command

%s: option

[System Processing]

Processing will be aborted.

[Action]

Re-execute after correcting options.

3.1.14 MCA00014

%s: "%s" option conflicts with "%s" option

[Description]

Options are conflicting.

[Parameters]

%s: command

%s: option

%s: option

[System Processing]

Processing will be aborted.

[Action]

Re-execute after correcting options.

3.1.15 MCA00015

%s: option requires an argument -- %s

[Description]

No argument specified for the option.

[Parameters]

%s: command

%s: option

[System Processing]

Processing will be aborted.

[Action]

Re-execute after correcting options.

3.1.16 MCA00016

%s: neither "%s" option nor environment variable "%s" specified

[Description]

Both of required option and equivalent environment variable were not specified.

[Parameters]

%s: command

%s: option

%s: environment variable

[System Processing]

Processing will be aborted.

[Action]

Re-execute after specifying required option or equivalent environment variable.

3.1.17 MCA00017

%s: out of memory

[Description]

Out of memory error occurred.

[Parameters]

%s: command

[System Processing]

Processing will be aborted.

[Action]

Obtain free memory space by stopping unnecessary processes or changing system settings.

3.1.18 MCA00018

out of memory

[Description]

Out of memory error occurred.

[System Processing]

Processing will be aborted.

[Action]

Obtain free memory space by stopping unnecessary processes or changing system settings.

3.1.19 MCA00019

detected an error on the monitored object "{0}({1})": {2}

[Description]

An error was detected on the monitored object.

[Parameters]

{0}: monitored object (server, database process, data storage destination directory, transaction log storage destination directory, tablespace directory)

{1}: object name (host name, database process name, directory path)

{2}: error detail ("no response:", "read/write error:" and detailed information)

[System Processing]

Perform failover or detaching.

If failover or detaching is already performed, these functions would be disabled.

[Action]

Refer to the description about workaround for failure of "Cluster Operation Guide".

3.1.20 MCA00020

unexpected error occurred in the monitoring process: {0}

[Description]

Monitoring process cannot continue because an unexpected error was occurred during its processing.

[Parameters]

{0}: error detail

[System Processing]

Continues processing.

[Action]

Refer to the description about workaround for failure of "Cluster Operation Guide".

3.1.21 MCA00021

starting to {2} from {0} to {1}.

[Description]

Switching standby server to primary server.

[Parameters]

{0}: server ID of primary server

{1}: server ID of standby server

{2}: "fail over" or "switch over"

[Action]

If Mirroring Controller executed switching automatically, find the message output before this message from system log or event log to identify the cause of switching, and then work around according to the Action of the message.

3.1.22 MCA00022

{2} completed.switched from {0} to {1}

[Description]

Switching standby server to primary server was completed.

[Parameters]

{0}: server ID of primary server

{1}: server ID of standby server

{2}: "fail over"or"switch over"

3.1.23 MCA00023

failed to {2} from {0} to {1}

[Description]

Failed to switch to primary server because of unexpected failure.

[Parameters]

{0}: server ID of primary server

{1}: server ID of standby server

{2}: "fail over"or"switch over"

[System Processing]

Processing of switching will be aborted.

[Action]

Find the message output before this message from display, system log or event log, and then work around according to the Action of the message.

3.1.24 MCA00024

starting to detach standby server "{0}" {1}

[Description]

Detaching standby server because of failure detected on standby server.

[Parameters]

{0}: server ID

{1}: "automatically" or none

[Action]

If Mirroring Controller executed detaching automatically, find the message output before this message from system log or event log to identify the cause of detaching, and then work around according to the Action of the message.

3.1.25 MCA00025

detach standby server "{0}" completed {1}

[Description]

Detached standby server.

[Parameters]

{0}: server ID

{1}: "automatically" or none

3.1.26 MCA00026

failed to {2} standby server "{0}" {1}

[Description]

Failed to detach standby server.

[Parameters]

{0}: server ID

{1}: "automatically" or none

{2}: "detach"

[System Processing]

Processing of detaching will be aborted.

[Action]

Refer to the description about workaround for failure of "Cluster Operation Guide".

3.1.27 MCA00027

another "{0}" command is running

[Description]

Cannot execute command with this operation mode because another command is running on the same or another server.

[Parameters]

{0}: command name

[System Processing]

Processing will be aborted.

[Action]

There is a case executing another command. Wait for completion of another command on the same or another server, and then re-execute.

In addition, there are the following cases when using mc_ctl command.

There is a case under processing of a failover and an automatic detach by Mirroring Controller. Wait for completion of the processing under operation, and re-execute.

If any of the following cases occurs, there is a possibility that the processing of Mirroring Controller interrupts. Re-execute the mc_ctl command after restarting Mirroring Controller.

- When abnormality occurs in the network
- When another server is downed
- When Mirroring Controller is stopped forcibly

3.1.28 MCA00028

communication timeout of Mirroring Controller occurred server:"{0}"

[Description]

Either of the followings has occurred.

- communication timeout between mc_ctl command and Mirroring Controller process has occurred.
- communication timeout between Mirroring Controller processes have occurred.
- Terminating database instance was not completed in the specified time.

[Parameters]

{0}: server ("localhost" or server ID)

[System Processing]

Processing will be aborted.

[Action]

Completion synchronization for terminating database instance might have timed out, because connections remained. Disconnect all connections, and re-execute it.

Reduce CPU or network load caused by the other processes. If could not reduce it, extend remote_call_timeout in "server identifier".conf.

3.1.29 MCA00029

could not create PID file of Mirroring Controller detail of cause:"{0}"

[Description]

Could not create PID file of Mirroring Controller.

[Parameters]

{0}: detail of cause

[System Processing]

Processing will be aborted.

[Action]

Identify the cause according to the message, and then remove it.

3.1.30 MCA00030

could not remove PID file of Mirroring Controller detail of cause:"%s"

[Description]

Could not remove PID file of Mirroring Controller.

[Parameters]

{0}: detail of cause

[Action]

Identify the cause according to the message, and then remove it.

3.1.31 MCA00031

could not read PID file of Mirroring Controller detail of cause:"%s"

[Description]

Could not read PID file of Mirroring Controller.

[Parameters]

{0}: detail of cause

[Action]

Identify the cause according to the message, and then remove it.

3.1.32 MCA00032

invalid contents of PID file "%s" of Mirroring Controller

[Description]

The contents of PID file of Mirroring Controller is invalid.

[Parameters]

{0}: file name

[System Processing]

Processing will be aborted.

[Action]

The following causes could be considered.

- The file was stored or replaced by mistake
- The file was corrupted

When starting Mirroring Controller, move or remove the file shown in the message.

When stopped Mirroring Controller, find ID of process named "mcagent" and terminate forcibly by using OS command.

3.1.33 MCA00033

Mirroring Controller is already running

[Description]

Mirroring Controller is already running.

[System Processing]

Processing will be aborted.

[Action]

If needed, stop Mirroring Controller, and re-execute.

3.1.34 MCA00034

cannot execute %s command because Mirroring Controller is not running

[Description]

Cannot execute Mirroring Controller command because Mirroring Controller process is not running.

[Parameters]

{0}: command name

[System Processing]

Processing will be aborted.

[Action]

Start Mirroring Controller, and re-execute.

3.1.35 MCA00035

failed to start database instance

[Description]

Failed to start database instance.

[System Processing]

Processing will be aborted.

[Action]

Find the database message output in the log files of database output before this message, and then work around according to the Action of the message.

3.1.36 MCA00036

failed to stop database instance target server:"{0}"

[Description]

Failed to stop database instance.

[Parameters]

{0}: target server ("localhost" or server ID)

[System Processing]

Processing will be aborted.

[Action]

Find the database message output in the log files of database on the target server output before this message, and then work around according to the Action of the message.

3.1.37 MCA00037

Mirroring Controller option is not installed

[Description]

This functionality is enabled by installing Mirroring Controller option.

[Parameters]

{0}: target server ("localhost" or server ID)

[System Processing]

Processing will be aborted.

[Action]

To use this functionality, install Mirroring Controller option, and then re-execute.

3.1.38 MCA00038

starting Mirroring Controller

[Description]

Starting Mirroring Controller.

3.1.39 MCA00039

Mirroring Controller started

[Description]

Mirroring Controller started.

3.1.40 MCA00040

failed to start Mirroring Controller

[Description]

Failed to start Mirroring Controller.

[System Processing]

Processing will be aborted.

[Action]

Work around according to the Action of the message output before this message.

On Windows, if there is no message outputted before this message, please refer to the message outputted to an event log.

3.1.41 MCA00041

stopping Mirroring Controller

[Description]

Stopping Mirroring Controller.

3.1.42 MCA00042

Mirroring Controller stopped target server:"{0}"

[Description]

Mirroring Controller stopped.

[Parameters]

{0}: target server ("localhost" or server ID)

3.1.43 MCA00043

failed to stop Mirroring Controller target server:"{0}"

[Description]

Failed to stop Mirroring Controller.

[Parameters]

{0}: target server ("localhost" or server ID)

[System Processing]

Processing will be aborted.

[Action]

Identify the cause from system log or event log on the target server, and work around.

3.1.44 MCA00044

stopping Mirroring Controller forcibly

[Description]

Stopping Mirroring Controller forcibly.

3.1.45 MCA00045

stopped Mirroring Controller forcibly

[Description]

Mirroring Controller stopped forcibly.

3.1.46 MCA00046

enabled failover target server:"{0}"

[Description]

Enabled failover and automatic detach.

3.1.47 MCA00047

failed to enable failover target server:"{0}"

[Description]

Failed to enable failover and automatic detach.

[System Processing]

Processing will be aborted.

[Action]

Identify the cause from messages on system log or event log, and work around.

3.1.48 MCA00048

disabled failover target server:"{0}"

[Description]

Disabled failover and automatic detach.

3.1.49 MCA00049

failed to disable failover target server:"{0}"

[Description]

Failed to disable failover and automatic detach.

[System Processing]

Processing will be aborted.

[Action]

Identify the cause from messages on system log or event log, and work around.

3.1.50 MCA00050

{0}: "server ID "{2}" specified with option "{1}" does not exist in definition file "{3}"

[Description]

server ID specified with the option does not exist in definition file.

[Parameters]

{0}: command name

{1}: option

{2}: server ID

{3}: file name

[System Processing]

Processing will be aborted.

[Action]

Re-execute after correcting options or definition file.

3.1.51 MCA00051

{0}: "IP address of the command execution server is not specified in definition file "{1}"

[Description]

IP address of the command execution server is not specified in definition file.

[Parameters]

{0}: command name

{1}: file name

[System Processing]

Processing will be aborted.

[Action]

Correct the definition file according to the message and parameter descriptions of "Cluster Operation Guide".

3.1.52 MCA00052

{0}: "wrong server ID "{2}" in definition file "{1}"

[Description]

Invalid descriptions were found in definition file.

[Parameters]

{0}: command name

{1}: file name

{2}: server ID

[System Processing]

Processing will be aborted.

[Action]

Correct the definition file according to the message and parameter descriptions of "Cluster Operation Guide".

3.1.53 MCA00053

未作成

MCA00054

"could not write to file "{0}": exception={1}: {2}"

[Description]

Failed to detach or synchronize standby server because could not write to the file.

[Parameters]

{0}: file name

{1}: exception type

{2}: exception detail

[System Processing]

Processing will be aborted.

[Action]

Check the error detail and eliminate causes, and detach or synchronize standby server according to "Actions when an Error Occurs" of "Cluster Operation Guide".

3.1.54 MCA00055

unexpected error occurred in the monitoring process: {0}

[Description]

Monitoring process could not continue because the unexpected error occurred.

[Parameters]

{0}: detail of cause

[System Processing]

Continues monitoring.

[Action]

Check the error detail and eliminate causes.

If you cannot clear the problem, contact Fujitsu technical support.

3.1.55 MCA00056

unexpected error occurred: {0}

[Description]

An unexpected error occurred.

[Parameters]

{0}: detail of cause

[System Processing]

Processing will be aborted.

[Action]

Check the error detail and eliminate cause.

If you cannot clear the problem, contact Fujitsu technical support.

3.1.56 MCA00057

failed to stop Mirroring Controller forcibly

[Description]

Failed to stop Mirroring Controller forcibly.

[System Processing]

Processing will be aborted.

[Action]

Check [Action] of the message output before this message, and re-execute.

If re-execution fails, terminate forcibly mc_agent process with OS command.

3.1.57 MCA00058

could not access path "%s" specified as a directory for Mirroring Controller detail of cause:"%s"

[Description]

could not access path specified as a directory for Mirroring Controller.

[Parameters]

%s: path name

%s: detail of cause

[System Processing]

Processing will be aborted.

[Action]

Check the error detail and eliminate causes.

3.1.58 MCA00059

system call error occurred:"%s" detail of cause:"%s"

[Description]

System call error occurred.

[Parameters]

%s: system call name

%s: detail of cause

[System Processing]

Processing will be aborted.

[Action]

Check the error detail and eliminate causes.

3.1.59 MCA00060

could not get installation path

[Description]

Symfoware Server may not be installed.

[System Processing]

Processing will be aborted.

[Action]

Re-install Symfoware Server.

3.1.60 MCA00061

could not access path "%1\$s" for parameter "%2\$s" in definition file "%3\$s" detail of cause: "%4\$s"

[Description]

could not access path for parameter in definition file.

[Parameters]

%3\$s: file name

%2\$s: parameter name

%1\$s: path name

%4\$s: detail of cause

[System Processing]

Processing will be aborted.

[Action]

Check the error detail and eliminate causes.

3.1.61 MCA00062

promotion processing completed

[Description]

Promotion processing completed.

3.1.62 MCA00063

promotion processing failed

[Description]

Promotion processing failed.

[System Processing]

Processing will be aborted.

[Action]

Clear the problem according to [Action] of the message which was output before this message in system log or in database server log.

3.1.63 MCA00064

stopped database instance forcibly

[Description]

Database instance stopped forcibly.

3.1.64 MCA00065

failed to stop database instance forcibly

[Description]

Failed to stop database instance forcibly.

[System Processing]

Processing will be aborted.

[Action]

Clear the problem according to [Action] of the message which was output before this message in system log or in database server log.

3.1.65 MCA00066

未作成

MCA00067

did not switch during a degeneration use

[Description]

Did not switch during a degeneration use.

[System Processing]

Processing will be aborted.

[Action]

If Mirroring Controller executed switching automatically, find the message output before this message from system log or event log to identify the cause of degeneration, and then eliminate causes according to [Action] of the message and try to switch with command.

3.1.66 MCA00068

{0}: "users other than an instance administrator have the access privileges for definition file {1}"

[Description]

users other than an instance administrator have the access privileges for definition file.

[Parameters]

{0}: command name

{1}: file name

[System Processing]

Processing will be aborted.

[Action]

Revoke all the access privileges for users other than an instance administrator.

MCA00069

could not execute because Mirroring Controller of the server "{0}" is not running

[Description]

Could not execute because Mirroring Controller is not running.

[Parameters]

{0}: server ID

[System Processing]

Processing will be aborted.

[Action]

Start Mirroring Controller, and try to switch with command.

3.1.67 MCA00070

[Try "%s --help" for more information.\n](#)

[Description]

--help option can show more additional information.

[Parameters]

%s: command name

[System Processing]

None.

[Action]

Check the message output before this message, and refer to descriptions shown by '--help' option.

3.1.68 MCA00071

[starting to {0}](#)

[Description]

Switching standby server to primary server.

[Parameters]

{0}: "switch over"

3.1.69 MCA00072

[failed to {0}](#)

[Description]

Failed to switch to primary server because of an unexpected failure.

[Parameters]

{0}: "switch over"

[System Processing]

Processing of switching will be aborted.

[Action]

Find the message output before this message from display, system log or event log, and then eliminate causes according to [Action] of the message.

3.1.70 MCA00073

error detected in handling of the database instance detail of cause:"{0}"

[Description]

Error detected in handling of the database instance for the following purposes.

- Obtain the port number of database instance
- Access to the data storage destination directory

[Parameters]

{0}: detail of cause

[System Processing]

Processing will be aborted.

[Action]

Check the error detail and eliminate causes.

3.1.71 MCA00074

could not read PID file of Mirroring Controller detail of cause:"{0}"

[Description]

Could not read PID file of Mirroring Controller.

[Parameters]

{0}: detail of cause

[Action]

Identify the cause according to the message, and then remove it.

3.1.72 MCA00075

invalid contents of PID file "{0}" of Mirroring Controller

[Description]

The contents of PID file of Mirroring Controller is invalid.

[Parameters]

{0}: file name

[System Processing]

Processing will be aborted.

[Action]

The following causes could be considered.

- The file was stored or replaced by mistake
- The file was corrupted

When starting Mirroring Controller, move or remove the file shown in the message.

When stopped Mirroring Controller, find ID of process named "mcagent" and terminate forcibly by using OS command.

3.1.73 MCA00076

cannot execute "{0}" command because Mirroring Controller is not running

[Description]

Cannot execute Mirroring Controller command because Mirroring Controller process is not running.

[Parameters]

{0}: command name

[System Processing]

Processing will be aborted.

[Action]

Start Mirroring Controller, and re-execute.

3.1.74 MCA00077

%s: argument of option "%s" is too long

[Description]

Argument of option is too long.

[Parameters]

%s: command name

%s: option

[System Processing]

Processing will be aborted.

[Action]

Re-execute after correcting options.

3.1.75 MCA00078

%s: invalid option -- %s

[Description]

Invalid option.

[Parameters]

%s: command name

%s: option

[System Processing]

Processing will be aborted.

[Action]

Re-execute after correcting options.

3.1.76 MCA00079

%s: unnecessary operand "%s"**[Description]**

Unnecessary operand.

[Parameters]

%s: command name

%s: operand

[System Processing]

Processing will be aborted.

[Action]

Re-execute after correcting operand.

3.1.77 MCA00080

%s: unrecognized operation mode or no operation mode specified**[Description]**

Unrecognized operation mode or no operation mode specified.

[Parameters]

%s: command name

[System Processing]

Processing will be aborted.

[Action]

Re-execute after correcting or specifying operation mode.

3.1.78 MCA00081

start to enable the parameter "{1}" required to build in the standby server "{0}"**[Description]**

Start to enable the parameter required to build in the standby server.

[Parameters]

{0}: server ID

{1}: parameter name

3.1.79 MCA00082

enabling the parameter "{1}" required to build in the standby server "{0}" completed**[Description]**

Enabling the parameter required to build in the standby server completed.

[Parameters]

{0}: server ID

{1}: parameter name

3.1.80 MCA00083

failed to enable the parameter "{1}" required to build in the standby server "{0}"

[Description]

Failed to enable the parameter required to build in the standby server.

The following causes could be considered.

- another command is running
- can not access definition file
- parameter does not exist

[Parameters]

{0}: server ID

{1}: parameter name

[System Processing]

Processing will be aborted.

[Action]

- If the parameter is not set

On the primary server, set the parameter of postgresql.conf file according to "parameter" description of "Cluster Operation Guide" and execute pg_ctl command with reload mode.

- Otherwise

Find the message output before this message from display, system log or event log, and then eliminate causes according to [Action] of the message. Then, on the primary server, set the parameter of postgresql.conf file according to "parameter" description of "Cluster Operation Guide" and execute pg_ctl command with reload mode.

3.1.81 MCA00084

primary server is already running

[Description]

Primary server is already running.

[System Processing]

Processing will be aborted.

[Action]

The standby server might be running without creating recovery.conf. Create recovery.conf, and re-execute.

3.1.82 MCA00085

cannot start Mirroring Controller because database instance is not running

[Description]

Cannot start Mirroring Controller because database instance is not running.

[System Processing]

Processing will be aborted.

[Action]

Start database instance, and re-execute.

3.1.83 MCA00086

could not get state of database instance detail of cause:"{0}"

[Description]

Could not get state of database instance.

[Parameters]

{0}: detail of cause

[System Processing]

Processing will be aborted.

[Action]

Check the error detail and eliminate causes.

3.1.84 MCA00087

unusable character is included in path "%s" specified as a directory for Mirroring Controller

[Description]

Unusable character is included in path specified as a directory for Mirroring Controller.

[Parameters]

%s: path name

[System Processing]

Processing will be aborted.

[Action]

Correct the path specified as a directory for Mirroring Controller according to the message and mc_ctl command descriptions of "Reference".

3.1.85 MCA00088

%1\$s: unusable character is included in server ID "%3\$s" specified with option "%2\$s"

[Description]

Unusable character is included in server ID specified with option.

[Parameters]

%1\$s: command name

%2\$s: option

%3\$s: server ID

[System Processing]

Processing will be aborted.

[Action]

Correct the server ID specified with option according to the message and mc_ctl command descriptions of "Reference".

3.1.86 MCA00089

only instance administrator can execute this command

[Description]

Only instance administrator who created the directory for Mirroring Controller can execute this command.

[System Processing]

Processing will be aborted.

[Action]

Re-execute the command by the instance administrator who created the directory for Mirroring Controller.

3.1.87 MCA00090

could not read file "{0}": Permission denied

[Description]

No read permissions for the file.

[System Processing]

Processing will be aborted.

[Action]

Re-execute the command, after granting the read permissions to the file.

3.1.88 MCA00091

"host name or IP address "{1}" of the primary server and the standby server in definition file "{0}" are same, but the --local-server option was not specified"

[Description]

Host name or IP address of the primary server and the standby server in definition file are same, but the --local-server option was not specified.

[Parameters]

{0}: file name

{1}: host name or IP address

[System Processing]

Processing will be aborted.

[Action]

If the primary server and the standby server are built in the same server, execute the mc_ctl command with the --local-server option.

If the primary server and the standby server are built in the different server, correct host name or IP address in the definition file.

3.1.89 MCA00092

this feature is not available in this edition

[Description]

This feature is not available in this edition.

[System Processing]

Processing will be aborted

[Action]

Please install the right edition for this feature.

3.1.90 MCA00093

installation environment is destroyed

[Description]

Symfoware Server may not be installed correctly or may be destroyed.

[System Processing]

Processing will be aborted.

[Action]

Re-install Symfoware Server.

3.1.91 MCA00094

%s: invalid argument for option %s

[Description]

Invalid argument for option.

[Parameters]

%s: command name

%s: option

[System Processing]

Processing will be aborted.

[Action]

Re-execute after correcting options.

3.1.92 MCA00095

could not remove file or directory "{0}"

[Description]

Could not remove the file or the directory.

[Parameters]

{0}: file name or directory name

[System Processing]

Processing will be aborted.

[Action]

Check the status of the file or the directory and eliminate causes, and then remove it.

3.1.93 MCA00096

"could not write file "{0}": exception={1}: {2}"

[Description]

Could not write the file.

[Parameters]

{0}: file name

{1}: exception type

{2}: exception detail

[System Processing]

Processing will be aborted.

[Action]

Identify the cause according to the message, and then remove it.

3.1.94 MCA00097

setup of standby server completed

[Description]

Setup of standby server completed.

3.1.95 MCA00098

setup of standby server failed

[Description]

Setup of standby server failed.

[System Processing]

Processing will be aborted.

[Action]

Find the message output before this message from display, system log or event log, and then eliminate causes according to [Action] of the message.

3.1.96 MCA00099

{0}: server "{1}" is running as a standby server

[Description]

Could not continue processing because database instance to be duplicated is not running as a primary server.

[Parameters]

{0}: command name

{1}: server ID

[System Processing]

Processing will be aborted.

[Action]

Re-execute this command on the standby server to be set up.

3.2 Message Numbers Beginning with MCA00100

3.2.1 MCA00100

cannot execute {0} command because Mirroring Controller is running

[Description]

Cannot execute this command because Mirroring Controller is running on the server to be set up.

[Parameters]

{0}: command name

[System Processing]

Processing will be aborted.

[Action]

Execute this command on server where primary server is not running. If execute it on the right server, stop Mirroring Controller and then re-execute it.

3.2.2 MCA00101

cannot execute {0} command because database instance is running

[Description]

Cannot execute this command because database instance is running on the server to be set up.

[Parameters]

{0}: command name

[System Processing]

Processing will be aborted.

[Action]

Execute this command on server where primary server is not running. If execute it on the right server, stop database instance and then re-execute it.

3.2.3 MCA00102

{0}: invalid argument value {2} for option {1}

[Description]

Invalid argument for option.

[Parameters]

{0}: command name

{1}: option

{2}: argument value

[System Processing]

Processing will be aborted.

[Action]

Re-execute after correcting argument value for the option.

3.2.4 MCA00103

could not move file or directory from {0} to {1}

[Description]

Could not move the file or the directory.

[Parameters]

{0}: source file or directory

{1}: target file or directory

[System Processing]

Processing will be aborted.

[Action]

Check the status of the file or the directory and eliminate causes, and then remove it.

3.2.5 MCA00104

could not create directory {0}

[Description]

Could not create the directory.

[Parameters]

{0}: target directory

[System Processing]

Processing will be aborted.

[Action]

Check the status of the directory and eliminate causes, and then remove it.

3.2.6 MCA00105

could not read the access privileges of {0}

[Description]

Could not read the access privileges.

[Parameters]

{0}: target directory

[System Processing]

Processing will be aborted.

[Action]

Check the status of the directory and eliminate causes, and then remove it.

3.2.7 MCA00106

failed to set the access privileges of {0}

[Description]

Failed to set the access privileges.

[Parameters]

{0}: target directory

[System Processing]

Processing will be aborted.

[Action]

Check the status of the directory and eliminate causes, and then remove it.

3.2.8 MCA00107

service "{0}" is not registered

[Description]

Service is not registered.

[Parameters]

{0}: Service name

[System Processing]

Processing will be aborted.

[Action]

Register service, and re-execute.

3.2.9 MCA00108

could not start service "{0}" detail of cause:"{1}"

[Description]

Could not start service.

[Parameters]

{0}: Service name

{1}: detail of cause

[System Processing]

Processing will be aborted.

[Action]

Check the error detail and eliminate causes.

3.2.10 MCA00109

could not start service "%s" detail of cause:"%s"

[Description]

Could not start service.

[Parameters]

%s: Service name

%s: detail of cause

[System Processing]

Processing will be aborted.

[Action]

Check the error detail and eliminate causes.

3.2.11 MCA00110

service "%s" is not registered

[Description]

Service is not registered.

[Parameters]

%s: Service name

[System Processing]

Processing will be aborted.

[Action]

Register service, and re-execute.

3.2.12 MCA00111

Mirroring Controller service "%s" has been registered

[Description]

Mirroring Controller service has been registered with Windows Service.

[Parameters]

%s: Service name

3.2.13 MCA00112

Mirroring Controller service "%s" has been unregistered

[Description]

Mirroring Controller service has been unregistered from Windows Service.

[Parameters]

%s: Service name

3.2.14 MCA00113

service name "%s" is already in use

[Description]

Service name is already in use.

[Parameters]

%s: Service name

[System Processing]

Processing will be aborted.

[Action]

Check the service name, and re-execute.

3.2.15 MCA00114

could not register service "%s" detail of cause: "%s"

[Description]

An error occurred during registration of service.

[Parameters]

%s: Service name

%s: detail of cause

[System Processing]

Processing will be aborted.

[Action]

Check the error detail and eliminate causes.

3.2.16 MCA00115

could not unregister service "%s" detail of cause: "%s"

[Description]

An error occurred during deregistration of service.

[Parameters]

%s: Service name

%s: detail of cause

[System Processing]

Processing will be aborted.

[Action]

Check the error detail and eliminate causes.

3.2.17 MCA00116

%s: option "%s" is required

[Description]

A required option is not specified.

[Parameters]

%s: command name

%s: option

[System Processing]

Processing will be aborted.

[Action]

Specify the required option, and re-execute.

3.2.18 MCA00117

no authority to execute this command

[Description]

Only the administrative user can run this command.

[System Processing]

Processing will be aborted.

[Action]

Invoke the administrator's prompt, and re-execute this command.

Appendix A Messages Output by PL/extJava

This appendix describes messages output by PL/extJava.

A.1 Message Information

This appendix describes messages that must be monitored with PL/extJava.

A.1.1 Message Output Format

This section describes the output format of messages.

Format 1

```
label : msgType: msgText (componentId)
```

Description

<i>label</i>	<i>msgType</i>	<i>msgText</i>	<i>componentId</i>
Featu re identi fier	"INFO" (Information)	<i>msgNumber</i> :	(STFSYMOIDB <i>vLfirstDigitOfArch itecture</i>) - <i>vL</i> : Version/level of Symfoware Server - <i>firstDigitOfArchitecture</i> : Product architecture ("3" for the 32-bit version; "6" for the 64-bit version)
	"WARNING" (Warning)	<i>msgDesc</i> : (%s1)	
	"ERROR" (Error)		

Output example

```
UX:PCMI: INFO: PCMI0011: PCMI service has started.: INSTANCE=/home/domain1/pcmi/isje6  
(STFSYMOIDB12103)  
~ (subsequent text is omitted)
```

Format 2

```
UX: label: msgType: msgNumber: msgText
```

Description

<i>label</i>	<i>msgType</i>	<i>msgNumber</i>	<i>msgText</i>
"AHS"	"INFO" (Information)	<i>ahs5digitNumber</i>	<i>msgDesc</i> [%s1]
	"WARNING" (Warning)		
	"ERROR" (Error)		

Output example

```
UX:AHS: INFO: ahs00001: HTTP Server started. [/opt/symfoserver64/java/ahs22/  
plextjava/domain1/conf/httpd_domain1.conf]
```

A.2 PL/extJava Messages

This chapter explains the Java EE related messages.



Messages that are not explained in this chapter

If not explained in the Messages, identify the cause of the problem from the message body and take appropriate action. If the problem is still not resolved, contact Fujitsu technical support.

A.2.1 Messages that Contain "CLI" in the Message ID

A.2.1.1 CLI100 to CLI199

CLI136 Port {0} should be a numeric value.

Variable Information

{0}: Specified port number

Explanation

The specified port number is invalid.

System Action

Processing is interrupted.

User Action



For Windows Server(R) 2003 or Windows Server(R) 2003 R2, specify an integer in the range from 5001 to 49151, and then reexecute the command.

For Windows Server(R) 2008 or Windows Server(R) 2008 R2, or Windows Server(R) 2012 or Windows Server(R) 2012 R2, specify an integer in the range from 1024 to 49151, and then reexecute the command.



Specify an integer in the range from 1024 to 32767, and then reexecute the command.

CLI141 No Domains to list.

Explanation

There are no domains.

System Action

Processing is interrupted.

User Action

The product environment has been corrupted, therefore reinstall the product.

A.2.1.2 CLI300 to CLI399

CLI306 Warning - The server located at {0} is not running.

Variable Information

{0}: Specified port number

Explanation

The specified Java EE DAS service has not been started.

System Action

Processing is interrupted.

A.2.1.3 CLI800 to CLI899

CLI801 Instance is already synchronized

Explanation

The synchronization processing for the server instance (Java VM) is complete.

System Action

Processing is continued.

A.2.1.4 CLI1300 to CLI1399

CLI1306 Warning - server instance is not running.

Explanation

The specified server instance has not been started.

System Action

Processing is interrupted.

A.2.2 Messages that Contain "CORE" in the Message ID

A.2.2.1 CORE10000 to CORE10199

INFO: CORE10003: Updated log levels for loggers.

Explanation

The log levels were updated.

System Action

Processing is continued.

INFO: CORE10101: Done with starting {0} container.

Variable Information

{0}: Container name

Explanation

The container was started.

SEVERE: CORE10103: Unable to start container {0}

Variable Information

{0}: Internal information

Explanation

Failed to start the container.

System Action

Processing is continued.

User Action

Follow the action advised in the exception information and any other messages output at the same time to remove the cause of the error.

A.2.2.2 When there is no Message Number

If not explained in the Messages, identify the cause of the problem from the message body and take appropriate action. If the problem still exists, contact Fujitsu technical support.

A.2.3 Messages that Contain "DPL" in the Message ID

A.2.3.1 DPL8000 to DPL8099

WARNING: DPL8031: Ignoring {0} because the containing archive {1} recorded it as a pre-existing stale file

Variable Information

{0}: File name

{1}: Java Application path

Explanation

The preexisting file will be ignored.

System Action

Processing is continued.

A.2.3.2 When there is no Message Number

If not explained in the Messages, identify the cause of the problem from the message body and take appropriate action. If the problem still exists, contact Fujitsu technical support.

A.2.4 Messages that Contain "GRIZZLY" in the Message ID

A.2.4.1 GRIZZLY0000 to GRIZZLY0099

WARNING: GRIZZLY0006: Exception accepting channel

Explanation

An exception occurred during request acceptance processing.

System Action

The processing to accept requests is repeated.

User Action

If no other messages are output after this message, it indicates that request acceptance has been successful as a result of reexecuting the processing to accept requests and no further action is required.

If other messages are output after this message, it indicates that request acceptance was not successful. Follow the action advised in the exception information and any other messages to remove the cause of the error.

WARNING: GRIZZLY0030: {0} exception.

Variable Information

{0}: Method name

Explanation

An exception has been thrown during socket option configuration.

System Action

Processing is continued.

User Action

Follow the action advised in the exception information and any other messages to remove the cause of the error. If the problem is still not resolved, contact Fujitsu technical support.

SEVERE: GRIZZLY0036: Error finishing request.

Explanation

An exception has been thrown during request recovery processing.

System Action

Processing is continued.

User Action

Follow the action advised in the exception information and any other messages to remove the cause of the error. If the problem is still not resolved, contact Fujitsu technical support.

SEVERE: GRIZZLY0037: Error finishing response.

Explanation

An exception has been thrown during response recovery processing.

System Action

Processing is continued.

User Action

Follow the action advised in the exception information and any other messages to remove the cause of the error. If the problem is still not resolved, contact Fujitsu technical support.

SEVERE: GRIZZLY0038: HTTP Processing error.

Explanation

An exception has been thrown during request processing.

System Action

Processing is continued.

User Action

Follow the action advised in the exception information and any other messages to remove the cause of the error. If the problem is still not resolved, contact Fujitsu technical support.

SEVERE: GRIZZLY0041: Unblocking keep-alive exception.

Explanation

An exception has been thrown during request analysis processing.

System Action

Request processing is interrupted.

User Action

Follow the action advised in the exception information and any other messages to remove the cause of the error. If the problem is not resolved, contact Fujitsu technical support.

SEVERE: GRIZZLY0042: Error creating internal request.

Explanation

An exception has been thrown during request preparation processing.

System Action

Request processing is interrupted.

User Action

Follow the action advised in the exception information and any other messages to remove the cause of the error. If the problem is still not resolved, contact Fujitsu technical support.

SEVERE: GRIZZLY0051: ProcessorTask exception.

Explanation

An unexpected exception occurred during request processing.

System Action

Processing is interrupted.

User Action

Follow the action advised in the exception information and any other messages to remove the cause of the error. If the problem is not resolved, contact Fujitsu technical support.

A.2.5 Messages that Contain "IJServer" in the Message ID

A.2.5.1 IJServer12000 to IJServer12099

A.2.5.1.1 IJServer12003

**(warn) IJServer12003: Cannot clean old log files. You must remove the old log file manually.
pid=<pid> tid=<tid>**

Variable Information

<pid> = Web server process ID

<tid> = Web server thread ID

Explanation

Old log files cannot be deleted.

User Action

Because old log files may exhaust the free disk space, manually delete old log files beyond the specified number of generations. Refer to "PL/extJava Log Information" in the Operation Guide for information on the log file output destination.

A.2.5.1.2 IJServer12004

(error) IJServer12004: Cannot connect to IJServer. The following are the most common causes of this error: IJServer stops or overloaded, Wrong IP address or port.

**serverName=<serverName> serverPort=<serverPort> host=<host> port=<port> uri=<uri>
errno=<errno> pid=<pid> tid=<tid>**

Variable Information

<serverName> = Server name of Web server

<serverPort> = Port number of Web server

<host> = Host name of container

<port> = Port number of container

<uri> = Web browser request URL

<errno> = Error number

<pid> = Web server process ID

<tid> = Web server thread ID

Explanation

The Web server connector cannot be connected to the container.

Cause

Possible causes are as follows:

1. The container process was forced to stop due to an application timeout.
2. A TCP/IP resource shortage occurred.
When this message is output and the "netstat -a" command lists a large number of "TIME_WAIT" connections between ephemeral ports and server instance ports, it means that the ephemeral ports may be depleted.
3. The container is overloaded. A memory shortage may have occurred in the Java VM.
4. The number of requests that was received exceeded the maximum number of connections to the server instance.
5. The container is in diminished operation.
6. In other cases, an error may have occurred in the container.

System Action

- If the container process concurrency is 1, the Web server connector interrupts connection to the container, and posts a message containing status code 500 (Internal Server Error) to the web browser.
- If the container process concurrency is 2 or more, the Web server connector ends connection to the container and attempts to connect to another container.

If connection to all containers fails, the Web server connector posts a message containing status code 500 (Internal Server Error) to the Web browser.

User Action

1. Tune the TCP/IP parameter. Check the network status with the "netstat -a" command, and check if there is a large number of connections in a "TIME_WAIT" state.
If it was confirmed that the ephemeral port was depleted, release unnecessary ports. Alternatively, increase the number of ports that can be used as ephemeral ports.

2. If this error message is output frequently, increase the server instance (JavaVM) or check the system configuration (hardware and software) and reconfigure an overload-resistant system. Consider upgrading the CPU as needed.

Refer to the event log (system log), or the logs mentioned in "Container" in the Operation Guide. If there is insufficient JavaVM memory ('OutOfMemoryError' occurs), refer to "Java Function Errors" in the Operation Guide, and then take action.

3. Check the logs mentioned in "Container" of the Operation Guide, and if an error was output, take the action advised in the message.

A.2.5.1.3 IJServer12007

(error) IJServer12007: Cannot create socket. The per-process descriptor table is full or out of streams resources. errno=<errno> pid=<pid> tid=<tid>

Variable Information

<errno> = Error number

<pid> = Web server process ID

<tid> = Web server thread ID

Explanation

A socket cannot be created because of a resource shortage.

System Action

The Web server connector interrupted its attempt to connect to the container, and sent the error message status code 500 (Internal Server Error) to the web browser.

User Action

Terminate other applications or increase the number of files that can be opened in the system.

A.2.5.1.4 IJServer12011

(info) IJServer12011: Cleaning up the old log files. file="<filename>" pid=<pid> tid=<tid>

Variable Information

<filename> = Old log file name

<pid> = Web server process ID

<tid> = Web server thread ID

Explanation

Cleaning up the old log files.

A.2.5.1.5 IJServer12016

(info) IJServer12016: Loading of the Web Server Connector properties. conf="<filename>" pid=<pid> tid=<tid>

Variable Information

<filename> = Property file of Web server connector

<pid> = Web server process ID

<tid> = Web server thread ID

Explanation

The property file of the Web server connector is loaded.

A.2.5.1.6 IJServer12017

(error) IJServer12017: No space left on device. directory= "<dir>" pid=<pid> tid=<tid>

Variable Information

<dir> = Directory name

<pid> = Web server process ID

<tid> = Web server thread ID

Explanation

The disk is short of free space.

User Action

Check if there is sufficient space to collect the logs mentioned in "Internal Log" of the Operation Guide. The required size can be calculated from the log size and the number of log generations.

A.2.5.1.7 IJServer12020

(warn) IJServer12020: Rollover log file has already existed. Rollover process is performed next time with the new name. file="<filename>" pid=<pid> tid=<tid>

Variable Information

<filename> = Log to be rotated

<pid> = Web server process ID

<tid> = Web server thread ID

Explanation

A file with the same name as the log file to be rotated already exists.

Many logs were generated in a short period, so rotation could not be performed.

Log rotation will be performed with a new name the next time a message is output.

User Action

Refer to the other messages that were output to the log file, and remove the cause of many logs being output.

A.2.5.1.8 IJServer12027

(error) IJServer12027: The connection of IJServer was aborted. The following are the most common causes of this error: IJServer stops, Web Application timed out, Setting up SSL on IJServer. serverName=<serverName> serverPort=<serverPort> host=<host> port=<port> uri=<uri> errno=<errno> pid=<pid> tid=<tid>

Variable Information

<serverName> = Server name of Web server

<serverPort> = Port number of Web server

<host> = Host name of container

<port> = Port number of container

<uri> = Web browser request URL

<errno> = Error number

<pid> = Web server process ID

<tid> = Web server thread ID

Explanation

The connection with the container has been interrupted.

Cause

Possible causes are as follows:

1. The container process is forcibly stopped because of an application timeout.
2. The container is stopped.
3. The container is temporarily stopped because an error occurred in the Java application.
4. The container is overloaded. A memory shortage may have occurred in the Java VM.
5. The number of requests that was received exceeded the maximum number of connections to the server instance (JavaVM).
6. The Web server connector Server instance IP address:Port Number settings are incorrect.
7. In other cases, an error may have occurred in the container.

System Action

The Web server connector interrupted connection to the container, and sent the error message status code 500 (Internal Server Error) to the web browser.

User Action

Do as follows:

Additionally, if a message was output to a log mentioned in "Container" of the Operation Guide, take the action advised in the message.

1. If this error message is output frequently, use the add-instance subcommand of the `pgx_jadmin` command to increase the number of server instances, or check the system configuration (hardware and software) and reconfigure an overload-resistant system. You may also consider upgrading the CPU.

Refer to the event log (system log), or the logs mentioned in "Container" in the Operation Guide. If there is insufficient JavaVM memory ('OutOfMemoryError' occurs), refer to "Java Function Errors" in the Operation Guide, and then take action.

2. Check the logs mentioned in "Container" of the Operation Guide. If an error has occurred, take action according to the message.

A.2.5.1.9 IJServer12032

(info) IJServer12032: The existing log file is rolled over to a new file. file="<filename>" pid=<pid> tid=<tid>

Variable Information

<filename> =Rotating log

<pid> = Web server process ID

<tid> = Web server thread ID

Explanation

The web server connector log was rotated to a new file.

A.2.5.1.10 IJServer12033

(info) IJServer12033: The most recent Web Server Connector properties have been loaded. conf="<filename>" pid=<pid> tid=<tid>

Variable Information

<filename> = Property file of Web server connector

<pid> = Web server process ID

<tid> = Web server thread ID

Explanation

The latest Web server connector properties have been loaded.

A.2.5.1.11 IJServer12034

(error) IJServer12034: The requests cannot be sent to Web Application.
serverName=<serverName> serverPort=<serverPort> host=<host> port=<port> uri=<uri>
func=<func> errno=<errno> pid=<pid> tid=<tid>

Variable Information

<serverName> = Server name of Web server

<serverPort> = Port number of Web server

<host> = Host name of container

<port> = Port number of container

<uri> = Web browser request URL

<func> = Name of the function in which an error occurred

<errno> = Error number

<pid> = Web server process ID

<tid> = Web server thread ID

Explanation

Data cannot be transferred to the Java application.

Cause

Possible causes are as follows:

- A system resource shortage occurred.
- A network or system error occurred.
- The connection with the container was aborted.

User Action

- Check the event log (system log) for system errors.
- Refer to the User Action in message IJServer12027 and take action.

A.2.5.1.12 IJServer12035

(error) IJServer12035: The requests sent to the Web Application did a timeout. Delay in Web Applications or IJServer overloaded.
serverName=<serverName> serverPort=<serverPort>
host=<host> port=<port> uri=<uri> time=<time> seconds pid=<pid> tid=<tid>

Variable Information

<serverName> = Server name of Web server

<serverPort> = Port number of Web server

<host> = Host name of container

<port> = Port number of container

<uri> = Web browser request URL

<time> = Timeout time

<pid> = Web server process ID

<tid> = Web server thread ID

Explanation

A timeout occurred during data transfer to the Web application. The form data sent from the Java browser cannot be transferred to the Java application.

Cause

Possible causes are as follows:

1. Java application processing was delayed.
2. The container is overloaded. A memory shortage may have occurred in the Java VM.
3. A network error occurred between the Web server and container.

System Action

The Web server connector interrupted connection to the container, and sent the error message status code 500 (Internal Server Error) to the web browser.

User Action

If this error message is output frequently, increase the server instance (JavaVM) or check the system configuration (hardware and software) and reconfigure an overload-resistant system. Consider upgrading the CPU as needed.

1. Check whether a processing delay occurred in the Java application.
2. Refer to the event log (system log), or the logs mentioned in "Container" in the Operation Guide. If there is insufficient JavaVM memory ('OutOfMemoryError' occurs), refer to "Java Function Errors" in the Operation Guide, and then take action.

A.2.5.1.13 IJServer12036

(error) IJServer12036: The response of the Web Application cannot be received.
serverName=<serverName> serverPort=<serverPort> host=<host> port=<port> uri=<uri>
func=<func> errno=<errno> pid=<pid> tid=<tid>

Variable Information

<serverName> = Server name of Web server

<serverPort> = Port number of Web server

<host> = Host name of container

<port> = Port number of container

<uri> = Web browser request URL

<func> = Name of the function in which an error occurred

<errno> = Error number

<pid> = Web server process ID

<tid> = Web server thread ID

Explanation

A response from the Java application cannot be received.

Cause

Possible causes are as follows:

- A system resource shortage occurred.
- A network or system error occurred.
- The connection with the container was aborted.

System Action

The Web server connector interrupted connection to the container, and sent the error message status code 500 (Internal Server Error) to the web browser.

User Action

- Check the event log (system log) for system errors.
- Refer to the User Action in message IJServer12027 and take action.

A.2.5.1.14 IJServer12037

(error) IJServer12037: Unable to create log file. Missing write permission for log file or file is already open with write access. Add write permission on the file or directory. file=" <filename>" errno=<errno> pid=<pid> tid=<tid>

Variable Information

<filename> = File name

<error> = Error number

<pid> = Web server process ID

<tid> = Web server thread ID

Explanation

Web server connector message cannot be logged.

Cause

Possible causes are as follows:

1. Write permission is not granted to the log file or the directory to which a log is to be output.
2. The log file has been opened by another application.
3. A directory having the same name as the log file exists.
4. When on a Windows(R) system, the network drive is specified to the log output directory of a Web server connector.

User Action

1. Close the log file.
2. If <filename> is a directory, change or delete the directory.
3. Specify the path name for a log output directory to be on a local disk
4. Move or delete <filename>.
5. Restart the instance.



A.2.5.1.15 IJServer12038

(error) IJServer12038: Unable to create log file. Too many open files. Close some of the opened files or close any unnecessary applications. file="<filename>" errno=<errno> pid=<pid> tid=<tid>

Variable Information

<filename> = File name

<error> = Error number

<pid> = Web server process ID

<tid> = Web server thread ID

Explanation

A Web server connector log file could not be created

Cause

Because too many files were open.

User Action

Terminate other applications, or increase the number of files that can be opened in the system.

A.2.5.1.16 IJServer12039

(error) IJServer12039: Unable to open file. No such file or permission denied. Add read permission on the file. file="<filename>" errno=<errno> pid=<pid> tid=<tid>

Variable Information

<filename> = File name

<error> = Error number

<pid> = Web server process ID

<tid> = Web server thread ID

Explanation

The indicated file cannot be opened.

Cause

Possible causes are as follows:

1. The file does not exist.
2. Read permission is not granted to the file.
3. Too many files are open.

User Action

1. Check whether the file exists.
2. Grant the file read permission.
3. Terminate other applications, or increase the number of files that can be opened in the system.

A.2.5.1.17 IJServer12040

(warn) IJServer12040: Unable to remove old log file. Missing write permission for old log file or file is already open with write access. You must remove the old log file manually. file="<filename>" errno=<errno> pid=<pid> tid=<tid>

Variable Information

<filename> = Name of old log file

<error> = Error number

<pid> = Web server process ID

<tid> = Web server thread ID

Explanation

The indicated old log file cannot be deleted.

Cause

Possible causes are as follows:

- Permission to write to the old log file is not granted.
- The old log file is opened by another application.

User Action

Because the old log file may exhaust the free disk space, manually delete the old log file.

A.2.5.1.18 IJServer12041

(warn) IJServer12041: Unable to rollover log file. pid=<pid> tid=<tid>

Variable Information

<pid> = Web server process ID

<tid> = Web server thread ID

Explanation

Log file rollover failed.

Cause

A log file could not be rolled over.

User Action

Take action according to the message that was output to the Web server connector log or event log (system log).

A.2.5.1.19 IJServer12042

(warn) IJServer12042: Unable to run Web Server Connector. conf="<filename>" webtype=<webtype> pid=<pid> tid=<tid>

Variable Information

<filename> = Property file of Web server connector

"none" is output if an error occurs immediately after the Web server connector is activated.

<webtype> = Web server I/F which the Web server connector is using.

"nsapi" is output when Microsoft (R) Internet Information Services is used, and "isapi" is output when Sun Java System Web Server is used.

This variable information is not outputted at the time of use of Interstage HTTP Server.

Property file of Web server connector

"none" is output if an error occurs immediately after the Web server connector is activated.

<pid> = Web server process ID

<tid> = Web server thread ID

Explanation

The Web server connector cannot be activated.

System Action

The Web server connector sent the error message status code 404 (Not Found) to the web browser.

The status code 404 (Not Found) may be notified. Moreover, after this message is output, the status code 404 (Not Found) may be notified also to other requests.

User Action

Take action according to the message that was output to the Web server connector log or event log (system log). If the Web server is active, stop it and restart it.

Note

In Microsoft(R) Internet Information Services 6.0, this message is output after the Web Server is started and the first access is made from the client. In Web Servers other than Microsoft(R) Internet Information Services 6.0, this message is output when the Web Server is started.

A.2.5.1.20 IJServer12043

(error) IJServer12043: Unable to write log file. Device was removed or an I/O error occurred. file="<filename>" errno=<errno> pid=<pid> tid=<tid>

Variable Information

<filename> = File name

<errno> = Error number

<pid> = Web server process ID

<tid> = Web server thread ID

Explanation

Web server connector messages cannot be logged.

Cause

An I/O error occurred. The disk was removed or the availabilities of a disk are insufficient.

User Action

Check the event viewer (system log) to check for system errors.

A.2.5.1.21 IJServer12044

(error) IJServer12044: Web Application does not respond. Web Application has timed out. Delay in Web Applications or IJServer overloaded. serverName=<serverName> serverPort=<serverPort> host=<host> port=<port> uri=<uri> time=<time> seconds pid=<pid> tid=<tid>

Variable Information

<serverName> = Server name of Web server

<serverPort> = Port number of Web server

<host> = Host name of container

<port> = Port number of container

<uri> = Web browser request URI

<time> = Timeout time

<pid> = Web server process ID

<tid> = Web server thread ID

Explanation

The Web application does not respond. A timeout occurred during waiting for a response from the Java application.

Cause

Possible causes are as follows:

1. The Java application failed to respond within the specified timeout time.
2. Java application processing was delayed.
3. The container is overloaded. A memory shortage may have occurred in the Java VM.
4. A network error occurred between the Web server and container.

System Action

The Web server connector interrupted connection to the container, and sent the error message status code 500 (Internal Server Error) to the web browser.

User Action

1. Check whether a processing delay or a hang-up occurred in the Java application.
2. If this error message is produced frequently, increase the server instances (Java VM) by referring to "Adding or Deleting Server Instances (Java VM)" under "Setting up and Operating PL/extJava" in the Operation Guide, or check the system configuration (hardware and software) and reconfigure an overload-resistant system. Consider upgrading the CPU as needed.

Refer to the event log (system log), or the logs mentioned in "Container" in the Operation Guide. If there is insufficient JavaVM memory ('OutOfMemoryError' occurs), refer to "Java Function Errors" in the Operation Guide, and then take action.

A.2.5.1.22 IJServer12045

**(warn) IJServer12045: Web Server Connector properties could not be loaded.
conf="<filename>" pid=<pid> tid=<tid>**

Variable Information

<filename> = Property file of Web server connector

<pid> = Web server process ID

<tid> = Web server thread ID

Explanation

The property file of the Web server connector cannot be loaded. The Web server connector operates with the properties most recently loaded, or those properties used at start of the Web server.

W

The Web server connector operates with the properties most recently loaded, or those properties used at start of the Web server.

L

The Web connector posts status code 500 (Internal Server Error) to the Web browser.

The Web connector posts status code 500 (Internal Server Error) to the Web browser also to the request after this message was output.

User Action

Refer to the Operation Guide, and take the action advised in the message output to the internal log or event log (system log).

A.2.5.1.23 IJServer12047

(info) IJServer12047: Web Server Connector running. conf="<filename>" pid=<pid> tid=<tid>

Variable Information

<filename>= Web server connector property file
<pid>= Web server process ID
<tid>= Web server thread ID

Explanation

The Web server connector has been activated.

A.2.5.1.24 IJServer12048

(info) IJServer12048: Web Server Connector stops running. conf="<filename>" pid=<pid> tid=<tid>

Variable Information

<filename>= Web server connector property file
<pid>= Web server process ID
<tid>= Web server thread ID

Explanation

The Web server connector has been stopped.

A.2.5.1.25 IJServer12049

(error) IJServer12049: Unable to open file. Too many open files. Close some of the opened files or close any unnecessary applications. file="<filename>" errno=<errno> pid=<pid> tid=<tid>

Variable Information

<filename> = File name
<errno> = Error number
<pid> = Web server process ID
<tid> = Web server thread ID

Explanation

A file cannot be opened.

Cause

There are too many opened files.

User Action

End other applications or increase the number of files that can be opened by the system.

A.2.5.1.26 IJServer12050

(error) IJServer12050: Unable to open file. Missing write permission for file or file is already open with write access. Add write permission on the file or directory. file="<filename>" errno=<errno> pid=<pid> tid=<tid>

Variable Information

<filename> = File name
<errno> = Error number

<pid> = Web server process ID

<tid> = Web server thread ID

Explanation

Unable to open file.

Cause

Possible causes are as follows:

- There is no authority written in the directory to which the file exists.
- The file is already opened by another application.
- A directory exists with the same name as the file.

User Action

Close the file.

When <filename> is a directory, move the directory or delete the directory.

A.2.5.1.27 IJServer12051

(error) IJServer12051: Unable to read file. Device was removed or an I/O error occurred. file="<filename>" errno=<errno> pid=<pid> tid=<tid>

Variable Information

<filename> = File name

<errno> = Error number

<pid> = Web server process ID

<tid> = Web server thread ID

Explanation

Unable to read file.

Cause

The I/O error occurred. The disk may have been removed.

User Action

Check whether with reference to an event log (system log), there are any abnormalities in a system.

A.2.5.1.28 IJServer12052

(error) IJServer12052: Unable to write file. Device was removed or an I/O error occurred. file="<filename>" errno=<errno> pid=<pid> tid=<tid>

Variable Information

<filename> = File name

<errno> = Error number

<pid> = Web server process ID

<tid> = Web server thread ID

Explanation

Unable to write file.

Cause

The I/O error occurred. The disk may have been removed, or be insufficiently available.

User Action

Check whether with reference to an event log (system log), there are any abnormalities in a system.

A.2.5.1.29 IJServer12054

(error) IJServer12054: HTTP request which contains wrong header was received. header=<http_header> pid=<pid> tid=<tid>

Variable Information

<http_header> = HTTP header

<pid> = Web server process ID

<tid> = Web server thread ID

Explanation

An HTTP request containing an illegal HTTP header was received.

Cause

The server may have been attacked externally.

System Action

The Web server connector aborts the connection to the container and notifies a status code 400 (Bad Request) message to the Web browser.

User Action

Based on the IP address or host name of the request source that is output to the access log described in "Web Server" in the Operation Guide, investigate the possibility that an attack has occurred.

A.2.5.1.30 IJServer12055

(error) IJServer12055: Web Server does not exist. pid=<pid> tid=<tid>

Variable Information

<pid> = Web server process ID

<tid> = Web server thread ID

Explanation

The Web server does not exist.

Cause

A system error occurred.

User Action

Contact a service engineer.

A.2.5.1.31 IJServer12056

(error) IJServer12056: A system error was returned by the operating system. func=<func> error=<error> pid=<pid> tid=<tid>

Variable Information

<func>= Function in which the error occurred

<error>= Error ID

<pid>= Web server process ID

<tid>= Web server thread ID

Explanation

A system error was returned by the operating system.

Cause

An operating system error occurred in the processing of the web server connector.

Another program may have locked an internal file of the web server connector.

User Action

Check if another program has locked a file under "Symfoware Server *installDir*java". If it has, stop the processing.

If the problem cannot be resolved, contact Fujitsu technical support.

A.2.5.1.32 IJServer12057

(error) IJServer12057: Unable to initialize Web Server Connector. pid=<pid> tid=<tid>

Variable Information

<pid>= Web server process ID

<tid>= Web server thread ID

Explanation

Web server connector initialization failed.

User Action

Contact Fujitsu technical support.

A.2.5.1.33 IJServer12058

(warn) IJServer12058: Web Server Connector property file contains an illegal value. conf=<filename> section=<section> key=<key> value=<value> pid=<pid> tid=<tid>

Variable Information

<filename>= Web server connector property file

<section>= Section in the web server connector property file

<key>= Key in the web server connector property file

<value>= Value specified in the web server connector property file

<pid>= Web server process ID

<tid>= Web server thread ID

Explanation

An invalid value was set in the web server connector property file.

User Action

Contact Fujitsu technical support.

A.2.5.1.34 IJServer12060

(error) IJServer12060: Internal error. detail={0} pid=<pid> tid=<tid>

Variable Information

{0}: Detailed message
<pid>= Web server process ID
<tid>= Web server thread ID

Explanation

An internal error occurred.

User Action

Contact Fujitsu technical support.

A.2.5.2 When there is no Message Number

If not explained in the Messages, identify the cause of the problem from the message body and take appropriate action. If the problem still exists, contact Fujitsu technical support.

A.2.6 Messages that Contain "IJ6INIT" in the Message ID

A.2.6.1 IJ6INIT0000 to IJ6INIT0099

INFO: IJ6INIT0001: ij6init command is started.

Explanation

Initialization of the Java EE environment has started.

INFO: IJ6INIT0002: ij6init command executed successfully.

Explanation

Initialization of the Java EE environment has finished.

ERROR: IJ6INIT0101: ij6init command failed.

Explanation

Initialization of the Java EE environment failed.

System Action

Processing is interrupted.

User Action

Refer to the error message that was output at the same time, and take the required action.

ERROR: IJ6INIT0102: Required file is not found. file='{0}'

Variable Information

{0}: File name

Explanation

The file was not found.

System Action

Processing is interrupted.

User Action

Check if the file exists.

If it does not exist, there may be a problem in the environment. Reinstall the product.

If the problem still exists, contact Fujitsu technical support.

ERROR: IJ6INIT0103: Has no permission for executing the command. cmd='{0}'

Variable Information

{0}: Command name

Explanation

The user does not have the privileges required to execute the command.

System Action

Processing is interrupted.

User Action

- Check the privileges of the user who executed the command. You must log in as the instance administrator to be able to execute this command.
- Check the execution privileges for commands shown in the variable information. If execution privileges have not been assigned, there may be a problem in the environment. Reinstall the product.
- If the problem still exists, contact Fujitsu technical support.

ERROR: IJ6INIT0104: Failed to get the Java information. details1='{0}'. details2='{1}'

Variable Information

{0}: Internal information

{1}: Internal information

Explanation

Failed to obtain the Java information.

System Action

Processing is interrupted.

User Action

- There may be insufficient system memory. Reexecute after stopping unnecessary services.
- If the problem still exists, contact Fujitsu technical support.

ERROR: IJ6INIT0105: File does not created. file='{0}'

Variable Information

{0}: File name

Explanation

Required files have not been created.

System Action

Processing is interrupted.

User Action

Contact Fujitsu technical support.

ERROR: IJ6INIT0106: Internal error occurred. details='{0}'

Variable Information

{0}: Details

Explanation

An internal error occurred.

System Action

Processing is interrupted.

User Action

- There may be a problem in the environment. Reinstall the product.
- If the problem still exists, contact Fujitsu technical support.

A.2.6.2 IJ6INIT1100 to IJ6INIT1199

ERROR: IJ6INIT1101: Error occurred before init the log. details='{0}'

Variable Information

{0}: Detail information

Explanation

An unexpected error occurred.

System Action

Processing is interrupted.

User Action

Refer to messages output to the console, or to the stack trace, and take the required action.

If the problem still exists, manually collect a copy of the stack trace and then contact Fujitsu technical support.

ERROR: IJ6INIT1102: Unexpected error occurred before init the log. details='{0}'

Variable Information

{0}: Detail information

Explanation

An unexpected error occurred.

System Action

Processing is interrupted.

User Action

Refer to Detail information {0}, and take the required action.

If the problem still exists, contact Fujitsu technical support.

ERROR: IJ6INIT1103: Unexpected error occurred. details='{0}'

Variable Information

{0}: Detail information

Explanation

An unexpected error occurred.

System Action

Processing is interrupted.

User Action

Refer to Detail information {0}, and take the required action.

If the problem still exists, contact Fujitsu technical support.

ERROR: IJ6INIT1104: Failed to get install directory

Explanation

An unexpected error occurred.

System Action

Processing is interrupted.

User Action

Contact Fujitsu technical support.

ERROR: IJ6INIT1105: Unexpected internal error Occured. details='{0}'

Variable Information

{0}: Internal information

Explanation

An unexpected error occurred.

System Action

Processing is interrupted.

User Action

Reinstall the product.

If the problem still exists, contact Fujitsu technical support.

ERROR: IJ6INIT1106: Failed to initialize the log file. file='{0}'**Variable Information**

{0}: File name

Explanation

Log initialization failed.

System Action

Processing is interrupted.

User Action

Manually collect a copy of messages output to the console, or to the stack trace, and then contact Fujitsu technical support.

ERROR: IJ6INIT1107: Failed to start process.**Explanation**

Process startup failed.

System Action

Processing is interrupted.

User Action

If messages have been output before or after, refer to the error message that was output, and take the required action.

If the problem still exists, contact Fujitsu technical support.

ERROR: IJ6INIT1108: Failed to execute command. cmd='{0}'. details='{1}'**Variable Information**

{0}: Command name

{1}: Detail information

Explanation

Execution of the command failed.

System Action

Processing is interrupted.

User Action

Refer to Detail information {1}, and take the required action.

If the problem still exists, contact Fujitsu technical support.

ERROR: IJ6INIT1109: Failed to execute command. cmd='{0}'. code='{1}'**Variable Information**

{0}: Command name

{1}: Return value

Explanation

Execution of the command failed.

System Action

Processing is interrupted.

User Action

If messages have been output before or after, refer to the error message that was output, and take the required action.

If the problem still exists, contact Fujitsu technical support.

ERROR: IJ6INIT1110: Failed to create domain.

Explanation

Failed to create the Java EE operating environment.

System Action

Processing is interrupted.

User Action

Check the following and after removing the problem, reexecute.

- Is there a problem in the directory specified as the *domainRootDir*?
- Is the parent directory of the specified directory in the *domainRootDir*?
- Is either an empty or non-existent directory specified as the *domainRootDir*?
- Is there permission to write to the *domainRootDir*?

Ensure that the directory specified in the *domainRootDir* satisfies the above and then reexecute.

ERROR: IJ6INIT1111: Failed to setup PCMI service. details='{0}'

Variable Information

{0}: Detail information

Explanation

Set up of the PCMI service failed.

System Action

Processing is interrupted.

User Action

Refer to Detail information {0}, and take the required action.

ERROR: IJ6INIT1112: Failed to rollback PCMI service. details='{0}'

Variable Information

{0}: Detail information

Explanation

The deletion process of the PCMI service failed.

System Action

Processing is interrupted.

User Action

Refer to messages output before and after this message, and take the required action.

ERROR: IJ6INIT1113: Failed to create symbolic link. src='{0}', dest='{1}'. details='{2}'

Variable Information

{0}: Symbolic link source

{1}: Symbolic link destination

{2}: Detail information

Explanation

Failed to create the symbolic link.

System Action

Processing is interrupted.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

ERROR: IJ6INIT1114: File already exist. file='{0}'

Variable Information

{0}: File name

Explanation

The file already exists.

System Action

Processing is interrupted.

User Action

The file already exists at the destination. Delete the file and then reexecute.

ERROR: IJ6INIT1115: Failed to create the directory. file='{0}'

Variable Information

{0}: Directory name

Explanation

Failed to create the directory.

System Action

Processing is interrupted.

User Action

Check the following and after removing the problem, reexecute.

- Does the directory have write permission?
- Does the directory already exist?
- Is there sufficient disk space for the directory to be created?

ERROR: IJ6INIT1116: Failed to copy the file. src='{0}'. dest='{1}'

Variable Information

{0}: Source file

{1}: Destination file

Explanation

Failed to copy the file.

System Action

Processing is interrupted.

User Action

Check the following and after removing the problem, reexecute.

- Does the destination directory have write permission?
- Does the file already exist at the destination?
- Is there sufficient disk space at the destination?
- Does the source file exist?

ERROR: IJ6INIT1117: Failed to delete the file. file='{0}'

Variable Information

{0}: File name

Explanation

Failed to delete the file.

System Action

Processing is interrupted.

User Action

Ensure that the file displayed in Variable Information {0} is not being used in another process.

If the file is being used, stop the program and then reexecute it.

ERROR: IJ6INIT1118: Failed to compare the paths. path1='{0}', path2='{1}'

Variable Information

{0}: Internal information

{1}: Internal information

Explanation

An internal error occurred.

System Action

Processing is interrupted.

User Action

Contact Fujitsu technical support.

ERROR: IJ6INIT1119: Failed to get canonical path. path='{0}'

Variable Information

{0}: Internal information

Explanation

An internal error occurred.

System Action

Processing is interrupted.

User Action

Contact Fujitsu technical support.

ERROR: IJ6INIT1120: Failed to create the property file. file='{0}'

Variable Information

{0}: File name

Explanation

Failed to create the file.

System Action

Processing is interrupted.

User Action

Check the following and after removing the problem, reexecute.

- Does the destination directory have write permission?
- Does the file already exist at the destination?
- Is there sufficient disk space at the destination?

ERROR: IJ6INIT1121: Failed to load the properties file. file='{0}'

Variable Information

{0}: File name

Explanation

Failed to load the properties file.

System Action

Processing is interrupted.

User Action

Check the following and after removing the problem, reexecute.

- Does the file exist?
- Is the file being used by another program?

ERROR: IJ6INIT1122: Can not create the file using the template file. src='{0}'. dest='{1}'

Variable Information

{0}: File name

{1}: File name

Explanation

Failed to create the file.

System Action

Processing is interrupted.

User Action

Check the following and after removing the problem, reexecute.

- Does the destination of {1} have write permission?
- Does the file already exist at the destination of {1} ?
- Is there sufficient disk space at the destination of {1} ?
- Does the file {0} exist?

ERROR: IJ6INIT1123: Failed to store the login information. details='{0}'

Variable Information

{0}: Detail information

Explanation

An internal error occurred.

System Action

Processing is interrupted.

User Action

Refer to Detail information {0}, and take the required action.

ERROR: IJ6INIT1124: Failed to setup Java EE 6 environment. details='{0}'

Variable Information

{0}: Detail information

Explanation

Failed to set up the Java EE operating environment.

System Action

Processing is interrupted.

User Action

Refer to Detail information {0}, and take the required action.

ERROR: IJ6INIT1125: Failed to check permission. details='{0}'

Variable Information

{0}: Detail information

Explanation

An internal error occurred.

System Action

Processing is interrupted.

User Action

Refer to Detail information {0}, and take the required action.

ERROR: IJ6INIT1126: Operation not permitted.

Explanation

You do not have the privileges required to execute this command.

System Action

Processing is interrupted.

User Action

Check the privileges of the user who executed the command.



The command must be executed by a system administrator user.

If the problem still exists, contact Fujitsu technical support.

ERROR: IJ6INIT1127: Failed to rollback event source. details='{0}'

Variable Information

{0}: Internal information

Explanation

Failed to perform rollback processing when the setup failed.

System Action

The failed process is skipped, and processing is continued.

User Action

Reinstall the product.

If the problem still exists, contact Fujitsu technical support.

ERROR: IJ6INIT1128: Failed to get system properties.

Explanation

Failed to obtain the system properties.

System Action

Processing is interrupted.

User Action

Allow access to the system properties.

If the problem still exists, contact Fujitsu technical support.

ERROR: IJ6INIT1129: Failed to load file. file='{0}'

Variable Information

{0}: File name

Explanation

Loading of the file has failed.

System Action

Processing is interrupted.

User Action

If the file that is assigned in the variable information was created by the user, remove the cause of the problem that is preventing the file from loading.

If the problem stillexists, or if the file that is assigned in the variable information was not created by the user, contact Fujitsu technical support.

ERROR: IJ6INIT1130: Failed to create file. file='{0}'

Variable Information

{0}: File name

Explanation

Creation of the file has failed.

System Action

Processing is interrupted.

User Action

Check the privileges of the user who executed the command. The user must have write privileges for the domain root directory.

If the problem still exists, contact Fujitsu technical support.

ERROR: IJ6INIT1131: Invalid option. option='{0}'

Variable Information

{0}: Command line option

Explanation

An invalid command line option is specified.

System Action

Processing is interrupted.

User Action

Ensure that the specified command line option is correct, and then reexecute the command.

If the problem still exists, contact Fujitsu technical support.

ERROR: IJ6INIT1132: Insufficient arguments.

Explanation

The command line option is used incorrectly.

System Action

Processing is interrupted.

User Action

Ensure the command line option is specified correctly, and then reexecute the command.

If the problem still exists, contact Fujitsu technical support.

ERROR: IJ6INIT1133: Required argument not found. arg='{0}'

Variable Information

{0}: Command line option

Explanation

The required command line option is not specified.

System Action

Processing is interrupted.

User Action

Ensure that the required command line option is specified, and then reexecute the command.

If the problem still exists, contact Fujitsu technical support.

ERROR: IJ6INIT1134: File not found. file='{0}'

Variable Information

{0}: Internal information

Explanation

Resources required for setup are missing.

System Action

Processing is interrupted.

User Action

There may be a problem in the environment in which the product is installed. Reinstall the product.

If the problem still exists, contact Fujitsu technical support.

A.2.7 Messages that Contain "JE6SETUP" in the Message ID

A.2.7.1 JE6SETUP0000 to JE6SETUP0999

INFO: JE6SETUP0001: je6setup command started.

Explanation

Setup processing has started.

INFO: JE6SETUP0002: je6setup command executed successfully.

Explanation

Setup processing has finished.

ERROR: JE6SETUP0101: je6setup command failed.

Explanation

Setup failed.

System Action

Processing is interrupted.

User Action

Refer to any other messages that were output at the same time, and take the required action.

ERROR: JE6SETUP0102: File not found. file='{0}'

Variable Information

{0}: File name

Explanation

The file was not found.

System Action

Processing is interrupted.

User Action

- Check if the file that is shown in the variable information exists. If it does not exist, there may be a problem in the environment. Reinstall the product.
- If the problem still exist, contact Fujitsu technical support.

ERROR: JE6SETUP0103: JE6SETUP0103: Command not executable. cmd='{0}'

Variable Information

{0}: Command name

Explanation

You do not have the privileges required to execute this command.

System Action

Processing is interrupted.

User Action

- Check the privileges of the user who executed the command.

W

The command must be executed by an operating system administrator user.

L

The command must be executed by a system administrator user.

L

- Check the execution privileges for commands shown in the variable information. If execution privileges have not been assigned, there may be a problem in the environment. Reinstall the product.

A.2.8 Messages that Contain "JE6UNSETUP" in the Message ID

A.2.8.1 JE6UNSETUP

FJJAVAEE6: ERROR: JE6UNSETUP: The Java EE 6 shared directory is not specified.

Explanation

The domain root directory (--sharedir) has not been specified.

System Action

Processing is interrupted.

User Action

Contact Fujitsu technical support.

FJJAVAEE6: ERROR: JE6UNSETUP: The Java EE 6 shared directory is not found. directory='{0}'.

Variable Information

{0}: Domain root directory path

Explanation

The specified domain root directory does not exist.

System Action

Processing is interrupted.

User Action

Contact Fujitsu technical support.

FJJAVAEE6: ERROR: JE6UNSETUP: The PCMI installed directory is not specified.

Explanation

The PCMI installation directory (--pcmipath) is not specified.

System Action

Processing is interrupted.

User Action

Contact Fujitsu technical support.

FJJAVAEE6: ERROR: JE6UNSETUP: The PCMI installed directory is not found. directory='{0}'.

Variable Information

{0}: PCMI installation directory path

Explanation

The specified PCMI installation directory does not exist.

System Action

Processing is interrupted.

User Action

Contact Fujitsu technical support.

FJJAVAEE6: ERROR: JE6UNSETUP: The PCMI instance directory is not found. directory='{0}'.

Variable Information

{0}: PCMI directory path

Explanation

An attempt was made to remove the setup of a domain root directory environment that is not using PCMI.

System Action

Processing is interrupted.

User Action

Contact Fujitsu technical support.

FJJAVAEE6: ERROR: JE6UNSETUP: Need --pcmi and --pcmipath paramaters because the PCMI instance directory is found. directory='{0}'.

Variable Information

{0}: PCMI directory path

Explanation

An attempt was made to remove the setup of a domain root directory environment that is using PCMI.

System Action

Processing is interrupted.

User Action

Contact Fujitsu technical support.

FJJAVAEE6: ERROR: JE6UNSETUP: The je6unsetup command failed.

Explanation

Failed to remove the FJJavaEE6 setup.

System Action

Processing is interrupted.

User Action

Contact Fujitsu technical support.

FJJAVAAE6: INFO: JE6UNSETUP: The je6unsetup command is started.

Explanation

Removal of the FJJAVAAE6 setup has started.

FJJAVAAE6: INFO: JE6UNSETUP: The je6unsetup command executed successfully.

Explanation

The FJJavaEE6 setup was removed successfully.

A.2.9 Messages that Contain "IJ6SETOPID" in the Message ID

A.2.9.1 IJ6SETOPID000 to IJ6SETOPID099

ERROR: IJ6SETOPID003: File {0} not found.

Variable Information

{0}: File name

Explanation

Execution of the command failed because the {0} file does not exist.

System Action

Processing is interrupted.

User Action

Possible causes as to why the file does not exist are as follows:

- It has been deleted
- An error occurred in referencing the shared disk.
- Check if the {0} file exists, and recover it to a state where it can be referenced. If recovery is not possible, contact Fujitsu technical support.

WARNING: IJ6SETOPID004: The environment was restored.

Explanation

The environment has been restored.

System Action

Processing is continued.

User Action

If no errors occur after this message, there is no need to take further action.

ERROR: IJ6SETOPID006: The username needs to be specified with the -u option.

Explanation

Execution of the command failed because the user name has not been specified.

System Action

Processing is interrupted.

User Action

Specify the correct user name while referring to the manual, and reexecute the command.

ERROR: IJ6SETOPID008: The specified user does not exist.

Explanation

Execution of the command failed because a user who does not exist was specified.

System Action

Processing is interrupted.

User Action

Specify an existing user name while referring to the manual, and reexecute the command.

ERROR: IJ6SETOPID010: The PCMI service has not been stopped.

Explanation

The PCMI service has not been stopped.

System Action

Processing is interrupted.

User Action

Reexecute the command after stopping the instance.

ERROR: IJ6SETOPID011: The Message Queue Broker has not been stopped.

Explanation

The message broker has not been stopped.

System Action

Processing is interrupted.

User Action

Reexecute the command after stopping the instance.

ERROR: IJ6SETOPID013: An error occurred when change file's owner. File name={0}

Variable Information

{0}: File name

Explanation

Execution of the command failed because an error occurred when changing the file owner.

System Action

Processing is interrupted.

User Action

Possible causes as to why the file owner cannot be changed are as follows:

- The file has been deleted
- An error occurred in referencing the shared disk

Check if the {0} file exists, and recover it to state where it can be referenced. If it is not possible to recover the file, contact Fujitsu technical support.

ERROR: IJSETOPID014: The status of service was not able to be acquired.

Explanation

Execution of the command failed because the status of the service could not be obtained.

System Action

Processing is interrupted.

User Action

A problem may have occurred with the PL/extJava. Perform the following actions:

- If a message has been output at the same time, take the action indicated in the message.
- Recover PL/extJava if possible.

If the above action is not applicable and the problem still exists, contact Fujitsu technical support.

A.2.10 Messages that Contain "JDBCRA" in the Message ID

A.2.10.1 JDBCRA0000 to JDBCRA0099

JDBCRA0002: Class name is wrong or classpath is not set for : {0}

Variable Information

{0}: Class name

Explanation

The specified class name is incorrect, or the classpath is not set.

System Action

Processing is interrupted.

User Action

Ensure that the specified class name is correct, or that the classpath for the specified class is set correctly.

A.2.10.2 When there is no Message Number

If not explained in the Messages, identify the cause of the problem from the message body and take appropriate action. If the problem still exists, contact Fujitsu technical support.

A.2.11 Messages that Contain "NAM" in the Message ID

A.2.11.1 NAM1000 to NAM1099

NAM1007: Problem with membership change notification. Exception occurred : {0}

Variable Information

{0}: Exception information

Explanation

An error occurred with the JDBC resources.

System Action

Processing is continued.

User Action

Refer to information output after this message, and remove the cause of the error.

A.2.12 Messages that Contain "OM" in the Message ID

A.2.12.1 OM1000 to OM1099

ERROR: ISJEE_OM1001: The shutdown time of cluster exceeded the process monitoring time: CLUSTER={0} INSTANCE={1} PID={2}

Variable Information

{0}: Database name
{1}: Server instance (Java VM) name
{2}: Process ID

Explanation

The processing to stop the container did not complete within the process monitoring time.

System Action

The server instance (Java VM) was stopped by force.

User Action

There is no response from the Java application, or processing may have been delayed. Refer to "No Response from Java Functions" in the Operation Guide, and take the required action.

ERROR: ISJEE_OM1003: All the application processes have been terminated: CLUSTER={0}

Variable Information

{0}: Database name

Explanation

The container failed to restart automatically, and all active server instances (Java VM) were stopped.

System Action

The container is stopped.

User Action

If any messages have been output to the event log (Windows(R)) or the system log (Linux) before or after this message, take the required action and investigate the cause of instance startup failure.

**ERROR: ISJEE_OM1004: The application process could not be reactivated automatically:
CLUSTER={0} INSTANCE={1} PID={2}**

Variable Information

{0}: Database name
{1}: Server instance (Java VM) name
{2}: Process ID

Explanation

Automatic restart processing for a server instance (Java VM) failed after the server instance (Java VM) terminated abnormally.

System Action

The container is stopped.
However, if one or more server instances (Java VM) of a container remain, processing is continued.

User Action

If any messages have been output to the event log (Windows(R)) or the system log (Linux) before or after this message, take the required action and investigate the cause of abnormal termination of the server instance (Java VM).

**ERROR: ISJEE_OM1006: Error occurred during startup of server application running under
cluster: CLUSTER={0} INSTANCE={1} PID={2}**

Variable Information

{0}: Database name
{1}: Server instance (Java VM) name
{2}: Process ID

Explanation

An error occurred during the start processing of the server instance (Java VM).

System Action

Container processing is interrupted.

User Action

If any messages have been output to the event log (Windows(R)) or the system log (Linux) before or after this message, take the required action and investigate the cause of instance startup failure.

ERROR: OM1010: Cluster is stopped: CLUSTER={0}

Variable Information

{0}: Database name

Explanation

The container has stopped.

System Action

Container processing is interrupted.

User Action

If any messages have been output to the event log (Windows(R)) or the system log (Linux) before or after this message, take the required action and investigate the cause of instance stopping failure.

ERROR: OM1011: A server application running under the cluster terminated abnormally: CLUSTER={0} INSTANCE={1} PID={2}

Variable Information

{0}: Database name
{1}: Server instance (Java VM) name
{2}: Process ID

Explanation

The server instance (Java VM) has terminated abnormally.

System Action

Processing is interrupted.

User Action

If any messages have been output to the event log (Windows(R)) or the system log (Linux) before or after this message, take the required action and investigate the cause of abnormal termination of the server instance (Java VM).

ERROR: OM1012: A system error occurred: CODE='{0}'

Variable Information

{0}: Error code

Explanation

A system error occurred.

System Action

Processing is interrupted.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

ERROR: OM1013: No response from JavaVM: CLUSTER={0} INSTANCE={1} PID={2}

Variable Information

{0}: Database name
{1}: Server instance (Java VM) name
{2}: Process ID

Explanation

There is no response from the server instance (Java VM). There may be a high load on the system, or insufficient memory.

System Action

Processing is continued.

User Action

Check if there is sufficient available memory.

Stop other applications, and reduce the load on the machine.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

ERROR: OM1014: Cluster quit abnormally: CLUSTER={0}

Variable Information

{0}:Database name

Explanation

The container has stopped because the server instance (Java VM) terminated abnormally.

System Action

The container is stopped.

User Action

If any messages have been output to the event log (Windows(R)) or the system log (Linux) before or after this message, take the required action and investigate the cause of abnormal termination of the server instance (Java VM). Restart the instance after removing the cause.

INFO: OM1015: Cluster was started up: CLUSTER={0}

Variable Information

{0}:Database name

Explanation

The container has started.

INFO: OM1016: Cluster was stopped: CLUSTER={0}

Variable Information

{0}:Database name

Explanation

The container has stopped.

INFO: OM1017: Cluster was stopped forcibly: CLUSTER={0}

Variable Information

{0}:Database name

Explanation

The container was stopped by force.

WARNING: OM1018: The process has stopped because JavaVM ran out of memory: CLUSTER={0} KIND={1} INSTANCE={2} PID={3}

Variable Information

{0}:Database name

{1}:Memory type code

{1}: Server instance (Java VM) name

{2}: Process ID

Explanation

There is insufficient Java VM heap area, therefore the container process stopped.

When Process ID {3} is "none", the process ID cannot be obtained because of one of the following causes:

- An incorrect Java VM option is used during the process startup

- The port used for debugging of the container is duplicated with the port of another server instance (Java VM)
- Debugging is performed for a container with 2 or more server instances (Java VM)
- The process is stopped using System.exit

System Action

The container process for which there is insufficient Java VM heap area is stopped.

User Action

If this message is output frequently, change the heap area specified in the Java VM option as follows.

When Memory type code: 0 (C heap area)

Reestimate the memory required to use the container, and check if sufficient memory is secured.

If it is, there may be insufficient memory to use other applications.

Reestimate the memory required to run other applications on the same machine, and investigate if there is sufficient memory.

If, as a result of the reestimation, it is confirmed that there is insufficient memory, contact the system administrator.

Ask the system administrator to add the main memory or extend the swap area.

Also, if the Java heap size is excessively large, use the modify-jvm-options subcommand of the pgx_jadmin command to reduce the specified size.

Refer to "Java Function Errors" in the Operation Guide for details.



Check if the maximum number of threads that can be executed by the instance administrator has been exceeded. If the maximum number has been exceeded, edit the /etc/security/limits.conf file, and take the required action.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

When Memory type code: 1 (Java heap area)

Use the modify-jvm-options subcommand of the pgx_jadmin command to extend the Java heap area, and then restart the instance.

Refer to "Java Function Errors" in the Operation Guide for details.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

When Memory type code: 2 (Java Perm area)

Use the modify-jvm-options subcommand of the pgx_jadmin command to extend the Java Perm area, and then restart the instance.

Refer to "Java Function Errors" in the Operation Guide for details.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

When Memory type code: -1 (Failed to obtain the Java VM information)

Take the required action described above for the Java heap area, Java Perm area, or C heap area.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

WARNING: OM1021: Cluster degeneration operation will commence: CLUSTER={0}

Variable Information

{0}:Database name

Explanation

The process failed to restart, therefore, the container operates with some server instances (Java VM) stopped.

System Action

Container operation is continued.

User Action

Remove the cause of the application process restart failure, and then restart the instance.

ERROR: OM1022: Cluster unable to start**Explanation**

One of the following occurred:

- Some of the server instances (Java VM) failed to start.
- All of the server instances (Java VM) failed to start.

System Action

Processing is continued.

User Action

If any messages have been output to the event log (Windows(R)) or the system log (Linux) before or after this message, take the required action and investigate the cause of instance startup failure.

ERROR: OM1025: An error occurred in the output of the jvm.log. FILE={0}**Variable Information**

{0}: Java VM log file

Explanation

Failed to output to the Java VM log file.

System Action

If this error occurs on startup, the container start processing is interrupted.
If the container has already started up, container operation is continued.

User Action

Take the following actions:

- Check if write privileges were assigned for the file.
- Check if write privileges were assigned for the log output directory or parent directory.
- Check if the log output directory settings are valid. If the log settings are not valid, change them.
- Ensure that the length of the log file's absolute path has not exceeded the maximum path length configured in the operating system. If it has, configure the length of the log file's absolute path so that it does not exceed the maximum path length configured in the operating system.
- The disk has become corrupted, therefore, access to the file or directory has failed. Check the disk.
- Due to a conflict with other processing, access to the disk is temporarily unavailable. Reexecute processing.
- If there is insufficient free disk space, secure more.

INFO: OM1026: Log rotation was successful. FILE={0}**Variable Information**

{0}:Java VM log file

Explanation

Rotation of the Java VM log file was successful.

ERROR: OM1027: Log rotation failed. FILE={0}**Variable Information**

{0}:Java VM log file

Explanation

Rotation of the Java VM log file failed.

System Action

If this error occurs on startup, the container start processing is interrupted.

If the container has already started, container operation continues. Rotation will be attempted the next time the log is output (when the rotation type is the log size) or the next time the log rotation time is reached (when the rotation type is the log collection time).

User Action

Take the following actions:

- Check if write privileges were assigned for the file.
- Check if write privileges were assigned for the log output directory or parent directory.
- The disk has become corrupted, therefore, access to the file or directory has failed. Check the disk.
- Due to a conflict with other processing, access to the disk is temporarily unavailable. The action is unnecessary.

ERROR: OM1030: There is an error for XML definition. TAG={0} ATTRIBUTE={1} VALUE={2}

Variable Information

{0}: Tag name

{1}: Attribute name

{2}: Value

Explanation

There are errors in the definition information of the container.

User Action

Ensure the correct values are specified in the definition information of the container, and reexecute the operation.

ERROR: OM1031: Directory deletion failed. PATH={0}

Variable Information

{0}: Path

Explanation

Failed to delete the directory.

System Action

Processing is interrupted.

User Action

Take the following actions:

- Check if write privileges were assigned for the log output directory or parent directory.
- The disk has become corrupted, therefore, access to the file or directory has failed. Check the disk.
- Due to a conflict with other processing, access to the disk is temporarily unavailable. Reexecute processing.

ERROR: OM1032: Unable to rotation the directory. PATH={0}

Variable Information

{0}:Path

Explanation

Rotation of the current directory failed.

System Action

Processing is interrupted.

User Action

Take the following actions:

- Check if write privileges were assigned for the log output directory or parent directory.
- The disk has become corrupted, therefore, access to the file or directory has failed. Check the disk.
- Due to a conflict with other processing, access to the disk is temporarily unavailable. Reexecute processing.

ERROR: OM1033: Directory creation failed. PATH={0}

Variable Information

{0}:Path

Explanation

Failed to create the directory.

System Action

Processing is interrupted.

User Action

Take the following actions:

- Check if write privileges were assigned for the log output directory or parent directory.
- The disk has become corrupted, therefore, access to the file or directory has failed. Check the disk.
- Due to a conflict with other processing, access to the disk is temporarily unavailable. Reexecute processing.

ERROR: OM1034: An error occurred in the output of the jvm.log. FILE={0} DETAIL={1}

Variable Information

{0}: Java VM log file

{1}: Error information

Explanation

Failed to output the Java VM log file.

System Action

If this error occurs on startup, the container start processing is interrupted.

If the container has already started up, container operation is continued.

User Action

Take the following actions:

- Check if write privileges were assigned for the file.
- Check if write privileges were assigned for the log output directory or parent directory.
- Check if the log output directory settings are valid. If the log settings are not valid, change them.
- Ensure that the length of the log file's absolute path has not exceeded the maximum path length configured in the operating system. If it has, configure the length of the log file's absolute path so that it does not exceed the maximum path length configured in the operating system.

- The disk has become corrupted, therefore, access to the file or directory has failed. Check the disk.
- Due to a conflict with other processing, access to the disk is temporarily unavailable. Reexecute processing.
- If there is insufficient free disk space, secure more.

ERROR: OM1035: No Message ID={0}**Variable Information**

{0}: Message ID

Explanation

Attempted to output a message that has not been defined.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

SEVERE: OM1036: Internal error occurred. DETAIL={0}**Variable Information**

{0}: Error information

Explanation

One of the following occurred:

1. A request was accepted during start processing, and therefore could not be processed.
2. An error occurred in internal processing.

User action

1. If this message is output during startup of an instance, ignore it.
Requests accepted during start processing will not be processed.
2. Refer to any other messages that were output at the same time, and take the required action.
If no other messages were output, contact Fujitsu technical support.

ERROR: OM1042: Cannot start the domain because the domain.xml was destroyed.**Explanation**

The Java EE DAS service failed to start due to the definition file being in an abnormal state.

System Action

Processing is interrupted.

User Action

There may be insufficient Java EE DAS service heap area, or the address space upper limit may have been exceeded.
Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

WARNING: OM1043: The domain.xml has been restored because the original file was destroyed.**Explanation**

The backed up definition file has been restored and the Java EE DAS service has started due to the definition file being in an abnormal state.

System Action

Java EE DAS service startup processing is continued.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

INFO: OM1044: Server Instance was started up: NAME={0} CLUSTER={1} CLUSTER_STATUS={2}

Variable Information

{0}: Server instance (Java VM) name

{1}:Database name

{2}:Container status

Explanation

The server instance (Java VM) has started.

INFO: OM1046: Server Instance was stopped forcibly: NAME={0} CLUSTER={1} CLUSTER_STATUS={2}

Variable Information

{0}: Server instance (Java VM) name

{1}:Database name

{2}:Container status

Explanation

The server instance (Java VM) was stopped by force.

ERROR: OM1057: There is a possibility that the definition file was destroyed.

Explanation

The definition file of the Java EE DAS service may be in an abnormal state due to insufficient free disk space.

System Action

Processing is interrupted.

User Action

The definition file is recovered when you restart the following service:

- Java EE DAS service

After restarting the above service, reexecute processing.

If there is insufficient free disk space, delete unnecessary files and then take the action shown above.

Note that the operation performed before this message is output may cause loss of information, therefore check the content of the operation.

If the definition file fails to recover even after restarting the service, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

ERROR: OM1065: Failed in the initialization of service: DETAIL={0}

Variable Information

{0}: Error information

Explanation

Initialization of the service failed for the following reason:

- Failed to load the library.

System Action

Processing is interrupted.

User Action

Check the detail message displayed in the error information and take the required action.

ERROR: OM1066: An error occurred while getting instance status: NAME={0}

Variable Information

{0}: Server instance (Java VM) name

Explanation

An error occurred while retrieving the server instance (Java VM) status, therefore the status could not be obtained. The server instance (Java VM) may have hung. Or, the server instance (Java VM) may have already started up.

System Action

Processing is interrupted.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

WARNING: ISJEE_OM1068: Failed to synchronize with Interstage Java EE DAS service. NAME={0}

Variable Information

{0}: Server instance (Java VM) name

Explanation

Synchronization of the repository failed.

System Action

Processing continues.

User Action

Synchronization of the repository failed, therefore it was not possible to update with the latest information. To update with the latest information, restart the instance.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.12.2 OM2000 to OM2099

INFO: OM2005: Cluster has been created: CLUSTER={0}

Variable Information

{0} : Database name

Explanation

The container has been created.

INFO: OM2006: Cluster has been deleted: CLUSTER={0}

Variable Information

{0} : Database name

Explanation

The container has been deleted.

ERROR: OM2008: Server Instance {0} must be stopped before that can be deleted.

Variable Information

{0}: Server instance (Java VM) name

Explanation

The server instance has not been stopped, therefore the operation failed.

System Action

Processing is interrupted.

User Action

Stop the server instance, and then reexecute the operation.

INFO: OM2012: Not all server instances in cluster {0} were successfully started.

Variable Information

{0}:Database name

Explanation

Not all server instances (Java VM) have started.

System Action

Processing is interrupted.

User Action

Refer to any other messages that were output at the same time, and take the required action.

INFO: OM2016: Cluster is already stopped: CLUSTER={0}

Variable Information

{0}:Database name

Explanation

The container has already been stopped.

System Action

Processing is interrupted.

INFO: OM2017: The server instance has been created: INSTANCE={0}

Variable Information

{0} : Server instance (Java VM) name

Explanation

The server instance (Java VM) has been created.

INFO: OM2018: The server instance has been deleted: INSTANCE={0}

Variable Information

{0} : Server instance (Java VM) name

Explanation

The server instance (Java VM) has been deleted.

ERROR: OM2044: An error occurred while getting cluster status: CLUSTER={0}

Variable Information

{0}: Container name

Explanation

An error occurred while retrieving the container status, therefore the status could not be obtained.

System Action

Processing is interrupted.

User Action

If this message is output, wait for a while then check the status of the domain or server instance (Java VM) using the `pgx_admin list-domain` subcommand or `pgx_admin list-container` subcommand.

If this does not resolve the problem, restart the instance.

ERROR: OM2045: Instance {0} is not running. Please start the instance first.

Variable Information

{0}: Server instance (Java VM) name

Explanation

The specified server instance has not been started.

System Action

Processing is interrupted.

User Action

Start the instance, and reexecute processing.

A.2.12.3 OM2100 to OM2199

ERROR: OM2112: Could not execute command. Command={0} Detail={1}

Variable Information

{0}: Command

{1}: Detail information

Explanation

The command could not be executed.

System Action

Processing is interrupted.

User Action

Take one of the following actions:

- If a message with a message number is output to Detail information, take the action indicated by the message.
- Check if the command exists.

If the command does not exist, it is possible that the command may have been deleted or the product may have been installed incorrectly. Install the product again.

If the command exists, check the command's execution privileges and configure the settings as a user with administrator privileges.

If the problem is still not resolved, contact Fujitsu technical support.

ERROR: OM2113: Specified port number of instance has already been used. Instance={0} Port={1}

Variable Information

{0}: Server instance (Java VM)

{1}: Port number

Explanation

The port number for server instance (Java VM) management is already in use.

System Action

Processing is interrupted.

User Action

Change the port number for server instance (Java VM) management to one that is not in use.

ERROR: OM2114: Invalid value was specified for a port number of instance. Instance={0} Port={1}

Variable Information

{0}: Server instance (Java VM)

{1}: Port number (system property)

Explanation

The specified port number for server instance (Java VM) management is an invalid value.

System Action

Processing is interrupted.

User Action

Ensure a valid port number is specified for server instance (Java VM) management.

ERROR: OM2120: An error occurred while setting web server connector. Detail={0}

Variable Information

{0}: Detail information

Explanation

An error occurred while setting the container.

System Action

Processing is interrupted.

User Action

Refer to the message displayed in Detail information, and then take the required action.

A.2.12.4 OM2900 to OM2999

ERROR: ISJEE_OM2997: Unable to connect to admin-server at given host: [{0}] and port: [{1}]. Please check if this server is up and running and that the host and port provided are correct.

Variable Information

{0}: Host name
{1}: Port number

Explanation

Failed to connect to the Java EE DAS service.

System Action

Processing is interrupted.

User Action

Refer to any messages that were output before or after this message, and take the required action. After taking action, restart the instance. If this message continues to be output despite taking the above action, contact Fujitsu technical support.

ERROR: ISJEE_OM2998: Error in Interstage Java EE DAS. ERROR={0}

Variable Information

{0}: Detail error message

Explanation

An error occurred in the Java EE DAS service.

System Action

Processing is interrupted.

User Action

Refer to the detail error message and remove the cause of the error. After taking action, restart the instance. If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.12.5 OM3000 to OM3099

WARNING: ISJEE_OM3000: Delaying cluster stop process because an application is still processing.

Explanation

Container stop processing is delayed because a Java application is still processing.

WARNING: ISJEE_OM3001: Commencing cluster stop process as all applications have finished processing.

Explanation

Container stop processing has started because all Java applications have finished processing.

INFO: ISJEE_OM3002: The server application timer function has started.

Explanation

The server instance (Java VM) timer functionality has started.

INFO: ISJEE_OM3003: The server application timer function has stopped.

Explanation

The server instance (Java VM) timer functionality has stopped.

WARNING: OM3004: No response from the application.: START={0} THREAD={1} APPLICATION={2}

Variable Information

{0}: Java Application processing start time

{1}: Processing thread information

{2}: Target Java application

Explanation

There is no response from the application.

System Action

Processing is continued.

User Action

Refer to the thread dump output to the Java VM log of PL/extJava, to check if there are any occurrences of deadlocks, loops or processing delays.

INFO: OM3006: An application timeout was notified to the PCMI runtime environment.

Explanation

Java application timeout has been notified to the PCMI service.

WARNING: OM3007: The application timeout could not be notified to the PCMI runtime environment.: CODE={0}

Variable Information

{0}: Internal information

Explanation

Java application timeout could not be notified to the PCMI service.

System Action

Processing is continued.

User Action

- Check the PL/extJava server log, and refer to any messages that have been output at the same time to remove the cause of the error.
- Refer to any messages that have been output to the event log (Windows(R)) or the system log (Linux) to remove the cause of the error.

INFO: OM3008: The running status of the cluster was notified to the PCMI runtime environment.

Explanation

A keep alive notification has been sent to the PCMI service.

WARNING: OM3009: The running status of the cluster could not be notified to the PCMI runtime environment.: CODE={0}

Variable Information

{0}: Internal information

Explanation

A keep alive notification could not be sent to the PCMI service.

System Action

Processing is continued.

User Action

- Refer to any messages that have been output to the PL/extJava server log, as well as the event log (Windows(R)) or system log (Linux), and check if an error has occurred.
- If the above does not apply, refer to the Java VM log of PL/extJava and check if an error has occurred.

WARNING: OM3014: An error occurred in the server application timer function. PCMI Error Code={0}

Variable Information

{0}: Error information

Explanation

Communication with the PCMI service failed.

System Action

Processing is continued.

The server application timer function is not operating correctly.

User Action

Take the following actions:

- Take the action indicated in the messages output before and after this message.
- Follow the action advised in messages output to the event log (Windows (R)) or the system log (Linux), and investigate the cause of the failure.

If the problem is still not resolved despite taking the above action, contact Fujitsu technical support.

A.2.12.6 OM3100 to OM3199

INFO: ISJEE_OM3100: Log rotation was successful. FILE={0}

Variable Information

{0}: Log file name

Explanation

Rotation of the log file ({0}) was successful.

ERROR: ISJEE_OM3101: Log rotation failed. FILE={0}

Variable Information

{0}: Log file name

Explanation

Failed to rotation the log file ({0}).

User Action

Possible causes are as follows: After taking action, reexecute the process.

- Access authority is not granted to the file.

Access authority of the file may have been changed. Restore the access authority for the file, and reexecute processing.

- The file or directory is referenced by another application.

Stop other applications, and reexecute processing.

- The disk is defective.

A defect on the disk may be preventing files and directories from being accessed. Run a disk check.

- Conflict with another process.

Conflict with another process may make the disk temporarily inaccessible. Reexecute processing.

- There is insufficient disk space.

There may not be enough free disk space, therefore manually delete any old log files that exceed the allowable number of generations. Refer to "PL/extJava Log Information" in the Operation Guide for information on the log file output directory.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

ERROR: ISJEE_OM3102: Failed to delete the log file. FILE={0}

Variable Information

{0}: Log file name

Explanation

Failed to delete the log file.

User Action

Possible causes are as follows: After taking action, reexecute the process.

- Access authority is not granted to the file.

Access authority of the file may have been changed. Restore the access authority for the file, and reexecute processing.

- The file or directory is referenced by another application.

Stop other applications, and reexecute processing.

- The disk is defective.

A defect on the disk may be preventing files and directories from being accessed. Run a disk check.

- Conflict with another process.

Conflict with another process may make the disk temporarily inaccessible. Reexecute processing.

- There is insufficient disk space.

There may not be enough free disk space, therefore manually delete any old log files that exceed the allowable number of generations. Refer to "PL/extJava Log Information" in the Operation Guide for information on the log file output directory.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

ERROR: ISJEE_OM3103: Failed to open the log file. FILE={0}**Variable Information**

{0}: Log file name

Explanation

Failed to open the log file ({0}).

User Action

Possible causes are as follows: After taking action, reexecute the process.

- Access authority is not granted to the file.

Access authority of the file may have been changed. Restore the access authority for the file, and reexecute processing.

- The file or directory is referenced by another application.

Stop other applications, and reexecute processing.

- The disk is defective.

A defect on the disk may be preventing files and directories from being accessed. Run a disk check.

- Conflict with another process.

Conflict with another process may make the disk temporarily inaccessible. Reexecute processing.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

WARNING: ISJEE_OM3104: Failed to open the log file. FILE={0}**Variable Information**

{0}: Log file name

Explanation

Failed to open the log file ({0}).

User Action

Possible causes are as follows: After taking action, reexecute the process.

- Access authority is not granted to the file.

Access authority of the file may have been changed. Restore the access authority for the file, and reexecute processing.

- The file or directory is referenced by another application.

Stop other applications, and reexecute processing.

- The disk is defective.

A defect on the disk may be preventing files and directories from being accessed. Run a disk check.

- Conflict with another process.

Conflict with another process may make the disk temporarily inaccessible. Reexecute processing.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

ERROR: ISJEE_OM3105: Failed to initialize the log file. DETAIL={0}**Variable Information**

{0}: Error detail

Explanation

Failed to initialize the log file.

User Action

Possible causes are as follows: After taking action, reexecute the process.

- Access authority is not granted to the file.

Access authority of the file may have been changed. Restore the access authority for the file, and reexecute processing.

- The file or directory is referenced by another application.

Stop other applications, and reexecute processing.

- The disk is defective.

A defect on the disk may be preventing files and directories from being accessed. Run a disk check.

- Conflict with another process.

Conflict with another process may make the disk temporarily inaccessible. Reexecute processing.

- There is insufficient disk space.

There may not be enough free disk space, therefore manually delete any old log files that exceed the allowable number of generations. Refer to "PL/extJava Log Information" in the Operation Guide for information on the log file output directory.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

ERROR: ISJEE_OM3107: Failed to write messages. FILE={0}**Variable Information**

{0}: Log file name

Explanation

Failed to output to the log file ({0}).

User Action

Possible causes are as follows: After taking action, reexecute the process.

- Access authority is not granted to the file.

Access authority of the file may have been changed. Restore the access authority for the file, and reexecute processing.

- The file or directory is referenced by another application.

Stop other applications, and reexecute processing.

- The disk is defective.

A defect on the disk may be preventing files and directories from being accessed. Run a disk check.

- Conflict with another process.

Conflict with another process may make the disk temporarily inaccessible. Reexecute processing.

- There is insufficient disk space.

There may not be enough free disk space, therefore manually delete any old log files that exceed the allowable number of generations. Refer to "PL/extJava Log Information" in the Operation Guide for information on the log file output directory.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

WARNING: ISJEE_OM3108: Output of the log has been stopped. FILE={0}**Variable Information**

{0}: Log file name

Explanation

The output to the log file ({0}) was stopped.

User Action

Possible causes are as follows: After taking action, reexecute the process.

- Access authority is not granted to the file.

Access authority of the file may have been changed. Restore the access authority for the file, and reexecute processing.

- The file or directory is referenced by another application.

Stop other applications, and reexecute processing.

- The disk is defective.

A defect on the disk may be preventing files and directories from being accessed. Run a disk check.

- Conflict with another process.

Conflict with another process may make the disk temporarily inaccessible. Reexecute processing.

- There is insufficient disk space.

There may not be enough free disk space, therefore manually delete any old log files that exceed the allowable number of generations. Refer to "PL/extJava Log Information" in the Operation Guide for information on the log file output directory.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.12.7 OM3200 to OM3299

INFO: ISJEE_OM3201: Alert monitoring function is {0}.**Variable Information**

{0}: Alert monitoring function operation mode

Explanation

The alert monitoring function operation mode was set.

WARNING: ISJEE_OM3202: Alert monitoring function is not available. ERROR={0}**Variable Information**

{0}: Error information

Explanation

The variable information is one of the following:

- "Failed to get monitor from fmoni"

- "Failed to get warning from fmoni (Java VM may be shutting down)"

The system is overloaded, and predictive monitoring cannot continue.

System Action

Java application processing is continued.

User Action

The variable information is one of the following:

- "Failed to get monitor from fmoni"
- "Failed to get warning from fmoni (Java VM may be shutting down)"

Ensure that there is no processing in the Java application that causes the system to become overloaded. After taking action, reregister the Java application and restart the instance.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

WARNING: ISJEE_OM3204: Alert monitoring function was detected the alert. CLUSTER={0} INSTANCE={1} MESSAGE={2}

Variable Information

- {0}: Container name
- {1}: Server instance (Java VM) name
- {2}: Detailed message

Explanation

An event was detected in which the alert monitoring function exceeds the alert for the alarm value.

Detailed message

The following detailed messages are output by the alert detected by the alert monitoring function.

The format of the time information contained in the detailed message is "year/month/day hours:minutes:seconds.milliseconds".

Detailed message	Meaning of the warning	Conditions of occurrence
<p>There are possibilities of OutOfMemoryError because of the lack of the memory: TIME={0} SIZE={1}</p> <p>TIME: Time of occurrence</p> <p>SIZE: Rough estimate of amount added to Heap area (Unit: Bytes) (*1)</p>	<p>The Heap area is insufficient, therefore there is a danger that OutOfMemoryError will occur.</p>	<p>When the Heap usage rate immediately after Full GC is greater than 95%.</p> <p>Alternatively, when the Heap usage rate immediately after Full GC is greater than 90%, AND the Heap size used since the occurrence of the previous Full GC has increased continuously for at least 3 times.</p>
<p>There are possibilities of OutOfMemoryError because of the lack of the Perm region: TIME={0} SIZE={1}</p> <p>TIME: Time of occurrence</p> <p>SIZE: Rough estimate of amount added to Perm area (Unit: Bytes) (*1)</p>	<p>The Perm area is insufficient, therefore there is a danger that OutOfMemoryError will occur.</p>	<p>When the Perm area usage amount is greater than 90%.</p>
<p>OutOfMemoryError warning is occurred because the Perm region is exhausted: TIME={0} SIZE={1}</p> <p>TIME: Time of occurrence</p>	<p>The Perm area usage amount is exhausted, therefore there is a danger that</p>	<p>When the increase in the Perm area usage amount since the previous measurement is greater than 10 per cent of the overall Perm area, AND</p>

Detailed message	Meaning of the warning	Conditions of occurrence
SIZE: Perm area increased amount (Unit: Bytes)	OutOfMemoryError will occur.	the Perm area usage rate that is assumed for the next increase of the same percentage is greater than 90%. Note that the value which is notified for "SIZE" is the size (increased amount) which will be assumed for increases of the same rate.
It takes long time to do the garbage collections many times: TIME={0} AVERAGE={1} TIME: Time of occurrence AVERAGE: Average time for Full GC for the previous three times (in milliseconds)	Full GC continuously takes a long time.	When the average value for Full GC time for the previous three times is longer than 5 seconds.
Inefficient garbage collections are run with the short intervals: TIME={0} WEIGHT={1} TIME: Time of occurrence WEIGHT: Usage rate of the old generation immediately before Full GC (in %)	Inefficient Full GC occurs in short intervals.	When the Full GC interval time for the previous three times is shorter than 20 seconds, AND the usage rate of the Old generation area immediately before Full GC is less than 65%.
The garbage collections are run with the short intervals because of the lack of the memory: TIME={0} SIZE={1} TIME: Time of occurrence SIZE: Rough estimate of amount added to Heap area (Unit: Bytes) (*1)	The Heap area is insufficient, therefore Full GC occurs in short intervals.	When the Full GC interval time for the previous three times is shorter than 20 seconds, AND the Heap usage rate immediately after Full GC is greater than 65%.
System.gc() are run with the short intervals: TIME={0} INTERVAL={1} TIME: Time of occurrence INTERVAL: Interval time for the java.lang.System.gc() method and the java.lang.Runtime.gc() method (in milliseconds)	The java.lang.System.gc() method and the java.lang.Runtime.gc() method occur in short intervals.	When the Full GC interval time for the previous three times is shorter than 20 seconds, AND the frequency of Full GC that occurs because of the java.lang.System.gc() method and the java.lang.Runtime.gc() method is high.
The garbage collections are run with the short intervals: TIME={0} INTERVAL={1} TIME: Time of occurrence INTERVAL: Full GC interval time (in milliseconds)	Full GC occurs in short intervals.	When the Full GC interval time for the previous three times is shorter than 20 seconds.

*1 To avoid warnings, it will be necessary to increase the Heap or Perm area size when the warning occurs. The value which is notified for "SIZE" is the rough estimate increased amount for this.

System Action

Application processing is continued.

User Action

Refer to "Java Function Errors" in the Operation Guide and change the heap area size and Perm area size for the server instance (Java VM) in the container. After taking action, restart the instance.

WARNING: ISJEE_OM3205: Alert monitoring function is stopped due to the unexpected error. CODE={0} ERROR={1}

Variable Information

{0}: Error information 1
{1}: Error information 2

Explanation

An unexpected error occurred, therefore alert monitoring function is stopped.

System Action

Java application processing is continued.
Alert monitoring function is stopped. After this warning is output, alert monitoring function is disabled.

User Action

Refer to the error information and establish the cause of the failure.
If the problem is still not resolved, contact a Systems Engineer.

ERROR: OM3209: A system error occurred. DETAIL={0}

Variable Information

{0}: Error information

Explanation

A system error occurred.

System Action

Processing is interrupted.

User Action

Contact Fujitsu technical support.

A.2.12.8 OM5000 to OM5099

ERROR: ISJEE_OM5002: Failed to send a notification that process named {0} is started. PCMI Error Code={1}.

Variable Information

{0}: Server instance (Java VM) name
{1}: Error information

Explanation

Failed to communicate with the PCMI service.

System Action

Processing is interrupted.

User Action

Take the following actions:

- Take the action indicated by the message output before and after this message.
- Take the action indicated by the message output to the event log (Windows(R)) or the system log (Linux), and investigate the cause of the failure.

If the problem persists, contact Fujitsu technical support.

INFO: ISJEE_OM5003: Java management agent started.

Explanation

Java management agent started.

A.2.13 Messages that Contain "ORBTPOOL" in the Message ID

A.2.13.1 ORBTPOOL00000 to ORBTPOOL00099

ORBTPOOL00007: Worker thread {0} caught throwable while executing work.

Variable Information

{0}: Thread information

Explanation

Worker thread {0} caught an exception.

System Action

An exception is posted to the Java application.

User Action

This message may be output when an instance is stopped.
There will be no impact on operations, so the message can be ignored.

A.2.14 Messages that Contain "PCMI" in the Message ID

A.2.14.1 PCMI0000 to PCMI0099

INFO: PCMI0000: The {0} command was processed normally.: INSTANCE={1}

Variable Information

{0}: Command name
{1}: PCMI directory path

Explanation

The command {0} terminated normally.

ERROR: PCMI0001: The {0} command was failed.: INSTANCE={1} POS={2} DETAIL={3}

Variable Information

{0}: Command name
{1}: PCMI directory path
{2}: Error information
{3}: System error number

Explanation

The command {0} failed.

System Action

Processing is interrupted.

User Action

If a message displaying the cause has been output before this message, take the action indicated by that message.

If a message displaying the cause has not been output before this message, take the action indicated by the message output to the event log (Windows(R)) or the system log (Linux) before this message and investigate the cause of command execution failure.

ERROR: PCMI0006: PCMI service does not exist in the directory.: INSTANCE={0}

Variable Information

{0}: PCMI directory path

Explanation

The PCMI service is not registered in the specified directory {0}.

The structure of the PCMI directory {0} may be corrupted.

System Action

Processing is interrupted.

User Action

If this message is output during installation, perform the installation again.

In all other cases, or if the problem is still not resolved despite taking the above action, contact Fujitsu technical support.

ERROR: PCMI0007: PCMI service is being created in the directory.: INSTANCE={0}

Variable Information

{0}: PCMI directory path

Explanation

The registration of the PCMI service is being processed.

System Action

Processing is interrupted.

User Action

Install or uninstall, again.

If this error message continues to occur, contact Fujitsu technical support.

ERROR: PCMI0008: An internal error occurred.: INSTANCE={0} POS={1} DETAIL={2}

Variable Information

{0}: PCMI directory path

{1}: Error information

{2}: System error number

Explanation

An internal error occurred.

System Action

Processing is interrupted.

User Action

Take one of the following actions:

- If a message displaying the cause has been output before this message, take the action indicated by that message.
- Make a note of System error number {2} that is output, and then notify the system administrator.

If this error message continues to occur, contact Fujitsu technical support.

ERROR: PCMI0009: A system error occurred.: INSTANCE={0} POS={1} DETAIL={2}

Variable Information

- {0}: PCMI directory path
- {1}: Error information
- {2}: System error number

Explanation

A system error occurred.

System Action

Processing is interrupted.

User Action

Take one of the following actions:

- If a message displaying the cause has been output before this message, take the action indicated by that message.
- Check Error information {1} and System error number {2} that are output, refer to the following table, and then take the action indicated by Error information {1} and System error number {2}.

Error information {1}	System error number {2}	Explanation/Action
-	[8,12,14]	There may be insufficient memory. Close unnecessary Java applications, and then reexecute the command.
[102,105,201]	-	There may not be enough free space for the device. Secure free space for the device, and then reexecute the command.
-	[4,28]	
All other cases		Make a note of Error information {1} and System error number {2}, and then notify the system administrator.

If this error message continues to occur, contact Fujitsu technical support.

ERROR: PCMI0010: A condition exists that the command cannot be executed.: INSTANCE={0}

Variable Information

- {0}: PCMI directory path

Explanation

The command cannot be executed. A process that cannot be executed at the same time may have been executed.

System Action

Processing is interrupted.

User Action

Wait for a while, and then reexecute the command.

INFO: PCMI0011: PCMI service has started.: INSTANCE={0}

Variable Information

{0}: PCMI directory path

Explanation

The PCMI service has started.

INFO: PCMI0012: PCMI service has stopped.: INSTANCE={0}

Variable Information

{0}: PCMI directory path

Explanation

The PCMI service has stopped.

ERROR: PCMI0013: PCMI service cannot be started.: INSTANCE={0}

Variable Information

{0}: PCMI directory path

Explanation

The PCMI service cannot be started.

System Action

Processing is interrupted.

User Action

If a message displaying the cause has been output before this message, take the action indicated by that message.

If a message displaying the cause has not been output before this message, take the action indicated by the message output to the event log (Windows(R)) or the system log (Linux) before this message and investigate the cause of command execution failure.

ERROR: PCMI0014: PCMI service cannot be stopped.: INSTANCE={0}

Variable Information

{0}: PCMI directory path

Explanation

The PCMI service cannot be stopped.

System Action

Processing is interrupted.

User Action

If a message displaying the cause has been output before this message, take the action indicated by that message.

If a message displaying the cause has not been output before this message, take the action indicated by the message output to the event log (Windows(R)) or the system log (Linux) before this message and investigate the cause of command execution failure.

ERROR: PCMI0015: An error occurred while getting PCMI service status.: INSTANCE={0} DETAIL={1}

Variable Information

{0}: PCMI directory path

{1}: System error number

Explanation

An error occurred while retrieving the PCMI status, therefore the status could not be obtained successfully. The PCMI service may have stopped responding.

System Action

Processing is interrupted.

User Action

If a message displaying the cause has been output before this message, take the action indicated by that message.

If a message displaying the cause has not been output before this message, take the action indicated by the message output to the event log (Windows(R)) or the system log (Linux) before this message and investigate the cause of command execution failure.

ERROR: PCMI0016: The directory is not empty.: INSTANCE={0}

Variable Information

{0}: PCMI directory path

Explanation

The specified PCMI directory {0} is not empty.

System Action

Processing is interrupted.

User Action

If this message is output during installation, empty the applicable directory {0} and perform the installation again.

ERROR: PCMI0018: PCMI service is started.: INSTANCE={0}

Variable Information

{0}: PCMI directory path

Explanation

The PCMI service has started.

System Action

Processing is interrupted.

User Action

If this message is output during uninstallation, stop the instance and perform the uninstallation again.

ERROR: PCMI0019: The pcminame is used.: INSTANCE={0}

Variable Information

{0}: PCMI directory path

Explanation

The PCMI service name is already being used.

If the uninstallation was performed before this operation, unnecessary resources may still exist.

System Action

Processing is interrupted.

User Action

Delete unnecessary resources using the following procedure, and then install again.



If "FUJITSU PCMI(isje6-<componentId>)" remains in services, execute the sc command as shown below to delete the "FUJITSU PCMI(isje6-<componentId>)" service.

```
sc delete "FUJITSU PCMI(isje6-<componentId>)"
```



If the following files exist, remove them using the rm command:

```
/etc/rc.d/init.d/FJSVpcmiisje6-componentId  
/etc/rc.d/rc2.d/S99FJSVpcmiisje6-componentId  
/etc/rc.d/rc3.d/S99FJSVpcmiisje6-componentId  
/etc/rc.d/rc4.d/S99FJSVpcmiisje6-componentId  
/etc/rc.d/rc5.d/S99FJSVpcmiisje6-componentId  
/etc/rc.d/rc0.d/K00FJSVpcmiisje6-componentId  
/etc/rc.d/rc1.d/K00FJSVpcmiisje6-componentId  
/etc/rc.d/rc6.d/K00FJSVpcmiisje6-componentId
```



Example

Configure *componentId* using the following format:

```
"STFSYMOIDB" + "VL" + " firstDigitOfArchitecture"
```

- *VL*: Version/level of Symfoware Server
- *firstDigitOfArchitecture*: Product architecture ("3" for the 32-bit version; "6" for the 64-bit version)

For Symfoware Server version "1210" with 64-bit product architecture, *componentId* will be configured as shown below:

```
STFSYMOIDB12106
```

WARNING: PCMI0021: PCMI service has not been set up.: INSTANCE={0}

Variable Information

{0}: PCMI directory path

Explanation

Automatic startup has not been configured for the PCMI service. Unnecessary resources may still exist.

System Action

Processing is continued.

User Action

Delete unnecessary resources using the following procedure, and then install again.



If "FUJITSU PCMI(isje6-<componentId>)" remains in services, execute the sc command as shown below to delete the "FUJITSU PCMI(isje6-<componentId>)" service.

```
sc delete "FUJITSU PCMI(isje6-<componentId>)"
```



If the following files exist, remove them using the rm command:

```
/etc/rc.d/init.d/FJSVpcmiisje6-componentId  
/etc/rc.d/rc2.d/S99FJSVpcmiisje6-componentId  
/etc/rc.d/rc3.d/S99FJSVpcmiisje6-componentId
```

```
/etc/rc.d/rc4.d/S99FJSVpcmiisje6-componentId  
/etc/rc.d/rc5.d/S99FJSVpcmiisje6-componentId  
/etc/rc.d/rc0.d/K00FJSVpcmiisje6-componentId  
/etc/rc.d/rc1.d/K00FJSVpcmiisje6-componentId  
/etc/rc.d/rc6.d/K00FJSVpcmiisje6-componentId
```

Example

Configure *componentId* using the following format:

```
"STFSYMOIDB" + "VL" + " firstDigitOfArchitecture"
```

- *VL*: Version/level of Symfoware Server
- *firstDigitOfArchitecture*: Product architecture ("3" for the 32-bit version; "6" for the 64-bit version)

For Symfoware Server version "1210" with 64-bit product architecture, *componentId* will be configured as shown below:

```
STFSYMOIDB12106
```

ERROR: PCMI0023: Does not have the authority to execute a command.: INSTANCE={0}

Variable Information

{0}: PCMI directory path

Explanation

A command was executed without an appropriate permission.

System Action

Processing is interrupted.

User Action

Reexecute the command as a user with privileges to execute the command.

ERROR: PCMI0026: Failed to get the common Java information.

Explanation

Failed to obtain the common Java information.

System Action

Processing is interrupted.

User Action

Contact Fujitsu technical support.

ERROR: PCMI0029: PCMI service already has stopped.

Explanation

The PCMI service has already stopped.

System Action

Processing is interrupted.

User Action

Check if the instance has started.

A.2.14.2 PCMI1000 to PCMI1099

INFO: PCMI1000: The PCMI service has started.: INSTANCE={0}

Variable Information

{0}: PCMI directory path

Explanation

The PCMI service has started.

INFO: PCMI1001: The PCMI service has stopped.: INSTANCE={0}

Variable Information

{0}: PCMI directory path

Explanation

The PCMI service has stopped.

INFO: PCMI1002: Process was started up.: INSTANCE={0} ID={1} ADAPTER={2}

Variable Information

{0}: PCMI directory path

{1}: Server instance (Java VM) name

{2}: Internal information

Explanation

The server instance (Java VM) {1} has started.

ERROR: PCMI1003: Process unable to start.: INSTANCE={0} ID={1} ADAPTER={2}

Variable Information

{0}: PCMI directory path

{1}: Server instance (Java VM) name

{2}: Internal information

Explanation

Failed to start the server instance (Java VM) {1}.

System Action

Processing is interrupted.

User Action

Take one of the following actions:

- If another message has been output at the same time as this message, take the action indicated by that message.
- If a message has been output to the event log (Windows(R)) or the system log (Linux) before this message, take the action indicated by that message and investigate the cause of instance startup failure.

If the issue is not resolved by the above actions, make a note of internal information {2}, and contact Fujitsu technical support.

ERROR: PCMI1007: The PCMI service cannot be started.: INSTANCE={0} DETAIL={1}

Variable Information

{0}: PCMI directory path

{1}: Detail information

Explanation

The PCMI service cannot be started.

System Action

Processing is interrupted.

User Action

Take one of the following actions:

- Check Detail information {1} that is output, remove the cause of the error, and then reexecute the command.
- If a message has been output to the event log (Windows(R)) or the system log (Linux) before this message, take the action indicated by that message and investigate the cause of instance startup failure.

If this error message continues to occur, make a note of Detail information {1}, contact Fujitsu technical support.

ERROR: PCMI1009: The PCMI service cannot be started.: INSTANCE={0}

Variable Information

{0}: PCMI directory path

Explanation

The PCMI service cannot be started.

System Action

Processing is interrupted.

User Action

Take one of the following actions:

- If another message has been output at the same time as this message, take the action indicated by that message.
- If a message has been output to the event log (Windows(R)) or the system log (Linux) before this message, take the action indicated by that message and investigate the cause of instance startup failure.

If this error message continues to occur, contact Fujitsu technical support.

ERROR: PCMI1011: The PCMI service cannot be started.

Explanation

The PCMI service cannot be started.

System Action

Processing is interrupted.

User Action

Take one of the following actions:

- If another message has been output at the same time as this message, take the action indicated by that message.
- If a message has been output to the event log (Windows(R)) or the system log (Linux) before this message, take the action indicated by that message and investigate the cause of instance startup failure.

If this error message continues to occur, contact Fujitsu technical support.

ERROR: PCMI1022: The start hook has terminated abnormally.: INSTANCE={0} DETAIL={1}

Variable Information

{0}: PCMI directory path

{1}: Detail information

Explanation

The processing of the startup script executed using the exit function when the PCMI service starts has terminated abnormally.

System Action

Processing is interrupted.

User Action

Check Detail information {1} that is output, refer to the following table, and then and take the action indicated.

Detail information {1}	Variable Information in Detail information {1}	Explanation/Action
Failed to execute command. [%s] [%d]	[%s]: Startup script path [%d]: Startup script return value	Ensure the host information for building PL/extJava has been added to the hosts file. If the problem still exists, contact Fujitsu technical support.
All other cases		Recover PL/extJava. If the problem still exists, contact Fujitsu technical support.

WARNING: PCMI1029: Internal error occurred while stopping the PCMI service.: INSTANCE={0}

Variable Information

{0}: PCMI directory path

Explanation

Internal error occurred while stopping the PCMI service.

System Action

Processing is continued.

User Action

Contact Fujitsu technical support.

ERROR: PCMI1030: The process terminated abnormally during startup.: INSTANCE={0} ID={1} ADAPTER={2} PID={3}

Explanation

The PCMI service has already stopped.

System Action

Processing is interrupted.

User Action

Check if the port number for domain management is correct. Or, check if the port number is not being used by another application.

INFO: PCMI1031: Process was stopped.: INSTANCE={0} ID={1} ADAPTER={2}

Variable Information

- {0}: PCMI directory path
- {1}: Server instance (Java VM) name
- {2}: Internal information

Explanation

The server instance (Java VM) {1} has stopped.

ERROR: PCMI1034: An internal error occurred in PCMI service.

Explanation

An internal error occurred in the PCMI service.

System Action

Processing is interrupted.

User Action

Check the message output to the event log (Windows(R)) or the system log (Linux) before this message, and take the action indicated by that message.

If this error message continues to occur, contact Fujitsu technical support.

ERROR: PCMI1035: Communication error occurred.: PROTOCOLID={0} REASON={1}

Variable Information

- {0}: Internal information
- {1}: Reason

Explanation

Communication error occurred.

System Action

The communication processing that failed is discarded. If this error occurs on startup, the processing is interrupted.

User Action

Check Internal information {0} and Reason {1} that are output, and remove the cause of the failure.

ERROR: PCMI1036: Failed to read communication environment definition file.: FILE={0}

Variable Information

- {0}: Communication environment definition file path

Explanation

Failed to read the communication environment definition file {0}.

System Action

Processing is interrupted.

User Action

Contact Fujitsu technical support.

ERROR: PCMI1037: Communication environment definition file contains an error.: PROTOCOLID={0} REASON={1}

Variable Information

{0}: Internal information

{1}: Reason

Explanation

The communication environment definition file is incorrect.

System Action

The PCMI service is stopped.

User Action

Contact Fujitsu technical support.

ERROR: PCMI1052: An I/O error occurred.: PATH={0}

Variable Information

{0}: File path

Explanation

An I/O error occurred.

System Action

Processing is interrupted.

User Action

Take one of the following actions:

- Check if the disk device where the file {0} is saved is working correctly.
- Check if the file {0} has been opened by another program. If it has, close the file {0}.

A.2.14.3 PCMI1100 to PCMI1199

ERROR: PCMI1101: The shutdown time of process exceeded the process monitoring time.: INSTANCE={0} ID={1} ADAPTER={2} PID={3}

Variable Information

{0}: PCMI directory path

{1}: Server instance (Java VM) name

{2}: Internal information

{3}: Process ID

Explanation

The processing to stop the process did not complete within the process monitoring time.

System Action

The application process is stopped by force.

User Action

Take one of the following actions:

- Check the log file, and investigate the cause of the long time required to stop the Java application process.
- Check the thread dump output to the Java VM log (console.log) of PL/extJava, and investigate if there is a problem in the Java application.

**ERROR: PCMI1102: The startup time of process exceeded the process monitoring time.:
INSTANCE={0} ID={1} ADAPTER={2} PID={3}**

Variable Information

- {0}: PCMI directory path
- {1}: Server instance (Java VM) name
- {2}: Internal information
- {3}: Process ID



When Process ID {3} is "unknown", the process ID cannot be obtained because of one of the following causes:

- The port used for debugging of the server instance (Java VM) is duplicated with the port of another server instance (Java VM) or application.
- The process was forcibly stopped by the user or another application.

Explanation

The processing to start the process did not complete within the process monitoring time.

System Action

The Java application process is stopped by force.

User Action

Take one of the following actions, and then reexecute processing:

- Check the thread dump output to the Java VM log (console.log) of PL/extJava, and investigate if there is a problem in the Java application.

ERROR: PCMI1103: The process has stopped.: ID={0} PID={1}

Variable Information

- {0}: Server instance (Java VM) name
- {1}: Process ID

Explanation

The instance process has terminated abnormally.

System Action

Processing is interrupted.

User Action

Take one of the following actions:

- If a message has been output to the event log (Windows(R)) or the system log (Linux) before this message, take the action indicated by that message and investigate the cause of abnormal termination of the process.
- If a message has not been output to the event log (Windows(R)) or the system log (Linux) before this message, check the log file and investigate if there is a problem in the Java application.
- If the instance has terminated abnormally, check the information output to the server log and Java VM log of PL/extJava, and investigate if there is any problem in the Java application.
- Check the thread dump output to the Java VM log of PL/extJava, and investigate if there is a problem in the Java application.

WARNING: PCMI1105: The process has stopped because JavaVM ran out of memory.: ID={0} PID={1} KIND={2}

Variable Information

{0}: Server instance (Java VM) name

{1}: Process ID

{2}: Memory type code

Explanation


There is insufficient Java VM heap area, therefore the process stopped.

System Action

The process for which there is insufficient Java VM heap area is stopped.

User Action

If this message is output frequently, refer to the following table and change the heap area specified in the Java VM option according to the memory type code {2} that is output. Refer to "Java Function Errors" in the Operation Guide for information on tuning.

Memory type code {2}	Action
0 (C heap area)	<p>Reestimate the memory required to run the PL/extJava, and check if sufficient memory is secured.</p> <p>If it is, there may be insufficient memory to use other applications. Reestimate the memory required to run other applications on the same machine, and investigate if there is sufficient memory.</p> <p>If, as a result of the reestimation, it is confirmed that there is insufficient memory, contact the system administrator. Ask the system administrator to add the main memory or extend the swap area.</p> <p>If the Java heap area is excessively large, reduce the Java VM heap area size and Perm area size. Refer to "Java Function Errors" in the Operation Guide for details.</p>
1 (Java VM heap area size)	<p>Extend the Java VM heap area size, and restart the instance. Check "heap_size" in the Java VM log of PL/extJava for the Java heap area when an OutOfMemoryError occurs.</p> <p>Refer to "Java Function Errors" in the Operation Guide for details.</p> <p> Note</p> <p>.....</p> <p>Even if "heap_size" in the Java VM log provides sufficient space for "max_heap_size", the heap area may be insufficient if the generated object is extremely large, or if there is no contiguous heap area. Extend the heap area in this case as well.</p> <p>.....</p>
2 (Java VM Perm area size)	<p>Extend the Java VM Perm area size, and restart the instance. Check "perm_size" in the Java VM log of PL/extJava for the Java permanent area when an OutOfMemoryError occurs.</p> <p>Refer to "Java Function Errors" in the Operation Guide for details.</p>
-1	<p>Check the setting value for "heap_type" in the Java VM log of PL/extJava to determine the memory type code, and take action for the C heap area, Java VM heap area size and Perm area size described above.</p>

Memory type code {2}	Action
(Failed to obtain the Java VM information)	Also, check the information output to the Java VM log of the instance for details of the insufficient Java VM heap area, and tune accordingly.

Example

Java VM log output example

```

:
-----
OutOfMemory Log
-----
pid=4696
heap_type=1
heap_size=136800
max_heap_size=6291456
perm_size=2052320
max_perm_size=67108864
requested_size=40000016
-----
VM is terminated by occurred OutOfMemoryError on Java heap.
"main" prio=6 tid=0x00307000 nid=0x12a8 [0x0092f000]
  java.lang.Thread.State: RUNNABLE
    at test.<init>(test.java:10)
    at test.main(test.java:5)

```

WARNING: PCMI1106: Application processing time exceeded monitoring time.: INSTANCE={0} ID={1} ADAPTER={2} PID={3}

Variable Information

- {0}: PCMI directory path
- {1}: Server instance (Java VM) name
- {2}: Internal information
- {3}: Process ID

Explanation

The Java application processing time has exceeded the monitoring time.

System Action

Application processing is continued.

User Action

If a message has been output to the event log (Windows(R)) or the system log (Linux) immediately before this message, take the action indicated by that message and investigate the cause of time-consuming Java application processing.

ERROR: PCMI1107: Application processing time exceeded monitoring time.: INSTANCE={0} ID={1} ADAPTER={2} PID={3}

Variable Information

- {0}: PCMI directory path
- {1}: Server instance (Java VM) name
- {2}: Internal information

{3}: Process ID

Explanation

The Java application processing time exceeded the monitoring time, therefore the Java application terminated abnormally.

System Action

The application is stopped.

User Action

If a message has been output to the event log (Windows(R)) or the system log (Linux) immediately before this message, take the action indicated by that message and investigate the cause of time-consuming Java application processing.

WARNING: PCMI1108: No response time exceeded monitoring time.: INSTANCE={0} ID={1} PID={2}

Variable Information

{0}: PCMI directory path

{1}: Server instance (Java VM) name

{2}: Process ID

Explanation

This is the notification, which indicates that the active state monitoring time was exceeded.

System Action

Processing is continued.

User Action

If a message has been output to the event log (Windows(R)) or the system log (Linux) immediately before this message, take the action indicated by that message and investigate the cause of response deterioration.

ERROR: PCMI1109: No response time exceeded monitoring time.: INSTANCE={0} ID={1} PID={2}

Variable Information

{0}: PCMI directory path

{1}: Server instance (Java VM) name

{2}: Process ID

Explanation

The notification of active state monitoring time was exceeded, therefore the server instance (Java VM) was stopped by force.

System Action

The server instance (Java VM) is stopped.

User Action

If a message has been output to the event log (Windows(R)) or the system log (Linux) immediately before this message, take the action indicated by that message and investigate the cause of response deterioration.

WARNING: PCMI1115: Abnormality occurred by the reactivation processing after the process had stopped. INSTANCE={0} ID={1} ADAPTER={2} DETAIL={3}

Variable Information

- {0}: PCMI directory path
- {1}: Server instance (Java VM) name
- {2}: Internal information
- {3}: Detail information

Explanation

An error occurred during restart processing after the process stopped.

System Action

The restart processing for the process is canceled.

User Action

Check Detail information {3} that is output, and remove the cause of the failure.

If this error message continues to occur, make a note of the error information in this message and contact Fujitsu technical support.

WARNING: PCMI1116: The process monitoring failed.: INSTANCE={0} ID={1} ADAPTER={2}

Variable Information

- {0}: PCMI directory path
- {1}: Server instance (Java VM) name
- {2}: Internal information

Explanation

The process monitoring has failed.

System Action

The process monitoring is continued after the process monitoring for the server instance (Java VM) {1} is skipped.

User Action

If another message has been output immediately before this message, take the action indicated by that message.

If a message has not been output immediately before this message, or this message is still output despite taking the above action, contact Fujitsu technical support.

WARNING: PCMI1118: Abnormality occurred by the stop procedure.: INSTANCE={0} ID={1} ADAPTER={2} DETAIL={3}

Variable Information

- {0}: PCMI directory path
- {1}: Server instance (Java VM) name
- {2}: Internal information
- {3}: Detail information

Explanation

An error occurred during the processing to stop the process.

System Action

Processing is continued.

User Action

Not required.

A.2.14.4 PCMI1200 to PCMI1299

ERROR: PCMI1200: Directory deletion failed.: PATH={0}

Variable Information

{0}: Path

Explanation

Failed to delete the directory {0}.

Possible causes are as follows:

- Write privileges have not been configured for the directory or the parent directory.
- The disk has become corrupted, therefore access to the file or directory has failed.
- Due to a conflict with other processing, access to the disk is temporarily unavailable.

System Action

Processing is interrupted.

User Action

- Check if write privileges have been configured for the directory or the parent directory.
- Check if the disk has become corrupted.
- If access to the disk is temporarily unavailable, wait for a while and then reexecute processing.

ERROR: PCMI1201: Unable to rotation the directory.: PATH={0} BACKUP_ROOT_PATH={1}

Variable Information

{0}: Current directory path

{1}: Current directory backup destination path

Explanation

Failed to rotate the current directory {0}.

Possible causes are as follows:

- Write privileges have not been configured for the directory or the parent directory.
- The disk has become corrupted, therefore access to the file or directory has failed.
- Due to a conflict with other processing, access to the disk is temporarily unavailable.

System Action

Processing is interrupted.

User Action

- Check if write privileges have been configured for the directory or the parent directory.
- Check if the disk has become corrupted.
- If access to the disk is temporarily unavailable, wait for a while and then reexecute processing.

ERROR: PCMI1202: Directory creation failed.: PATH={0}

Variable Information

{0}: Path

Explanation

Failed to create the directory {0}.

Possible causes are as follows:

- Write privileges have not been configured for the directory or the parent directory.
- The disk has become corrupted, therefore access to the file or directory has failed.
- Due to a conflict with other processing, access to the disk is temporarily unavailable.

System Action

Processing is interrupted.

User Action

- Check if write privileges have been configured for the directory or the parent directory.
- Check if the disk has become corrupted.
- If access to the disk is temporarily unavailable, wait for a while and then reexecute processing.

A.2.14.5 PCMI1300 to PCMI1399

INFO: PCMI1300: Log rotated successfully.: FILE={0}

Variable Information

{0}: Log file path

Explanation

Rotation of the log file {0} was successful.

WARNING: PCMI1301:Log rotation failed.: FILE={0}, REASON={1}

Variable Information

{0}: Log file path

{1}: Reason

Explanation

Rotation of the log file {0} failed for the reason in {1}.

System Action

The rotation processing is canceled, and the server instance processing is continued.

User Action

- If there is insufficient free disk space, secure more.
- If access privileges have not been configured correctly for the log file to be rotated, configure these privileges.
- If an I/O error occurred, check if the disk device where the log file is saved is running normally.
- Check if a file with the same name as the log file name after rotation exists. If a file with the same name exists, delete or back up the file.
- If another program has opened the log file, close the log file.
- Check if an old generation log file has been locked.

ERROR: PCMI1302: Failed in preparing for logging to the file.: FILE={0}, REASON={1}**Variable Information**

{0}: Log file path

{1}: Reason

Explanation

Initialization of the log file {0} failed for the reason in {1}.

System Action

Log file initialization is interrupted, and server instance (Java VM) processing is continued.

User Action

- If there is insufficient free disk space, secure more.
- If access privileges have not been configured correctly for the log file, configure these privileges.
- If an I/O error occurred, check if the disk device where the log file is saved is running normally.
- If another program has opened the log file, close the log file.
- Ensure that the length of the log file's absolute path has not exceeded the maximum path length configured in the operating system. If it has, configure the length of the log file's absolute path so that it does not exceed the maximum path length configured in the operating system.

INFO: PCMI1303: Pending output was flushed.: FILE={0}**Variable Information**

{0}: Log file path

Explanation

A pending message was output to the log file {0}.

WARNING: PCMI1304: Something went wrong in the drainer. It will be stopped.**Explanation**

An error has occurred in the log collection thread. The log collection feature will be stopped.

System Action

The server instance (Java VM) processing is continued.

User Action

To continue Java VM log collection for PL/extJava, restart the instance.

ERROR: PCMI1306: Failed in logging standard output to the file.: FILE={0}, REASON={1}**Variable Information**

{0}: Log file path

{1}: Reason

Explanation

Output to the log file {0} failed for the reason in {1}.

System Action

The server instance (Java VM) processing is continued.

User Action

- If there is insufficient free disk space, secure more.
- If an I/O error occurred, check if the disk device where the log file is saved is running normally.

ERROR: PCMI1307: Failed in initializing the trace log file.

Explanation

Failed to initialize the trace log file.

System Action

The processing to start the PCMI service is canceled.

User Action

Restart the instance.

A.2.15 Messages that Contain "PWC" in the Message ID

A.2.15.1 PWC1000 to PWC1999

SEVERE: PWC1240: Container {0} has not been started

Variable Information

{0}: Java application name

Explanation

Failed to start the Java application {0}.

System Action

Processing is continued.

User Action

Refer to the exception information that will be output after this message.

PWC1277: Exception sending context destroyed event to listener instance of class {0}

Variable Information

{0}: Listener class name

Explanation

An error occurred in the call to the contextDestroyed method of the listener.

System Action

The deactivation processing of the Java application is interrupted.

User Action

Follow the action advised in the exception information and any other messages to remove the cause of the error.

A.2.15.2 PWC3000 to PWC3999

SEVERE: PWC3983: Coyote connector has not been started

Explanation

The HTTP listener has not been started.

System Action

Processing is continued.

User Action

The instance may have failed to start. Follow the action advised in the other messages and the exception information output to remove the cause of the error.

SEVERE: PWC3989: An exception or error occurred in the container during the request processing

Explanation

An exception or error occurred in the container during request processing.

Cause

An exception occurred in the instance during request processing.
The instance stop processing or definition items may have been changed.

User Action

If this message is output during stop processing, ignore it.
Requests accepted during stop processing will not be processed.
Refer to the message and the exception output before and after this message, and resolve the problem.
If the problem is still not resolved despite taking the above action, contact Fujitsu technical support.

A.2.15.3 PWC4000 to PWC4999

PWC4012: Unable to resolve IP address {0} into host name

Variable Information

{0}: IP address used for DNS reverse lookup

Explanation

The host name could not be resolved from the IP address.

System Action

Processing is continued.

User Action

Check if the variable information {0} is displaying the correct IP address. If an invalid IP address is displayed, investigate if there is a possibility of attacks being encountered.

A.2.16 Messages that Contain "RAR" in the Message ID

A.2.16.1 RAR5000 to RAR5099

RAR5009:Cannot load external-jndi-resource factory-class "{0}"

Variable Information

{0}: Factory class name

Explanation

The factory class of an external resource failed to load.

System Action

Processing is continued without registering the naming service of the resource for which the error occurred.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

RAR5010:external-jndi-resource factory-class "[{0}]" must be of type javax.naming.spi.InitialContextFactory

Variable Information

{0}: Factory class name

Explanation

The external resource factory class must implement the javax.naming.spi.InitialContextFactory interface.

System Action

Processing is continued without registering the naming service of the resource for which the error occurred.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

RAR5011:Exception thrown creating initial context for external JNDI factory "[{0}]"

Variable Information

{0}: External JDBC resource name

Explanation

An exception occurred during generation of the initial context for an external resource.

System Action

Processing is continued.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

RAR5012:Cannot create external-jndi-resource factory-class "[{0}]"

Variable Information

{0}: External resource factory class

Explanation

Factory class generation failed for the external resource.

System Action

Processing is continued.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

RAR5029:Unexpected exception while registering component**Explanation**

An unexpected exception occurred while registering the component.

System Action

Processing is continued.

User Action

Refer to the exception information output immediately after this message, and remove the cause of the error.

RAR5031:System Exception**Explanation**

A system exception occurred during a resource operation.

System Action

An exception is returned to the caller.

User Action

Refer to the exception information output immediately after this message, and remove the cause of the error.

RAR5035:Unexpected exception while destroying resource from pool {0}. Exception message: {1}**Variable Information**

{0}: JDBC connection pool name

{1}: Exception information

Explanation

An exception occurred while discarding the resource.

System Action

Processing is continued.

User Action

Refer to Exception information output immediately before this message.

INFO: RAR5074 : Table based validation detected invalid connection. Querying the table {0} failed.**Variable Information**

{0}: Table name

Explanation

An invalid connection was detected during connection validation when "table" was selected. SELECT statement execution to the table {0} failed.

System Action

Processing is continued.

User Action

Check if the instance is started. Also, check if users who connect to the instance have privileges for executing SELECT statements to tables that are targeted for connection testing.

A.2.16.2 RAR5100 to RAR5199

WARNING: ISJEE_RAR5117: Failed to obtain/create connection from connection pool [{0}]. Reason : {1}

Variable Information

{0}: Connection pool name

{1}: Exception information

Explanation

Acquisition of a connection from the connection pool failed.

System Action

An exception is returned to the calling source.

User Action

Refer to the exception information and remove the cause of the error.

NFO: RAR5118 : isValid based validation detected invalid connection.

Explanation

Connection validation which uses isValid in validation method has detected invalid connections.

System Action

Processing is continued.

User Action

Check if the instance has started. Also, check if the state of the instance is normal. Identify the cause of the error from the instance log information and remove it, and then reexecute processing.

WARNING: RAR5199 : The JDBC driver does not support isValid method

Explanation

The current driver does not support the isValid method.

System Action

Processing is continued.

User Action

- Configure a JDBC driver that supports the isValid method.
- Change the validation method to table.

A.2.16.3 RAR6000 to RAR6099

RAR6000 : Invalid deployment descriptor, no connection-definition found either via ra.xml or annotations for the resource-adapter [{0}]

Variable Information

{0}: Resource adapter name

Explanation

The deployment descriptor (ra.xml) or the annotation for the resource adapter {0} is invalid.

System Action

Processing is continued.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

RAR6002 : Could not instantiate class : {0}

Variable Information

{0}: JavaBean class name

Explanation

Instantiation failed for JavaBean class {0}.

System Action

Processing is continued.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

RAR6013 : Could not publish connector descriptor in JNDI : {0}

Variable Information

{0}: JDBC resource name

Explanation

Registration of the deployment descriptor for the JDBC resource name {0} failed.

System Action

Processing is continued.

User Action

Refer to the exception information output immediately after this message, remove the cause of the error, and then execute the processing again.

RAR6014 : Could not find the connector descriptor in the rar : {0}

Variable Information

{0}: Module name

Explanation

The module {0} deployment descriptor was not found.

System Action

Processing is continued.

User Action

Refer to the exception information output immediately after this message, remove the cause of the error, and then execute the processing again.

RAR6017 : Failed to get connection pool object {0} via JNDI lookup : {1}

Variable Information

{0}: JDBC connection pool name
{1}: Exception information

Explanation

Failed to obtain the JDBC connection pool via JDBC resource lookup.

System Action

Processing is continued.

User Action

Refer to Exception information output immediately after this message, remove the cause of the error, and then execute the processing again.

RAR6019 : Failed to get connector descriptor from registry. RarName : {0}

Variable Information

{0}: Resource adapter name

Explanation

Acquisition of resource adapter definition information failed.

System Action

Processing is continued.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

RAR6035 : Resource adapter start failed.

Variable Information

{0}: Module name

Explanation

Resource adapter start processing failed.

System Action

Processing is continued.

User Action

Refer to the stack trace output before and after the error to identify the cause of the error and remove it, and then restart the instance.

A.2.16.4 RAR7000 to RAR7099

RAR7099: The mcf being used to allocate the connection and the MCF in the pool are not equal.

Explanation

The ManagedConnectionFactory used to allocate the logical connection does not match the ManagedConnectionFactory in the JDBC connection pool.

System Action

Processing is continued.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.16.5 RAR7100 to RAR7199

INFO: RAR7114: Unable to get ClientInfo for connection : {0}

Variable Information

{0}: Detail information

Explanation

getClientInfo failed for the reason in {0}.

System Action

Processing is continued.

User Action

Refer to Detail information {0}, and remove the cause of the error.

INFO: RAR7115: Unable to set ClientInfo for connection : {0}

Variable Information

{0}: Detail information

Explanation

setClientInfo failed for the reason in {0}.

System Action

Processing is continued.

User Action

Refer to Detail information{0}, and remove the cause of the error.

RAR7132: Unable to enlist the resource in transaction. Returned resource to pool. Pool name: [{0}]

Variable Information

{0}: JDBC connection pool name

Explanation

The resource cannot be registered in the transaction.

System Action

The resource is returned to the JDBC connection pool and an exception is returned to the Java application.

User Action

Refer to the exception information output immediately prior to this message, remove the cause of the error, and then execute the application again.

Alternatively, refer to the information output at {0}, take the following actions, and then execute the application again:

- Check if the instance is operating correctly.
- Check if there is a problem with the connection between the instance and the network.

RAR7140: Unable to set log-writer for resource-adapter [{0}] : {1}**Variable Information**

{0}: Class name
{1}: Exception information

Explanation

Setting the LogWriter settings to the ManagedConnectionFactory failed.

System Action

Processing is continued.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.16.6 RAR8000 to RAR8099

WARNING: RAR8022: Failed to get invalid connections from Managed Connection Factory {0}. Exception = {1}; Message = {2}**Variable Information**

{0}: JDBC connection pool name
{1}: Exception class name
{2}: Exception information

Explanation

An exception ({1}) occurred when the connection was obtained from the JDBC connection pool ({0}).

System Action

Processing is continued.

User Action

Refer to Exception information {2}, and remove the cause of the error.

INFO: RAR8029: Resource [{0}] of type [{1}] is not enabled**Variable Information**

{0}: Resource name
{1}: Internal information

Explanation

The resource {0} is not referenced by the Interstage Java EE 6 DAS service or the server instance to which this message is output.

System Action

Processing is continued.

User Action

If this message is output, or resource {0} is not used by the server instance (Java VM), no further action is required.
If it is necessary to use the resource, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

RAR8054: Exception while creating an unpooled [test] connection for pool [{0}], {1}

Variable Information

{0}: JDBC connection pool name
{1}: Exception information

Explanation

An exception was thrown during the creation of a connection for the JDBC connection pool {0}.

System Action

Processing is continued.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

SEVERE: RAR8059: Exception while trying to find properties of class [{0}], set log-level to FINE for more information, {1}

Variable Information

{0}: Class name
{1}: Error information

Explanation

An error ({1}) occurred when the properties of class name {0} were referenced.

System Action

Processing is continued.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

WARNING: RAR8068: Using default datasource : {0} for pool : {1}

Variable Information

{0}: Datasource class name
{1}: JDBC connection pool name

Explanation

There is no datasource class corresponding to the specified datasource class name, therefore the default datasource name ({0}) will be used.

System Action

Processing is continued.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.16.7 RAR8500 to RAR8599

SEVERE: RAR8501: Exception during endpoint activation for ra [{0}], activationSpecClass [{1}] : {2}

Variable Information

{0}: Resource adapter name
{1}: activationSpec class name
{2}: Exception information

Explanation

An exception occurred during the processing that enables the resource adapter ({0}).

System Action

Processing is interrupted.

User Action

Refer to Exception information {2}, and remove the cause of the error.

RAR8505: Application [{0}] does not seem to have started. Skipping Inbound Recovery for the application.

Variable Information

{0}: Application name

Explanation

Not subject to transaction recovery processing.

System Action

Processing is continued.

A.2.16.8 RAR9000 to RAR9099

RAR9033: Thread-pool [{0}] not found

Variable Information

{0}: Thread pool ID

Explanation

The thread pool {0} was not found.

System Action

Processing is continued.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

RAR9034: An error occurred during instantiation of the work manager for resource-adapter [{0}]

Variable Information

{0}: Exception information

Explanation

An error occurred during WorkManager initialization.

System Action

Processing is continued.

User Action

Follow the action advised in Exception information output immediately after this message to remove the cause of the error, and then reexecute processing.

A.2.17 Messages that Contain "SEC" in the Message ID

A.2.17.1 SEC1000 to SEC1099

INFO: SEC1001: Security Manager is ON.

Explanation

Security Manager is enabled.

INFO: SEC1002: Security Manager is OFF.

Explanation

Security Manager is disabled.

INFO: SEC1010: Entering Security Startup Service

Explanation

The security service will start.

INFO: SEC1011: Security Service(s) Started Successfully

Explanation

The security service started successfully.

A.2.17.2 SEC1100 to SEC1199

INFO: SEC1115: Realm [{0}] of classtype [{1}] successfully created.

Variable Information

{0}: Realm name

{1}: Class name

Explanation

The realm was created.

INFO: SEC1117: Realm [{0}] successfully updated.

Variable Information

{0}: Realm name

Explanation

The realm was updated.

System Action

Processing is continued.

A.2.17.3 SEC1200 to SEC1299

WARNING: SEC1202: No support to read Principals in SecretKeyCallback.

Explanation

SecretKeyCallback Principals cannot be referenced.

System Action

Processing is continued.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

WARNING: SEC1203: GFAuthConfigFactory unable to load Provider: {0}, exception : {1}, cause : {2}.

Variable Information

{0}: Provider name
{1}: Exception information
{2}: Cause information

Explanation

Failed to load the AuthConfigProvider implementation class.

System Action

Processing is continued.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.18 Messages that Contain "WEB" in the Message ID

A.2.18.1 WEB0100 to WEB0199

SEVERE: WEB0122: Unable to start web container

Explanation

Failed to start the web container.

System Action

Processing is interrupted.

User Action

Follow the action advised in the exception information and any other messages output at the same time to remove the cause of the error.

SEVERE: WEB0123: Unable to stop web container

Explanation

Failed to stop the container.

System Action

Processing is continued.

User Action

Follow the action advised in the exception information and any other messages output at the same time to remove the cause of the error.

WARNING: WEB0153: Unable to load configuration of web module [{0}]

Variable Information

{0}: Java application name

Explanation

An exception occurred while loading the Java application.

System Action

Processing is continued.

User Action

Follow the action advised in the exception information and any other messages output at the same time to remove the cause of the error.

WARNING: WEB0156: Exception during invocation of PreDestroy-annotated method on JSP tag handler [{0}]

Variable Information

{0}: Class information

Explanation

An exception was thrown by the @PreDestroy-annotated method of the tag class being used on JSP.

System Action

Processing is continued.

User Action

Follow the action advised in the exception information output at the same time to remove the cause of the error.

SEVERE: WEB0157: Unable to load session uuid generator [{0}]

Variable Information

{0}: Internal information

Explanation

Failed to initialize the web application.

System Action

Processing is continued.

User Action

Contact Fujitsu technical support.

SEVERE: WEB0161: Error loading web module [{0}]

Variable Information

{0}: Java application name

Explanation

Failed to load the Java application.

System Action

Processing is continued.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

SEVERE: WEB0163: Exception processing HttpService configuration change

Explanation

Failed to change the HTTP service or the network configuration definition item.

System Action

Processing is continued.

User Action

Follow the action advised in the exception information and any other messages output at the same time to remove the cause of the error.

INFO: WEB0169: Created HTTP listener [{0}] on host/port [{1}:{2}]

Variable Information

{0}: HTTP listener name

{1}: IP address

{2}: Port number

Explanation

The HTTP listener settings were configured.

INFO: WEB0171: Created virtual server [{0}]

Variable Information

{0}: Internal information

Explanation

The container settings were configured.

INFO: WEB0172: Virtual server [{0}] loaded default web module [{1}]

Variable Information

{0}: Internal information

{1}: Internal information

Explanation

The web container settings were configured.

A.2.18.2 WEB0300 to WEB0399

WARNING: WEB0333: Unable to rename access log file {0} to {1}

Variable Information

{0}: Log file name before being renamed

{1}: Log file name after being renamed

Explanation

Failed to rename the log file for HTTP access log rotation.

System Action

The log file before being renamed is reopened, and processing is continued.

User Action

- If there is insufficient free disk space, secure more.
- If access privileges have not been configured correctly, change the access privileges so that the log file for which rotation is performed can be accessed.
- If an I/O error occurred, check if the disk device where the log file is saved is running normally.
- Check if a file with the same name as the log file name after rotation exists. If a file with the same name exists, delete or back up the file.

SEVERE: WEB0351: Access logger has not yet been started

Explanation

The HTTP access log failed to start, therefore the processing to stop the HTTP access log was not performed.

System Action

The processing to stop the HTTP access log is not performed.

User Action

Not required.

WARNING: WEB0357: Unable to remove access log file {0}

Variable Information

{0}: Log file name

Explanation

Failed to remove the log file for HTTP access log rotation.

System Action

Processing is continued.

The log file for which the removal attempt failed is not removed after that.

User Action

- Remove the log file for which the removal attempt failed.
- If access privileges have not been configured correctly, change access privileges so that the log file for which removal is performed can be accessed.
- If an I/O error occurred, check if the disk device where the log file is saved is running normally.

A.2.18.3 WEB0600 to WEB0699

INFO: WEB0671: Loading application [{0}] at [{1}]

Variable Information

{0}: Java application name
{1}: Context root name

Explanation

The Java application has been loaded.

A.2.18.4 WEB0700 to WEB0799

WARNING: WEB0791: An invalid request was received. The request does not match request-check value [{0}].

Variable Information

{0}: Value set for the operation mode to access the container

Explanation

An illegal attack may have been encountered from an external source.

System Action

The status code 400 (Bad Request) is returned.

User Action

Investigate whether an attack has been encountered based on the IP addresses recorded in the HTTP access log.

A.2.18.5 WEB2000 to WEB2999

SEVERE: WEB2100: Unexpected error occurred while configuring session id. code={0}

Variable Information

{0}: Cause code

Explanation

Failed to initialize the Java application.

System Action

Java application initialization is interrupted. The Java application cannot be used.

User Action

Contact Fujitsu technical support.

WARNING: WEB2106: Network configuration is not proper. code={0}

Variable Information

{0}: Cause code

Explanation

The network environment is not appropriate.

System Action

Processing is continued.

User Action

If this message is output to a machine that is not connected to a network, ignore this message.



If the cause of the problem is other than the above, contact Fujitsu technical support.

A.2.18.6 WEB5000 to WEB5099

SEVERE: WEB5001: Exception during processing of event of type {0} for web module {1}

Variable Information

{0}: Internal information
{1}: Context information

Explanation

Event processing for the Java application failed.

System Action

Processing is interrupted.

User Action

Follow the action advised in the exception information and any other messages output at the same time to remove the cause of the error.

A.2.18.7 WEB9000 to WEB9099

WEB9033: Unable to load class with name [{0}], reason: {1}

Variable Information

{0}: Class name
{1}: Exception information

Explanation

Failed to load the class.

System Action

Class loading is interrupted.
The class that you tried to load cannot be used.

User Action

Follow the action advised in Exception information and any other messages to remove the cause of the error.

WARNING: WEB9034: SQL driver deregistration failed

Explanation

Failed to delete references to the JDBC driver loaded by the web class loader.

System Action

Processing is continued.

User Action

Follow the action advised in the exception information and any other messages to remove the cause of the error.

WARNING: WEB9035: Unable to read data for class with name [{0}]

Variable Information

{0}: Class name

Explanation

Failed to read the class.

System Action

Processing is continued.

User Action

Follow the action advised in the exception information and any other messages to remove the cause of the error.

WEB9038: Unable to validate JAR entry with name {0}

Variable Information

{0}: Resource name

Explanation

The resource {0} could not be detected in the JAR file under WEB-INF/lib.

System Action

Resource detection processing will be interrupted.

User Action

Follow the action advised in the exception information and any other messages to remove the cause of the error.

A.2.18.8 WEB9900 to WEB9999

WEB9901: Failed to close resource [{0}]

Variable Information

{0}: Resource obtained from the web class loader

Explanation

Failed to close the resource.

System Action

Processing is continued.

User Action

Refer to the other messages and the exception information output at the same time, and remove the cause of the error.

A.2.18.9 When there is no Message Number

If not explained in the Messages, identify the cause of the problem from the message body and take appropriate action. If the problem still exists, contact Fujitsu technical support.

A.2.19 Messages that Contain "WELD" in the Message ID

A.2.19.1 WELD-000200 to WELD-000299

WELD-000214 Attempt to call begin() on a long-running conversation

Explanation

javax.enterprise.context.Conversation#begin() was executed in a state where the Conversation scope had already started.

System Action

Processing is interrupted.

User Action

Review the Java application processing so that `javax.enterprise.context.Conversation#begin()` is not executed after the Conversation scope is started.

WELD-000215 Attempt to call end() on a transient conversation

Explanation

`javax.enterprise.context.Conversation#end()` was executed in a state where the Conversation scope had not yet started.

System Action

Processing is interrupted.

User Action

Review the Java application processing so that `javax.enterprise.context.Conversation#end()` is not executed in a state where the Conversation scope has not yet started.

A.2.19.2 WELD-000300 to WELD-000399

WELD-000321 No conversation found to restore for id {0}

Variable Information

{0}: Conversation scope ID number

Explanation

The Conversation scope of ID {0} was not found.

System Action

Processing is interrupted.

User Action

The Conversation scope of ID {0} may have ended because of a timeout.

Check if a timeout has occurred.

A.2.19.3 WELD-000400 to WELD-000499

WELD-000404 Conditional observer method [{0}] cannot be declared by a @Dependent scoped bean

Variable Information

{0}: Observer method

Explanation

The Observer method has been declared for the Dependent scope class.

System Action

Processing is interrupted.

User Action

Change the scope of the class for which the Observer method has been declared to a scope other than Dependent.

A.2.19.4 WELD-000800 to WELD-000899

WELD-000816 Cannot determine constructor to use for {0}

Variable Information

{0}: Interface implemented by the injected class

Explanation

A class has not been specified for the @New annotation argument.

System Action

Processing is interrupted.

User Action

Specify the class to be injected in the argument.

A.2.19.5 WELD-000900 to WELD-000999

WELD-000900 1.1.8 (is)

Explanation

This message shows the version of the CDI.

A.2.19.6 WELD-001300 to WELD-001399

WELD-001318 Cannot resolve an ambiguous dependency between {0}

Variable Information

{0}: Injected class candidate

Explanation

There are multiple classes that can be injected.

System Action

Processing is interrupted.

User Action

Check the CDI-related definition so that the class to be injected can be identified.

A.2.19.7 WELD-001400 to WELD-001499

WELD-001408 Unsatisfied dependencies for type [{0}] with qualifiers [{1}] at injection point [{2}]

Variable Information

{0}: Injected class or interface

{1}: Injected class qualifier

{2}: Injection destination

Explanation

Either the CDI-related definition for the injected class is insufficient, or the CDI is not valid.

System Action

Processing is interrupted.

User Action

Check the CDI-related definition for the injected class. Alternatively, check if beans.xml has been stored in the Java application.

WELD-001409 Ambiguous dependencies for type [{0}] with qualifiers [{1}] at injection point [{2}]. Possible dependencies [{3}]

Variable Information

{0}: Injected class or interface
{1}: Injected class qualifier
{2}: Injection destination
{3}: Injected class candidate

Explanation

There are multiple classes that can be injected.

System Action

Processing is interrupted.

User Action

Check the CDI-related definition so that the class to be injected can be identified.

WELD-001417 Enabled interceptor class {0} is neither annotated @Interceptor nor registered through a portable extension

Variable Information

{0}: Class defined as the Interceptor in beans.xml

Explanation

The @Interceptor annotation has not been granted to the class specified as the Interceptor in beans.xml.

System Action

Processing is interrupted.

User Action

To use an Interceptor, grant the @Interceptor annotation.
If the Interceptor is not to be used, delete the content specified for the Interceptor from beans.xml.

WELD-001422 Enabled alternative {0} is not annotated @Alternative

Variable Information

{0}: Class defined as the Alternative in beans.xml

Explanation

The @Alternative annotation has not been granted to the class in which the Alternative is enabled.

System Action

Processing is interrupted.

User Action

Grant the @Alternative annotation.

WELD-001424 The following disposal methods were declared but did not resolve to a producer method: {0}

Variable Information

{0}: disposer method

Explanation

The configuration of the disposer method is incorrect.

System Action

Processing is interrupted.

User Action

Check the definitions of the producer and disposer methods.

WELD-001450 **Interceptor method {0} does not declare that it throws Exception.**

Variable Information

{0}: Method specified for the Interceptor

Explanation

Throwing exceptions has not been declared in the Interceptor.

System Action

Processing is continued.

User Action

Declare the throwing of exceptions in the Interceptor.

A.2.20 Messages that Contain "WSC" in the Message ID

A.2.20.1 WSC04100 to WSC04199

ERROR: WSC04109: The specified IP address and port number are already in use in another IJServer cluster: Please specify different values: Specified value={0}

Variable Information

{0}: Specified port number

Explanation

The port number that you are trying to set for the server instance, and the port number for the server instance (Java VM) of the same combination, are already in use for another server instance (Java VM).

System Action

Processing is interrupted.

User Action

Specify a port number that is not in use by another server instance (Java VM).

ERROR: WSC04112: Could not access file: {0}

Variable Information

{0}: Detail information

Explanation

Could not access file.

System Action

Processing is interrupted.

User Action

The following causes can be considered. Remove the cause, and reexecute processing.

If the problem still exists, contact Fujitsu technical support.

- Access authority is not granted to the file.
Access authority of the file may have been changed. Restore the access authority for the file, and reexecute processing.
- The file or directory is referenced by another application.
Stop other applications, and reexecute processing.
- The disk is defective.
A defect on the disk may be preventing files and directories from being accessed. Run a disk check
- Conflict with another process.
Conflict with another process may make the disk temporarily inaccessible. Reexecute processing.

ERROR: WSC04163: Some log files could not be deleted: Please delete remaining log files manually: Log output directory={0}

Variable Information

{0}: Log output place directory

Explanation

Some log files could not be deleted.

System Action

Processing is interrupted.

User Action

Check if some log files remain in the directory displayed in Variable Information.

Delete the log files which remain by manual operation.

A log file cannot be deleted when the others are referring to that log file.

ERROR: WSC04199: Unknown error occurred: {0}

Variable Information

{0}: Detail information

Explanation

- When Detail information {0} displays "Failed to allocate memory":
There is insufficient memory.
- When Detail information {0} displays any other message:
An unexpected error has occurred.

System Action

Processing is interrupted.

User Action

- When Detail information {0} displays "Failed to allocate memory":
Check if there is sufficient memory. Stop other applications, and reduce the load on the machine.
- When Detail information {0} displays any other message:
Contact Fujitsu technical support.

A.2.20.2 WSC04400 to WSC04499

ERROR: WSC04404: Value specified for the maximum number of connections to the Web container is invalid: Specify a value from 0 to 2048: Specified value={0}

Variable Information

{0}: Maximum number of connections to the container

Explanation

Invalid maximum number of connections to the container.

System Action

Processing is interrupted.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

ERROR: WSC04426: The specified IP address or port number is invalid: Specified value={0}

Variable Information

{0}: port number

Explanation

The specified port number does not exist.

Alternatively, an invalid port number has been specified.

System Action

Processing is interrupted.

User Action

Check the port number.

ERROR: WSC04427: The specified IP address and port number already exist: Specify different values: Specified value={0}

Variable Information

{0}: port number

Explanation

The port number that you are trying to set for the server instance, and the port number for the server instance (Java VM) of the same combination, are already in use.

System Action

Processing is interrupted.

User Action

Specify a port number that is not in use by another server instance (Java VM).

ERROR: WSC04498: Cannot create the Web server connector operating environment: {0}

Variable Information

{0}: Detail information

Explanation

Unable to create the operating environment of the web server connector.

System Action

Processing is interrupted.

User Action

Possible causes are given below. After taking the appropriate action, reexecute processing.

- Access authority is not granted to the file.
Access authority of the file may have been changed. Restore the access authority for the file, and reexecute processing.
- The disk is defective.
A defect on the disk may be preventing files and directories from being accessed. Run a disk check.
- There is insufficient disk space.
Secure sufficient free disk space.

ERROR: WSC04499: Internal definition error: {0}

Variable Information

{0}: Detail information

Explanation

There are errors in the internal definition information of the web server connector.

The definitions are in an abnormal state due to direct editing of the internal definition file or unexpected errors.

System Action

Processing is interrupted.

User Action

If there are backed up resources, restore them.

A.2.21 Messages that Contain "ahs" in the Message ID

A.2.21.1 ahs00000 to ahs00099

This section details the messages numbered between ahs00000 and ahs00099.

A.2.21.1.1 ahs00001

AHS: INFO: ahs00001: HTTP Server started. [%s1]**Variable Information**

%s1 = Environment definition file name

Explanation

The web server has been started.

A.2.21.1.2 ahs00002

AHS: INFO: ahs00002: HTTP Server stopped. [%s1]**Variable Information**

%s1 = Environment definition file name

Explanation

The web server has been stopped.

A.2.21.1.3 ahs00004

AHS: ERROR: ahs00004: Pre-configuration failed [%s1]**Variable Information**

%s1 = Environment definition file name

Explanation

An error occurred during initialization preprocessing.

System Action

The web server execution processing is aborted.

User Action

Refer to the message that was output at the same time and fix the error.

If the cause of errors cannot be found, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.1.4 ahs00005

AHS: ERROR: ahs00005: Unable to open logs [%s1]**Variable Information**

%s1 = Environment definition file name

Explanation

An error occurred during log initialization processing.

The File Descriptor number required to run the web server may be invalid.

System Action

The web server execution processing is aborted.

User Action

Refer to the message that was output at the same time and fix the error.

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.1.5 ahs00006

AHS: ERROR: ahs00006: Configuration Failed [%s1]

Variable Information

%s1 = Environment definition file name

Explanation

An error occurred during initialization processing.

System Action

The web server execution processing is aborted.

User Action

Refer to the message that was output at the same time and fix the error.

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.1.6 ahs00008

AHS: ERROR: ahs00008: %s1: Module "%s2" is not compatible with this version of Apache (found %s3, need %s4). Please contact the vendor for the correct version. [%s5]

Variable Information

%s1 = Web server program name

%s2 = Plug-in module name

%s3 = Plug-in module major version

%s4 = Web server program major version

%s5 = Environment definition file name

Explanation

The major version (%s4) of the web server program and the major version (%s3) of the plug-in module (%s2) are different.

System Action

The web server execution processing is aborted.

User Action

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.1.7 ahs00009

AHS: ERROR: ahs00009: %s1: Module "%s2" could not be loaded, because the dynamic module limit was reached. Please increase DYNAMIC_MODULE_LIMIT and recompile. [%s3]

Variable Information

%s1 = Web server program name

%s2 = Plug-in module name

%s3 = Environment definition file name

Explanation

The maximum number of plug-in modules that can be used has been exceeded.

System Action

The web server execution processing is aborted.

User Action

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.1.8 ahs00010

AHS: ERROR: ahs00010: Syntax error in -C/-c directive: %s1 [%s2]

Variable Information

%s1 = Syntax error description

%s2 = Environment definition file name

Explanation

The syntax of the directive specified for the -C or -c option is incorrect.

System Action

The web server execution processing is aborted.

User Action

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.1.9 ahs00011

AHS: ERROR: ahs00011: %s1: Could not open configuration file %s2: %s3 [%s2]

Variable Information

%s1 = Web server program name

%s2 = Environment definition file name

%s3 = Error details information

Explanation

The environment definition file (%s2) could not be opened.

System Action

The web server execution processing is aborted.

User Action

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.1.10 ahs00012

AHS: ERROR: ahs00012: %s1 Syntax error on line %s2 of %s3: %s4 [%s3]

Variable Information

%s1 = Web server program name

%s2 = The line in the environment definition file

%s3 = Environment definition file name

%s4 = Syntax error description



Note

The web server program name (%s1) may not be output.

Explanation

Syntax error (%s4) occurred in the environment definition file (%s3).

System Action

The web server execution processing is aborted.

User Action

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.1.11 ahs00013

AHS: ERROR: ahs00013: (%s1)%s2: Invalid config file path %s3 [%s3]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Environment definition file name

Explanation

The specified environment definition file (%s3) path is incorrect.

System Action

The web server execution processing is aborted.

User Action

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.1.12 ahs00014

AHS: ERROR: ahs00014: (%s1)%s2: alloc_listener: failed to set up sockaddr for %s3 [%s4]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Host name

%s4 = Environment definition file name

Explanation

Failed to retrieve information for the host (%s3) specified in the web server environment definition file.

System Action

The web server execution processing is aborted.

User Action

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.1.13 ahs00015

AHS: ERROR: ahs00015: (%s1)%s2: alloc_listener: failed to get a socket for %s3 [%s4]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Host name

%s4 = Environment definition file name

Explanation

A communication socket could not be created.

System Action

The web server execution processing is aborted.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.1.14 ahs00016

AHS: ERROR: ahs00016: (%s1)%s2: make_sock: for address %s3, apr_socket_opt_set: (%s4) [%s5]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = IP address:Port number

%s4 = Socket option

%s5 = Environment definition file name

Explanation

The socket option (%s4) could not be set.

System Action

The web server start processing is canceled.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.1.15 ahs00017

AHS: WARNING: ahs00017: (%s1)%s2: make_sock: failed to set %s3 for address %s4, using default [%s5]

Variable Information

- %s1 = Error details number
- %s2 = Error details context
- %s3 = IP address:Port number
- %s4 = Socket option
- %s5 = Environment definition file name

Explanation

The socket option (%s4) could not be set. The socket option runs using the system default value.

System Action

The web server start processing is continued.

User Action

- Resolve the cause of the error according to the error details context (%s2).
- If the cause cannot be identified, recover PL/extJava.
- If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.1.16 ahs00018

AHS: ERROR: ahs00018: (%s1)%s2: make_sock: could not bind to address %s3 [%s4]

Variable Information

- %s1 = Error details number
- %s2 = Error details context
- %s3 = IP address:Port number
- %s4 = Environment definition file name

Explanation

An address could not be assigned to the socket.

System Action

The web server start processing is canceled.

User Action

Take the action described in table below, according to Error details number (%s1).

Error details number (%s1)	Meaning/Required Action
W OS 10013 OS 10048	If this message is output when the instance starts, take one of the following actions: <ul style="list-style-type: none">- If the instance was restarted immediately after being stopped, the release processing for the IP address or the port number (%s3) used by the instance that was stopped may not have completed. Wait for a while (several seconds), and then restart the instance.
L 98	

Error details number (%s1)	Meaning/Required Action
	- Another service is using the IP address and port number (%s3) or port number (%s3). Check whether the IP address and port number specified for the web server is also specified for another service. If so, terminate that service, or use a different IP address and/or port number. If the IP address and port number settings are correct, collect diagnostic information for the product using the FJQSS (Information Collection Tool), and contact your SE (systems engineer).
W OS 10049	An invalid address was specified.
L 22 99	Recover PL/extJava. If this message continues to be output despite taking the above action, contact Fujitsu technical support.
L 99	The IP address (%3) was mapped to an invalid network interface. Check the settings of the network interface to which the IP address (%3) was mapped. If the settings are correct, collect diagnostic information with the <i>iscollectinfo</i> command, and contact your SE (systems engineer).
All other cases	Resolve the cause of the error according to the error details context (%s2). Recover PL/extJava. If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.1.17 ahs00019

AHS: ERROR: ahs00019: (%s1)%s2: make_sock: unable to listen for connections on address %s3 [%s4]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = IP address:Port number

%s4 = Environment definition file name

Explanation

Socket wait status transition failed.

System Action

The web server start processing is canceled.

User Action

Take the following actions:

- Resolve the cause of the error according to the error details context (%s2).
- Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.1.18 ahs00020

AHS: ERROR: ahs00020: no listening sockets available, shutting down [%s1]**Variable Information**

%s1 = Environment definition file name

Explanation

A valid receiver port number has not been set in the environment definition file (%s1).

System Action

The web server execution processing is aborted.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.1.19 ahs00021

AHS: ERROR: ahs00021: (%s1)%s2: Couldn't start ErrorLog process [%s3]**Variable Information**

%s1 = Error details number

%s2 = Error details context

%s3 = Environment definition file name

Explanation

The log output program specified in the web server environment definition file (%s3) could not be started.

System Action

The web server execution processing is aborted.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.1.20 ahs00022

AHS: ERROR: ahs00022: (%s1)%s2: %s3: Invalid error log path %s4. [%s5]**Variable Information**

%s1 = Error details number

%s2 = Error details context

%s3 = Web server program name

%s4 = Error log file name

%s5 = Environment definition file name

Explanation

The path of the error log file (%s4) could not be found.

System Action

The web server execution processing is aborted.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.1.21 ahs00023

AHS: ERROR: ahs00023: (%s1)%s2: %s3: could not open error log file %s4. [%s5]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Web server program name

%s4 = Error log file name

%s5 = Environment definition file name

Explanation

The error log file (%s4) specified in the web server environment definition file (%s5) could not be opened.

System Action

The web server execution processing is aborted.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.1.22 ahs00024

AHS: ERROR: ahs00024: piped_log_spawn: unable to setup child process '%s1': %s2 [%s3]

Variable Information

%s1 = Log output program name

%s2 = Error details context

%s3 = Environment definition file name

Explanation

Initialization processing for the log output program (%s1) failed.

System Action

The web server execution processing is aborted.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.1.23 ahs00025

AHS: ERROR: ahs00025: unable to start piped log program '%s1': %s2 [%s3]

Variable Information

%s1 = Log output program name

%s2 = Error details context

%s3 = Environment definition file name

Explanation

The log output program (%s1) could not be started.

System Action

The web server execution processing is aborted.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.1.24 ahs00026

AHS: ERROR: ahs00026: (%s1)%s2: Invalid PID file path %s3, ignoring. [%s4]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Process management file name

%s4 = Environment definition file name

Explanation

The path of the process management file (%s3) could not be found.

System Action

The web server start processing is continued.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.1.25 ahs00028

AHS: ERROR: ahs00028: %s1: could not log pid to file %s2 [%s3]

Variable Information

%s1 = Web server program name

%s2 = Process management file name

%s3 = Environment definition file name

Explanation

The process management file (%s1) could not be opened.

System Action

The web server start processing is continued.

User Action

Contact Fujitsu technical support.

A.2.21.1.26 ahs00029

AHS: ERROR: ahs00029: [%s1] file %s2, line %s3, assertion "%s4" failed [%s5]

Variable Information

%s1 = Time of occurrence

%s2 = Source file name

%s3 = Source file line number

%s4 = Details information

%s5 = Environment definition file name

Explanation

An error occurred in the web server.

System Action

The web server execution processing is aborted.

User Action

Contact Fujitsu technical support.

A.2.21.1.27 ahs00030

AHS: ERROR: ahs00030: (%s1)%s2: Fatal error: unable to create global pool for use with by the scoreboard [%s3]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Environment definition file name

Explanation

The memory management area that is used in scoreboard management could not be created.

System Action

The web server start processing is canceled.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.1.28 ahs00031

AHS: ERROR: ahs00031: (%s1)%s2: Fatal error: Invalid Scoreboard path %s3 [%s4]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Scoreboard file path

%s4 = Environment definition file name

Explanation

The path of the scoreboard file (%s3) could not be found.

System Action

The web server start processing is canceled.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.1.29 ahs00032

AHS: ERROR: ahs00032: (%s1)%s2: Unable to create or access scoreboard (anonymous shared memory failure) [%s3]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Environment definition file name

Explanation

The shared memory that is used in the scoreboard could not be acquired.

System Action

The web server start processing is canceled.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.1.30 ahs00033

AHS: ERROR: ahs00033: (%s1)%s2: cannot allocate scoreboard [%s3]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Environment definition file name

Explanation

The memory that is used in the scoreboard could not be acquired.

System Action

The web server start processing is canceled.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.1.31 ahs00034

AHS: ERROR: ahs00034: (%s1)%s2: unable to create or access scoreboard "%s3" (name-based shared memory failure) [%s4]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Scoreboard name

%s4 = Environment definition file name

Explanation

The shared memory that is used in the scoreboard (%s3) could not be acquired.

System Action

The web server start processing is canceled.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.1.32 ahs00035

AHS: ERROR: ahs00035: (%s1)%s2: invalid transfer log path %s3. [%s4]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Access log file name

%s4 = Environment definition file name

Explanation

The path of the access log file (%s3) could not be found.

System Action

The web server program execution processing is aborted.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.1.33 ahs00036

AHS: ERROR: ahs00036: (%s1)%s2: could not open transfer log file %s3. [%s4]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Access log file name

%s4 = Environment definition file name

Explanation

The access log file (%s3) could not be opened.

System Action

The web server execution processing is aborted.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.1.34 ahs00037

AHS: ERROR: ahs00037: (%s1)%s2: Invalid mime types config path %s3 [%s4]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = MIME type settings file name

%s4 = Environment definition file name

Explanation

The path of the MIME type settings file (%s3) could not be found.

System Action

The web server start processing is canceled.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.1.35 ahs00038

AHS: ERROR: ahs00038: (%s1)%s2: could not open mime types config file %s3. [%s4]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = MIME type settings file name

%s4 = Environment definition file name

Explanation

The MIME type settings file (%s3) could not be opened.

System Action

The web server start processing is canceled.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.1.36 ahs00040

AHS: ERROR: ahs00040: (%s1)%s2: mod_rewrite: Parent could not create RewriteLock file %s3 [%s4]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Name of the lock file for the rewrite function

%s4 = Environment definition file name

Explanation

The lock file (%s3) for the rewrite function could not be created.

System Action

The web server start processing is canceled.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.1.37 ahs00041

AHS: ERROR: ahs00041: (%s1)%s2: mod_unique_id: unable to find hostname of the server [%s3]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Environment definition file name

Explanation

The host name could not be acquired.

System Action

The web server start processing is canceled.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.1.38 ahs00042

AHS: ERROR: ahs00042: (%s1)%s2: mod_unique_id: unable to find IPv4 address of "%s3" [%s4]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Host name

%s4 = Environment definition file name

Explanation

The name of Host (%s3) could not be resolved.

System Action

W

The web server execution processing is continued.

L

The web server execution processing is aborted.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.1.39 ahs00043

AHS: WARNING: ahs00043: Require %s1 > 0, setting to 1 [%s2]

Variable Information

%s1 = Directive name

%s2 = Environment definition file name

Explanation

A value of "0" or less was set for the directive (%s1) in the environment definition file (%s2). The directive (%s1) requires a value of "1".

System Action

The web server execution processing is continued.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.1.40 ahs00044

W

AHS: WARNING: ahs00044: ThreadLimit of %s1 exceeds compile time limit of %s2 threads, lowering ThreadLimit to %s2. [%s3]

L

AHS: WARNING: ahs00044: ThreadLimit of %s1 exceeds compile time limit of %s2 servers, lowering ThreadLimit to %s2. [%s3]

Variable Information

%s1 = The value set for the ThreadLimit directive

%s2 = Limit for the ThreadLimit directive

%s3 = Environment definition file name

Explanation

The maximum number of communication threads (%s1) set in the web server environment definition file (%s3) has exceeded the server hard limit (%s2). The number of communication threads requires a limit of (%s2) to be set.

System Action

The web server execution processing is continued.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.1.41 ahs00045

AHS: WARNING: ahs00045: ThreadsPerChild of %s1 exceeds ThreadLimit value of %s2 threads, lowering ThreadsPerChild to %s2. To increase, please see the ThreadLimit directive. [%s3]

Variable Information

%s1 = The value set for the ThreadsPerChild directive

%s2 = Limit for the ThreadsPerChild directive

%s3 = Environment definition file name

Explanation

The maximum number of communication threads (%s1) set in the web server environment definition file (%s3) has exceeded the limit (%s2). The number of communication threads requires a limit of (%s2) to be set.

System Action

The web server execution processing is continued.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.2 ahs00100 to ahs00199

This section details the messages numbered between ahs00100 and ahs00199.

A.2.21.2.1 ahs00100

AHS: ERROR: ahs00100: (%s1)%s2: Failed to get the full path of %s3 [%s4]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Web server program name

%s4 = Environment definition file name

Explanation

The full path of the web server program (%s3) could not be found.

System Action

The web server program execution processing is aborted.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.2.2 ahs00101

AHS: ERROR: ahs00101: %s1: Service is already installed. [%s2]

Variable Information

%s1 = Service name

%s2 = Environment definition file name

Explanation

The web server service (%s1) has already been registered.

System Action

The web server service registration processing is aborted.

User Action

Check the service (%s1) registration status in the Services window ([Control Panel] > [Administrative Tools] > [Services]).

A.2.21.2.3 ahs00104

AHS: ERROR: ahs00104: (%s1)%s2: Parent: Cannot create shutdown event %s3 [%s4]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Event object name

%s4 = Environment definition file name

Explanation

The shutdown event object (%s3) could not be created.

System Action

The web server start processing is canceled.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.2.4 ahs00105

AHS: ERROR: ahs00105: (%s1)%s2: Parent: Cannot create restart event %s3 [%s4]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Event object name

%s4 = Environment definition file name

Explanation

The restart event object (%s3) could not be created.

System Action

The web server start processing is canceled.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.2.5 ahs00106

AHS: ERROR: ahs00106: (%s1)%s2: %s3: Unable to create the start_mutex. [%s4]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Service name

%s4 = Environment definition file name

Explanation

Exclusive resources for the daemon process could not be created.

System Action

The web server start processing is canceled.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.2.6 ahs00107

AHS: ERROR: ahs00107: (%s1)%s2: master_main: create child process failed. Exiting. [%s3]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Environment definition file name



.....
The error details number (%s1) and the error details context (%s2) "(%s1)%s2: " may not be output.
.....

Explanation

An error occurred in daemon process create processing.

System Action

The web server start processing is canceled.

User Action

Refer to the message that was output at the same time and fix the error.

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.2.7 ahs00108

AHS: ERROR: ahs00108: (%s1)%s2: master_main: WaitForMultipleObjects WAIT_FAILED -- doing server shutdown [%s3]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Environment definition file name

Explanation

An error occurred in daemon process status monitoring.

System Action

The web server program execution processing is aborted.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.2.8 ahs00109

AHS: ERROR: ahs00109: (%s1)%s2: master_main: WaitForMultipleObjects with INFINITE wait exited with WAIT_TIMEOUT [%s3]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Environment definition file name

Explanation

A timeout occurred in daemon process status monitoring.

System Action

The web server program execution processing is aborted.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.2.9 ahs00111

AHS: ERROR: ahs00111: Parent: child process exited with status %s1 -- Aborting. [%s2]

Variable Information

%s1 = Daemon process exit code

%s2 = Environment definition file name

Explanation

An error occurred in the daemon process.

System Action

The web server program execution processing is aborted.

User Action

Refer to the message or error logs output at the same time and fix the error.

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.2.10 ahs00112

AHS: ERROR: ahs00112: (%s1)%s2: GetModuleFileName failed

Variable Information

%s1 = Error details number

%s2 = Error details context

Explanation

The full path of the web server program could not be acquired.

System Action

The web server service registration processing is aborted.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.2.11 ahs00120

AHS: ERROR: ahs00120: (%s1)%s2: ISAPI: could not create the isapi cache pool [%s3]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Environment definition file name

Explanation

The memory management area for the mod_isapi module could not be created.

System Action

The web server execution processing is aborted.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.2.12 ahs00123

AHS: ERROR: ahs00123: (%s1)%s2: Parent: Failed to get full path of %s3 [%s4]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Web server program name

%s4 = Environment definition file name

Explanation

The path of the web server program (%s3) could not be found.

System Action

The web server start processing is canceled.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.2.13 ahs00124

AHS: ERROR: ahs00124: (%s1)%s2: Parent: Unable to %s3 [%s4]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Erroneous processing contents

%s4 = Environment definition file name

Explanation

Failed to copy the start event handle.

System Action

The web server start processing is canceled.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.2.14 ahs00125

AHS: ERROR: ahs00125: (%s1)%s2: Parent: Could not create %s3 event for child process [%s4]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Event type

%s4 = Environment definition file name

Explanation

An event object could not be created.

System Action

The web server start processing is canceled.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.2.15 ahs00126

AHS: ERROR: ahs00126: (%s1)%s2: Parent: Failed to create the child process. [%s3]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Environment definition file name

Explanation

A daemon process could not be created.

System Action

The web server start processing is canceled.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.2.16 ahs00127

AHS: ERROR: ahs00127: (%s1)%s2: Parent: WSADuplicateSocket failed for socket %s3. Check the FAQ. [%s4]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Socket descriptor

%s4 = Environment definition file name

Explanation

The socket could not be reproduced.

System Action

The web server start processing is canceled.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.2.17 ahs00128

AHS: ERROR: ahs00128: (%s1)%s2: %s3: Failed to start the service process. [%s4]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Service name

%s4 = Environment definition file name

Explanation

The web server service (%s3) could not be started.

System Action

The web server start processing is canceled.

User Action

Refer to the message that was output at the same time and fix the error.

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.2.18 ahs00129

AHS: ERROR: ahs00129: (%s1)%s2: Child %s3: _beginthreadex failed. Unable to create all worker threads. Created %s4 of the %s5 threads requested with the ThreadsPerChild configuration directive. [%s6]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Process ID of the daemon process

%s4 = The number of created communication threads

%s5 = The value set for the ThreadsPerChild directive

%s6 = Environment definition file name

Explanation

The communication thread could not be created.

System Action

The web server is stopped.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.2.19 ahs00130

AHS: INFO: ahs00130: Parent: child process exited with status %s1 -- Restarting. [%s2]

Variable Information

%s1 = Process ID of the daemon process

%s2 = Environment definition file name

Explanation

The daemon process is restarted.

A.2.21.2.20 ahs00131

AHS: WARNING: ahs00131: Server ran out of threads to serve requests. Consider raising the ThreadsPerChild setting [%s1]

Variable Information

%s1 = Environment definition file name

Explanation

The number of simultaneous connection requests from the client has exceeded the value set for the number of communication threads in the web server environment definition file (%s1) (maximum number of requests).



.....
This message is output the first time the number of requests exceeds the maximum value for the number of simultaneous connections after the web server starts up. Once this message is output, it is not output again until the web server restarts.
.....

System Action

The web server execution processing is continued.

User Action

Use the add-instance subcommand of the pgx_jadmin command to add additional server instances (JavaVM) as necessary.

A.2.21.2.21 ahs00132

AHS: ERROR: ahs00132: (%s1)%s2: OpenEvent on %s3 event [%s4]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Event object name

%s4 = Environment definition file name

Explanation

The event object (%s3) could not be opened.

System Action

The web server execution processing is continued.

User Action

Collect diagnostic information using the *iscollectinfo* command, and contact your SE (systems engineer).

A.2.21.2.22 ahs00133

AHS: ERROR: ahs00133: (%s1)%s2: SetEvent on %s3 event [%s4]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Event object name

%s4 = Environment definition file name

Explanation

Failed to set the signal status of the event object (%s3).

System Action

The web server execution processing is continued.

User Action

Collect diagnostic information using the *iscollectinfo* command, and contact your SE (systems engineer).

A.2.21.2.23 ahs00134

AHS: ERROR: ahs00134: (%s1)%s2: Parent: Failed to get the current path [%s3]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Environment definition file name

Explanation

Failed to retrieve the current path.

System Action

The web server execution processing is continued.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.2.24 ahs00135

AHS: ERROR: ahs00135: (%s1)%s2: Parent: Could not set child process stdout [%s3]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Environment definition file name

Explanation

Failed to change the configuration for the standard output of the daemon process.

System Action

The web server execution processing is continued.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.2.25 ahs00136

AHS: ERROR: ahs00136: (%s1)%s2: Parent: Could not set child process stderr [%s3]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Environment definition file name

Explanation

Failed to change the configuration for the standard error output of the daemon process.

System Action

The web server execution processing is continued.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.2.26 ahs00137

AHS: ERROR: ahs00137: (%s1)%s2: ResetEvent(shutdown_event) [%s3]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Environment definition file name

Explanation

Failed to reset the event object used for shutdown.

System Action

The web server is stopped.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.2.27 ahs00138

AHS: ERROR: ahs00138: (%s1)%s2: Parent: ResetEvent(restart_event) failed. [%s3]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Environment definition file name

Explanation

Failed to reset the event object used for restart.

System Action

The web server is restarted.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.2.28 ahs00139

AHS: ERROR: ahs00139: (%s1)%s2: Parent: SetEvent for child process %s3 failed [%s4]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Daemon process handle

%s4 = Environment definition file name

Explanation

Failed to set the signal status of the event object used for stopping the daemon process.

System Action

The web server is restarted.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.3 ahs00200 to ahs00299

This section details the messages numbered between ahs00200 and ahs00299.

A.2.21.3.1 ahs00200

AHS: ERROR: ahs00200: (%s1)%s2: Error retrieving pid file %s3 [%s4]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Process management file

%s4 = Environment definition file name

Explanation

The process management file (%s3) could not be read.

System Action

The web server execution processing is aborted.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.3.2 ahs00201

AHS: WARNING: ahs00201: httpd (pid %s1) already running [%s2]

Variable Information

%s1 = Process ID

%s2 = Environment definition file name

Explanation

The web server is already running.

System Action

The web server start processing is canceled.

A.2.21.3.3 ahs00202

AHS: WARNING: ahs00202: httpd (no pid file) not running [%s1]

Variable Information

%s1 = Environment definition file name

Explanation

The web server is not running.

System Action

The web server stop processing is canceled.

A.2.21.3.4 ahs00203

AHS: WARNING: ahs00203: httpd (pid %s1?) not running [%s2]

Variable Information

%s1 = Process ID

%s2 = Environment definition file name

Explanation

The web server process (%s1) does not exist.

System Action

The web server stop processing is canceled.

A.2.21.3.5 ahs00204

AHS: WARNING: ahs00204: httpd not running, trying to start [%s1]

Variable Information

%s1 = Environment definition file name

Explanation

The web server is not running.

System Action

The web server start processing is started.

A.2.21.3.6 ahs00205

AHS: ERROR: ahs00205: (%s1)%s2: sending signal to server [%s3]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Environment definition file name

Explanation

The signal failed to be sent to the daemon process.

System Action

The web server execution processing is aborted.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.3.7 ahs00206

AHS: ERROR: ahs00206: Child %s1 returned a Fatal error... Apache is exiting! [%s2]

Variable Information

%s1 = Process ID of the communication process

%s2 = Environment definition file name

Explanation

An error occurred in the communication process (%s1).

System Action

The web server execution processing is aborted.

User Action

Refer to the message that was output at the same time and fix the error.

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.3.8 ahs00207

AHS: ERROR: ahs00207: (%s1)%s2: apr_proc_detach failed [%s3]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Environment definition file name

Explanation

A daemon process could not be generated.

System Action

The web server start processing is canceled.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.3.9 ahs00208

AHS: ERROR: ahs00208: (%s1)%s2: Could not open pipe-of-death. [%s3]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Environment definition file name

Explanation

A pipe could not be created.

System Action

The web server start processing is canceled.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.3.10 ahs00209

AHS: ERROR: ahs00209: (%s1)%s2: Couldn't create accept lock [%s3]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Environment definition file name

Explanation

Exclusive resources for connection could not be created.

System Action

The web server start processing is canceled.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.3.11 ahs00210

AHS: ERROR: ahs00210: (%s1)%s2: Couldn't set permissions on cross-process lock; check User and Group directives [%s3]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Environment definition file name

Explanation

Authority failed to be set for exclusive resources for connection.

System Action

The web server start processing is canceled.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.3.12 ahs00213

AHS: ERROR: ahs00213: (%s1)%s2: Couldn't initialize cross-process lock in child [%s3]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Environment definition file name

Explanation

Exclusive resources for connection could not be initialized.

System Action

The web server is stopped.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.3.13 ahs00214

AHS: ERROR: ahs00214: (%s1)%s2: setuid: unable to change to uid: %s3 [%s4]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = User ID

%s4 = Environment definition file name

Explanation

The User ID (%s3) specified in the web server environment definition file (%s4) could not be set.

System Action

The communication process where the error occurred is closed, and the web server execution processing is continued.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.3.14 ahs00215

AHS: ERROR: ahs00215: (%s1)%s2: getpwuid: couldn't determine user name from uid %s3, you probably need to modify the User directive [%s4]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = User ID

%s4 = Environment definition file name



Note

.....
Error details number (%s1) and Error details context (%s2) "(%s1)%s2:" may not be output.
.....

Explanation

The User ID (%s3) entry specified in the web server environment definition file (%s4) could not be found.

System Action

The communication process where an error occurred is closed, and the web server execution processing is continued.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.3.15 ahs00216

AHS: ERROR: ahs00216: (%s1)%s2: setgid: unable to set group id to Group %s3 [%s4]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Group ID

%s4 = Environment definition file name

Explanation

The Group ID (%s3) specified in the web server environment definition file (%s4) could not be set.

System Action

The communication process where an error occurred is closed, and the web server execution processing is continued.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.3.16 ahs00217

AHS: ERROR: ahs00217: (%s1)%s2: initgroups: unable to set groups for User %s3 and Group %s4 [%s5]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = User ID

%s4 = Group ID

%s5 = Environment definition file name

Explanation

The group access list could not be initialized.

System Action

The communication process where an error occurred is closed, and the web server execution processing is continued.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.3.17 ahs00219

AHS: ERROR: ahs00219: (%s1)%s2: mod_rewrite: Parent could not set permissions on RewriteLock; check User and Group directives [%s3]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Environment definition file name

Explanation

The authority for the lock file for the rewrite function could not be set.

System Action

The web server start processing is canceled.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.3.18 ahs00221

AHS: WARNING: ahs00221: MaxClients of %s1 would require %s2 servers, and would exceed the ServerLimit value of %s3. Automatically lowering MaxClients to %s4. To increase, please see the ServerLimit directive. [%s5]

Variable Information

%s1 = The value set for the MaxClients directive

%s2 = The maximum number of communication processes

%s3 = The value set for the ServerLimit directive

%s4 = Limit for the MaxClients directive

%s5 = Environment definition file name

Explanation

The maximum number of simultaneous connections (%s1) set in the web server environment definition file (%s5) has exceeded the server hard limit (%s4). The number of simultaneous connections requires a limit of (%s4) to be set.

System Action

The web server execution processing is continued.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.3.19 ahs00222

AHS: WARNING: ahs00222: ServerLimit of %s1 exceeds compile time limit of %s2 servers, lowering ServerLimit to %s2. [%s3]

Variable Information

%s1 = The value set for the ServerLimit directive

%s2 = Limit for the ServerLimit directive

%s3 = Environment definition file name

Explanation

The value (%s1) set for the number of communication threads in the web server environment definition file (%s3) has exceeded the limit (%s2). The number of communication threads requires a value of limit (%s2).

System Action

The web server execution processing is continued.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.3.20 ahs00223

AHS: ERROR: ahs00223: %s1: bad user name %s2 [%s3]

Variable Information

%s1 = Web server program name

%s2 = User name specified in the User directive

%s3 = Environment definition file name

Explanation

The user name (%s2) specified in the web server environment definition file (%s3) could not be found.

System Action

The web server program execution processing is aborted.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.3.21 ahs00224

AHS: ERROR: ahs00224: %s1: bad group name %s2 [%s3]

Variable Information

%s1 = Web server program name

%s2 = Group name specified in the Group directive

%s3 = Environment definition file name

Explanation

The group name (%s2) specified in the web server environment definition file (%s3) could not be found.

System Action

The web server execution processing is aborted.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.3.22 ahs00227

AHS: ERROR: ahs00227: (%s1)%s2: unable to control socket non-blocking status [%s3]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Environment definition file name

Explanation

The non-blocking of the socket failed.

System Action

The web server start processing is canceled.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.3.23 ahs00228

AHS: WARNING: ahs00228: server reached MaxClients setting, consider raising the MaxClients setting [%s1]

Variable Information

%s1 = Environment definition file name

Explanation

The number of simultaneous connection requests from the client has exceeded the value (maximum number of requests) set for the number of simultaneous connections in the web server environment definition file (%s1).



Note

.....

This message is output the first time the number of requests exceeds the maximum value for the number of simultaneous connections after the web server starts up. Once this message is output, it is not output again until the web server restarts.

.....

System Action

The web server execution processing is continued.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.3.24 ahs00229

AHS: ERROR: ahs00229: (%s1)%s2: apr_thread_create: unable to create listener thread [%s3]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Environment definition file name

Explanation

The thread could not be created.

System Action

The communication process where an error occurred is closed, and the web server execution processing is continued.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.3.25 ahs00230

AHS: ERROR: ahs00230: (%s1)%s2: Couldn't initialize signal thread [%s3]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Environment definition file name

Explanation

Failed to initialize the thread signal.

System Action

The communication process where an error occurred is closed, and the web server execution processing is continued.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.3.26 ahs00231

AHS: ERROR: ahs00231: (%s1)%s2: fork: Unable to fork new process [%s3]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Environment definition file name

Explanation

A communication process could not be created.

System Action

The web server execution processing is continued.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.3.27 ahs00232

AHS: ERROR: ahs00232: (%s1)%s2: Cannot chroot when not started as root [%s3]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Environment definition file name

Explanation

Unable to retrieve the user ID that starts the daemon process.

System Action

The communication process where an error occurred is closed, and the web server execution processing is continued.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.3.28 ahs00233

AHS: ERROR: ahs00233: (%s1)%s2: Can't chdir to %s3 [%s4]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Directory name

%s4 = Environment definition file name

Explanation

Unable to change the current directory to the directory (%s3).

System Action

The communication process where an error occurred is closed, and the web server execution processing is continued.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.3.29 ahs00234

AHS: ERROR: ahs00234: (%s1)%s2: Can't chroot to %s3 [%s4]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Directory name

%s4 = Environment definition file name

Explanation

Unable to change the root directory to the directory (%s3).

System Action

The communication process where an error occurred is closed, and the web server execution processing is continued.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.3.30 ahs00235

AHS: ERROR: ahs00235: (%s1)%s2: apr_socket_accept: giving up. [%s3]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Environment definition file name

Explanation

A network error was detected.

System Action

The communication process where an error occurred is closed, and the web server execution processing is continued.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.3.31 ahs00236

AHS: ERROR: ahs00236: (%s1)%s2: apr_socket_accept: (client socket) [%s3]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Environment definition file name

Explanation

An attempt to connect to the client socket failed.

System Action

The communication process where an error occurred is closed, and the web server execution processing is continued.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.3.32 ahs00237

AHS: ERROR: ahs00237: (%s1)%s2: ap_queue_init() failed [%s3]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Environment definition file name

Explanation

Failed to initialize the internal queue.

System Action

The communication process where an error occurred is closed, and the web server execution processing is continued.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.3.33 ahs00238

AHS: ERROR: ahs00238: (%s1)%s2: ap_queue_info_create() failed [%s3]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Environment definition file name

Explanation

Failed to create the communication queue.

System Action

The communication process where an error occurred is closed, and the web server execution processing is continued.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.3.34 ahs00239

AHS: ERROR: ahs00239: (%s1)%s2: malloc: out of memory [%s3]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Environment definition file name

Explanation

Memory could not be obtained.

System Action

The communication process where an error occurred is closed, and the web server execution processing is continued.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.3.35 ahs00240

AHS: ERROR: ahs00240: (%s1)%s2: apr_thread_create: unable to create worker thread [%s3]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Environment definition file name

Explanation

Failed to create the communication thread.

System Action

The communication process where an error occurred is closed, and the web server execution processing is continued.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.3.36 ahs00241

AHS: WARNING: ahs00241: detected MinSpareThreads set to non-positive. Resetting to 1 to avoid almost certain Apache failure. Please read the documentation. [%s1]

Variable Information

%s1 = Environment definition file name

Explanation

The value set for the minimum number of communication threads in a standby state in the web server environment definition file was "0" or less. '1' will be assumed as the minimum number of communication threads in a standby state.

System Action

The web server execution processing is continued.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.3.37 ahs00242

AHS: WARNING: ahs00242: MaxClients (%s1) must be at least as large as ThreadsPerChild (%s2). Automatically increasing MaxClients to %s2. [%s3]

Variable Information

%s1 = The value set for the MaxClients directive

%s2 = The value set for the ThreadsPerChild directive

%s3 = Environment definition file name

Explanation

The value set for the number of simultaneous connections in the web server environment definition file was less than the value set for the number of communication threads. '%2' will be assumed as the number of communication threads for the number of simultaneous connections.

System Action

The web server execution processing is continued.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.3.38 ahs00243

AHS: WARNING: ahs00243: MaxClients (%s1) is not an integer multiple of ThreadsPerChild (%s2), lowering MaxClients to %s3 for a maximum of %4 child processes, [%s5]

Variable Information

%s1 = The value set for the MaxClients directive

%s2 = The value set for the ThreadsPerChild directive

%s3 = Limit for the MaxClients directive

%s4 = The maximum number of communication processes

%s5 = Environment definition file name

Explanation

The maximum number of simultaneous connections (%1) set in the web server environment definition file (%s5) is not an integer multiple of the value (%2) set for the number of communication threads. '%3' will be assumed as the number of simultaneous connections.

System Action

The web server execution processing is continued.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.3.39 ahs00244

AHS: ERROR: ahs00244: No active workers found... Apache is exiting! [%s1]

Variable Information

%s1 = Environment definition file name

Explanation

There are no active communication threads.

System Action

The web server execution processing is aborted.

User Action

Collect troubleshooting information on the product using FJQSS(Information Collection Tool), and contact your SE (systems engineer).

A.2.21.3.40 ahs00245

AHS: INFO: ahs00245: seg fault or similar nasty error detected in the parent process [%s1]

Variable Information

%s1 = Environment definition file name

Explanation

- The daemon process received one of the following signals:
- SIGSEGV
- SIGBUS
- SIGABORT
- SIGABRT
- SIGILL

System Action

The daemon process is closed.

User Action

Collect troubleshooting information on the product using FJQSS (Information Collection Tool), and contact your SE (systems engineer).

A.2.21.4 ahs00400 to ahs00499

This section details the messages numbered between ahs00400 and ahs00499.

A.2.21.4.1 ahs00401

AHS: ERROR: ahs00401: (%s1)%s2: Couldn't start TraceLog process. [%s3]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Environment definition file name



Note

.....
The error details number (%s1) and the error details context (%s2) "(%s1)%s2: " may not be output.
.....

Explanation

The log output program specified in the web server environment definition file (%s3) could not be started.

System Action

The web server start processing is canceled.

User Action

Refer to the message that was output at the same time and fix the error.

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.4.2 ahs00402

AHS: ERROR: ahs00402: (%s1)%s2: Invalid TraceLog file path %s3. [%s4]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Name of the log file for trace output

%s4 = Environment definition file name

Explanation

The path of the log file (%s3) for trace output could not be found.

System Action

The web server start processing is canceled.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.4.3 ahs00403

AHS: ERROR: ahs00403: (%s1)%s2: Could not open TraceLog file %s3. [%s4]

Variable Information

%s1 = Error details number

%s2 = Error details context

%s3 = Name of the log file for trace output

%s4 = Environment definition file name

Explanation

The log file (%s3) for trace output could not be opened.

System Action

The web server start processing is canceled.

User Action

Resolve the cause of the error according to the error details context (%s2).

If the cause cannot be identified, recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.5 ahs70000 to ahs70099

This section details the messages numbered between ahs70000 and ahs70099.

A.2.21.5.1 ahs70004

AHS: ERROR: ahs70004: (%s1)%s2:Cannot get enough memory

Variable Information

%s1 = Error details number

%s2 = Error details content

Explanation

Failed to acquire work memory.

User Action

Close unnecessary programs.

A.2.21.5.2 ahs70005

AHS: ERROR: ahs70005: (%s1)%s2:Error writing to log file. %s3 messages lost.

Variable Information

%s1 = Error details number

%s2 = Error details content

%s3 = Message management number in the log file (Internal code)

Explanation

Failed to write to the log file. There might not be enough space on the disk that stores the log files.

User Action

Confirm the disk size assigned as the [domain root] directory. If it is not sufficient, secure more space.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.21.5.3 ahs70007

AHS: INFO: ahs70007: Log can now be output to the log file(%s1). (%s2)

Variable Information

%s1 = File name

%s2 = Number of messages failed to be output.

Explanation

Log can now be output to the log file (%s1).

A.2.21.5.4 ahs70008

AHS: INFO: ahs70008: The file was rotated because the file size of the log file(%s1) reached the upper limit of the system.

Variable Information

%s1 = File name

Explanation

The file was rotated because the file size of the log file (%s1), reached the system's upper limit.

A.2.21.5.5 ahs70009

AHS: ERROR: ahs70009: The log could not be output because the file size of the log file reached the upper limit of the system.

Explanation

The log could not be output because the log file size reached the system's upper limit.

System Action

The web server execution processing is aborted.

User Action

Stop the instance, back up the log file that reached the file size upper limit for the system, and then restart the instance.



Change the file size upper limit of the system using the *ulimit* command (for Bourne shell types) or the *limit* command (for C shell types). Restart the web server in the relevant shell to use the updated values.

A.2.21.6 ahs81000 to ahs81099

This section details the messages numbered between ahs81000 and ahs81099.

A.2.21.6.1 ahs81001

AHS: INFO: ahs81001: HTTP Server is starting. [%s1]

Variable Information

%s1 = Environment definition file name

Explanation

The web server is starting.

A.2.21.6.2 ahs81002

AHS: INFO: ahs81002: HTTP Server is stopping. [%s1]

Variable Information

%s1 = Environment definition file name

Explanation

The web server is stopping.

A.2.21.6.3 ahs81003

AHS: INFO: ahs81003: HTTP Server is restarting. [%s1]

Variable Information

%s1 = Environment definition file name

Explanation

The web server is restarting.

A.2.22 Messages without a Message ID

A.2.22.1 Messages that are Output when the pgx_jadmin Command is Executed

**Authentication failed for user: {0}
(Usually, this means invalid user name and/or password)**

Variable Information

{0}: User name

Explanation

The admin user ID and/or password is invalid.

System Action

Processing is interrupted.

User Action

Specify the correct user name and password, and then reexecute the command.

com.sun.enterprise.universal.xml.MinixmlParserException: {0}

Variable Information

{0}: Detail message

Explanation

Failed to parse domain.xml.

System Action

Processing is interrupted.

User Action

The product environment has been corrupted, therefore reinstall the product.

Command {0} failed.

Variable Information

{0}: Subcommand name

Explanation

Failed to execute the command that was output to the Variable Information subcommand name.

System Action

Processing is interrupted.

User Action

Based on the message that was output at the same time, remove the cause of the error, and then reexecute the command.

Command failed on node {0} ({1}): {2}

Variable Information

{0}: Node name

{1}: Host name

{2}: Detail information

Explanation

The command has failed to execute.

System Action

Processing is interrupted.

User Action

Take the action indicated by the message output at the same time, remove the cause of command execution failure, and then reexecute the command.

Could not contact the DAS running at {0}:{1}. This could be because a firewall is blocking the connection back to the DAS or because the DAS host is known by a different name on the instance host {2}. To change the hostname that the DAS uses to identify itself please update the DAS admin HTTP listener address.

Variable Information

{0}: Host name
{1}: Port number

Explanation

Failed to connect to the Java EE DAS service.

System Action

Processing is interrupted.

User Action

The instance may have stopped. Check if it is running.

If the instance is running, it is possible that the ephemeral ports are depleted

Check the network status using the "netstat -a" command, and ensure that a large number of "TIME_WAIT" status connections do not exist. If it is confirmed that the ephemeral ports are depleted, release unnecessary ports. Alternatively, increase the number of ports that can be used as ephemeral ports.

Error starting domain {0}.

Variable Information

{0}: Domain name

Explanation

An error occurred during the Java EE DAS service start processing.

System Action

Processing is interrupted.

User Action

Based on the message that was output at the same time, remove the cause of the error, and then reexecute the command.

Failed to rendezvous with DAS on {0}:{1}. Please check if this server is running, that the host and port are correct, and that this server is configured to allow remote access.

Variable Information

{0}: Host name
{1}: Port number

Explanation

Failed to connect to the Java EE DAS service.

System Action

Processing is interrupted.

User Action

The instance may have stopped. Check if it is running.

If the instance is running, it is possible that the ephemeral ports have run out.

Refer to "java.net.SocketException: No buffer space available (maximum connections reached?)" in "[A.2.22.5 Exception Information that Starts with "java.net.SocketException"](#)", and then take the required action.

Failed to start process named {0}. Detail={1}**Variable Information**

{0}: Server instance (Java VM) name

{1}: Detail information

Explanation

Failed to start the server instance (Java VM).

System Action

Processing is interrupted.

User Action

Take the following actions:

- Take the action indicated by the message output before and after this message.
- Take the action indicated by the message output to the event log (Windows(R)) or the system log (Linux), and investigate the cause of the failure.

If the problem is still not resolved despite taking the above action, contact Fujitsu technical support.

Failed to start process named {0}. PCMI Error Code={1}.**Variable Information**

{0}: Server instance (Java VM) name

{1}: Error information

Explanation

Failed to start the server instance (Java VM).

System Action

Processing is interrupted.

User Action

Take the following actions:

- Take the action indicated by the message output before and after this message.
- Check Error information {1} that was output, and then follow the action advised in the table below.

Error information {1}	Explanation and Action
100	Failed to read the PCMI profile, or the value specified for the PCMI profile definition item is incorrect. Recover PL/extJava. If this message continues to be output despite taking the above action, contact Fujitsu technical support.
700	An error occurred during the instance start processing. Take the action indicated by the message output to the event log (Windows(R)) or the system log (Linux), and investigate the cause of the failure. If a message is not output, investigate the cause of the failure based on the information output to the PL/extJava server log and the Java VM log. If a message that shows a Java VM error is output, refer to "Operation Guide" - "Java Function Errors".

Error information {1}	Explanation and Action
	In all other cases, take the following actions: <ul style="list-style-type: none"> - There may be insufficient memory. Check if there is sufficient memory. - Ensure that the port numbers used by the domain or container are not being used by another application. - Recover PL/extJava. - If this message continues to be output despite taking the above action, contact Fujitsu technical support.
Other error information	Contact Fujitsu technical support.

Incorrect current master password. You will not be able to change it.

Explanation

The specified current master password is invalid.

System Action

Processing is interrupted.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

Instance {0} seems to be offline; command {1} was not replicated to that instance

Variable Information

{0}: Server instance (JavaVM) name

{1}: Subcommand name

Explanation

The server instance (JavaVM) is not running, therefore the synchronization processing could not be performed.

System Action

Processing is continued.

User Action

Not required.

The synchronization processing will be performed automatically when the instance starts the next time.

Invalid boolean value for option: {0}, Value: {1}

Variable Information

{0}: Option name

{1}: Specified value

Explanation

The value that was specified as the "Bool" value option was neither "true" nor "false", therefore execution of the command failed.

System Action

Processing is interrupted.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

Invalid file for option: --{0}: {1}

Variable Information

{0}: Option name

{1}: Cause of the error

Explanation

Cannot reference the file, therefore execution of the command failed.

System Action

Processing is interrupted.

User Action

Check if the file displayed in Variable Information exists and whether there are sufficient access privileges, and then reexecute the command.

remote failure: {0}: Could not start instance {0} on node {1} ({2}).

Variable Information

{0}: Server instance (JavaVM) name

{1}: Node name

{2}: Host name

Explanation

Failed to start the server instance (JavaVM).

System Action

Processing is interrupted.

User Action

An error occurred during start processing of the instance.

Take the action indicated by the message output at the same time and the message output to the event log (Windows(R)) or the system log (Linux), and investigate the cause of the instance start failure.

If a message has not been output, investigate the cause of the failure based on the information output to the PL/extJava server log and the JavaVM log.

remote failure: Adding User to file realm {0} failed. User name cannot be empty. User name cannot be empty.

Variable Information

{0}: file realm name

Explanation

The user name that is specified when the file realm user is created cannot be empty.

System Action

Processing is interrupted.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

remote failure: Authrealm named {0} not found.

Variable Information

{0}: Realm name

Explanation

The realm name does not exist.

System Action

Processing is interrupted.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

remote failure: File realm {0} does not exist.

Variable Information

{0}: file realm name

Explanation

The file realm name does not exist.

System Action

Processing is interrupted.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

remote failure: Specified file user {0} not found No such user [{0}]. No such user [{0}].

Variable Information

{0}: file realm user

Explanation

The file realm user does not exist.

System Action

Processing is interrupted.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

remote failure: There is no cluster named {0} in this domain.

Variable Information

{0}: Database name

Explanation

The specified database does not exist.

System Action

Processing is interrupted.

User Action

Check if the database exists.

remote failure: Unknown plain text format. A properly formatted response from a PlainTextActionReporter \n\ always starts with one of these 2 strings: PlainTextActionReporterSUCCESS or PlainTextActionReporterFAILURE. The response we received from the server was not understood: {0}

Variable Information

{0}: Response message

Explanation

The response that was received is invalid.

System Action

Processing is interrupted.

User Action

Based on the message that was output at the same time, remove the cause of the error, and then reexecute the command.

remote failure: Updating user {0} in file realm {1} failed. {2}

Variable Information

{0}: User name

{1}: file realm name

{2}: Detail information

Explanation

Failed to update the file realm user.

System Action

Processing is interrupted.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

remote failure: Updating user in file realm {0} failed. User name cannot be empty. User name cannot be empty.

Variable Information

{0}: file realm name

Explanation

The user name that is specified when the file realm user is updated cannot be empty.

System Action

Processing is interrupted.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

**remote failure: User {0} does not exist in file realm {1}. No such user [{0}].
No such user [{0}].**

Variable Information

{0}: User name

{1}: file realm name

Explanation

The file realm user does not exist.

System Action

Processing is interrupted.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

**Remote server does not listen for requests on [localhost:{0}]. Is the server up?
No such local command, {1}. To run remote commands, start the application server (e.g.
'asadmin start-domain').**

Variable Information

{0}: Port number

{1}: Subcommand name

Explanation

The database is not running using the specified port number.

System Action

Processing is interrupted.

User Action

Start the instance, or specify the correct port number, and then reexecute the command.

**Server {0} is running. You need to stop the instance before the master-password can be
changed.**

Variable Information

{0}: Server instance (JavaVM) name

Explanation

The server instance has not stopped.

System Action

Processing is interrupted.

User Action

Stop the instance.

Server instance directory {0} does not exist or is not a directory

Variable Information

{0}: Server instance (JavaVM) path

Explanation

The specified server instance (JavaVM) does not exist.

System Action

Processing is interrupted.

User Action

Check if the server instance (Java VM) exists.

Something went wrong in creating the local filesystem for instance {1}: {2}

Variable Information

{0}: Server instance (JavaVM) name

{1}: Error information

Explanation

Failed to create the server instance (JavaVM).

System Action

Processing is interrupted.

User Action

Refer to the error information message output at the same time, and then take the action indicated.

The server exited prematurely with exit code {0}. Before it died, it produced the following output: {1}

Variable Information

{0}: Return value

{1}: Message output by the Java EE DAS service

Explanation

During start processing, the Java EE DAS service ended with return value {0}.

System Action

Processing is interrupted.

User Action

Refer to the message {1} output by the Java EE DAS service to remove the cause of the instance start processing failure.

WARNING: Command {0} did not complete successfully on server instance {1}: {2}

Variable Information

{0}: Command name

{1}: Server instance (JavaVM) name

{2}: Exception information

Explanation

The command has failed to execute.

System Action

Processing is interrupted.

User Action

If the exception information output at the same time contains the string "java.net.SocketException: No buffer space available (maximum connections reached?)", the ephemeral ports may be depleted.

Refer to "[A.2.22.5 Exception Information that Starts with "java.net.SocketException"](#)" - "java.net.SocketException: No buffer space available (maximum connections reached?)", and then take the required action.

A.2.22.2 Messages that are Output during PCMI Operations

error occured while initializing PcmiTraceLogFilehandler

Explanation

An error occurred during trace log file initialization.

System Action

Processing is continued.

User Action

Privileges to execute commands may not have been set for the user who executed the command. Check the user privileges, and reexecute the command as a user with privileges to execute the command.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.22.3 Messages that are Output during Web Container Operations

SEVERE: Cannot find port information from domain.xml

Explanation

A port number has not been specified for the HTTP listener.

System Action

Processing to set the port number is interrupted.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

WARNING: Can not parse network-listener port number: null

Explanation

A port number has not been specified for the HTTP listener.

System Action

Processing to set the port number is interrupted.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

**SEVERE: Config Listener class com.sun.enterprise.v3.services.impl.DynamicConfigListener notification took too long
java.util.concurrent.TimeoutException**

Explanation

Failed to initialize the HTTP listener.

System Action

Initialization of the HTTP listener is interrupted.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

**SEVERE: doSelect exception
java.lang.IllegalArgumentException: corePoolSize > maxPoolSize: {0} > {1}**

Variable Information

{0}: Minimum pool size

{1}: Maximum pool size

Explanation

The minimum pool size has exceeded the maximum pool size.

System Action

The request is not processed.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

**SEVERE: doSelect exception
java.util.concurrent.RejectedExecutionException: The thread pool's task queue is full, limit: {0}**

Variable Information

{0}: Queue size

Explanation

The container thread pool queue is full, therefore the request cannot be processed.

System Action

The request is not processed.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

**Exception in grizzly thread
java.lang.IllegalArgumentException: Invalid range**

Explanation

The value that was specified for the HTTP listener port number is invalid.

System Action

Processing to set the port number is interrupted.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

SEVERE: Exception while processing config bean changes : java.lang.NumberFormatException: null

Explanation

A port number has not been specified for the HTTP listener.

System Action

Processing to set the port number is interrupted.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

INFO: Grizzly Framework {0} started in: {1}ms - bound to [{2}:{3}]

Variable Information

{0}: Internal information

{1}: Internal information

{2}: IP address

{3}: Port number

Explanation

The port number settings have been configured.

WARNING: Invalid address for {0}: {1}

Variable Information

{0}: Listener name

{1}: Network address

Explanation

The network address is invalid.

System Action

Processing is continued.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

INFO: JACC Policy Provider:Failed Permission Check: {0}

Variable Information

{0}: Detail information

Explanation

An attempt to call a method without the required privileges was made.

System Action

Processing is interrupted.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

WARNING: More than the maximum number of request parameters (GET plus POST) for a single request ({0}) were detected. Any parameters beyond this limit have been ignored. To change this limit, set the maxParameterCount attribute on the Connector.

Variable Information

{0}: Maximum value of the HTTP request parameter

Explanation

The number of HTTP request parameters has exceeded the maximum value {0}.

System Action

Processing is executed ignoring those parameters which have exceeded the maximum number allowed.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

**SEVERE: Network listener configuration error. Type: CHANGE
java.lang.RuntimeException: Cannot find port information from domain configuration**

Explanation

A port number has not been specified for the HTTP listener.

System Action

Processing to set the port number is interrupted.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

INFO: Network listener {0} on port {1} disabled per domain.xml

Variable Information

{0}: HTTP listener name

{1}: Port number

Explanation

The HTTP listener has been disabled.

System Action

Processing is continued.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

WARNING: No Principals mapped to Role [{0}]

Variable Information

{0}: Security role name specified in the deployment descriptor (web.xml)

Explanation

The user or group that corresponds to the security role name specified in the deployment descriptor (web.xml) has not been defined in the Interstage deployment descriptor (glassfish-web.xml).

System Action

Processing is interrupted.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

WARNING: Realm file: com.sun.enterprise.security.auth.realm.NoSuchUserException: No such user [{0}]

Variable Information

{0}: User or group specified in the Interstage deployment descriptor (glassfish-web.xml) security-role-mapping tag

Explanation

The user or group does not exist in the file realm.

System Action

Processing is interrupted.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

WARNING: Response Error during finishResponse

Explanation

An exception occurred in processing to send the response.

System Action

Processing to send the response is interrupted.

User Action

- The client may have disconnected before the instance returned the response to the client. Review the client settings.
- Follow the action advised in the exception information output at the same time to remove the cause of the error.

StandardWrapperValve[{0}]: PWC1406: Servlet.service() for servlet {1} threw exception

Variable Information

{0}: Servlet name

{1}: Servlet name

Explanation

The servlet service method returned an exception.

System Action

Processing is interrupted.

User Action

Refer to the other messages and exception information that were output at the same time, and remove the cause of the error.

Unable to call method {0} on servlet context {1}, because this servlet context has already been initialized

Variable Information

{0}: Method name

{1}: Context root

Explanation

The Java application of the context root {1} has already been initialized, therefore the method {0} cannot be executed.

User Action

Change the timing for calling the method {0} to when the context is initialized.

SEVERE: Unknown address null

Explanation

The network address is invalid.

System Action

Processing is continued.

User Action

Recover PL/extJava.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.22.4 Messages that are Output while the Process is Running

SEVERE: Aborting, Failed to start container {0}

Variable Information

{0}: Internal information

Explanation

Failed to start the container.

System Action

Processing is interrupted.

User Action

Refer to the other messages and the exception information output at the same time, and remove the cause of the error.

SEVERE: Cannot start container {0}**Variable Information**

{0}: Container name

Explanation

Failed to start the container.

System Action

Processing is interrupted.

User Action

Refer to the other messages and the exception information output at the same time, and remove the cause of the error.

**SEVERE: doSelect IOException
java.io.IOException: Unable to establish loopback connection****Explanation**

Failed to establish a loopback connection.

System Action

Processing is interrupted.

User Action

If "java.net.SocketException: No buffer space available (maximum connections reached?)" is included in the exception information output at the same time, it is possible that the ephemeral ports have run out.

Refer to "java.net.SocketException: No buffer space available (maximum connections reached?)" in "[A.2.22.5 Exception Information that Starts with "java.net.SocketException"](#)", and then take the required action.

**SEVERE: doSelect IOException
java.net.BindException: No free port within range: {0}:{1}={2}****Variable Information**

{0}: Host name or IP address information

{1}: Port number

{2}: Internal information

Explanation

The specified IP address or port number cannot be used.

System Action

Start processing is interrupted.

User Action

Check if the port number {1} is already being used.

Exception while preparing the app**Explanation**

An exception occurred while loading the Java application.

System Action

The Java application load processing is interrupted, and the start processing continues.

User Action

Refer to any error messages output before or after this message, and remove the cause.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

jaccfactory.notfound

Explanation

The JACC factory was not found.

System Action

Processing is interrupted.

User Action

Refer to the other messages and the exception information output at the same time, and remove the cause of the error.

Log Format field separator is not a character so using default.

Explanation

The initial value will be used as the log message separator character.

System Action

Processing is continued.

User Action

Not required.

Record begin marker is not a proper value so using default.

Explanation

The initial value will be used as the log message start string.

System Action

Processing is continued.

User Action

Not required.

Record end marker is not a proper value so using default.

Explanation

The initial value will be used as the log message end string.

System Action

Processing is continued.

User Action

Not required.

SEVERE: Shutting down v3 due to startup exception : Address family not supported by protocol family: bind: {0}:{1}={2}

Variable Information

{0}: Host name or IP address information
{1}: Port number
{2}: Internal information

Explanation

The specified IP address or port number cannot be used.

System Action

Start processing is interrupted.

User Action

Check if the port number {1} is already being used.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

SEVERE: Shutting down v3 due to startup exception : No free port within range: {0}:{1}={2}

Variable Information

{0}: Host name or IP address information
{1}: Port number
{2}: Internal information

Explanation

The specified IP address or port number cannot be used.

System Action

Start processing is interrupted.

User Action

Check if the port number {1} is already being used.

If this message continues to be output despite taking the above action, contact Fujitsu technical support.

A.2.22.5 Exception Information that Starts with "java.net.SocketException"

java.net.SocketException: No buffer space available (maximum connections reached?)

Explanation

Insufficient buffer space.

System Action

Processing is interrupted.

User Action

If this message is output, it is possible that the ephemeral ports have run out.

Check the network status using the "netstat -a" command, and ensure that a large number of "TIME_WAIT" status connections do not exist.

If it is confirmed that the ephemeral ports are depleted, release unnecessary ports. Alternatively, increase the number of ports that can be used as ephemeral ports.

Index

	[E]	
Error type.....		2
	[F]	
Format of messages output to the server message log.....		1
Format of messages returned to an application.....		1
	[M]	
Message Format.....		1
Message number.....		2
Messages Output by PL/extJava.....		1325
Message text.....		2
Mirroring Controller Message Format.....		3
	[N]	
Notes on monitoring messages output to the server message log		1
Notes on monitoring messages returned to an application.....		1
	[O]	
Overview of Messages.....		1
	[U]	
Using this Document with FUJITSU Integrated System HA Database Ready.....		4